MATERIAL SAFETY DATA SHEET CAMEL 157P CC

Version Number 1.0 Revision Date 08/16/2007 Page 1 of 7 Print Date 11/30/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

| Product Stewardship (770) 271-5902 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident). |
|---|
| CAMEL 157P CC |
| CC10103335 |
| Mixture |
| Mixture |
| Industrial Applications |
| |

2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

| Components | CAS-No. | Weight % |
|--------------------------------|------------|----------|
| Rutile, antimony chromium buff | 68186-90-3 | 5 - 10 |
| Titanium dioxide | 13463-67-7 | 10 - 30 |

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

| Routes of Exposure: | : Inhalation, Ingestion, Skin contact |
|---|---|
| Acute exposure | |
| Inhalation Ingestion Eyes | Resin particles, like other inert materials, can be mechanically irritating. May be harmful if swallowed. Resin particles, like other inert materials, are mechanically irritating to |
| Skin | eyes. : Experience shows no unusual dermatitis hazard from routine handling. |
| Chronic exposure | : Refer to Section 11 for Toxicological Information. |
| Medical Conditions Aggravated by Exposure: | : None known. |



MATERIAL SAFETY DATA SHEET CAMEL 157P CC

Version Number 1.0 Revision Date 08/16/2007 Page 2 of 7 Print Date 11/30/2011

| | 4. FIRST AID MEASURES | |
|---|--|------------------|
| Inhalation | Move to fresh air in case of accidental inhalation of fun overheating or combustion. When symptoms persist or doubt seek medical advice. | |
| Ingestion | Do not induce vomiting without medical advice. When persist or in all cases of doubt seek medical advice. | symptoms |
| Eyes | Rinse immediately with plenty of water, also under the least 15 minutes. If eye irritation persists, seek medical | |
| Skin | Wash off with soap and plenty of water. If skin irritation medical attention. | on persists seek |
| | 5. FIRE-FIGHTING MEASURES | |
| Flash point | Not applicable | |
| Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media Special Fire Fighting | Not applicable Not applicable Not applicable Carbon dioxide blanket, Water spray, Dry powder, Foa Fullface self-contained breathing apparatus (SCBA) use | |
| Procedures Unusual Fire/Explosion Hazards | pressure mode should be worn to prevent inhalation of contaminants. Carbon dioxide (CO2), carbon monoxide (CO), oxides (NOx), other hazardous materials, and smoke are all po | of nitrogen |
| | CCIDENTAL RELEASE MEASURES | |
| Personal precautions | Wear appropriate personal protection during cleanup, so impervious gloves, boots and coveralls. | uch as |
| Environmental precautions | Should not be released into the environment. The prod be allowed to enter drains, water courses or the soil. | uct should not |
| Methods for cleaning up | Clean up promptly by sweeping or vacuum. Package a plastic, cardboard or metal containers for disposal. Refe of this MSDS for proper disposal methods. | |
| | 7. HANDLING AND STORAGE | |
| Handling | Take measures to prevent the build up of electrostatic c only in areas with appropriate exhaust ventilation. | harge. Heat |
| Storage | Keep containers dry and tightly closed to avoid moistur | e absorption |

2/7

POLYONE CORPORATION

PolyOne

MATERIAL SAFETY DATA SHEET CAMEL 157P CC

Version Number 1.0 Revision Date 08/16/2007 Page 3 of 7 Print Date 11/30/2011

| | ar | nd contamination. Keep in a d | ry, cool place. | |
|-----------------------------------|------------------------|--|-----------------------|------------------|
| 8.] | EXPOSURE | CONTROLS / PERSONAL | PROTECTION | |
| Respiratory protection | : N | o personal respiratory protecti | ve equipment normally | required. |
| Eye/Face Protection | : Sa | afety glasses with side-shields | | |
| Hand protection | : P | rotective gloves | | |
| Skin and body protection | 1 : L | ong sleeved clothing | | |
| Additional Protective Measures | : Si | afety shoes | | |
| General Hygiene Considerations | | andle in accordance with good ash hands before breaks and a | | safety practice. |
| Engineering measures | | eat only in areas with appropr ppropriate exhaust ventilation | | . Provide |
| Exposure limit(s) | | | | |
| Components | Value | Exposure time | Exposure type | List: |
| Rutile, antimony chromium buff | 0.5 mg/m3 | Time Weighted Average (TWA): | as Cr | ACGIH |
| | 0.5 mg/m3 | PEL: | as Cr | OSHA Z1 |
| | 0.5 mg/m3 | Time Weighted Average (TWA): | | MX OEL |
| | | | | |
| | 0.5 mg/m3 | Time Weighted Average (TWA): | as Sb | ACGIH |
| | 0.5 mg/m3 0.5 mg/m3 | Time Weighted Average (TWA): PEL: | as Sb as Sb | ACGIH OSHA Z1 |
| | Ū | (TWA): | | |
| Titanium dioxide | 0.5 mg/m3 | (TWA): PEL: Time Weighted Average | as Sb | OSHA Z1 |

9. PHYSICAL AND CHEMICAL PROPERTIES

Time Weighted Average

(TWA): Short Term Exposure Limit

(STEL):

- Form Appearance Color Odour Melting point/range
- Solid
 pellets
 TAN
 Very faint
 Not determined

10 mg/m3

20 mg/m3

Evaporation rate Specific Gravity Bulk density Vapour pressure Vapour density

as Ti

as Ti

Not applicableNot determinedNot establishedNot applicableNot applicable

MX OEL

MX OEL



MATERIAL SAFETY DATA SHEET CAMEL 157P CC

Version Number 1.0 Revision Date 08/16/2007 Page 4 of 7 Print Date 11/30/2011

| Boiling Point Water solubil | | | applicable luble | рН | : | Not applicable |
|--------------------------------|---------------|-------|---|--------------------|-----------|------------------|
| | | 10. 9 | STABILITY AND RE | EACTIVITY | | |
| Stability | | : S | table. | | | |
| Hazardous Po | olymerization | : V | Vill not occur. | | | |
| Conditions to | avoid | | Leep away from oxidiz ecomposition, do not o | 00 | n flame. | To avoid thermal |
| Incompatible | Materials | : I | ncompatible with stron | g acids and oxidiz | ing agent | ·S. |
| Hazardous de products | composition | | Carbon dioxide (CO2), NOx), other hazardous | | | e |

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

| CAS-No. | Chemical Name | Effect | Target Organ |
|------------|--------------------------------|------------------|---------------------------------|
| 68186-90-3 | Rutile, antimony chromium buff | Irritant | Eyes, Skin, Respiratory system. |
| 13463-67-7 | Titanium dioxide | Systemic effects | Respiratory system. |

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

| CAS-No. | Chemical Name | OSHA | IARC | NTP |
|------------|------------------|------|------|-----|
| 13463-67-7 | Titanium dioxide | no | 2B | no |

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

Additional Health Hazard Information:

Rutile, antimony chromium buff 68186-90-3 Can cause eye irritation. Can cause skin irritation. Symptoms may include redness and burning of skin, and other skin damage. Additional symptoms of skin contact may include: antimony measles (a red, pimply rash).

PolyOne.

MATERIAL SAFETY DATA SHEET CAMEL 157P CC

Version Number 1.0 Revision Date 08/16/2007 Page 5 of 7 Print Date 11/30/2011

| | 12. ECOLOGICAL INFORMATION |
|-------------------------------|---|
| Persistence and degradability | : Not readily biodegradable. |
| Environmental Toxicity | : Chemicals are not readily available as they are bound within the polymer matrix. |
| Bioaccumulation Potential | : Chemicals are not readily available as they are bound within the polymer matrix. |
| Additional advice | : No data available |
| | 13. DISPOSAL CONSIDERATIONS |
| Product | : Like most thermoplastic plastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations. |
| Contaminated packaging | : Recycling is preferred when possible. The generator of waste materia has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations. |
| | 14. TRANSPORT INFORMATION |
| | |
| U.S. DOT Classification | : Not regulated for transportation. |
| ICAO/IATA (air) | : Refer to specific regulation. |
| IMO / IMDG (maritime) | : Refer to specific regulation. |
| | 15. REGULATORY INFORMATION |
| US Regulations: | |
| OSHA Status | : Classified as hazardous based on components. |
| TSCA Status | : All components of this product are listed on or exempt from the TSCA Inventory. |
| US. EPA CERCLA Hazardous | Substances (40 CFR 302) |
| Not applicable | |
| | |

PolyOne.

MATERIAL SAFETY DATA SHEET CAMEL 157P CC

Version Number 1.0 Revision Date 08/16/2007 Page 6 of 7 Print Date 11/30/2011

California Proposition : Not applicable 65

SARA Title III Section 302 Extremely Hazardous Substance

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

SARA Title III Section 313 Toxic Chemicals:

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

| Chemical Name | CAS-No. | Weight % |
|--------------------------------|------------|--------------|
| CHROMIUM III COMPOUNDSANTIMONY | 68186-90-3 | 5.00 - 10.00 |
| COMPOUNDS | | |

Canadian Regulations:

National Pollutant Release Inventory (NPRI)

| Chemical Name | CAS-No. | Weight % | NPRI ID# |
|--------------------------------|------------|--------------|----------|
| Aluminum oxide | 1344-28-1 | 0.10 - 1.00 | 13 |
| Rutile, antimony chromium buff | 68186-90-3 | 5.00 - 10.00 | 69 |
| | | 5.00 - 10.00 | 17 |

WHMIS Classification : D2A

WHMIS Ingredient Disclosure List

| CAS-No. | |
|------------|--|
| 68186-90-3 | |

DSL

: All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.

National Inventories:

| Australia AICS | : Listed |
|----------------|------------------|
| China IECS | : Listed |
| Europe EINECS | : Listed |
| Japan ENCS | : Not determined |
| Korea KECI | : Listed |

MATERIAL SAFETY DATA SHEET CAMEL 157P CC

Version Number 1.0 Revision Date 08/16/2007 Page 7 of 7 Print Date 11/30/2011

Philippines PICCS : Listed

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.