MATERIAL SAFETY DATA SHEET RIGHT WHITE

Version Number 1.0 Revision Date 09/10/2007 Page 1 of 6 Print Date 11/30/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone:Emergency telephone:	roduct Stewardship (770) 271-5902 CHEMTREC 1-800-424-9300 (24hrs for spill, le: r accident).	ak, fire, exposure
Product name	IGHT WHITE	
Product code	C10103740	
Chemical Name	fixture	
CAS-No.	fixture	
Product Use	ndustrial Applications	

2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight %
Silica, amorphous	7631-86-9	5 - 10
Titanium dioxide	13463-67-7	60 - 100

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation Ingestion	Resin particles, like other inert materials, can be mechanically irritating.May be harmful if swallowed.
Eyes	: Resin particles, like other inert materials, are mechanically irritating to eyes.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.
Medical Conditions Aggravated by Exposure:	: None known.

PolyOne.

MATERIAL SAFETY DATA SHEET *RIGHT WHITE*

Version Number 1.0 Revision Date 09/10/2007 Page 2 of 6 Print Date 11/30/2011

	4. FIRST AID MEASURES	
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all case doubt seek medical advice.	s of
Ingestion	: Do not induce vomiting without medical advice. When symptom persist or in all cases of doubt seek medical advice.	5
Eyes	: Rinse immediately with plenty of water, also under the eyelids, fo least 15 minutes. If eye irritation persists, seek medical attention.	r at
Skin	: Wash off with soap and plenty of water. If skin irritation persists medical attention.	seel
	5. FIRE-FIGHTING MEASURES	
Flash point	: Not applicable	
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media	 Not applicable Not applicable Not applicable Not applicable Carbon dioxide blanket, Water spray, Dry powder, Foam. 	
Special Fire Fighting Procedures	: Fullface self-contained breathing apparatus (SCBA) used in positi pressure mode should be worn to prevent inhalation of airborne contaminants.	ve
Unusual Fire/Explosion Hazards	: Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitroger (NOx), other hazardous materials, and smoke are all possible.	l
	ACCIDENTAL RELEASE MEASURES	
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.	
Environmental precautions	: Should not be released into the environment. The product should be allowed to enter drains, water courses or the soil.	not
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material plastic, cardboard or metal containers for disposal. Refer to Sectio of this MSDS for proper disposal methods.	
	7. HANDLING AND STORAGE	
Handling	: Take measures to prevent the build up of electrostatic charge. He only in areas with appropriate exhaust ventilation.	at
Storage	: Keep containers dry and tightly closed to avoid moisture absorption	on

2/6



MATERIAL SAFETY DATA SHEET **RIGHT WHITE**

Version Number 1.0 Revision Date 09/10/2007 Page 3 of 6 Print Date 11/30/2011

	EXPOSURE	CONTROLS / PERSONAL	PROTECTION		
Respiratory protection	: N	o personal respiratory protecti	ve equipment normally r	equired.	
Eye/Face Protection	: S	afety glasses with side-shields			
Hand protection	: P	rotective gloves			
Skin and body protection	: L	: Long sleeved clothing			
Additional Protective Measures	: S	: Safety shoes			
General Hygiene Considerations		: Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.			
Engineering measures		leat only in areas with appropri ppropriate exhaust ventilation a		Provide	
Exposure limit(s)					
Components	Value	Exposure time	Exposure type	List:	
Silica, amorphous	0.8 mg/m3	Time Weighted Average		Z3	
	10 / 2	(TWA):	T 1 1 1 1 . 1 .	MVOEL	
	10 mg/m3	Time Weighted Average (TWA):	Inhalable particulate.	MX OEL	
		Time Weighted Average	Respirable dust.	MX OEL	
	3 mg/m3				
Titanium dioxide	3 mg/m3	(TWA): Time Weighted Average		ACGIH	
Titanium dioxide		(TWA):	Total dust.		
Titanium dioxide	10 mg/m3	(TWA): Time Weighted Average (TWA):	Total dust. as Ti	OSHA Z1	
Titanium dioxide	10 mg/m3	(TWA): Time Weighted Average (TWA): PEL: Time Weighted Average		OSHA Z1	
Titanium dioxide	10 mg/m3 15 mg/m3 10 mg/m3 20 mg/m3	(TWA): Time Weighted Average (TWA): PEL: Time Weighted Average (TWA): Short Term Exposure Limit	as Ti as Ti	OSHA Z1 MX OEL	
Titanium dioxide	10 mg/m3 15 mg/m3 10 mg/m3 20 mg/m3	(TWA): Time Weighted Average (TWA): PEL: Time Weighted Average (TWA): Short Term Exposure Limit (STEL): CAL AND CHEMICAL PRO	as Ti as Ti PERTIES	OSHA Z1 MX OEL	
Form Appearance	10 mg/m3 15 mg/m3 10 mg/m3 20 mg/m3 9. PHYSIC	(TWA): Time Weighted Average (TWA): PEL: Time Weighted Average (TWA): Short Term Exposure Limit (STEL): CAL AND CHEMICAL PRO Evapor ts Specifi	as Ti as Ti PERTIES ration rate : Not c Gravity : Not	OSHA Z1 MX OEL MX OEL applicable determined	
Form Appearance Color	10 mg/m3 15 mg/m3 10 mg/m3 20 mg/m3 9. PHYSIC : Solic : pelle : WHI	(TWA): Time Weighted Average (TWA): PEL: Time Weighted Average (TWA): Short Term Exposure Limit (STEL): CAL AND CHEMICAL PRO I Evapor ts Specifi TE Bulk d	as Ti as Ti PERTIES ration rate : Not c Gravity : Not ensity : Not	OSHA Z1 MX OEL MX OEL applicable determined established	
Form Appearance Color Odour	10 mg/m3 15 mg/m3 10 mg/m3 20 mg/m3 9. PHYSIC : Solic : pelle : WHI : Very	(TWA): Time Weighted Average (TWA): PEL: Time Weighted Average (TWA): Short Term Exposure Limit (STEL): CAL AND CHEMICAL PRO I Evapor ts Specifi TE Bulk d faint Vapou	as Ti as Ti PERTIES ration rate : Not c Gravity : Not ensity : Not r pressure : Not	OSHA Z1 MX OEL MX OEL applicable determined established applicable	
Form Appearance Color	10 mg/m3 15 mg/m3 10 mg/m3 20 mg/m3 9. PHYSIO : Solid : pelle : WHI : Very : Not of	(TWA): Time Weighted Average (TWA): PEL: Time Weighted Average (TWA): Short Term Exposure Limit (STEL): CAL AND CHEMICAL PRO I Evapor ts Specifi TE Bulk d faint Vapou	as Ti as Ti PPERTIES ration rate : Not c Gravity : Not ensity : Not r pressure : Not r density : Not	OSHA Z1 MX OEL MX OEL applicable determined established	
Form Appearance Color Odour Melting point/range	10 mg/m3 15 mg/m3 10 mg/m3 20 mg/m3 9. PHYSIO : Solid : pelle : WHI : Very : Not of	(TWA): Time Weighted Average (TWA): PEL: Time Weighted Average (TWA): Short Term Exposure Limit (STEL): CAL AND CHEMICAL PRO I Evapor ts Specifi TE Bulk d faint Vapou determined Vapou	as Ti as Ti PPERTIES ration rate : Not c Gravity : Not ensity : Not r pressure : Not r density : Not	OSHA Z1 MX OEL MX OEL applicable determined established applicable applicable	

POLYONE CORPORATION



MATERIAL SAFETY DATA SHEET **RIGHT WHITE**

Version Number 1.0 Revision Date 09/10/2007

Page 4 of 6 Print Date 11/30/2011

Stability	:	Stable.
Hazardous Polymerization	:	Will not occur.
Conditions to avoid	:	Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
Incompatible Materials	:	Incompatible with strong acids and oxidizing agents.
Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
7631-86-9	Silica, amorphous	Irritant	Eyes, Respiratory system.
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.

LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
7631-86-9	Silica, amorphous	Oral LD50Oral LD50	15,000 mg/kg22,500 mg/kg	mouserat

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
13463-67-7	Titanium dioxide	no	2B	no

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

12. ECOLOGICAL INFORMATION



MATERIAL SAFETY DATA SHEET *RIGHT WHITE*

sion Number 1.0 ision Date 09/10/2007	Page 5 Print Date 11/30/2
Persistence and degradability	: Not readily biodegradable.
Environmental Toxicity	: Chemicals are not readily available as they are bound within the polymer matrix.
Bioaccumulation Potential	: Chemicals are not readily available as they are bound within the polymer matrix.
Additional advice	: No data available
	13. DISPOSAL CONSIDERATIONS
Product	: Like most thermoplastic plastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste materia has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. DOT Classification	: Not regulated for transportation.
ICAO/IATA (air)	: Refer to specific regulation.
IMO / IMDG (maritime)	: Refer to specific regulation.
	15. REGULATORY INFORMATION
US Regulations:	
OSHA Status	: Classified as hazardous based on components.
TSCA Status	: All components of this product are listed on or exempt from the TSCA Inventory.
US. EPA CERCLA Hazardous	Substances (40 CFR 302)
Not applicable	
California Proposition	: Not applicable

PolyOne.

MATERIAL SAFETY DATA SHEET *RIGHT WHITE*

Version Number 1.0		Page 6 of 6
Revision Date 09/10/2007	Print Date	11/30/2011

65

SARA Title III Section 302 Ex	xtremely Hazardous Substance
Unless specific chemicals are	identified under this section, this product is Not Applicable under this regulation
SARA Title III Section 313 To	oxic Chemicals:
Unless specific chemicals are	identified under this section, this product is Not Applicable under this regulation
Canadian Regulations:	
National Pollutant Rele	ease Inventory (NPRI)
Not applicable	
WHMIS Classification	n : D2A
WHMIS Ingredient Dis	sclosure List
CAS-No. 7631-86-9	
DSL	: All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.
National Inventories:	
Australia AICS	: Listed
China IECS	: Listed
Europe EINECS	: Listed
Japan ENCS	: Listed
Korea KECI	: Listed
Philippines PICCS	: Listed
(16. OTHER INFORMATION