MATERIAL SAFETY DATA SHEET IMPERIAL LAVENDER 270C

Version Number 1.0 Revision Date 09/12/2007 Page 1 of 6 Print Date 12/1/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone Emergency telephone	:	Product Stewardship (770) 271-5902 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	IMPERIAL LAVENDER 270C
Product code	:	CC10103999
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight %
Calcium carbonate	1317-65-3	5 - 10
Titanium dioxide	13463-67-7	30 - 60

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation Ingestion Eyes	 Resin particles, like other inert materials, can be mechanically irritating. May be harmful if swallowed. Resin particles, like other inert materials, are mechanically irritating to over
Skin	eyes. : Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.
Medical Conditions Aggravated by Exposure:	: None known.

PolyOne.

MATERIAL SAFETY DATA SHEET IMPERIAL LAVENDER 270C

Version Number 1.0 Revision Date 09/12/2007 Page 2 of 6 Print Date 12/1/2011

	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for a least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists se medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: Not applicable
Flammable Limits	
Upper explosion limit	: Not applicable
Lower explosion limit	: Not applicable
Autoignition temperature	: Not applicable
Suitable extinguishing media	: Carbon dioxide blanket, Water spray, Dry powder, Foam.
Special Fire Fighting Procedures	: Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.
Unusual Fire/Explosion Hazards	: Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.
Storage	: Keep containers dry and tightly closed to avoid moisture absorption

PolyOne.

MATERIAL SAFETY DATA SHEET IMPERIAL LAVENDER 270C

Version Number 1.0 Revision Date 09/12/2007 Page 3 of 6 Print Date 12/1/2011

8. E	EXPOSURE	CONTROLS / PERSONAL	PROTECTION			
Respiratory protection	: No personal respiratory protective equipment normally required.					
Eye/Face Protection	: S	: Safety glasses with side-shields				
Hand protection	: P	Protective gloves				
Skin and body protection	: L	long sleeved clothing				
Additional Protective Measures	: S	afety shoes				
General Hygiene Considerations		Handle in accordance with good Vash hands before breaks and a		afety practice		
Engineering measures		Heat only in areas with appropri ppropriate exhaust ventilation a		Provide		
Exposure limit(s)						
Components	Value	Exposure time	Exposure type	List:		
Components Calcium carbonate		Exposure time PEL:	Exposure type Respirable fraction.			
Components Calcium carbonate	5 mg/m3	PEL:	Respirable fraction.	OSHA Z1		
		PEL: PEL: Time Weighted Average				
	5 mg/m3 15 mg/m3	PEL: PEL:	Respirable fraction.	OSHA Z1 OSHA Z1		
	5 mg/m3 15 mg/m3 10 mg/m3	PEL: PEL: Time Weighted Average (TWA): Short Term Exposure Limit	Respirable fraction.	OSHA Z1 OSHA Z1 MX OEL		
Calcium carbonate	5 mg/m3 15 mg/m3 10 mg/m3 20 mg/m3	PEL: PEL: Time Weighted Average (TWA): Short Term Exposure Limit (STEL): Time Weighted Average (TWA): PEL:	Respirable fraction.	OSHA Z1 OSHA Z1 MX OEL MX OEL		
Calcium carbonate	5 mg/m3 15 mg/m3 10 mg/m3 20 mg/m3 10 mg/m3 15 mg/m3 10 mg/m3	PEL: PEL: Time Weighted Average (TWA): Short Term Exposure Limit (STEL): Time Weighted Average (TWA): PEL: Time Weighted Average (TWA):	Respirable fraction. Total dust. Total dust. as Ti	OSHA Z1 OSHA Z1 MX OEL MX OEL ACGIH OSHA Z1 MX OEL		
Calcium carbonate	5 mg/m3 15 mg/m3 10 mg/m3 20 mg/m3 10 mg/m3 15 mg/m3	PEL: PEL: Time Weighted Average (TWA): Short Term Exposure Limit (STEL): Time Weighted Average (TWA): PEL: Time Weighted Average	Respirable fraction. Total dust. Total dust.	OSHA Z1 OSHA Z1 MX OEL MX OEL ACGIH OSHA Z1		
Calcium carbonate	5 mg/m3 15 mg/m3 10 mg/m3 20 mg/m3 10 mg/m3 10 mg/m3 20 mg/m3	PEL: PEL: Time Weighted Average (TWA): Short Term Exposure Limit (STEL): Time Weighted Average (TWA): PEL: Time Weighted Average (TWA): Short Term Exposure Limit	Respirable fraction. Total dust. Total dust. as Ti as Ti	OSHA Z1 OSHA Z1 MX OEL MX OEL ACGIH OSHA Z1 MX OEL		
Calcium carbonate Titanium dioxide	5 mg/m3 15 mg/m3 10 mg/m3 20 mg/m3 10 mg/m3 10 mg/m3 20 mg/m3 20 mg/m3	PEL: PEL: Time Weighted Average (TWA): Short Term Exposure Limit (STEL): Time Weighted Average (TWA): PEL: Time Weighted Average (TWA): Short Term Exposure Limit (STEL): CAL AND CHEMICAL PRO	Respirable fraction. Total dust. Total dust. as Ti as Ti PERTIES	OSHA Z1 OSHA Z1 MX OEL MX OEL ACGIH OSHA Z1 MX OEL MX OEL		
Calcium carbonate Titanium dioxide Form	5 mg/m3 15 mg/m3 10 mg/m3 20 mg/m3 10 mg/m3 15 mg/m3 10 mg/m3 20 mg/m3 20 mg/m3 9. PHYSIC : Solid	PEL: PEL: Time Weighted Average (TWA): Short Term Exposure Limit (STEL): Time Weighted Average (TWA): PEL: Time Weighted Average (TWA): Short Term Exposure Limit (STEL): CAL AND CHEMICAL PRO	Respirable fraction. Total dust. Total dust. as Ti as Ti PERTIES ration rate : Not	OSHA Z1 OSHA Z1 MX OEL MX OEL ACGIH OSHA Z1 MX OEL MX OEL		
Calcium carbonate Calcium carbonate Titanium dioxide Form Appearance	5 mg/m3 15 mg/m3 10 mg/m3 20 mg/m3 10 mg/m3 10 mg/m3 20 mg/m3 20 mg/m3 9. PHYSIC : Solic : pelle	PEL: PEL: Time Weighted Average (TWA): Short Term Exposure Limit (STEL): Time Weighted Average (TWA): PEL: Time Weighted Average (TWA): Short Term Exposure Limit (STEL): CAL AND CHEMICAL PRO d Evapor ets Specifi	Respirable fraction. Total dust. Total dust. as Ti as Ti PERTIES ration rate : Not c Gravity : Not	OSHA Z1 OSHA Z1 MX OEL MX OEL ACGIH OSHA Z1 MX OEL MX OEL		
Calcium carbonate Calcium carbonate Titanium dioxide Form Appearance Color	5 mg/m3 15 mg/m3 10 mg/m3 20 mg/m3 10 mg/m3 10 mg/m3 20 mg/m3 20 mg/m3 9. PHYSIC : Solid : pelle : PUR	PEL: PEL: Time Weighted Average (TWA): Short Term Exposure Limit (STEL): Time Weighted Average (TWA): PEL: Time Weighted Average (TWA): Short Term Exposure Limit (STEL): CAL AND CHEMICAL PRO d Evapor ets Specifi PLE Bulk d	Respirable fraction. Total dust. Total dust. as Ti as Ti PERTIES ration rate : Not c Gravity : Not ensity : Not	OSHA Z1 OSHA Z1 MX OEL MX OEL ACGIH OSHA Z1 MX OEL MX OEL		
Calcium carbonate Calcium carbonate Titanium dioxide Form Appearance Color Odour	5 mg/m3 15 mg/m3 10 mg/m3 20 mg/m3 10 mg/m3 10 mg/m3 10 mg/m3 20 mg/m3 9. PHYSIC : Solic : pelle : PUR : Very	PEL: PEL: Time Weighted Average (TWA): Short Term Exposure Limit (STEL): Time Weighted Average (TWA): PEL: Time Weighted Average (TWA): Short Term Exposure Limit (STEL): CAL AND CHEMICAL PRO d Evapor ets Specifi PLE Bulk dy faint Vapour	Respirable fraction. Total dust. Total dust. as Ti as Ti PERTIES ration rate : Not c Gravity : Not ensity : Not r pressure : Not	OSHA Z1 OSHA Z1 MX OEL MX OEL ACGIH OSHA Z1 MX OEL MX OEL MX OEL		
Calcium carbonate Calcium carbonate Titanium dioxide Form Appearance Color	5 mg/m3 15 mg/m3 10 mg/m3 20 mg/m3 10 mg/m3 10 mg/m3 10 mg/m3 20 mg/m3 20 mg/m3 9. PHYSIC : Solid : pelle : PUR : Very : Not	PEL: PEL: Time Weighted Average (TWA): Short Term Exposure Limit (STEL): Time Weighted Average (TWA): PEL: Time Weighted Average (TWA): Short Term Exposure Limit (STEL): CAL AND CHEMICAL PRO d Evapor ets Specifi PLE Bulk dy faint Vapour	Respirable fraction. Total dust. as Ti as Ti OPERTIES ration rate : Not c Gravity : Not ensity : Not r pressure : Not r density : Not	OSHA Z1 OSHA Z1 MX OEL MX OEL ACGIH OSHA Z1 MX OEL MX OEL		

blvUn<u>e</u>

MATERIAL SAFETY DATA SHEET IMPERIAL LAVENDER 270C

Version Number 1.0 Revision Date 09/12/2007 Page 4 of 6 Print Date 12/1/2011

Stability	:	Stable.
Hazardous Polymerization	:	Will not occur.
Conditions to avoid	:	Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
Incompatible Materials	:	Incompatible with strong acids and oxidizing agents.
Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
1317-65-3	Calcium carbonate	Irritant	Eyes, Skin.
		Systemic effects	Eyes, Skin, Respiratory system.
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
13463-67-7	Titanium dioxide	no	2B	no

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

12. ECOLOGICAL INFORMATION

Persistence and degradability	:	Not readily biodegradable.
Environmental Toxicity	:	Chemicals are not readily available as they are bound within the polymer matrix.
Bioaccumulation Potential	:	Chemicals are not readily available as they are bound within the

PolyOne.

MATERIAL SAFETY DATA SHEET IMPERIAL LAVENDER 270C

Version Number 1.0 Revision Date 09/12/2007 Page 5 of 6 Print Date 12/1/2011

	polymer matrix.	
Additional advice	No data available	
	13. DISPOSAL CONSIDERATIONS	3
Product	Like most thermoplastic plastics the possible recycling is preferred to dis generator of waste material has the r classification, transportation and dis applicable federal, state/provincial a	posal or incineration. The esponsibility for proper waste posal in accordance with
Contaminated packaging	Recycling is preferred when possible has the responsibility for proper was and disposal in accordance with app and local regulations.	te classification, transportation
	14. TRANSPORT INFORMATION	
U.S. DOT Classification	Not regulated for transportation.	
ICAO/IATA (air)	Refer to specific regulation.	
IMO / IMDG (maritime)	Refer to specific regulation.	
	15. REGULATORY INFORMATION	N
US Regulations:		
OSHA Status	Classified as hazardous based on co	mponents.
TSCA Status	: All components of this product are l Inventory.	isted on or exempt from the TSCA
US. EPA CERCLA Hazardo	bstances (40 CFR 302)	
Not applicable		
California Proposition 65	: Not applicable	
SARA Title III Section 302 I	mely Hazardous Substance	
Unloss specific chamicals are	tified under this section, this product is	Not Applicable under this regul

MATERIAL SAFETY DATA SHEET IMPERIAL LAVENDER 270C

Version Number 1.0 Revision Date 09/12/2007 Page 6 of 6 Print Date 12/1/2011

SARA Title III Section 313 Toxic Chemicals:

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

Canadian Regulations:

Chemical Name			CAS-No.	Weight %	NPRI ID#
Aluminum oxide			1344-28-1	0.10 - 1.00	13
WHMIS Classification	:	D2A			
DSL	:		ts of this product at (DSL) or are exec	are on the Canadia empt.	n Domestic
ational Inventories:					
Australia AICS	:	Listed			
China IECS	:	Listed			
Europe EINECS	:	Listed			
Japan ENCS	:	Listed			
Korea KECI	:	Listed			
Philippines PICCS	:	Listed			
		16 OTHER I	NFORMATION	I	

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.