MATERIAL SAFETY DATA SHEET SPARKLE FLAKE

Version Number 1.0 Revision Date 09/13/2007

Page 1 of 6 Print Date 12/1/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone:Emergency telephone:	:	Product Stewardship (770) 271-5902 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	SPARKLE FLAKE
Product code	:	CC10104127
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight %	
Titanium dioxide	13463-67-7	5 - 10	
Aluminum oxide	1344-28-1	10 - 30	

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation Ingestion Eyes	 Resin particles, like other inert materials, can be mechanically irritating. May be harmful if swallowed. Resin particles, like other inert materials, are mechanically irritating to
Skin	eyes. : Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.
Medical Conditions Aggravated by Exposure:	: None known.

PolyOne.

MATERIAL SAFETY DATA SHEET **SPARKLE FLAKE**

Version Number 1.0 Revision Date 09/13/2007 Page 2 of 6 Print Date 12/1/2011

		4. FIRST AID MEASURES
Inhalation	:	Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	:	Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	:	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	:	Wash off with soap and plenty of water. If skin irritation persists seel medical attention.
		5. FIRE-FIGHTING MEASURES
Flash point	:	Not applicable
Flammable Limits		
Upper explosion limit		Not applicable
Lower explosion limit	:	Not applicable
Autoignition temperature	:	Not applicable
Suitable extinguishing media	:	Carbon dioxide blanket, Water spray, Dry powder, Foam.
Special Fire Fighting Procedures	:	Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.
Unusual Fire/Explosion Hazards	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.
	6. A	CCIDENTAL RELEASE MEASURES
Personal precautions	:	Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	:	Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	:	Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 13 of this MSDS for proper disposal methods.
		7. HANDLING AND STORAGE
Handling	:	Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.
Storage	:	Keep containers dry and tightly closed to avoid moisture absorption

PolyOne.

MATERIAL SAFETY DATA SHEET SPARKLE FLAKE

Version Number 1.0 Revision Date 09/13/2007 Page 3 of 6 Print Date 12/1/2011

: N : S : F : I : S : S : H V : H	CONTROLS / PERSON No personal respiratory p Safety glasses with side- Protective gloves Long sleeved clothing Safety shoes Handle in accordance with Vash hands before break Heat only in areas with a ppropriate exhaust vention Exposure time Time Weighted Ave	protectiv shields th good i cs and at ppropria ilation a	re equipment norma industrial hygiene a t the end of workday ate exhaust ventilati	nd safety practic y.
: S : F : L : S : H V : H a	Safety glasses with side- Protective gloves Long sleeved clothing Safety shoes Handle in accordance with Wash hands before break Heat only in areas with a ppropriate exhaust vention Exposure time Time Weighted Ave	shields th good as and at ppropria ilation a	industrial hygiene a the end of workday ate exhaust ventilati t machinery.	nd safety practic y. ion. Provide List:
: F : L : S : H V : H a	Protective gloves Long sleeved clothing Safety shoes Handle in accordance with Wash hands before break Heat only in areas with a ppropriate exhaust vention Exposure time Time Weighted Ave	th good i cs and at ppropria ilation a	the end of workday ate exhaust ventilati t machinery.	y. Ion. Provide
: I : S : H V : H a	Long sleeved clothing Safety shoes Handle in accordance wit Wash hands before break Heat only in areas with a ppropriate exhaust vention Exposure time Time Weighted Ave	cs and at ppropria ilation a	the end of workday ate exhaust ventilati t machinery.	y. Ion. Provide
: S : H V : H a	Safety shoes Handle in accordance with Wash hands before break Heat only in areas with a appropriate exhaust vention Exposure time Time Weighted Ave	cs and at ppropria ilation a	the end of workday ate exhaust ventilati t machinery.	y. Ion. Provide
: H V : H a	Handle in accordance with Wash hands before break Heat only in areas with a ppropriate exhaust vention Exposure time Time Weighted Ave	cs and at ppropria ilation a	the end of workday ate exhaust ventilati t machinery.	y. Ion. Provide
V : H a	Wash hands before break Heat only in areas with a ppropriate exhaust vention Exposure time Time Weighted Ave	cs and at ppropria ilation a	the end of workday ate exhaust ventilati t machinery.	y. Ion. Provide
alue	ppropriate exhaust venti Exposure time Time Weighted Ave	ilation a	t machinery.	List:
	Time Weighted Ave		Exposure type	
	Time Weighted Ave		Exposure type	
ng/m3	-			ACGIH
	(TWA):	rage		
ng/m3	PEL:		Respirable fractio	on. OSHA Z
ng/m3	PEL:		Total dust.	OSHA Z
ng/m3	Time Weighted Ave (TWA):	rage		MX OEL
ng/m3	-	rage		ACGIH
ng/m3	PEL:		Total dust.	OSHA Z
ng/m3	Time Weighted Ave (TWA):	rage	as Ti	MX OEL
ng/m3		Limit	as Ti	MX OEL
PHYSI	CAL AND CHEMICA	L PRO	PERTIES	
	ets	Specific	c Gravity :	Not applicable Not determined
				Not established
				Not applicable
		-		Not applicable
	11	рН	:	Not applicable
	ng/m3 ng/m3 ng/m3 ng/m3 ng/m3 ng/m3 ng/m3 ng/m3 PHYSI : Solid : pelld : GRH : Very : Not : Not	ng/m3 PEL: ng/m3 Time Weighted Ave (TWA): (TWA): ng/m3 Time Weighted Ave (TWA): (TWA): ng/m3 PEL: ng/m3 Time Weighted Ave (TWA): (TWA): ng/m3 Short Term Exposure (STEL): (STEL): PHYSICAL AND CHEMICA : Solid : : pellets : : GREY : : Not determined : : Not applicable	ng/m3 PEL: ng/m3 Time Weighted Average (TWA): ng/m3 Time Weighted Average (TWA): ng/m3 PEL: ng/m3 PEL: ng/m3 Time Weighted Average (TWA): ng/m3 Short Term Exposure Limit (STEL): PHYSICAL AND CHEMICAL PRO : Solid : pellets : pellets : Very faint : Not determined : Not applicable	ng/m3 PEL: Total dust. ng/m3 Time Weighted Average (TWA): Total dust. ng/m3 Time Weighted Average (TWA): Total dust. ng/m3 PEL: Total dust. ng/m3 PEL: Total dust. ng/m3 PEL: Total dust. ng/m3 Time Weighted Average (TWA): as Ti ng/m3 Short Term Exposure Limit (STEL): as Ti PHYSICAL AND CHEMICAL PROPERTIES E Solid Evaporation rate : pellets Specific Gravity : GREY Bulk density : : Vapour pressure : : Not determined Vapour density :

10. STABILITY AND REACTIVITY

blvUn<u>e</u>

MATERIAL SAFETY DATA SHEET SPARKLE FLAKE

Version Number 1.0 Revision Date 09/13/2007 Page 4 of 6 Print Date 12/1/2011

Stability	:	Stable.
Hazardous Polymerization	:	Will not occur.
Conditions to avoid	:	Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
Incompatible Materials	:	Incompatible with strong acids and oxidizing agents.
Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.
1344-28-1	Aluminum oxide	Systemic effects	Eyes, Skin, Respiratory system.

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

CAS-No.	CAS-No. Chemical Name		IARC	NTP
13463-67-7	Titanium dioxide	no	2B	no

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

Persistence and degradability	:	Not readily biodegradable.
Environmental Toxicity	:	Chemicals are not readily available as they are bound within the polymer matrix.
Bioaccumulation Potential	:	Chemicals are not readily available as they are bound within the polymer matrix.

POLYONE CORPORATION

PolyOne.

MATERIAL SAFETY DATA SHEET **SPARKLE FLAKE**

Version Number 1.0 Revision Date 09/13/2007 Page 5 of 6 Print Date 12/1/2011

	: No data available
	13. DISPOSAL CONSIDERATIONS
Product	: Like most thermoplastic plastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste materia has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. DOT Classification	: Not regulated for transportation.
ICAO/IATA (air)	: Refer to specific regulation.
IMO / IMDG (maritime)	: Refer to specific regulation.
	15. REGULATORY INFORMATION
US Regulations:	
OSHA Status	: Classified as hazardous based on components.
TSCA Status	: All components of this product are listed on or exempt from the TSCA Inventory.
US. EPA CERCLA Hazardou	s Substances (40 CFR 302)
Not applicable	
California Propositior 65	a : Not applicable
SARA Title III Section 302 E	xtremely Hazardous Substance

MATERIAL SAFETY DATA SHEET SPARKLE FLAKE

Version Number 1.0 Revision Date 09/13/2007 Page 6 of 6 Print Date 12/1/2011

SARA Title III Section 313 Toxic Chemicals:

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation Chemical Name CAS-No. Weight %

		0
ALUMINUM OXIDE (FIBROUS FORMS)	1344-28-1	10.00 - 30.00

Canadian Regulations:

National Pollutant Release Inventory (NPRI)			
Chemical Name	CAS-No.	Weight %	NPRI ID#
Aluminum oxide	1344-28-1	10.00 - 30.00	13

WHMIS Classification : D2A

WHMIS Ingredient Disclosure List

:

CAS-No.	
1344-28-1	

DSL

All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.

National Inventories:

Australia AICS	: Not determined	
China IECS	: Listed	
Europe EINECS	: Listed	
Japan ENCS	: Not determined	
Korea KECI	: Listed	
Philippines PICCS	: Not determined	

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.