PolvOne

MATERIAL SAFETY DATA SHEET DARK GREY GF

Version Number 1.1 Revision Date 09/21/2007 Page 1 of 7 Print Date 12/1/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone:Emergency telephone:	:	Product Stewardship (770) 271-5902 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	DARK GREY GF
Product code	:	CC10104272
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight %
1,6-Hexanediamine,	70624-18-9	1 - 5
N,N'-bis(2,2,6,6-tetramethyl-4-piperidinyl)-,		
polymer with 2,4,6-trichloro-1,3,5-triazine,		
reaction products		
Rutile, antimony chromium buff	68186-90-3	1 - 5

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation Ingestion Eyes	 Resin particles, like other inert materials, can be mechanically irritating. May be harmful if swallowed. Resin particles, like other inert materials, are mechanically irritating to eves.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.

PolyOne.

MATERIAL SAFETY DATA SHEET **DARK GREY GF**

Version Number 1.1 Revision Date 09/21/2007 Page 2 of 7 Print Date 12/1/2011

Medical Conditions : None known. Aggravated by Exposure:				
	4. FIRST AID MEASURES			
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases doubt seek medical advice.	of		
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.			
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for least 15 minutes. If eye irritation persists, seek medical attention.	at		
Skin	: Wash off with soap and plenty of water. If skin irritation persists se medical attention.	el		
	5. FIRE-FIGHTING MEASURES			
Flash point	: Not applicable			
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	 Not applicable Not applicable Not applicable Carbon dioxide blanket, Water spray, Dry powder, Foam. Fullface self-contained breathing apparatus (SCBA) used in positiv pressure mode should be worn to prevent inhalation of airborne contaminants. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible. 	e		
	6. ACCIDENTAL RELEASE MEASURES			
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.			
Environmental precautions	: Should not be released into the environment. The product should n be allowed to enter drains, water courses or the soil.	ot		
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material ir plastic, cardboard or metal containers for disposal. Refer to Section of this MSDS for proper disposal methods.			
	7. HANDLING AND STORAGE			
Handling	: Take measures to prevent the build up of electrostatic charge. Heat			



MATERIAL SAFETY DATA SHEET **DARK GREY GF**

sion Date 09/21/2007			Print	Page Date 12/1/
	01	nly in areas with appropriate e	xhaust ventilation.	
Storage		eep containers dry and tightly nd contamination. Keep in a d		e absorption
8.1	EXPOSURE	CONTROLS / PERSONAL	PROTECTION	
Respiratory protection	: N	o personal respiratory protecti	ve equipment normally	required.
Eye/Face Protection	: Sa	afety glasses with side-shields		
Hand protection	: P1	rotective gloves		
Skin and body protection	: L	ong sleeved clothing		
Additional Protective Measures	: Sa	afety shoes		
General Hygiene Considerations		andle in accordance with good ash hands before breaks and a		afety practic
	ar	ppropriate exhaust ventilation	at machinery.	
Exposure limit(s)				
	Value	Exposure time	-	List
Exposure limit(s) Components Rutile, antimony chromium buff	Value 0.5 mg/m3	Exposure time Time Weighted Average (TWA):	Exposure type as Cr	List: ACGIH
Components Rutile, antimony			Exposure type	ACGIH
Components Rutile, antimony	0.5 mg/m3	Time Weighted Average (TWA):	Exposure type as Cr	ACGIH OSHA Z
Components Rutile, antimony	0.5 mg/m3 0.5 mg/m3	Time Weighted Average (TWA): PEL: Time Weighted Average	Exposure type as Cr	ACGIH OSHA Z MX OEI
Components Rutile, antimony	0.5 mg/m3 0.5 mg/m3 0.5 mg/m3	Time Weighted Average (TWA): PEL: Time Weighted Average (TWA): Time Weighted Average	Exposure type as Cr as Cr	ACGIH OSHA Z MX OEI ACGIH
Components Rutile, antimony	0.5 mg/m3 0.5 mg/m3 0.5 mg/m3 0.5 mg/m3	Time Weighted Average (TWA): PEL: Time Weighted Average (TWA): Time Weighted Average (TWA):	Exposure type as Cr as Cr as Sb	ACGIH OSHA Z MX OEI ACGIH OSHA Z
Components Rutile, antimony	0.5 mg/m3 0.5 mg/m3 0.5 mg/m3 0.5 mg/m3 0.5 mg/m3	Time Weighted Average (TWA): PEL: Time Weighted Average (TWA): Time Weighted Average (TWA): PEL: Time Weighted Average	Exposure type as Cr as Cr as Sb as Sb as Sb	ACGIH OSHA Z MX OEI ACGIH OSHA Z
Components Rutile, antimony	0.5 mg/m3 0.5 mg/m3 0.5 mg/m3 0.5 mg/m3 0.5 mg/m3	Time Weighted Average (TWA): PEL: Time Weighted Average (TWA): Time Weighted Average (TWA): PEL: Time Weighted Average (TWA):	Exposure type as Cr as Cr as Sb as Sb as Sb as Sb	ACGIH OSHA Z MX OEI ACGIH OSHA Z
Components Rutile, antimony chromium buff	0.5 mg/m3 0.5 mg/m3 0.5 mg/m3 0.5 mg/m3 0.5 mg/m3 0.5 mg/m3	Time Weighted Average (TWA): PEL: Time Weighted Average (TWA): Time Weighted Average (TWA): PEL: Time Weighted Average (TWA): CAL AND CHEMICAL PRO	Exposure type as Cr as Cr as Sb as Sb as Sb as Sb DPERTIES ration rate : Not	ACGIH OSHA Z MX OEI ACGIH OSHA Z MX OEI
Components Rutile, antimony chromium buff	0.5 mg/m3 0.5 mg/m3 0.5 mg/m3 0.5 mg/m3 0.5 mg/m3 0.5 mg/m3 9. PHYSIC : Solid : pellet : GRE	Time Weighted Average (TWA): PEL: Time Weighted Average (TWA): Time Weighted Average (TWA): PEL: Time Weighted Average (TWA): CAL AND CHEMICAL PRO	Exposure type as Cr as Cr as Sb as Sb as Sb operties ration rate : Not ic Gravity : Not lensity : Not	ACGIH OSHA Z MX OEI ACGIH OSHA Z MX OEI
Components Rutile, antimony chromium buff 	0.5 mg/m3 0.5 mg/m3 0.5 mg/m3 0.5 mg/m3 0.5 mg/m3 0.5 mg/m3 9. PHYSIC : Solid : pellet : GRE : Very	Time Weighted Average (TWA): PEL: Time Weighted Average (TWA): Time Weighted Average (TWA): PEL: Time Weighted Average (TWA): PEL: Time Weighted Average (TWA): PEL: Time Weighted Average (TWA): Evapo Specific Y Bulk d faint Vapou	Exposure type as Cr as Cr as Sb as Sb as Sb as Sb DPERTIES ration rate : Not ic Gravity : Not lensity : Not r pressure : Not	ACGIH OSHA Z MX OEI ACGIH OSHA Z MX OEI applicable
Components Rutile, antimony chromium buff	0.5 mg/m3 0.5 mg/m3 0.5 mg/m3 0.5 mg/m3 0.5 mg/m3 0.5 mg/m3 9. PHYSIC : Solid : pellet : GRE : Very : Not c	Time Weighted Average (TWA): PEL: Time Weighted Average (TWA): Time Weighted Average (TWA): PEL: Time Weighted Average (TWA): Built display ts Specification Specification Y Bulk display faint Vapou determined Vapou	Exposure type as Cr as Cr as Sb as Sb as Sb as Sb oPERTIES ration rate : Not ic Gravity : Not lensity : Not r pressure : Not r density : Not	ACGIH OSHA Z MX OEI ACGIH OSHA Z MX OEI applicable applicable applicable applicable
Components Rutile, antimony chromium buff 	0.5 mg/m3 0.5 mg/m3 0.5 mg/m3 0.5 mg/m3 0.5 mg/m3 0.5 mg/m3 9. PHYSIC : Solid : pellet : GRE : Very : Not c	Time Weighted Average (TWA): PEL: Time Weighted Average (TWA): Time Weighted Average (TWA): PEL: Time Weighted Average (TWA): PEL: Time Weighted Average (TWA): PEL: Time Weighted Average (TWA): Evapo Specific Y Bulk d faint Vapou	Exposure type as Cr as Cr as Sb as Sb as Sb as Sb oPERTIES ration rate : Not ic Gravity : Not lensity : Not r pressure : Not r density : Not	ACG OSHA MX C ACG OSHA MX C

10. STABILITY AND REACTIVITY

MATERIAL SAFETY DATA SHEET **DARK GREY GF**

Version Number 1.1 Revision Date 09/21/2007

Page 4 of 7 Print Date 12/1/2011

Stability	:	Stable.
Hazardous Polymerization	:	Will not occur.
Conditions to avoid	:	Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
Incompatible Materials	:	Incompatible with strong acids and oxidizing agents.
Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
70624-18-9	1,6-Hexanediamine, N,N'-bis(2,2,6,6-tetrameth yl-4-piperidinyl)-,polymer with 2,4,6-trichloro-1,3,5-triazi ne, reaction products	Irritant	Eyes, Skin, Respiratory system.
68186-90-3	Rutile, antimony chromium buff	Irritant	Eyes, Skin, Respiratory system.

LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
70624-18-9	1,6-Hexanediamine, N,N'-bis(2,2,6,6-tetrameth yl-4-piperidinyl)-,polymer with 2,4,6-trichloro-1,3,5-triazi ne, reaction products	Oral LD50 Dermal LD50	> 2,000 mg/kg > 3,000 mg/kg	rat rat

Additional Health Hazard Information:

Rutile, antimony chromium buff 68186-90-3 Can cause eye irritation. Can cause skin irritation. Symptoms may include redness and burning of skin, and other skin damage. Additional symptoms of skin contact may include: antimony measles (a red, pimply rash).

12. ECOLOGICAL INFORMATION

Persistence and degradability

: Not readily biodegradable.

PolyOne.

MATERIAL SAFETY DATA SHEET **DARK GREY GF**

Environmental Toxicity	: Chemicals are not readily available as they are bound within the polymer matrix.
Bioaccumulation Potential	: Chemicals are not readily available as they are bound within the polymer matrix.
Additional advice	: No data available
	13. DISPOSAL CONSIDERATIONS
Product	: Like most thermoplastic plastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste materia has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. DOT Classification	: Not regulated for transportation.
ICAO/IATA (air)	: Refer to specific regulation.
IMO / IMDG (maritime)	: Refer to specific regulation.
	15. REGULATORY INFORMATION
US Regulations:	
OSHA Status	: Classified as hazardous based on components.
TSCA Status	: All components of this product are listed on or exempt from the TSCA Inventory.
US. EPA CERCLA Hazardous	Substances (40 CFR 302)
Not applicable	
California Proposition 65	: Not applicable

PolyOne.

MATERIAL SAFETY DATA SHEET DARK GREY GF

Version Number 1.1 Revision Date 09/21/2007 Page 6 of 7 Print Date 12/1/2011

SARA Title III Section 302 Extremely Hazardous Substance

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

SARA Title III Section 313 Toxic Chemicals:

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

Chemical Name	CAS-No.	Weight %
CHROMIUM III COMPOUNDSANTIMONY	68186-90-3	1.00 - 5.00
COMPOUNDS		
ZINC COMPOUNDS	1314-98-3	10.00 - 30.00

Canadian Regulations:

National Pollutant Release Inventory (NPRI)

Chemical Name	CAS-No.	Weight %	NPRI ID#
Rutile, antimony chromium buff	68186-90-3	1.00 - 5.00	69
		1.00 - 5.00	17
Zinc sulfide	1314-98-3	10.00 - 30.00	231

WHMIS Classification : D2B

WHMIS Ingredient Disclosure List

CAS-No.
68186-90-3

DSL

All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.

National Inventories:

Australia AICS	:	Listed
China IECS	:	Listed
Europe EINECS	:	Listed
Japan ENCS	:	Not determined
Korea KECI	:	Not determined
Philippines PICCS	:	Not determined

:

16. OTHER INFORMATION

PolyOne

MATERIAL SAFETY DATA SHEET **DARK GREY GF**

Version Number 1.1 Revision Date 09/21/2007 Page 7 of 7 Print Date 12/1/2011

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.