# MATERIAL SAFETY DATA SHEET WARM GRAY 5C PE OUT

Version Number 1.0 Revision Date 09/24/2007

Page 1 of 7 Print Date 12/1/2011

#### 1. PRODUCT AND COMPANY IDENTIFICATION

#### POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone Emergency telephone	:	Product Stewardship (770) 271-5902 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	WARM GRAY 5C PE OUT
Product code	:	CC10104291
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

#### 2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight %
1,6-Hexanediamine,	70624-18-9	1 - 5
N,N'-bis(2,2,6,6-tetramethyl-4-piperidinyl)-,		
polymer with 2,4,6-trichloro-1,3,5-triazine,		
reaction products		
Phenol,	25973-55-1	1 - 5
2-(2H-benzotriazol-2-yl)-4,6-bis(1,1-dimeth		
ylpropyl)-		
Titanium dioxide	13463-67-7	5 - 10

#### **3. HAZARDS IDENTIFICATION**

#### **EMERGENCY OVERVIEW**

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

#### POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation Ingestion Eyes	<ul> <li>Resin particles, like other inert materials, can be mechanically irritating.</li> <li>May be harmful if swallowed.</li> <li>Resin particles, like other inert materials, are mechanically irritating to eyes.</li> </ul>

PolyOne.

# MATERIAL SAFETY DATA SHEET WARM GRAY 5C PE OUT

Version Number 1.0 Revision Date 09/24/2007 Page 2 of 7 Print Date 12/1/2011

Skin	Experience shows no unusual dermatitis hazard from routine handlir			
Chronic exposure	: Refer to Section 11 for Toxicological Information.			
Medical Conditions Aggravated by Exposure:				
	4. FIRST AID MEASURES			
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.			
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.			
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.			
Skin	: Wash off with soap and plenty of water. If skin irritation persists seel medical attention.			
	5. FIRE-FIGHTING MEASURES			
Flash point	: Not applicable			
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media	<ul> <li>Not applicable</li> <li>Not applicable</li> <li>Not applicable</li> <li>Carbon dioxide blanket, Water spray, Dry powder, Foam.</li> </ul>			
Special Fire Fighting Procedures	: Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.			
Unusual Fire/Explosion Hazards	<ul> <li>Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.</li> </ul>			
	6. ACCIDENTAL RELEASE MEASURES			
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.			
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.			
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 12			

PolyOne.

# MATERIAL SAFETY DATA SHEET WARM GRAY 5C PE OUT

Version Number 1.0 Revision Date 09/24/2007 Page 3 of 7 Print Date 12/1/2011

		7. HANDLING AND STORAGE
Handling	:	Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.
Storage	:	Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.
8. EXI	OSUI	RE CONTROLS / PERSONAL PROTECTION
Respiratory protection	:	No personal respiratory protective equipment normally required.
Eye/Face Protection	:	Safety glasses with side-shields
Hand protection	:	Protective gloves
Skin and body protection	:	Long sleeved clothing
Additional Protective Measures	:	Safety shoes
General Hygiene Considerations	:	Handle in accordance with good industrial hygiene and safety practice Wash hands before breaks and at the end of workday.
Engineering measures	:	Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.
Exposure limit(s)		

Components	Value	Exposure time	Exposure type	List:
Titanium dioxide	10 mg/m3	Time Weighted Average		ACGIH
		(TWA):		
	15 mg/m3	PEL:	Total dust.	OSHA Z1
	10 mg/m3	Time Weighted Average	as Ti	MX OEL
		(TWA):		
	20 mg/m3	Short Term Exposure Limit	as Ti	MX OEL
		(STEL):		

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

- Form Appearance Color Odour Melting point/range Boiling Point: Water solubility
- Solid
  pellets
  GREY
  Very faint
  Not determined
  Not applicable
  Insoluble
- Evaporation rate Specific Gravity Bulk density Vapour pressure Vapour density pH
- Not applicable
  Not determined
  Not established
  Not applicable
  Not applicable
  Not applicable

PolvOne

# **MATERIAL SAFETY DATA SHEET** WARM GRAY 5C PE OUT

Version Number 1.0 Revision Date 09/24/2007

\_

Page 4 of 7 Print Date 12/1/2011

	10. STABILITY AND REACTIVITY		
Stability	: Stable.		
Hazardous Polymerization	: Will not occur.		
Conditions to avoid	: Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.		
Incompatible Materials	: Incompatible with strong acids and oxidizing agents.		
Hazardous decomposition products	: Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.		

#### **11. TOXICOLOGICAL INFORMATION**

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

<u>Toxicity Overview</u> This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
70624-18-9	1,6-Hexanediamine, N,N'-bis(2,2,6,6-tetrameth yl-4-piperidinyl)-,polymer with 2,4,6-trichloro-1,3,5-triazi ne, reaction products	Irritant	Eyes, Skin, Respiratory system.
25973-55-1	Phenol, 2-(2H-benzotriazol-2-yl)-4 ,6-bis(1,1-dimethylpropyl) -	Systemic effects	Kidney, Liver, reproductive system.
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.

#### LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
70624-18-9	1,6-Hexanediamine, N,N'-bis(2,2,6,6-tetrameth yl-4-piperidinyl)-,polymer with 2,4,6-trichloro-1,3,5-triazi ne, reaction products	Oral LD50 Dermal LD50	> 2,000 mg/kg > 3,000 mg/kg	rat rat

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

PolyOne.

# MATERIAL SAFETY DATA SHEET WARM GRAY 5C PE OUT

Version Number 1.0 Revision Date 09/24/2007 Page 5 of 7 Print Date 12/1/2011

CAS-No.	Chemical Name	OSHA	IARC	NTP	
13463-67-7	Fitanium dioxide	no	2B	no	
2B - The component is p NTP Carcinogen Classifi	cinogenic to humans. robably carcinogenic to hu ossibly carcinogenic to hur cations:	nans.			
	sonably anticipated to be a	human carcinogen.			
	12. ECOLOGICA	AL INFORMATION			
Persistence and degradab	ility : Not readily bio	odegradable.			
Environmental Toxicity	: Chemicals are polymer matrix	not readily available a x.	s they are bound v	vithin the	
Bioaccumulation Potentia		: Chemicals are not readily available as they are bound within the polymer matrix.			
Additional advice	: No data availa	ble			
	13. DISPOSAL (	CONSIDERATIONS			
Product	possible recycl generator of w classification,	moplastic plastics the p ling is preferred to disp aste material has the re transportation and disp eral, state/provincial ar	oosal or incineration esponsibility for proposal in accordance	on. The roper waste e with	
Contaminated packaging	has the response	referred when possible sibility for proper wast accordance with appl lations.	e classification, tra	ansportation	
	14. TRANSPOR	<b>TINFORMATION</b>			
U.S. DOT Classification	: Not regulated	for transportation.			
ICAO/IATA (air)	: Refer to specif	: Refer to specific regulation.			
IMO / IMDG (maritime)	: Refer to specif	ic regulation.			
	15. REGULATO	RY INFORMATION			
US Regulations:					

# MATERIAL SAFETY DATA SHEET WARM GRAY 5C PE OUT

Japan ENCS

Version Number 1.0 Page 6 of 7 Print Date 12/1/2011 Revision Date 09/24/2007 **OSHA Status** Classified as hazardous based on components. • **TSCA Status** All components of this product are listed on or exempt from the TSCA : Inventory. US. EPA CERCLA Hazardous Substances (40 CFR 302) Not applicable California Proposition : Not applicable 65 SARA Title III Section 302 Extremely Hazardous Substance Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation SARA Title III Section 313 Toxic Chemicals: Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation Canadian Regulations: National Pollutant Release Inventory (NPRI) Weight % Chemical Name CAS-No. NPRI ID# Rutile, antimony chromium buff 68186-90-3 0.10 - 1.00 69 0.10 - 1.00 17 WHMIS Classification : D2A DSL All components of this product are on the Canadian Domestic : Substances List (DSL) or are exempt. National Inventories: Australia AICS : Listed China IECS · Listed Europe EINECS Listed :

Not determined

•

*PolyOne* 

# MATERIAL SAFETY DATA SHEET WARM GRAY 5C PE OUT

Version Number 1.0 Revision Date 09/24/2007 Page 7 of 7 Print Date 12/1/2011

Korea KECI

: Not determined

Philippines PICCS

: Not determined

#### **16. OTHER INFORMATION**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.