MATERIAL SAFETY DATA SHEET **DEEP RED 18-1655TP**

Version Number 1.0 Revision Date 09/20/2007

Page 1 of 6 Print Date 12/1/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone:Emergency telephone:	Product Stewardship (770) 271-5902 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name :	DEEP RED 18-1655TP
Product code :	CC10104309
Chemical Name :	Mixture
CAS-No. :	Mixture
Product Use :	Industrial Applications

2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight %
Iron oxide	1309-37-1	1 - 5
Calcium carbonate	1317-65-3	5 - 10

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact		
Acute exposure			
Inhalation Ingestion Eyes	 Resin particles, like other inert materials, can be mechanically irritating. May be harmful if swallowed. Resin particles, like other inert materials, are mechanically irritating to 		
Skin	eyes. : Experience shows no unusual dermatitis hazard from routine handling.		
Chronic exposure	: Refer to Section 11 for Toxicological Information.		
Medical Conditions Aggravated by Exposure:	: None known.		

PolyOne.

MATERIAL SAFETY DATA SHEET **DEEP RED 18-1655TP**

Version Number 1.0 Revision Date 09/20/2007 Page 2 of 6 Print Date 12/1/2011

		4. FIRST AID MEASURES
Inhalation	:	Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	:	Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	:	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	:	Wash off with soap and plenty of water. If skin irritation persists seek medical attention.
		5. FIRE-FIGHTING MEASURES
Flash point	:	Not applicable
Flammable Limits		
Upper explosion limit		Not applicable
Lower explosion limit	:	Not applicable
Autoignition temperature	:	Not applicable
Suitable extinguishing media	:	Carbon dioxide blanket, Water spray, Dry powder, Foam.
Special Fire Fighting Procedures	:	Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.
Unusual Fire/Explosion Hazards	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.
	6. A	CCIDENTAL RELEASE MEASURES
Personal precautions	:	Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	:	Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	:	Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 13 of this MSDS for proper disposal methods.
		7. HANDLING AND STORAGE
Handling	:	Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.
Storage	:	Keep containers dry and tightly closed to avoid moisture absorption

2/6

PolyOne.

MATERIAL SAFETY DATA SHEET **DEEP RED 18-1655TP**

Version Number 1.0 Revision Date 09/20/2007

_

_

.

Page 3 of 6 Print Date 12/1/2011

8. H	EXPOSURE	CONTROLS / PERSONAL	PROTECTION		
Respiratory protection	: N	lo personal respiratory protecti	ve equipment normally r	required.	
	: Safety glasses with side-shields			1	
Eye/Face Protection	: 5				
Hand protection	: P	Protective gloves			
Skin and body protection	: L	Long sleeved clothing			
Additional Protective Measures	: S	Safety shoes			
General Hygiene Considerations		Iandle in accordance with good Vash hands before breaks and a		afety practice	
Engineering measures		leat only in areas with appropri ppropriate exhaust ventilation a		Provide	
Exposure limit(s)					
Components	Value	Exposure time	Exposure type	List:	
Calcium carbonate	5 mg/m3	PEL:	Respirable fraction.	OSHA Z1	
	15 mg/m3	PEL:	Total dust.	OSHA Z1	
	10 mg/m3	Time Weighted Average (TWA):		MX OEL	
	20 mg/m3	Short Term Exposure Limit		MX OEL	
		(SIEL):			
Iron oxide	5 mg/m3	(STEL): Time Weighted Average (TWA):	Respirable fraction.	ACGIH	
Iron oxide			Respirable fraction. Fume.	ACGIH OSHA Z1	
Iron oxide	5 mg/m3 10 mg/m3 5 mg/m3	Time Weighted Average (TWA):	-		
Iron oxide	10 mg/m3	Time Weighted Average (TWA): PEL: Time Weighted Average	Fume.	OSHA Z1	
Iron oxide	10 mg/m3 5 mg/m3 10 mg/m3	Time Weighted Average (TWA): PEL: Time Weighted Average (TWA): Short Term Exposure Limit	Fume. as Fe as Fe	OSHA Z1 MX OEL	
	10 mg/m3 5 mg/m3 10 mg/m3 9. PHYSIC	Time Weighted Average (TWA): PEL: Time Weighted Average (TWA): Short Term Exposure Limit (STEL): CAL AND CHEMICAL PRO	Fume. as Fe as Fe DPERTIES	OSHA Z1 MX OEL MX OEL	
Form	10 mg/m3 5 mg/m3 10 mg/m3 9. PHYSIC : Solid	Time Weighted Average (TWA): PEL: Time Weighted Average (TWA): Short Term Exposure Limit (STEL): CAL AND CHEMICAL PRO	Fume. as Fe as Fe DPERTIES ration rate : Not	OSHA Z1 MX OEL MX OEL applicable	
Form Appearance	10 mg/m3 5 mg/m3 10 mg/m3 9. PHYSIC : Solic : pelle	Time Weighted Average (TWA): PEL: Time Weighted Average (TWA): Short Term Exposure Limit (STEL): CAL AND CHEMICAL PRO	Fume. as Fe as Fe DPERTIES ration rate : Not ic Gravity : Not	OSHA Z1 MX OEL MX OEL applicable determined	
Form Appearance Color	10 mg/m3 5 mg/m3 10 mg/m3 9. PHYSIC : Solid : pelle : RED	Time Weighted Average (TWA): PEL: Time Weighted Average (TWA): Short Term Exposure Limit (STEL): CAL AND CHEMICAL PRO the Evapor sts Specifi Bulk d	Fume. as Fe as Fe DPERTIES ration rate : Not ic Gravity : Not ensity : Not	OSHA Z1 MX OEL MX OEL applicable determined established	
Form Appearance Color Odour	10 mg/m3 5 mg/m3 10 mg/m3 9. PHYSIO : Solid : pelle : RED : Very	Time Weighted Average (TWA): PEL: Time Weighted Average (TWA): Short Term Exposure Limit (STEL): CAL AND CHEMICAL PRO the Evapor the Evapor the Specific D Bulk d	Fume. as Fe as Fe OPERTIES ration rate : Not ic Gravity : Not ensity : Not r pressure : Not	OSHA Z1 MX OEL MX OEL applicable determined established applicable	
Form Appearance Color	10 mg/m3 5 mg/m3 10 mg/m3 9. PHYSIO : Solid : pelle : RED : Very : Not	Time Weighted Average (TWA): PEL: Time Weighted Average (TWA): Short Term Exposure Limit (STEL): CAL AND CHEMICAL PRO the Evapor the Evapor the Specific D Bulk d	Fume. as Fe as Fe OPERTIES ration rate : Not ic Gravity : Not ensity : Not r pressure : Not r density : Not	OSHA Z1 MX OEL MX OEL applicable determined established	

PolyOne

MATERIAL SAFETY DATA SHEET **DEEP RED 18-1655TP**

Version Number 1.0 Revision Date 09/20/2007 Page 4 of 6 Print Date 12/1/2011

Stability	:	Stable.
Hazardous Polymerization	:	Will not occur.
Conditions to avoid	:	Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
Incompatible Materials	:	Incompatible with strong acids and oxidizing agents.
Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
1309-37-1	Iron oxide	Systemic effects	Respiratory system.
1317-65-3	Calcium carbonate	Irritant	Eyes, Skin.
		Systemic effects	Eyes, Skin, Respiratory system.

Dereistance and degradability	. Not readily biodegradable
Persistence and degradability	: Not readily biodegradable.
Environmental Toxicity	: Chemicals are not readily available as they are bound within the polymer matrix.
Bioaccumulation Potential	: Chemicals are not readily available as they are bound within the polymer matrix.
Additional advice	: No data available
	13. DISPOSAL CONSIDERATIONS
Product	: Like most thermoplastic plastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste materia has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.

PolyOne.

MATERIAL SAFETY DATA SHEET **DEEP RED 18-1655TP**

Version Number 1.0 Revision Date 09/20/2007

Page 5 of 6 Print Date 12/1/2011

	14. TRANSPORT INFORMATION
U.S. DOT Classification	: Not regulated for transportation.
ICAO/IATA (air)	: Refer to specific regulation.
IMO / IMDG (maritime)	: Refer to specific regulation.
	15. REGULATORY INFORMATION
US Regulations:	
OSHA Status	: Classified as hazardous based on components.
TSCA Status	: All components of this product are listed on or exempt from the TSCA Inventory.
US. EPA CERCLA Hazardou	as Substances (40 CFR 302)
Not applicable	
California Proposition	Not applicable
65	n : Not applicable
65 SARA Title III Section 302 E	Extremely Hazardous Substance
65 SARA Title III Section 302 E	
65 SARA Title III Section 302 E	Extremely Hazardous Substance
65 SARA Title III Section 302 E	Extremely Hazardous Substance identified under this section, this product is Not Applicable under this regulatio
65 SARA Title III Section 302 E Unless specific chemicals are SARA Title III Section 313 T	Extremely Hazardous Substance identified under this section, this product is Not Applicable under this regulatio
65 SARA Title III Section 302 E Unless specific chemicals are SARA Title III Section 313 T	Extremely Hazardous Substance identified under this section, this product is Not Applicable under this regulatio Yoxic Chemicals:
65 SARA Title III Section 302 E Unless specific chemicals are SARA Title III Section 313 T Unless specific chemicals are Canadian Regulations:	Extremely Hazardous Substance identified under this section, this product is Not Applicable under this regulatio Yoxic Chemicals:
65 SARA Title III Section 302 E Unless specific chemicals are SARA Title III Section 313 T Unless specific chemicals are Canadian Regulations:	Extremely Hazardous Substance identified under this section, this product is Not Applicable under this regulatio 'oxic Chemicals: identified under this section, this product is Not Applicable under this regulatio
65 SARA Title III Section 302 E Unless specific chemicals are SARA Title III Section 313 T Unless specific chemicals are Canadian Regulations: National Pollutant Rel	Extremely Hazardous Substance identified under this section, this product is Not Applicable under this regulatio 'oxic Chemicals: identified under this section, this product is Not Applicable under this regulatio ease Inventory (NPRI)

PolyOne

MATERIAL SAFETY DATA SHEET **DEEP RED 18-1655TP**

Version Number 1.0 Revision Date 09/20/2007 Page 6 of 6 Print Date 12/1/2011

National Inventories:

Australia AICS	: Listed	
China IECS	: Listed	
Europe EINECS	: Not determined	1
Japan ENCS	: Listed	
Korea KECI	: Listed	
Philippines PICCS	: Listed	

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.