PolvOne

MATERIAL SAFETY DATA SHEET **RED UV 2**

Version Number 1.0 Revision Date 09/26/2007 Page 1 of 8 Print Date 12/1/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone:Emergency telephone:	:	Product Stewardship (770) 271-5902 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	RED UV 2
Product code	:	CC10104467
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight %
Calcium carbonate	1317-65-3	1 - 5
Titanium dioxide	13463-67-7	1 - 5
C.I. Pigment Red 108	58339-34-7	30 - 60

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact		
Acute exposure			
Inhalation Ingestion Eyes	 Resin particles, like other inert materials, can be mechanically irritating. May be harmful if swallowed. Resin particles, like other inert materials, are mechanically irritating to eyes. 		
Skin	: Experience shows no unusual dermatitis hazard from routine handling.		
Chronic exposure	: Refer to Section 11 for Toxicological Information.		

POLYONE CORPORATION



MATERIAL SAFETY DATA SHEET **RED UV 2**

Version Number 1.0 Revision Date 09/26/2007 Page 2 of 8 Print Date 12/1/2011

Medical Conditions Aggravated by Exposure:	: None known.
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases or doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists see medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: Not applicable
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media	 Not applicable Not applicable Not applicable Carbon dioxide blanket, Water spray, Dry powder, Foam.
Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	 Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 1 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.



MATERIAL SAFETY DATA SHEET **RED UV 2**

Version Number	er 1.0
Revision Date	09/26/2007

Page 3 of 8 Print Date 12/1/2011

Storage

: Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Respiratory protection	:	No personal respiratory protective equipment normally required.
Eye/Face Protection	:	Safety glasses with side-shields
Hand protection	:	Protective gloves
Skin and body protection	:	Long sleeved clothing
Additional Protective Measures	:	Safety shoes
General Hygiene Considerations	:	Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.
Engineering measures	:	Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.

Exposure limit(s)

PolyOne

MATERIAL SAFETY DATA SHEET **RED UV 2**

Version Number 1.0 Revision Date 09/26/2007 Page 4 of 8 Print Date 12/1/2011

Components	Value	Exposure time	Exposure type	List:
C.I. Pigment Red 108	0.002 mg/m3	Time Weighted Average (TWA):	Respirable fraction. as Cd	ACGIH
	0.01 mg/m3	Time Weighted Average (TWA):	as Cd	ACGIH
	0.005 mg/m3	Time Weighted Average (TWA):		OSHA
	0.0025 mg/m3	OSHA Action level:		OSHA
	0.01 mg/m3	Time Weighted Average (TWA):	Total dust. as Cd	MX OEL
	0.002 mg/m3	Time Weighted Average (TWA):	Respirable dust. as Cd	MX OEL
	0.2 mg/m3	Time Weighted Average (TWA):	as Se	ACGIH
	0.2 mg/m3	PEL:	as Se	OSHA Z1
	0.2 mg/m3	Time Weighted Average (TWA):	as Se	MX OEL
Calcium carbonate	5 mg/m3	PEL:	Respirable fraction.	OSHA Z1
	15 mg/m3	PEL:	Total dust.	OSHA Z1
	10 mg/m3	Time Weighted Average (TWA):		MX OEL
	20 mg/m3	Short Term Exposure Limit (STEL):		MX OEL
Titanium dioxide	10 mg/m3	Time Weighted Average (TWA):		ACGIH
	15 mg/m3	PEL:	Total dust.	OSHA Z1
	10 mg/m3	Time Weighted Average (TWA):	as Ti	MX OEL
	20 mg/m3	Short Term Exposure Limit (STEL):	as Ti	MX OEL

9. PHYSICAL AND CHEMICAL PROPERTIES

Form Appearance Color Odour Melting point/range Boiling Point: Water solubility Solid
pellets
RED
Very faint
Not determined
Not applicable
Insoluble

: Stable.

:

Evaporation rate Specific Gravity Bulk density Vapour pressure Vapour density pH

Keep away from oxidizing agents and open flame. To avoid thermal

Not applicableNot determined

: Not established

- Not applicableNot applicable
- Not applicableNot applicable

10. STABILITY AND REACTIVITY

Stability

Hazardous Polymerization : Will not occur.

Conditions to avoid

4/8

MATERIAL SAFETY DATA SHEET **RED UV 2**

Version Number 1.0 Revision Date 09/26/2007

Page 5 of 8 Print Date 12/1/2011

 decomposition, do not overheat.

 Incompatible Materials
 : Incompatible with strong acids and oxidizing agents.

Hazardous decomposition
products:Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen
(NOx), other hazardous materials, and smoke are all possible.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
1317-65-3	Calcium carbonate	Irritant	Eyes, Skin.
		Systemic effects	Eyes, Skin, Respiratory system.
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.
58339-34-7	C.I. Pigment Red 108	Irritant	Eyes, Skin.
		Systemic effects	Liver, central nervous system
			(CNS), Kidney.

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
13463-67-7	Titanium dioxide	no	2B	no
58339-34-7	C.I. Pigment Red 108	yes	1	no

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

Additional Health Hazard Information:

C.I. Pigment Red 108 58339-34-7 Can produce rapid and sometimes fatal pulmonary edema. Chronic absorption leads to liver and kidney damage.

12. ECOLOGICAL INFORMATION

Persistence and degradability	:	Not readily biodegradable.
Environmental Toxicity	:	Chemicals are not readily available as they are bound within the polymer matrix.



MATERIAL SAFETY DATA SHEET **RED UV 2**

sion Number 1.0 ision Date 09/26/2007	Page of Page of Print Date 12/1/.
Bioaccumulation Potential	: Chemicals are not readily available as they are bound within the polymer matrix.
Additional advice	: No data available
	13. DISPOSAL CONSIDERATIONS
Product	: Like most thermoplastic plastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste materi has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. DOT Classification	: Not regulated for transportation.
ICAO/IATA (air)	: Refer to specific regulation.
IMO / IMDG (maritime)	: Refer to specific regulation.
	15. REGULATORY INFORMATION
US Regulations:	
OSHA Status	: Classified as hazardous based on components.
TSCA Status	: All components of this product are listed on or exempt from the TSC Inventory.
US. EPA CERCLA Hazardous	Substances (40 CFR 302)
Not applicable	
California Proposition 65	: WARNING! This product contains a chemical known to the State o California to cause cancer., WARNING! This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

MATERIAL SAFETY DATA SHEET **RED UV 2**

Version Number 1.0 Revision Date 09/26/2007 Page 7 of 8 Print Date 12/1/2011

SARA Title III Section 302 Extremely Hazardous Substance

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

SARA Title III Section 313 Toxic Chemicals:

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulationChemical NameCAS-No.Weight %CADMIUM COMPOUNDSSELENIUM COMPOUNDS58339-34-730.00 - 60.00

Canadian Regulations:

	National Pollutant Release Inventory (NPRI)			
Γ	Chemical Name	CAS-No.	Weight %	NPRI ID#
Γ	C.I. Pigment Red 108	58339-34-7	30.00 - 60.00	233
Γ			30.00 - 60.00	200

WHMIS Classification : D2A

WHMIS Ingredient Disclosure List

CAS-No.	
58339-34-7	

DSL

All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.

National Inventories:

Australia AICS	: Listed	
China IECS	: Listed	
Europe EINECS	: Listed	
Japan ENCS	: Not deter	rmined
Korea KECI	: Not deter	rmined
Philippines PICCS	: Not deter	rmined

:

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The

<u>PolyOne</u>

MATERIAL SAFETY DATA SHEET **RED UV 2**

Version Number 1.0 Revision Date 09/26/2007 Page 8 of 8 Print Date 12/1/2011

information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.