PolvOne

MATERIAL SAFETY DATA SHEET **PVC GREEN**

Version Number 1.0 Revision Date 10/26/2007 Page 1 of 7 Print Date 12/2/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone Emergency telephone	:	Product Stewardship (770) 271-5902 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	PVC GREEN
Product code	:	CC10104512
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight %
Aluminate (Al(OH)63-), (OC-6-11)-, magnesium carbonate hydroxide (2:6:1:4)	11097-59-9	1 - 5
Titanium dioxide	13463-67-7	1 - 5
Calcium carbonate	1317-65-3	10 - 30

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation	: Particulates, like other inert materials can be mechanically irritating. Excessive inhalation of product vapors, especially during heating or processing, may be irritating to respiratory system.
Ingestion	: May be harmful if swallowed.
Eyes	: Particulates, like other inert materials can be mechanically irritating.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.

PolyOne.

MATERIAL SAFETY DATA SHEET PVC GREEN

Version Number 1.0 Revision Date 10/26/2007 Page 2 of 7 Print Date 12/2/2011

Medical Conditions: None known.Aggravated by Exposure:				
	4. FIRST AID MEASURES			
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.			
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.			
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for a least 15 minutes. If eye irritation persists, seek medical attention.			
Skin	: Wash off with soap and plenty of water. If skin irritation persists see medical attention.			
	5. FIRE-FIGHTING MEASURES			
Flash point	: Not applicable			
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media Special Fire Fighting Procedures	 Not applicable Not applicable Not applicable Carbon dioxide blanket, Water spray, Dry powder, Foam. Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne 			
Unusual Fire/Explosion Hazards	 contaminants. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible. May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under fire conditions. 			
	6. ACCIDENTAL RELEASE MEASURES			
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.			
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.			
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 3 of this MSDS for proper disposal methods.			

PolyOne

MATERIAL SAFETY DATA SHEET **PVC GREEN**

Version Number 1.0 Revision Date 10/26/2007 Page 3 of 7 Print Date 12/2/2011

		7. HANDLING AND STORAGE			
Handling	:	Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.			
Storage	rage : Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.				
8. EXI	POSUF	RE CONTROLS / PERSONAL PROTECTION			
Respiratory protection	:	No personal respiratory protective equipment normally required.			
Eye/Face Protection	:	Safety glasses with side-shields			
Hand protection	:	Protective gloves			
Skin and body protection	:	Long sleeved clothing			
Additional Protective Measures	:	Safety shoes			
General Hygiene Considerations	:	Handle in accordance with good industrial hygiene and safety practice Wash hands before breaks and at the end of workday.			
Engineering measures	:	Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.			

Exposure limit(s)

Components	Value	Exposure time	Exposure type	List:
Calcium carbonate	5 mg/m3	PEL:	Respirable fraction.	OSHA Z1
	15 mg/m3	PEL:	Total dust.	OSHA Z1
	10 mg/m3	Time Weighted Average		MX OEL
		(TWA):		
	20 mg/m3	Short Term Exposure Limit		MX OEL
		(STEL):		
Titanium dioxide	10 mg/m3	Time Weighted Average		ACGIH
		(TWA):		
	15 mg/m3	PEL:	Total dust.	OSHA Z1
	10 mg/m3	Time Weighted Average	as Ti	MX OEL
		(TWA):		
	20 mg/m3	Short Term Exposure Limit	as Ti	MX OEL
		(STEL):		

9. PHYSICAL AND CHEMICAL PROPERTIES

Form Appearance : Solid : pellets Evaporation rate Specific Gravity Not applicableNot determined

MATERIAL SAFETY DATA SHEET **PVC GREEN**

: GREEN

Version Number 1.0 Revision Date 10/26/2007

Color

: Very faint: Not determined: Not applicable: Insoluble	Vapour pressure Vapour density pH	Not applicableNot applicableNot applicable
10. STABILITY AN	D REACTIVITY	
: Stable.		
: Will not occur.		
		flame. To avoid thermal
acetal copolymers processing. At pro destructive and inv mechanically clear quantities of these	and with amine containing cessing conditions, these rolve rapid degradation. T a processing equipment to materials from coming in	g materials during materials are mutually 'horoughly purge and avoid even trace
(NOx), hydrogen c smoke are all possi or more) above 392 °C) may result in p	hloride (HCl), other hazar ible. Prolonged heating (a 2 °F (200 °C) or short terr roduct decomposition and	rdous materials, and approximately 30 minute n heating at 482 °F (250
	 Not determined Not applicable Insoluble 10. STABILITY AND Stable. Will not occur. Keep away from or decomposition, do Avoid contact with acetal copolymers processing. At prodestructive and invine chanically clear quantities of these Prevent cross contact Carbon dioxide (C (NOx), hydrogen c smoke are all possior more) above 392 °C) may result in product of the set of t	 Not determined Vapour density Not applicable pH Insoluble 10. STABILITY AND REACTIVITY Stable.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
11097-59-9	Aluminate (Al(OH)63-),	Irritant	Eyes, Skin.
	(OC-6-11)-, magnesium		
	carbonate hydroxide		
	(2:6:1:4)		
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.
1317-65-3	Calcium carbonate	Irritant	Eyes, Skin.
		Systemic effects	Eyes, Skin, Respiratory system.

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

Page 4 of 7 Print Date 12/2/2011

: Not established

PolvUn<u>e</u>

Bulk density

PolyOne.

7 1

POLYONE CORPORATION

MATERIAL SAFETY DATA SHEET **PVC GREEN**

VC GREEN					
ersion Number 1.0 evision Date 10/26/2007			Print	Page 5 Date 12/2/2	
50131011 Date 10/20/2007				Duit 12/2/2	
CAS-No.	Chemical Name	OSHA	IARC	NTP	
13463-67-7	Titanium dioxide	no	2B	no	
2B - The component is p NTP Carcinogen Classif	ccinogenic to humans. probably carcinogenic to huma possibly carcinogenic to human	15.			
2 - The component is rea	sonably anticipated to be a hu	_			
	12. ECOLOGICAL	INFORMATION			
Persistence and degradal	Persistence and degradability : Not readily biodegradable.				
Environmental Toxicity	nvironmental Toxicity : Chemicals are not readily available as they are bound within the polymer matrix.				
Bioaccumulation Potenti	al : Chemicals are no polymer matrix.	: Chemicals are not readily available as they are bound within the polymer matrix.			
Additional advice	: No data available	: No data available			
	13. DISPOSAL CO	NSIDERATIONS			
Product	possible recycling generator of wast classification, tran	plastic plastics the j g is preferred to disp e material has the re- nsportation and disp , state/provincial an	oosal or incineration esponsibility for prosal in accordance	on. The oper waste with	
Contaminated packaging	has the responsibility and disposal in ac	: Recycling is preferred when possible. The generator of waste materia has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.			
	14. TRANSPORT	INFORMATION			
U.S. DOT Classification	: Not regulated for	transportation.			
ICAO/IATA (air)	: Refer to specific	egulation			

IMO / IMDG (maritime) : Refer to specific regulation.

15. REGULATORY INFORMATION

US Regulations:

POLYONE CORPORATION

PolyOne.

MATERIAL SAFETY DATA SHEET **PVC GREEN**

/ersion Number 1.0 Revision Date 10/26/2007		Pr	Page 6 of 7 int Date 12/2/2011		
OSHA Status : Classified as ha	zardous based on	components.			
TSCA Status : All component Inventory.	s of this product a	re listed on or exem	pt from the TSCA		
US. EPA CERCLA Hazardous Substances (40 CFR	302)				
Not applicable					
California Proposition : Not applicable 65					
SARA Title III Section 302 Extremely Hazardous S	ubstance				
Unless specific chemicals are identified under this se	ection, this produc	t is Not Applicable	under this regulation		
Unless specific chemicals are identified under this so Canadian Regulations: National Pollutant Release Inventory (NPRI)	ection, this produc	t is Not Applicable	under this regulation		
Chemical Name	CAS-No.	Weight %	NPRI ID#		
Phthalocyanine green	1328-53-6	10.00 - 30.00	71		
Zinc stearate	557-05-1	0.10 - 1.00	231		
WHMIS Classification : D2A WHMIS Ingredient Disclosure List CAS-No. 11097-59-9 1328-53-6					
DSL : All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.					
National Inventories:					
Australia AICS : Listed					
	5/7				

PolvOne

MATERIAL SAFETY DATA SHEET **PVC GREEN**

Version Number 1.0 Revision Date 10/26/2007 Page 7 of 7 Print Date 12/2/2011

China IECS:ListedEurope EINECS:ListedJapan ENCS:Not determinedKorea KECI:ListedPhilippines PICCS:Listed

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.