PolvOne

MATERIAL SAFETY DATA SHEET BLACK P-C 40%

Version Number 1.0 Revision Date 10/30/2007

Page 1 of 7 Print Date 12/2/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone:Emergency telephone:		Product Stewardship (770) 271-5902 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	BLACK P-C 40%
Product code	:	CC10105612
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight %
1,6-Hexanediamine,	70624-18-9	1 - 5
N,N'-bis(2,2,6,6-tetramethyl-4-piperidinyl)-,		
polymer with 2,4,6-trichloro-1,3,5-triazine,		
reaction products		
Phenol,	25973-55-1	1 - 5
2-(2H-benzotriazol-2-yl)-4,6-bis(1,1-dimeth		
ylpropyl)-		
Titanium dioxide	13463-67-7	1 - 5

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation Ingestion Eyes	 Resin particles, like other inert materials, can be mechanically irritating. May be harmful if swallowed. Resin particles, like other inert materials, are mechanically irritating to eyes.



MATERIAL SAFETY DATA SHEET **BLACK P-C 40%**

Version Number 1.0 Revision Date 10/30/2007 Page 2 of 7 Print Date 12/2/2011

Skin	: Experience shows no unusual dermatitis hazard from routine handlin
Chronic exposure	: Refer to Section 11 for Toxicological Information.
Medical Conditions Aggravated by Exposure:	: None known.
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for a least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists se medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: Not applicable
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media Special Fire Fighting Procedures	 Not applicable Not applicable Not applicable Carbon dioxide blanket, Water spray, Dry powder, Foam. Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne
Unusual Fire/Explosion Hazards	 contaminants. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section of this MSDS for proper disposal methods.

POLYONE CORPORATION

<u>PolyOne</u>.

MATERIAL SAFETY DATA SHEET BLACK P-C 40%

Version Number 1.0 Revision Date 10/30/2007 Page 3 of 7 Print Date 12/2/2011

		7. HANDLING AND STORAGE		
Handling	:	Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.		
Storage	:	Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.		
8. EXPO	OSUE	RE CONTROLS / PERSONAL PROTECTION		
Respiratory protection	:	No personal respiratory protective equipment normally required.		
Eye/Face Protection	:	Safety glasses with side-shields		
Hand protection	:	Protective gloves		
Skin and body protection	:	Long sleeved clothing		
Additional Protective Measures	:	Safety shoes		
General Hygiene Considerations	:	Handle in accordance with good industrial hygiene and safety practice Wash hands before breaks and at the end of workday.		
Engineering measures	:	Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.		

Components	Value	Exposure time	Exposure type	List:
Titanium dioxide	10 mg/m3	Time Weighted Average		ACGIH
		(TWA):		
	15 mg/m3	PEL:	Total dust.	OSHA Z1
	10 mg/m3	Time Weighted Average	as Ti	MX OEL
	_	(TWA):		
	20 mg/m3	Short Term Exposure Limit	as Ti	MX OEL
		(STEL):		

9. PHYSICAL AND	CHEMICAL PROPERTIES

- Form Appearance Color Odour Melting point/range Boiling Point: Water solubility
- Solid
 pellets
 BLACK
 Very faint
 Not determined
 Not applicable
 Insoluble
- Evaporation rate Specific Gravity Bulk density Vapour pressure Vapour density pH
- Not applicable
 Not determined
 Not established
 Not applicable
 Not applicable
 Not applicable

PolyOne.

MATERIAL SAFETY DATA SHEET BLACK P-C 40%

Version Number 1.0 Revision Date 10/30/2007 Page 4 of 7 Print Date 12/2/2011

10. STABILITY AND REACTIVITY		
Stability	: Stable.	
Hazardous Polymerization	: Will not occur.	
Conditions to avoid	: Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.	
Incompatible Materials	: Incompatible with strong acids and oxidizing agents.	
Hazardous decomposition products	: Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.	

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

<u>Toxicity Overview</u> This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
70624-18-9	1,6-Hexanediamine, N,N'-bis(2,2,6,6-tetrameth yl-4-piperidinyl)-,polymer with 2,4,6-trichloro-1,3,5-triazi ne, reaction products	Irritant	Eyes, Skin, Respiratory system.
25973-55-1	Phenol, 2-(2H-benzotriazol-2-yl)-4 ,6-bis(1,1-dimethylpropyl) -	Systemic effects	Kidney, Liver, reproductive system.
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.

LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
70624-18-9	1,6-Hexanediamine, N,N'-bis(2,2,6,6-tetrameth yl-4-piperidinyl)-,polymer with 2,4,6-trichloro-1,3,5-triazi ne, reaction products	Oral LD50 Dermal LD50	> 2,000 mg/kg > 3,000 mg/kg	rat rat

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

PolyOne.

MATERIAL SAFETY DATA SHEET **BLACK P-C 40%**

Version Number 1.0 Revision Date 10/30/2007 Page 5 of 7 Print Date 12/2/2011

13403-07-7	namum 0			o. Chemical Name OSHA IARC Titanium dioxide no 2B	
3463-67-7 Titanium dioxide no 2B no					
IARC Carcinogen Classifi 1 - The component is carc 2A - The component is pro 2B - The component is po NTP Carcinogen Classific 1 - The component is know 2 - The component is reas	inogenic obably ca ssibly car ations: wn to be a	rcinogenic to huma cinogenic to human a human carcinogen			
	12	2. ECOLOGICAL	INFORMATION		
Persistence and degradabi	lity :	Not readily biode	gradable.		
Environmental Toxicity	:	Chemicals are not polymer matrix.	readily available as	s they are bound w	vithin the
Bioaccumulation Potentia	l :	Chemicals are not polymer matrix.	readily available as	s they are bound w	vithin the
Additional advice	:	: No data available			
	1	3. DISPOSAL CO	NSIDERATIONS		
Product	:	possible recycling generator of waste classification, trar	plastic plastics the p s is preferred to disp e material has the re asportation and disp , state/provincial an	osal or incinerations of a sponsibility for prosal in accordance	on. The coper waste with
Contaminated packaging	: Recycling is preferred when possible. The generator of waste mate has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincia and local regulations.		ansportation		
	1	4. TRANSPORT	INFORMATION		
U.S. DOT Classification	:	Not regulated for	transportation.		
ICAO/IATA (air)	:	Refer to specific r	-		
IMO / IMDG (maritime)	:	Refer to specific r	regulation.		
	15	5. REGULATORY	INFORMATION		
US Regulations:					

PolyOne.

MATERIAL SAFETY DATA SHEET **BLACK P-C 40%**

Version Number 1.0 Revision Date 10/30/2007	Page 6 of 7 Print Date 12/2/2011
	Classified as hogordous based on components
OSHA Status :	Classified as hazardous based on components.
TSCA Status :	All components of this product are listed on or exempt from the TSCA Inventory.
US. EPA CERCLA Hazardous Sub	stances (40 CFR 302)
Not applicable	
California Proposition : 65	Not applicable
SARA Title III Section 302 Extrem	ely Hazardous Substance
	fied under this section, this product is Not Applicable under this regulation
SARA Title III Section 313 Toxic C	Chemicals:
Unless specific chemicals are identi	fied under this section, this product is Not Applicable under this regulation
Canadian Regulations:	
National Pollutant Release In	nventory (NPRI)
Not applicable	
WHMIS Classification :	D2A
DSL :	All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.
National Inventories:	
Australia AICS :	Listed
China IECS :	Listed
Europe EINECS :	Listed
Japan ENCS :	Not determined
Korea KECI :	Not determined
Philippines PICCS :	Not determined

PolyOne

MATERIAL SAFETY DATA SHEET BLACK P-C 40%

Version Number 1.0 Revision Date 10/30/2007 Page 7 of 7 Print Date 12/2/2011

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.