PolvOne

### MATERIAL SAFETY DATA SHEET FIRESTIK PINK

Version Number 1.0 Revision Date 11/13/2007 Page 1 of 7 Print Date 12/2/2011

### 1. PRODUCT AND COMPANY IDENTIFICATION

#### POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone Emergency telephone	:	Product Stewardship (770) 271-5902 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	FIRESTIK PINK
Product code	:	CC10105832
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

### 2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight %
Aluminate (Al(OH)63-), (OC-6-11)-, magnesium carbonate hydroxide (2:6:1:4)	11097-59-9	1 - 5
Calcium carbonate	1317-65-3	5 - 10
Titanium dioxide	13463-67-7	30 - 60

#### 3. HAZARDS IDENTIFICATION

#### **EMERGENCY OVERVIEW**

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

#### POTENTIAL HEALTH EFFECTS

<b>Routes of Exposure:</b>	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation	: Particulates, like other inert materials can be mechanically irritating. Excessive inhalation of product vapors, especially during heating or processing, may be irritating to respiratory system.
Ingestion	: May be harmful if swallowed.
Eyes	: Particulates, like other inert materials can be mechanically irritating.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.

**POLYONE CORPORATION** 

PolyOne.

## MATERIAL SAFETY DATA SHEET FIRESTIK PINK

Version Number 1.0 Revision Date 11/13/2007 Page 2 of 7 Print Date 12/2/2011

Medical Conditions       : None known.         Aggravated by Exposure:					
	4. FIRST AID MEASURES				
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases o doubt seek medical advice.				
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.				
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for a least 15 minutes. If eye irritation persists, seek medical attention.				
Skin	: Wash off with soap and plenty of water. If skin irritation persists see medical attention.				
	5. FIRE-FIGHTING MEASURES				
Flash point	: Not applicable				
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media Special Fire Fighting Procedures	<ul> <li>Not applicable</li> <li>Not applicable</li> <li>Not applicable</li> <li>Not applicable</li> <li>Carbon dioxide blanket, Water spray, Dry powder, Foam.</li> <li>Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne</li> </ul>				
Unusual Fire/Explosion Hazards	<ul> <li>contaminants.</li> <li>Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible. May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under fire conditions.</li> </ul>				
	5. ACCIDENTAL RELEASE MEASURES				
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.				
Environmental precautions	: Should not be released into the environment. The product should no be allowed to enter drains, water courses or the soil.				
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 1 of this MSDS for proper disposal methods.				

PolyOne

## MATERIAL SAFETY DATA SHEET FIRESTIK PINK

Version Number 1.0 Revision Date 11/13/2007 Page 3 of 7 Print Date 12/2/2011

	7.	HANDLING AND STORAGE				
Handling		ake measures to prevent the build up of electrostatic charge. Heat nly in areas with appropriate exhaust ventilation.				
Storage	rage : Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.					
8. EXP	OSURE	<b>CONTROLS / PERSONAL PROTECTION</b>				
Respiratory protection	: N	to personal respiratory protective equipment normally required.				
Eye/Face Protection	: S	afety glasses with side-shields				
Hand protection	: P	rotective gloves				
Skin and body protection	: L	ong sleeved clothing				
Additional Protective Measures	: S	afety shoes				
General Hygiene Considerations		Iandle in accordance with good industrial hygiene and safety practice Vash hands before breaks and at the end of workday.				
Engineering measures		leat only in areas with appropriate exhaust ventilation. Provide ppropriate exhaust ventilation at machinery.				

Exposure limit(s)

Components	Value	Exposure time	Exposure type	List:
Calcium carbonate	oonate 5 mg/m3 PEL:		Respirable fraction.	OSHA Z1
	15 mg/m3	PEL:	Total dust.	OSHA Z1
	10 mg/m3	Time Weighted Average		MX OEL
		(TWA):		
	20 mg/m3	Short Term Exposure Limit		MX OEL
		(STEL):		
Titanium dioxide	10 mg/m3	Time Weighted Average		ACGIH
		(TWA):		
	15 mg/m3	PEL:	Total dust.	OSHA Z1
	10 mg/m3	Time Weighted Average	as Ti	MX OEL
		(TWA):		
	20 mg/m3	Short Term Exposure Limit	as Ti	MX OEL
		(STEL):		

### 9. PHYSICAL AND CHEMICAL PROPERTIES

Form Appearance : Solid : pellets Evaporation rate Specific Gravity Not applicableNot determined

### **MATERIAL SAFETY DATA SHEET** FIRESTIK PINK

Version Number 1.0	
Revision Date 11/13/2007	

Odour Melting point/range Boiling Point: Water solubility	<ul><li>Very faint</li><li>Not determined</li><li>Not applicable</li><li>Insoluble</li></ul>	Bulk density Vapour pressure Vapour density pH	<ul><li>Not established</li><li>Not applicable</li><li>Not applicable</li><li>Not applicable</li><li>Not applicable</li></ul>		
	10. STABILITY AND F	REACTIVITY			
Stability	: Stable.				
Hazardous Polymerization	: Will not occur.				
Conditions to avoid	1 7	: Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.			
Incompatible Materials	acetal copolymers and processing. At proces destructive and involv mechanically clean pr quantities of these ma	Avoid contact with strong oxidizers. Also, avoid contact with acetal or acetal copolymers and with amine containing materials during processing. At processing conditions, these materials are mutually destructive and involve rapid degradation. Thoroughly purge and mechanically clean processing equipment to avoid even trace quantities of these materials from coming in contact with each other. Prevent cross contamination of feedstocks.			
Hazardous decomposition products	(NOx), hydrogen chlo smoke are all possible or more) above 392 °I	F (200 °C) or short term luct decomposition and	dous materials, and pproximately 30 minute 1 heating at 482 °F (250		

### 11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
11097-59-9	Aluminate (Al(OH)63-), (OC-6-11)-, magnesium carbonate hydroxide (2:6:1:4)	Irritant	Eyes, Skin.
1317-65-3	Calcium carbonate	Irritant	Eyes, Skin.
		Systemic effects	Eyes, Skin, Respiratory system.
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

Page 4 of 7 Print Date 12/2/2011

PolyOne

PolyOne.

# MATERIAL SAFETY DATA SHEET FIRESTIK PINK

ision Date 11/13/2007				Plint	Date 12/2
CAS-No.	Che	emical Name	OSHA	IARC	NTP
13463-67-7	Titanium d	ioxide	no	2B	no
IARC Carcinogen Class 1 - The component is ca 2A - The component is 2B - The component is	rcinogenic probably ca	rcinogenic to humans			
NTP Carcinogen Classi 1 - The component is kr 2 - The component is re	nown to be a		an carcinogen.		
	12	2. ECOLOGICAL I	NFORMATION		
Persistence and degrada	bility :	Not readily biodegr	adable.		
Environmental Toxicity	:	Chemicals are not r polymer matrix.	eadily available as	s they are bound w	vithin the
Bioaccumulation Potent	tial :	Chemicals are not r polymer matrix.	eadily available as	s they are bound w	vithin the
Additional advice	:	No data available			
	1	3. DISPOSAL CON	SIDERATIONS		
Product	:	Like most thermopl possible recycling i generator of waste classification, trans applicable federal,	s preferred to disp material has the re portation and disp	osal or incinerations sponsibility for prosal in accordance	on. The oper waste with
Contaminated packaging : Recycling is preferred when possible. The generator of waste mater has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.					
	1	14. TRANSPORT IN	FORMATION		
U.S. DOT Classification	- ·	Not regulated for tr	ansportation		
	1.	-	-		
ICAO/IATA (air) : Refer to specific regulation.					
IMO / IMDG (maritime	) :	Refer to specific reg	gulation.		
	15	5. REGULATORY I	NFORMATION		

PolyOne.

# MATERIAL SAFETY DATA SHEET FIRESTIK PINK

ersion Number 1.0 evision Date 11/13/2007			F	Page 6 of 7 Print Date 12/2/2011
OGUA Status		d hd		
OSHA Status	: Classified as h	azardous based or	i components.	
TSCA Status	: All componen Inventory.	ts of this product a	are listed on or exer	npt from the TSCA
US. EPA CERCLA Hazardous S	Substances (40 CFR	302)		
Not applicable				
California Proposition 65	: WARNING! California to c		iins a chemical kno	own to the State of
SARA Title III Section 302 Extr	emely Hazardous S	ubstance		
Unless specific chemicals are ide	entified under this s	ection, this produ	ct is Not Applicabl	e under this regulation
Unless specific chemicals are ide Canadian Regulations: National Pollutant Releas		-	ct is Not Applicabl	e under this regulation
Chemical Name		CAS-No.	Weight %	NPRI ID#
Aluminum oxide		1344-28-1	0.10 - 1.00	13
Zinc stearate		557-05-1	0.10 - 1.00	231
WHMIS Classification WHMIS Ingredient Discl CAS-No. 11097-59-9	: D2A losure List			
DSL		tts of this product st (DSL) or are exe	are on the Canadia empt.	n Domestic
National Inventories:				
Australia AICS	: Listed			
China IECS	: Listed			

*PolyOne* 

## MATERIAL SAFETY DATA SHEET FIRESTIK PINK

Version Number 1.0 Revision Date 11/13/2007 Page 7 of 7 Print Date 12/2/2011

Europe EINECS:ListedJapan ENCS:Not determinedKorea KECI:ListedPhilippines PICCS:Listed

### **16. OTHER INFORMATION**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.