PolyOne

MATERIAL SAFETY DATA SHEET **DK GRAY 560090**

Version Number 1.0 Revision Date 11/07/2007

Page 1 of 8 Print Date 12/2/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone:Emergency telephone:	Product Stewardship (770) 271-5902 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name :	DK GRAY 560090
Product code :	CC10105857
Chemical Name :	Mixture
CAS-No. :	Mixture
Product Use :	Industrial Applications

2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight %
Nickel antimony yellow rutile (C.I. Pigment Yellow 53)	8007-18-9	1 - 5
Calcium carbonate	1317-65-3	1 - 5
Carbon black	1333-86-4	1 - 5
Titanium dioxide	13463-67-7	10 - 30

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation Ingestion	Resin particles, like other inert materials, can be mechanically irritating.May be harmful if swallowed.
Eyes	 Resin particles, like other inert materials, are mechanically irritating to eyes.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.

POLYONE CORPORATION



MATERIAL SAFETY DATA SHEET **DK GRAY 560090**

Version Number 1.0 Revision Date 11/07/2007 Page 2 of 8 Print Date 12/2/2011

Medical Conditions	: None known.
Aggravated by Exposure:	
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seek medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: Not applicable
Flammable Limits	
Upper explosion limit	: Not applicable
Lower explosion limit	: Not applicable
Autoignition temperature Suitable extinguishing media	Not applicableCarbon dioxide blanket, Water spray, Dry powder, Foam.
s and a shore shore gains and g	
Special Fire Fighting Procedures	: Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.
Unusual Fire/Explosion Hazards	 Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 13 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE



MATERIAL SAFETY DATA SHEET **DK GRAY 560090**

Version Number 1.0 Revision Date 11/07/2007		Page 3 of 8 Print Date 12/2/2011
Handling	:	Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.
Storage	:	Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.
8. EXP	OSUF	RE CONTROLS / PERSONAL PROTECTION
Respiratory protection	:	No personal respiratory protective equipment normally required.
Eye/Face Protection	:	Safety glasses with side-shields
Hand protection	:	Protective gloves
Skin and body protection	:	Long sleeved clothing
Additional Protective Measures	:	Safety shoes
General Hygiene Considerations	:	Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.
Engineering measures	:	Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.
Exposure limit(s)		

PolyOne

MATERIAL SAFETY DATA SHEET **DK GRAY 560090**

Version Number 1.0 Revision Date 11/07/2007 Page 4 of 8 Print Date 12/2/2011

Components	Value	Exposure time	Exposure type	List:
Nickel antimony yellow rutile (C.I. Pigment Yellow 53)	1 mg/m3	PEL:	as Ni	OSHA Z1
	0.2 mg/m3	Time Weighted Average (TWA):	Inhalable fraction. as Ni	ACGIH
	0.5 mg/m3	Time Weighted Average (TWA):	as Sb	ACGIH
	0.5 mg/m3	PEL:	as Sb	OSHA Z1
	0.5 mg/m3	Time Weighted Average (TWA):	as Sb	MX OEL
Calcium carbonate	5 mg/m3	PEL:	Respirable fraction.	OSHA Z1
	15 mg/m3	PEL:	Total dust.	OSHA Z1
	10 mg/m3	Time Weighted Average (TWA):		MX OEL
	20 mg/m3	Short Term Exposure Limit (STEL):		MX OEL
Carbon black	3.5 mg/m3	Time Weighted Average (TWA):		ACGIH
	3.5 mg/m3	PEL:		OSHA Z1
	3.5 mg/m3	Time Weighted Average (TWA):		MX OEL
	7 mg/m3	Short Term Exposure Limit (STEL):		MX OEL
Titanium dioxide	10 mg/m3	Time Weighted Average (TWA):		ACGIH
	15 mg/m3	PEL:	Total dust.	OSHA Z1
	10 mg/m3	Time Weighted Average (TWA):	as Ti	MX OEL
	20 mg/m3	Short Term Exposure Limit (STEL):	as Ti	MX OEL

9. PHYSICAL AND CHEMICAL PROPERTIES

- Form Appearance Color Odour Melting point/range Boiling Point: Water solubility
- Solid
 pellets
 GREY
 Very faint
 Not determined
 Not applicable
 Insoluble

: Stable.

Evaporation rate Specific Gravity Bulk density Vapour pressure Vapour density pH

Keep away from oxidizing agents and open flame. To avoid thermal

- Not applicableNot determined
- Not determinedNot established
- : Not established : Not applicable
- : Not applicable
- : Not applicable
- **10. STABILITY AND REACTIVITY**

- Stability

:

Hazardous Polymerization : Will not occur.

Conditions to avoid

4/8

MATERIAL SAFETY DATA SHEET **DK GRAY 560090**

Version Number 1.0 Revision Date 11/07/2007 Page 5 of 8 Print Date 12/2/2011

Incompatible Materials:Incompatible with strong acids and oxidizing agents.Hazardous decomposition
products:Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen
(NOx), other hazardous materials, and smoke are all possible.

decomposition, do not overheat.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
8007-18-9	Nickel antimony yellow rutile (C.I. Pigment Yellow 53)	Irritant	Eyes, Skin.
		sensitizer	Skin.
1317-65-3	Calcium carbonate	Irritant	Eyes, Skin.
		Systemic effects	Eyes, Skin, Respiratory system.
1333-86-4	Carbon black	Systemic effects	Eyes, Respiratory system.
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.

LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
1333-86-4	Carbon black	Oral LD50	>15,400 mg/kg	rat
		Dermal LD50	> 3 gm/kg	rabbit

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
8007-18-9	Nickel antimony yellow rutile (C.I. Pigment Yellow 53)	no	1	no
13463-67-7	Titanium dioxide	no	2B	no

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

PolvOne

MATERIAL SAFETY DATA SHEET **DK GRAY 560090**

Version Number 1.0 Revision Date 11/07/2007

Page 6 of 8 Print Date 12/2/2011

Additional Health Hazard Information:

Nickel antimony yellow rutile (C.I. Pigment Yellow 53) 8007-18-9 Skin sensitizer "nickel itch", with pulmonary, brain, liver, kidney and muscle effects.

Additional Health Hazard Information:

Carbon black 1333-86-4 Carcinogenicity: Many inhalation toxicologists believe that the tumor response observed in the referenced rat studies is species specific and does not correlate to human exposure. However, the IARC evaluation in Monograph Volume 65, issued in April 1996 concluded that, "There is sufficient evidence in experimental animals for the carcinogenicity of carbon black". Based on this evaluation, along with their evaluation of inadequate evidence of carcinogenicity in humans, IARC's overall evaluation is that "Carbon Black is possibly carcinogenic to humans (Group 2B). The IARC 2B listing only pertains to airborne, unbound carbon black particles of respirable size. Carbon Black has not been listed as a carcinogen by the National Toxicology Program (NTP) or the Occupational Safety and Health Administration (OSHA). The National Institute of Occupational Safety and Health (NIOSH) criteria document on carbon black recommends that only carbon black with PAH (polynuclear aromatic hydrocarbon) levels greater than 0.1% be considered suspect carcinogens.

	12. ECOLOGICAL INFORMATION
Persistence and degradability	: Not readily biodegradable.
Environmental Toxicity	: Chemicals are not readily available as they are bound within the polymer matrix.
Bioaccumulation Potential	: Chemicals are not readily available as they are bound within the polymer matrix.
Additional advice	: No data available
	13. DISPOSAL CONSIDERATIONS
Product Contaminated packaging	 Like most thermoplastic plastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations. Recycling is preferred when possible. The generator of waste materia has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. DOT Classification	: Not regulated for transportation.
ICAO/IATA (air)	: Refer to specific regulation.
IMO / IMDG (maritime)	: Refer to specific regulation.

PolyOne.

MATERIAL SAFETY DATA SHEET **DK GRAY 560090**

Version Number 1.0 Revision Date 11/07/2007

Page 7 of 8 Print Date 12/2/2011

S Regulations:						
5 Regulations.						
OSHA Status :	Classified as h	nazardous ł	based on	componer	its.	
TSCA Status : All components of this product are listed on or exempt from the TSCA Inventory.						
S. EPA CERCLA Hazardous Subs	stances (40 CFF	R 302)				
Not applicable						
California Proposition : 65	WARNING! California to c	-		ns a chem	ical kno	own to the State o
ARA Title III Section 302 Extreme	ely Hazardous S	Substance				
lless specific chemicals are identit	fied under this	section thi	s product	is Not A	nlicabl	a under this regul
			s produce		product	
ARA Title III Section 313 Toxic C	'hemicals.					
	mennears.					
aloss specific chamicals are identit		saction thi	s pr oduct	is Not A	nliashl	o under this regul
		section, thi				
Chemical Name	fied under this		s product CAS-N 8007-18	lo.	oplicabl Weigh 1.00	nt %
Chemical Name NICKEL COMPOUNDSANTIM	fied under this		CAS-N	lo.	Weigh	nt %
Chemical Name NICKEL COMPOUNDSANTIM	fied under this		CAS-N	lo.	Weigh	nt %
Chemical Name NICKEL COMPOUNDSANTIM madian Regulations: National Pollutant Release In	fied under this	UNDS	CAS-N 8007-18	Io. 3-9	Weigh	nt % - 5.00
Chemical Name NICKEL COMPOUNDSANTIM madian Regulations: National Pollutant Release In Chemical Name	fied under this s	UNDS	CAS-N 8007-18	Io. 3-9 Weigt	Weigh 1.00 -	nt % - 5.00 NPRI ID#
Chemical Name NICKEL COMPOUNDSANTIM anadian Regulations: National Pollutant Release In Chemical Name Nickel antimony yellow rutile (C.	fied under this s	UNDS	CAS-N 8007-18	Io. 3-9	Weigh 1.00 -	nt % - 5.00
Chemical Name NICKEL COMPOUNDSANTIM anadian Regulations: National Pollutant Release In Chemical Name Nickel antimony yellow rutile (C. Yellow 53)	fied under this s	UNDS () CAS-N 8007-1	CAS-N 8007-18 No. 8-9	To. 3-9 Weigh 1.00 - 1.00 -	Weigh 1.00 tt % 5.00 5.00	nt % - 5.00 NPRI ID# 168 17
Chemical Name NICKEL COMPOUNDSANTIM anadian Regulations: National Pollutant Release In Chemical Name Nickel antimony yellow rutile (C. Yellow 53)	fied under this s	UNDS	CAS-N 8007-18 No. 8-9	To. 3-9 Weigh 1.00 -	Weigh 1.00 tt % 5.00 5.00	nt % - 5.00 NPRI ID# 168
nless specific chemicals are identit Chemical Name NICKEL COMPOUNDSANTIM anadian Regulations: National Pollutant Release In Chemical Name Nickel antimony yellow rutile (C. Yellow 53) Phthalocyanine green	fied under this s	UNDS () CAS-N 8007-1	CAS-N 8007-18 No. 8-9	To. 3-9 Weigh 1.00 - 1.00 -	Weigh 1.00 tt % 5.00 5.00	nt % - 5.00 NPRI ID# 168 17
Chemical Name NICKEL COMPOUNDSANTIM anadian Regulations: National Pollutant Release In Chemical Name Nickel antimony yellow rutile (C. Yellow 53)	fied under this s	UNDS () CAS-N 8007-1	CAS-N 8007-18 No. 8-9	To. 3-9 Weigh 1.00 - 1.00 -	Weigh 1.00 tt % 5.00 5.00	nt % - 5.00 NPRI ID# 168 17

POLYONE CORPORATION

PolyOne.

MATERIAL SAFETY DATA SHEET **DK GRAY 560090**

Version Number 1.0 Revision Date 11/07/2007

Page 8 of 8 Print Date 12/2/2011

1333-86-4 DSL	:	All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.
National Inventories:		
Australia AICS	:	Listed
China IECS	:	Listed
Europe EINECS	:	Listed
Japan ENCS	:	Not determined
Korea KECI	:	Listed
Philippines PICCS	:	Not determined
		16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.