MATERIAL SAFETY DATA SHEET WHITE LC

Version Number 1.0 Revision Date 11/09/2007 Page 1 of 6 Print Date 12/2/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone Emergency telephone	:	Product Stewardship (770) 271-5902 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	WHITE LC
Product code	:	CC10105872
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight %
Silica, amorphous	7631-86-9	5 - 10
Titanium dioxide	13463-67-7	60 - 100

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Skin contact, Ingestion
Acute exposure	
Inhalation	: Inhalation of airborne droplets may cause irritation of the respiratory tract.
Ingestion	: May be harmful if swallowed.
Eyes	: Irritating to eyes and respiratory system.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.
Medical Conditions Aggravated by Exposure:	: None known.

PolyOne.

MATERIAL SAFETY DATA SHEET WHITE LC

Version Number 1.0 Revision Date 11/09/2007 Page 2 of 6 Print Date 12/2/2011

	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. Seek medical attention after significant exposure.
Ingestion	: Do not induce vomiting without medical advice. Seek medical attention if necessary.
Eyes	: Rinse immediately with plenty of water for at least 15 minutes. If ey irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists see medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: Greater than 200 °F (93 °C)
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media	 Not applicable Not applicable Not applicable Carbon dioxide blanket, Dry powder, Foam.
Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	 Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.
	5. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: The product should not be allowed to enter drains, water courses or th soil. Should not be released into the environment.
Methods for cleaning up	: Soak up with inert absorbent material (e.g. sand, silica gel, acid binder universal binder, sawdust). Package all material in appropriate container for disposal. Refer to Section 13 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Heat only in areas with appropriate exhaust ventilation.
Storage	: Keep containers dry and tightly closed to avoid moisture absorption

PolyOne.

MATERIAL SAFETY DATA SHEET WHITE LC

Version Number 1.0 Revision Date 11/09/2007

Page 3 of 6 Print Date 12/2/2011

0.1	EXPOSURE	CONTROLS / PERSONAL	PROTECTION			
Respiratory protection	: U	Inder normal handling condition	ons a respirator may not b	e required.		
Eye/Face Protection	: S	: Safety glasses with side-shields				
Hand protection	: P	rotective gloves				
Skin and body protection	: L	ong sleeved clothing				
Additional Protective Measures	: S	afety shoes				
General Hygiene Considerations		landle in accordance with good Vash hands before breaks and a		afety practice		
Engineering measures		leat only in areas with appropri ppropriate exhaust ventilation a		Provide		
Exposure limit(s) Components	Value	Exposure time	Exposure type	List:		
Silica, amorphous	0.8 mg/m3	Time Weighted Average	Exposure type	Z3		
Silica, amorphous	0.8 mg/m3	(TWA):		25		
	10 mg/m3	Time Weighted Average (TWA):	Inhalable particulate.	MX OEL		
	3 mg/m3	Time Weighted Average (TWA):	Respirable dust.	MX OEL		
	10 mg/m3	Time Weighted Average		ACGIH		
Titanium dioxide	8	(TWA):				
Titanium dioxide	15 mg/m3	(TWA): PEL:	Total dust.	OSHA Z1		
Titanium dioxide			Total dust. as Ti			
Titanium dioxide	15 mg/m3	PEL: Time Weighted Average				
Titanium dioxide	15 mg/m3 10 mg/m3 20 mg/m3	PEL: Time Weighted Average (TWA): Short Term Exposure Limit	as Ti as Ti	OSHA Z1 MX OEL MX OEL		
Titanium dioxide	15 mg/m3 10 mg/m3 20 mg/m3 9. PHYSIC : liqui	PEL: Time Weighted Average (TWA): Short Term Exposure Limit (STEL): CAL AND CHEMICAL PRO d Evapor	as Ti as Ti DPERTIES ration rate : Not	MX OEL		
Form Appearance	15 mg/m3 10 mg/m3 20 mg/m3 9. PHYSIC : liqui : Visc	PEL: Time Weighted Average (TWA): Short Term Exposure Limit (STEL): CAL AND CHEMICAL PRO d Evapor ous, liquid Specifi	as Ti as Ti DPERTIES ration rate : Not ic Gravity : Not	MX OEL MX OEL established determined		
Form Appearance Color	15 mg/m3 10 mg/m3 20 mg/m3 9. PHYSIO : liqui : Visc : WHI	PEL: Time Weighted Average (TWA): Short Term Exposure Limit (STEL): CAL AND CHEMICAL PRO d Evapor ous, liquid Specifi TE Bulk d	as Ti as Ti DPERTIES ration rate : Not ic Gravity : Not ensity : Not	MX OEL MX OEL established determined applicable		
Form Appearance Color Odour	15 mg/m3 10 mg/m3 20 mg/m3 9. PHYSIO : liqui : Visc : WHI : Very	PEL: Time Weighted Average (TWA): Short Term Exposure Limit (STEL): CAL AND CHEMICAL PRO d Evapor ous, liquid Specifi TE Bulk d faint Vapou	as Ti as Ti DPERTIES ration rate : Not ic Gravity : Not ensity : Not r pressure : Not	MX OEL MX OEL established determined applicable determined		
Form Appearance Color Odour Melting point/range	15 mg/m3 10 mg/m3 20 mg/m3 9. PHYSIO : liqui : Visc : WHI : Very : Not	PEL: Time Weighted Average (TWA): Short Term Exposure Limit (STEL): CAL AND CHEMICAL PRC d Evapor ous, liquid Specifi (TE Bulk d faint Vapou applicable Vapou	as Ti as Ti DPERTIES ration rate : Not ration rate : Not ensity : Not r pressure : Not r density : Not	MX OEL MX OEL established determined applicable determined determined		
Form Appearance Color Odour	15 mg/m3 10 mg/m3 20 mg/m3 9. PHYSIO : liqui : Visc : WHI : Very : Not	PEL: Time Weighted Average (TWA): Short Term Exposure Limit (STEL): CAL AND CHEMICAL PRO d Evapor ous, liquid Specifi TE Bulk d faint Vapou applicable applicable PH	as Ti as Ti DPERTIES ration rate : Not ration rate : Not ensity : Not r pressure : Not r density : Not	MX OEL MX OEL established determined applicable determined		

MATERIAL SAFETY DATA SHEET WHITE LC

Version Number 1.0 Revision Date 11/09/2007

Page 4 of 6 Print Date 12/2/2011

Stability	:	Stable.
Hazardous Polymerization	:	Will not occur.
Conditions to avoid	:	Keep away from oxidizing agents and open flame.
Incompatible Materials	:	Incompatible with strong acids and oxidizing agents.
Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
7631-86-9	Silica, amorphous	Irritant	Eyes, Respiratory system.
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.

LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
7631-86-9	Silica, amorphous	Oral LD50Oral	15,000 mg/kg22,500	mouserat
		LD50	mg/kg	

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
13463-67-7Titanium dioxide		no	2B	no

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

12. ECOLOGICAL INFORMATION

PolyOne.

MATERIAL SAFETY DATA SHEET **WHITE LC**

Version Number 1.0 Revision Date 11/09/2007 Page 5 of 6 Print Date 12/2/2011

Persistence and degradability	:	Not readily biodegradable.
Environmental Toxicity	:	Adverse ecological impact is not known or expected under normal use
Bioaccumulation Potential	:	Does not bioaccumulate.
Additional advice	:	No data available
	1	3. DISPOSAL CONSIDERATIONS
Product	:	Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	:	Recycling is preferred when possible. The generator of waste materia has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	1	4. TRANSPORT INFORMATION
U.S. DOT Classification		Not regulated for transportation.
ICAO/IATA (air)		Not regulated for transportation.
IMO / IMDG (maritime)	•	Not regulated for transportation.
	15	5. REGULATORY INFORMATION
US Regulations:		
OSHA Status	:	Classified as hazardous based on components.
TSCA Status	:	All components of this product are listed on or exempt from the TSCA Inventory.
US. EPA CERCLA Hazardous	Sub	stances (40 CFR 302)
Not applicable		
California Proposition 65	:	Not applicable

MATERIAL SAFETY DATA SHEET WHITE LC

Version Number 1.0	
Revision Date 11/09/2007	

Page 6 of 6 Print Date 12/2/2011

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

SARA Title III Section 313 Toxic Chemicals:

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

Canadian Regulations:

National Pollutant Release Inventory (NPRI)

Chemical Name	CAS-No.	Weight %	NPRI ID#
Bis (2-ethylhexyl) adipate	103-23-1	10.00 - 30.00	24

WHMIS Classification : D2A

WHMIS Ingredient Disclosure List

CAS-No.	
103-23-1	
7631-86-9	

:

DSL

All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.

National Inventories:

Australia AICS	:	Listed
China IECS	:	Listed
Europe EINECS	:	Listed
Japan ENCS	:	Listed
Korea KECI	:	Listed
Philippines PICCS	:	Listed

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.