MATERIAL SAFETY DATA SHEET **BLACK SPARKLE 620587**

Version Number 1.0 Revision Date 11/13/2007

Page 1 of 7 Print Date 12/2/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone:Emergency telephone:	Product Stewardship (770) 271-5902 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name :	BLACK SPARKLE 620587
Product code :	CC10105953
Chemical Name :	Mixture
CAS-No. :	Mixture
Product Use :	Industrial Applications

2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight %
Titanium dioxide	13463-67-7	1 - 5
Aluminum	7429-90-5	10 - 30

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation Ingestion Eyes	 Resin particles, like other inert materials, can be mechanically irritating. May be harmful if swallowed. Resin particles, like other inert materials, are mechanically irritating to
Skin	eyes.Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.
Medical Conditions Aggravated by Exposure:	: None known.

PolyOne.

MATERIAL SAFETY DATA SHEET **BLACK SPARKLE 620587**

Version Number 1.0 Revision Date 11/13/2007 Page 2 of 7 Print Date 12/2/2011

		4. FIRST AID MEASURES
Inhalation	:	Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	:	Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	:	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	:	Wash off with soap and plenty of water. If skin irritation persists seek medical attention.
		5. FIRE-FIGHTING MEASURES
Flash point	:	Not applicable
Flammable Limits		
Upper explosion limit		Not applicable
Lower explosion limit	:	Not applicable
Autoignition temperature	÷	Not applicable
Suitable extinguishing media	:	Carbon dioxide blanket, Water spray, Dry powder, Foam.
Special Fire Fighting Procedures	:	Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.
Unusual Fire/Explosion Hazards	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.
	6. A	CCIDENTAL RELEASE MEASURES
Personal precautions	:	Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	:	Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	:	Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 13 of this MSDS for proper disposal methods.
		7. HANDLING AND STORAGE
Handling	:	Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.
Storage	:	Keep containers dry and tightly closed to avoid moisture absorption

2/7

PolyOne

MATERIAL SAFETY DATA SHEET **BLACK SPARKLE 620587**

Version Number 1.0 Revision Date 11/13/2007 Page 3 of 7 Print Date 12/2/2011

	aı	nd contamination. Keep in a c	dry, cool place.		
8. E	XPOSURE	CONTROLS / PERSONAL	PROTECTION		
Respiratory protection	: N	o personal respiratory protect	ive equipment normally re	equired.	
Eye/Face Protection	: S	afety glasses with side-shields	3		
Hand protection	: P	rotective gloves			
Skin and body protection	: L	ong sleeved clothing			
Additional Protective : Safety shoes Measures					
General Hygiene Considerations		andle in accordance with good Vash hands before breaks and		fety practice.	
Engineering measures		eat only in areas with appropription propriate exhaust ventilation		Provide	
Exposure limit(s)					
Components	Value	Exposure time	Exposure type	List:	
Aluminum	10 mg/m3	Time Weighted Average (TWA):	Dust.	ACGIH	
	5 mg/m3	Time Weighted Average (TWA):	Pyrophoric powder. as Al	ACGIH	
			T 1 1 1 1		
	15 mg/m3	PEL:	Total dust. as Al	OSHA Z1	

C C	(TWA):		
15 mg/m3	PEL:	Total dust.	OSHA Z1
10 mg/m3	Time Weighted Average (TWA):	as Ti	MX OEL
20 mg/m3	Short Term Exposure Limit (STEL):	as Ti	MX OEL
0 DITYCI	TAL AND CHENTICAL DDC	DED/DED/	

Time Weighted Average

(TWA):

Time Weighted Average

(TWA):

Time Weighted Average

9. PHYSICAL AND CHEMICAL PROPERTIES

Form Appearance Color Odour Melting point/range

Titanium dioxide

Solid
pellets
BLACK
Very faint
Not determined

5 mg/m3

10 mg/m3

10 mg/m3

Evaporation rate Specific Gravity Bulk density Vapour pressure Vapour density

Pyrophoric powder.

Dust.

Not applicableNot determinedNot establishedNot applicableNot applicable

MX OEL

MX OEL

ACGIH

MATERIAL SAFETY DATA SHEET **BLACK SPARKLE 620587**

Version Number 1.0 Revision Date 11/13/2007

Page 4 of 7 Print Date 12/2/2011

Boiling Point: Water solubility	: Not applicable : Insoluble	рН	: Not applicable
	10. STABILITY	AND REACTIVITY	
Stability	: Stable.		
Hazardous Polymerization	: Will not occur.		
Conditions to avoid	1 1	m oxidizing agents and o do not overheat.	open flame. To avoid thermal
Incompatible Materials	: Incompatible w	ith strong acids and oxi	dizing agents.
Hazardous decomposition products		e (CO2), carbon monoxidazardous materials, and	de (CO), oxides of nitrogen smoke are all possible.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.
7429-90-5	Aluminum	Irritant	Skin, Respiratory system.
		Systemic effects	Eyes, Skin, Respiratory system.

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
13463-67-7	Titanium dioxide	no	2B	no

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

12. ECOLOGICAL INFORMATION

Persistence and degradability

: Not readily biodegradable.

PolyOne.

MATERIAL SAFETY DATA SHEET **BLACK SPARKLE 620587**

Version Number 1.0 Revision Date 11/13/2007 Page 5 of 7 Print Date 12/2/2011

Environmental Toxicity	: Chemicals are not readily available as they are bound within the polymer matrix.				
Bioaccumulation Potential	: Chemicals are not readily available as they are bound within the polymer matrix.				
Additional advice	: No data available				
13. DISPOSAL CONSIDERATIONS					
Product	: Like most thermoplastic plastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.				
Contaminated packaging	: Recycling is preferred when possible. The generator of waste materia has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.				
	14. TRANSPORT INFORMATION				
U.S. DOT Classification	: Not regulated for transportation.				
ICAO/IATA (air)	: Refer to specific regulation.				
IMO / IMDG (maritime)	: Refer to specific regulation.				
	15. REGULATORY INFORMATION				
US Regulations:					
OSHA Status	: Classified as hazardous based on components.				
TSCA Status	: All components of this product are listed on or exempt from the TSCA Inventory.				
US. EPA CERCLA Hazardous	Substances (40 CFR 302)				
Not applicable					
California Proposition 65	: Not applicable				

MATERIAL SAFETY DATA SHEET **BLACK SPARKLE 620587**

Version Number 1.0 Revision Date 11/13/2007

Page 6 of 7 Print Date 12/2/2011

SARA Title III Section 302 Extremely Hazardous Substance

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

SARA Title III Section 313 Toxic Chemicals:

U	nless specific chemicals are identified under this section, this	s product is Not Ap	plicable under this	s regulation
	Chemical Name	CAS-No.	Weight %	
	ALUMINUM (FUME OR DUST)	7429-90-5	10.00 - 30.00	

Canadian Regulations:

National Pollutant Release Inventory (NPRI)			
Chemical Name	CAS-No.	Weight %	NPRI ID#
Aluminum	7429-90-5	10.00 - 30.00	12

WHMIS Classification : D2A

WHMIS Ingredient Disclosure List

	S-No.
7429-90-5	9-90-5

DSL

All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.

National Inventories:

Australia AICS	: Listed
China IECS	: Listed
Europe EINECS	: Listed
Japan ENCS	: Not determined
Korea KECI	: Listed
Philippines PICCS	: Not determined

:

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The

PolyOne.

MATERIAL SAFETY DATA SHEET **BLACK SPARKLE 620587**

Version Number 1.0 Revision Date 11/13/2007 Page 7 of 7 Print Date 12/2/2011

information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.