MATERIAL SAFETY DATA SHEET UV GRAPHITE A

Version Number 1.0 Revision Date 11/26/2007 Page 1 of 7 Print Date 12/2/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone Emergency telephone	:	Product Stewardship (770) 271-5902 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	UV GRAPHITE A
Product code	:	CC10106390
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight %
1,6-Hexanediamine,	70624-18-9	5 - 10
N,N'-bis(2,2,6,6-tetramethyl-4-piperidinyl)-,		
polymer with 2,4,6-trichloro-1,3,5-triazine,		
reaction products		
Cobalt aluminate blue spinel (C.I. Pigment	1345-16-0	1 - 5
Blue 28)		
Carbon black	1333-86-4	1 - 5
Rutile (TiO2)	1317-80-2	10 - 30

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation Ingestion Eyes	 Resin particles, like other inert materials, can be mechanically irritating. May be harmful if swallowed. Resin particles, like other inert materials, are mechanically irritating to eyes.



MATERIAL SAFETY DATA SHEET UV GRAPHITE A

Version Number 1.0 Revision Date 11/26/2007 Page 2 of 7 Print Date 12/2/2011

	: Experience shows no unusual dermatitis hazard from routine handling
Chronic exposure	: Refer to Section 11 for Toxicological Information.
Medical Conditions Aggravated by Exposure:	: None known.
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases o doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists see medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: Not applicable
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media	 Not applicable Not applicable Not applicable Carbon dioxide blanket, Water spray, Dry powder, Foam.
Special Fire Fighting Procedures	: Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.
Unusual Fire/Explosion Hazards	: Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 1 of this MSDS for proper disposal methods.

POLYONE CORPORATION

PolyOne

MATERIAL SAFETY DATA SHEET UV GRAPHITE A

Version Number 1.0 Revision Date 11/26/2007 Page 3 of 7 Print Date 12/2/2011

		7. HANDLING AND STORAGE
Handling	:	Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.
Storage	:	Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.
8. EXP	OSUF	RE CONTROLS / PERSONAL PROTECTION
Respiratory protection	:	No personal respiratory protective equipment normally required.
Eye/Face Protection	:	Safety glasses with side-shields
Hand protection	:	Protective gloves
Skin and body protection	:	Long sleeved clothing
Additional Protective Measures	:	Safety shoes
General Hygiene Considerations	:	Handle in accordance with good industrial hygiene and safety practice Wash hands before breaks and at the end of workday.
Engineering measures	:	Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.

Exposure limit(s)

Components	Value	Exposure time	Exposure type	List:
Cobalt aluminate blue	0.02	Time Weighted Average	as Co	ACGIH
spinel (C.I. Pigment	mg/m3	(TWA):		
Blue 28)				
Carbon black	3.5 mg/m3	Time Weighted Average		ACGIH
		(TWA):		
	3.5 mg/m3	PEL:		OSHA Z1
	3.5 mg/m3	Time Weighted Average		MX OEL
		(TWA):		
	7 mg/m3	Short Term Exposure Limit		MX OEL
	_	(STEL):		

9. PHYSICAL AND CHEMICAL PROPERTIES

- Form Appearance Color Odour Melting point/range
- : Solid
 : pellets
 : GREY
 : Very faint
 : Not determined
- Evaporation rate Specific Gravity Bulk density Vapour pressure Vapour density
- Not applicable
 Not determined
 Not established
 Not applicable
 Not applicable



MATERIAL SAFETY DATA SHEET UV GRAPHITE A

Version Number 1.0 Revision Date 11/26/2007

_

Page 4 of 7 Print Date 12/2/2011

Boiling Point: Water solubility	: Not applicable : Insoluble	рН	: Not applicable
	10. STABILITY AND	REACTIVITY	
Stability	: Stable.		
Hazardous Polymerization	: Will not occur.		
Conditions to avoid	: Keep away from oxi decomposition, do n	00	open flame. To avoid thermal
Incompatible Materials	: Incompatible with st	rong acids and oxi	dizing agents.
Hazardous decomposition products		,.	de (CO), oxides of nitrogen smoke are all possible.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

<u>Toxicity Overview</u> This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
70624-18-9	1,6-Hexanediamine, N,N'-bis(2,2,6,6-tetrameth yl-4-piperidinyl)-,polymer with 2,4,6-trichloro-1,3,5-triazi ne, reaction products	Irritant	Eyes, Skin, Respiratory system.
1345-16-0	Cobalt aluminate blue spinel (C.I. Pigment Blue 28)	Irritant	Eyes, Skin, Respiratory system.
		sensitizer	Skin.
1333-86-4	Carbon black	Systemic effects	Eyes, Respiratory system.

LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
70624-18-9	1,6-Hexanediamine,	Oral LD50	> 2,000 mg/kg	rat
	N,N'-bis(2,2,6,6-tetrameth	Dermal LD50	> 3,000 mg/kg	rat
	yl-4-piperidinyl)-,polymer			
	with			
	2,4,6-trichloro-1,3,5-triazi			
	ne, reaction products			
1333-86-4	Carbon black	Oral LD50	>15,400 mg/kg	rat
		Dermal LD50	> 3 gm/kg	rabbit

MATERIAL SAFETY DATA SHEET UV GRAPHITE A

Version Number 1.0 Revision Date 11/26/2007 Page 5 of 7 Print Date 12/2/2011

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
1345-16-0	Cobalt aluminate blue spinel	no	2B	no
	(C.I. Pigment Blue 28)			
1317-80-2	Rutile (TiO2)	no	2B	no

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

Additional Health Hazard Information:

Carbon black 1333-86-4 Carcinogenicity: Many inhalation toxicologists believe that the tumor response observed in the referenced rat studies is species specific and does not correlate to human exposure. However, the IARC evaluation in Monograph Volume 65, issued in April 1996 concluded that, "There is sufficient evidence in experimental animals for the carcinogenicity of carbon black". Based on this evaluation, along with their evaluation of inadequate evidence of carcinogenicity in humans, IARC's overall evaluation is that "Carbon Black is possibly carcinogenic to humans (Group 2B). The IARC 2B listing only pertains to airborne, unbound carbon black particles of respirable size. Carbon Black has not been listed as a carcinogen by the National Toxicology Program (NTP) or the Occupational Safety and Health Administration (OSHA). The National Institute of Occupational Safety and Health (NIOSH) criteria document on carbon black recommends that only carbon black with PAH (polynuclear aromatic hydrocarbon) levels greater than 0.1% be considered suspect carcinogens.

12. ECOLOGICAL INFORMATION
: Not readily biodegradable.
: Chemicals are not readily available as they are bound within the polymer matrix.
: Chemicals are not readily available as they are bound within the polymer matrix.
: No data available
13. DISPOSAL CONSIDERATIONS
: Like most thermoplastic plastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with



MATERIAL SAFETY DATA SHEET UV GRAPHITE A

applicable federal, state/provincial and local regulations. Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations. 14. TRANSPORT INFORMATION Not regulated for transportation. Refer to specific regulation. Refer to specific regulation. 5. REGULATORY INFORMATION
Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations. 14. TRANSPORT INFORMATION Not regulated for transportation. Refer to specific regulation. Refer to specific regulation.
has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations. 14. TRANSPORT INFORMATION Not regulated for transportation. Refer to specific regulation. Refer to specific regulation.
Not regulated for transportation. Refer to specific regulation. Refer to specific regulation.
Refer to specific regulation. Refer to specific regulation.
Refer to specific regulation. Refer to specific regulation.
Refer to specific regulation.
5. REGULATORY INFORMATION
Classified as hazardous based on components.
All components of this product are listed on or exempt from the TSCA Inventory.
bstances (40 CFR 302)
Not applicable
nely Hazardous Substance
tified under this section, this product is Not Applicable under this regulation
Chemicals:
tified under this section, this product is Not Applicable under this regulation CAS-No. Weight %
1345-16-0 1.00 - 5.00
I
r t

<u>PolyOne</u>

MATERIAL SAFETY DATA SHEET UV GRAPHITE A

Version Number 1.0					
Revision Date 1	1/26/2007				

Page 7 of 7 Print Date 12/2/2011

National Pollutant Release Inventory (NPRI) Chemical Name			CAS-No. 1345-16-0	Weight % 1.00 - 5.00	NPRI ID# 70	
Cobalt aluminate blue spinel (C.I. Pigment Blue 28)						
WHMIS Classification WHMIS Ingredient Di CAS-No.		0211				
1333-86-4 DSL Vational Inventories:	:	All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.				
Australia AICS	:	Not determined	L			
China IECS	:	Not determined				
Europe EINECS	:	Not determined				
Japan ENCS	:	Not determined				
Korea KECI	:	Not determined				
Philippines PICCS	:	Not determined	l			
			NFORMATION			

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.