MATERIAL SAFETY DATA SHEET **PE YELLOW 123C**

Version Number 1.0 Revision Date 01/14/2008

Page 1 of 6 Print Date 12/3/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Product Stewardship (770) 271-5902 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
PE YELLOW 123C
CC10107592
Mixture
Mixture
Industrial Applications

2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight %
Calcium carbonate	1317-65-3	1 - 5
Titanium dioxide	13463-67-7	10 - 30

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation	: Resin particles, like other inert materials, can be mechanically irritating.
Ingestion	: May be harmful if swallowed.
Eyes	: Resin particles, like other inert materials, are mechanically irritating to eyes.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.

PolyOne.

MATERIAL SAFETY DATA SHEET **PE YELLOW 123C**

Version Number 1.0 Revision Date 01/14/2008 Page 2 of 6 Print Date 12/3/2011

Medical Conditions Aggravated by Exposure:	: None known.
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases o doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for a least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seek medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: Not applicable
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media	 Not applicable Not applicable Not applicable Carbon dioxide blanket, Water spray, Dry powder, Foam.
Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	 Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should no be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 13 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.

POLYONE CORPORATION

PolyOne

MATERIAL SAFETY DATA SHEET **PE YELLOW 123C**

Version Number 1.0 Revision Date 01/14/2008 Page 3 of 6 Print Date 12/3/2011

Storage

: Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Respiratory protection	:	No personal respiratory protective equipment normally required.
Eye/Face Protection	:	Safety glasses with side-shields
Hand protection	:	Protective gloves
Skin and body protection	:	Long sleeved clothing
Additional Protective Measures	:	Safety shoes
General Hygiene Considerations	:	Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.
Engineering measures	:	Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.

Exposure limit(s)

Components	Value	Exposure time Exposure type		List:
Calcium carbonate	5 mg/m3	PEL:	Respirable fraction.	OSHA Z1
	15 mg/m3	PEL:	Total dust.	OSHA Z1
	10 mg/m3	Time Weighted Average (TWA):		MX OEL
	20 mg/m3	Short Term Exposure Limit (STEL):		MX OEL
Titanium dioxide	10 mg/m3	Time Weighted Average (TWA):		ACGIH
	15 mg/m3	PEL:	Total dust.	OSHA Z1
		Time Weighted Average (TWA):	as Ti	MX OEL
		Short Term Exposure Limit (STEL):	as Ti	MX OEL

9. PHYSICAL AND CHEMICAL PROPERTIES

Form Appearance Color Odour Melting point/range Boiling Point: Water solubility Solid
pellets
YELLOW
Very faint
Not determined
Not applicable
Insoluble

Evaporation rate Specific Gravity Bulk density Vapour pressure Vapour density pH Not applicable
Not determined
Not established
Not applicable
Not applicable
Not applicable

MATERIAL SAFETY DATA SHEET **PE YELLOW 123C**

Version Number 1.0 Revision Date 01/14/2008 Page 4 of 6 Print Date 12/3/2011

		10	. STABILITY AND REACTIVITY	
St	ability :	:	Stable.	
Ha	azardous Polymerization :		Will not occur.	
Co	onditions to avoid :	:	Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.	
In	compatible Materials :	•	Incompatible with strong acids and oxidizing agents.	
	azardous decomposition : oducts	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.	

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
1317-65-3	Calcium carbonate	Irritant	Eyes, Skin.
		Systemic effects	Eyes, Skin, Respiratory
			system.
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
13463-67-7 Titanium dioxide		no	2B	no

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

12. ECOLOGICAL INFORMATION

Persistence and degradability

: Not readily biodegradable.

Environmental Toxicity

: Chemicals are not readily available as they are bound within the

PolyOne.

MATERIAL SAFETY DATA SHEET **PE YELLOW 123C**

Version Number 1.0 Revision Date 01/14/2008 Page 5 of 6 Print Date 12/3/2011

	polymer matrix.
Bioaccumulation Potential	: Chemicals are not readily available as they are bound within the polymer matrix.
Additional advice	: No data available
	13. DISPOSAL CONSIDERATIONS
Product	: Like most thermoplastic plastics the product can be recycled. Whe possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. DOT Classification	: Not regulated for transportation.
ICAO/IATA (air)	: Refer to specific regulation.
IMO / IMDG (maritime)	: Refer to specific regulation.
	15. REGULATORY INFORMATION
US Regulations:	
OSHA Status	: Classified as hazardous based on components.
TSCA Status	: All components of this product are listed on or exempt from the TSCA Inventory.
US. EPA CERCLA Hazardous	Substances (40 CFR 302)
Not applicable	
California Proposition	: Not applicable
65	

PolyOne

Page 6 of 6

POLYONE CORPORATION

MATERIAL SAFETY DATA SHEET **PE YELLOW 123C**

Version Number 1.0

Revision Date 01/14/2008				Pı	rint Date 12/3/2011
Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation					
SARA Title III Section 313 Tox	cic (Chemicals:			
Unless specific chemicals are id	lenti	fied under this sec	tion, this product	is Not Applicable	under this regulation
Canadian Regulations:					
National Pollutant Relea	se I	nventory (NPRI)			
Chemical Name		, , , , , , , , , , , , , , , , , , ,	CAS-No.	Weight %	NPRI ID#
Aluminum oxide			1344-28-1	0.10 - 1.00	13
WHMIS Classification DSL	:		of this product ar DSL) or are exem	e on the Canadian npt.	Domestic
National Inventories:					
Australia AICS	:	Listed			
China IECS	:	Listed			
Europe EINECS	:	Not determined			
Japan ENCS	:	Not determined			
Korea KECI	:	Listed			
Philippines PICCS	:	Listed			
		16. OTHER IN	FORMATION		

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.