## MATERIAL SAFETY DATA SHEET **4T1A-CAMEL/GF600A33**

Version Number 1.0 Revision Date 03/28/2008

Page 1 of 8 Print Date 1/3/2012

### 1. PRODUCT AND COMPANY IDENTIFICATION

#### POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone Emergency telephone	:	Product Stewardship (770) 271-5902 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	4T1A-CAMEL/GF600A33
Product code	:	CC10110228
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

### 2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight %
1,6-Hexanediamine, N,N'-bis(2,2,6,6- tetramethyl-4-piperidinyl)-,polymer with 2,4,6-trichloro-1,3,5-triazine, reaction products	70624-18-9	1 - 5
2,4,8,10-Tetraoxa-3,9- diphosphaspiro[5.5]undecane, 3,9-bis[2,4- bis(1,1-dimethylethyl)phenoxy]-	26741-53-7	1 - 5
Calcium carbonate	1317-65-3	1 - 5
Silica, amorphous	7631-86-9	1 - 5
Rutile, antimony chromium buff	68186-90-3	5 - 10
Titanium dioxide	13463-67-7	10 - 30

#### **3. HAZARDS IDENTIFICATION**

#### **EMERGENCY OVERVIEW**

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

### POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
A cute exposure	

#### Acute exposure

Inhalation

: Resin particles, like other inert materials, can be mechanically

PolyOne.

# MATERIAL SAFETY DATA SHEET 4T1A-CAMEL/GF600A33

sion Number 1.0 ision Date 03/28/2008	Page 2 Print Date 1/3/2
	irritating.
Ingestion	: May be harmful if swallowed.
Eyes	: Resin particles, like other inert materials, are mechanically irritating to
Skin	eyes. : Experience shows no unusual dermatitis hazard from routine handling
Chronic exposure	: Refer to Section 11 for Toxicological Information.
Medical Conditions Aggravated by Exposure:	: None known.
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases o doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seek medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: Not applicable
Flammable Limits	
Upper explosion limit	: Not applicable
Lower explosion limit	: Not applicable
Autoignition temperature	: Not applicable
Suitable extinguishing media	: Carbon dioxide blanket, Water spray, Dry powder, Foam.
Special Fire Fighting	: Fullface self-contained breathing apparatus (SCBA) used in positive
Procedures	pressure mode should be worn to prevent inhalation of airborne
	contaminants.
Unusual Fire/Explosion	: Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen
Hazards	(NOx), other hazardous materials, and smoke are all possible.
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.

PolyOne.

# MATERIAL SAFETY DATA SHEET 4T1A-CAMEL/GF600A33

Version Number 1.0 Revision Date 03/28/2008		Page 3 of 8 Print Date <i>1/3/2012</i>
Methods for cleaning up	pl	lean up promptly by sweeping or vacuum. Package all material in astic, cardboard or metal containers for disposal. Refer to Section 3 of this MSDS for proper disposal methods.
	7.	HANDLING AND STORAGE
Handling		ake measures to prevent the build up of electrostatic charge. Heat aly in areas with appropriate exhaust ventilation.
Storage		eep containers dry and tightly closed to avoid moisture absorption ad contamination. Keep in a dry, cool place.
8. EX	POSURE	CONTROLS/PERSONAL PROTECTION
Respiratory protection	: N	o personal respiratory protective equipment normally required.
Eye/Face Protection	: Sa	afety glasses with side-shields
Hand protection	: P1	rotective gloves
Skin and body protection	: L	ong sleeved clothing
Additional Protective Measures	: Sa	afety shoes
General Hygiene Considerations		andle in accordance with good industrial hygiene and safety ractice. Wash hands before breaks and at the end of workday.
Engineering measures		eat only in areas with appropriate exhaust ventilation. Provide propriate exhaust ventilation at machinery.
Exposure limit(s)		

PolvOne

# MATERIAL SAFETY DATA SHEET **4T1A-CAMEL/GF600A33**

Version Number 1.0 Revision Date 03/28/2008 Page 4 of 8 Print Date 1/3/2012

Components	Value	Exposure time	Exposure type	List:
Calcium carbonate	5 mg/m3	PEL:	Respirable fraction.	OSHA Z1
	15 mg/m3	PEL:	Total dust.	OSHA Z1
	10 mg/m3	Time Weighted Average (TWA):		MX OEL
	20 mg/m3	Short Term Exposure Limit (STEL):		MX OEL
Rutile, antimony chromium buff	0.5 mg/m3	Time Weighted Average (TWA):	as Cr	ACGIH
	0.5 mg/m3	PEL:	as Cr	OSHA Z1
	0.5 mg/m3	Time Weighted Average (TWA):		MX OEL
	0.5 mg/m3	Time Weighted Average (TWA):	as Sb	ACGIH
	0.5 mg/m3	PEL:	as Sb	OSHA Z1
	0.5 mg/m3	Time Weighted Average (TWA):	as Sb	MX OEL
Silica, amorphous	0.8 mg/m3	Time Weighted Average (TWA):		Z3
	10 mg/m3	Time Weighted Average (TWA):	Inhalable particulate.	MX OEL
	3 mg/m3	Time Weighted Average (TWA):	Respirable dust.	MX OEL
Titanium dioxide	10 mg/m3	Time Weighted Average (TWA):		ACGIH
	15 mg/m3	PEL:	Total dust.	OSHA Z1
	10 mg/m3	Time Weighted Average (TWA):	as Ti	MX OEL
	20 mg/m3	Short Term Exposure Limit (STEL):	as Ti	MX OEL

### 9. PHYSICAL AND CHEMICAL PROPERTIES

- Form Appearance Color Odour Melting point/range Boiling Point: Water solubility
- Solid
  pellets
  BROWN
  Very faint
  Not determined
  Not applicable
  Insoluble

Evaporation rate Specific Gravity Bulk density Vapour pressure Vapour density pH

- : Not applicable
- : Not determined
- Not establishedNot applicable
- Not applicableNot applicable
  - Not applicable

:

**10. STABILITY AND REACTIVITY** 

Stability

: Stable.

:

Will not occur.

Hazardous Polymerization

Conditions to avoid

: Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.

PolyOne

## **MATERIAL SAFETY DATA SHEET** 4T1A-CAMEL/GF600A33

Version Number 1.0 Revision Date 03/28/2008 Page 5 of 8 Print Date 1/3/2012

Incompatible Materials	:	Incompatible with strong acids and oxidizing agents.
Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.

#### **11. TOXICOLOGICAL INFORMATION**

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

<u>Toxicity Overview</u> This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
70624-18-9	1,6-Hexanediamine, N,N'-	Irritant	Eyes, Skin, Respiratory
	bis(2,2,6,6-tetramethyl-4-		system.
	piperidinyl)-,polymer with		
	2,4,6-trichloro-1,3,5-		
	triazine, reaction products		
26741-53-7	2,4,8,10-Tetraoxa-3,9-	Toxic	Refer to LC50 / LD50 Data on
	diphosphaspiro[5.5]undeca		MSDS
	ne, 3,9-bis[2,4-bis(1,1-		
	dimethylethyl)phenoxy]-		
1317-65-3	Calcium carbonate	Irritant	Eyes, Skin.
		Systemic effects	Eyes, Skin, Respiratory
			system.
7631-86-9	Silica, amorphous	Irritant	Eyes, Respiratory system.
68186-90-3	Rutile, antimony	Irritant	Eyes, Skin, Respiratory
	chromium buff		system.
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.

### LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
70624-18-9	1,6-Hexanediamine, N,N'-	Oral LD50	> 2,000 mg/kg	rat
	bis(2,2,6,6-tetramethyl-4-	Dermal LD50	> 3,000 mg/kg	rat
	piperidinyl)-,polymer with			
	2,4,6-trichloro-1,3,5-			
	triazine, reaction products			
26741-53-7	2,4,8,10-Tetraoxa-3,9-	LC50	> 2 gm/m3	rat
	diphosphaspiro[5.5]undeca	Oral LD50	5,580 mg/kg	rat
	ne, 3,9-bis[2,4-bis(1,1-	Dermal LD50	> 200 mg/kg	rabbit
	dimethylethyl)phenoxy]-			
7631-86-9	Silica, amorphous	Oral	15,000	mouserat
		LD50Oral	mg/kg22,500	
		LD50	mg/kg	

Carcinogenicity

# MATERIAL SAFETY DATA SHEET 4T1A-CAMEL/GF600A33

Version Number 1.0 Revision Date 03/28/2008 Page 6 of 8 Print Date 1/3/2012

This product contains the following components which, in their pure form, have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
13463-67-7	Titanium dioxide	no	2B	no

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

### Additional Health Hazard Information:

Rutile, antimony chromium buff 68186-90-3 Can cause eye irritation. Can cause skin irritation. Symptoms may include redness and burning of skin, and other skin damage. Additional symptoms of skin contact may include: antimony measles (a red, pimply rash).

	12. ECOLOGICAL INFORMATION
Persistence and degradability	: Not readily biodegradable.
Environmental Toxicity	: Chemicals are not readily available as they are bound within the polymer matrix.
Bioaccumulation Potential	: Chemicals are not readily available as they are bound within the polymer matrix.
Additional advice	: No data available
	13. DISPOSAL CONSIDERATIONS
Product Contaminated packaging	<ul> <li>Like most thermoplastic plastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.</li> <li>Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.</li> </ul>
	14. TRANSPORT INFORMATION
U.S. DOT Classification	: Not regulated for transportation.

PolyOne.

# MATERIAL SAFETY DATA SHEET **4T1A-CAMEL/GF600A33**

						F	َ Page Print Date 1/3/
ICAO/IATA (air)	:	Refer to specific	c regulatio	on.			
IMO / IMDG (maritime)		-	-				
IMO / IMDG (maritime)	:	Refer to specific	e regulatio	m.			
	15	5. REGULATOR	Y INFO	RMATIO	N		
US Regulations:							
<b>OSHA Status</b>	:	Classified as ha	zardous ba	ased on co	mponent	ts.	
TSCA Status	:	All components		roduct are	listed on	or exer	npt from the
US. EPA CERCLA Hazardou	s Sub	stances (40 CFR	302)				
Not applicable							
California Proposition 65	:	Not applicable					
SARA Title III Section 302 E	xtrem	ely Hazardous Su	Ibstance				
Unless specific chemicals are	identi	ified under this se	ction, this	product i	s Not Ap	plicable	under this regul
SARA Title III Section 313 To	ovic (	Themicals:					
						. 1 1 1 .	. 1 1
Unless specific chemicals are Chemical Name	Ident	ined under this se	cuon, uns	CAS-No		Weight	
CHROMIUM III COMPOU COMPOUNDS	JNDS	ANTIMONY		68186-90		5.00 -	10.00
Canadian Regulations:							
	ease I	nventory (NPRI)					
National Pollutant Rele		, (- · · · · · · · · · · · · · · · · · ·	CAS-N	0.	Weight	t %	NPRI ID#
National Pollutant Rele			68186-9	90-3	5.00 - 1	10.00	69
	buff		00100-3				
Chemical Name	buff		557-05-	1	5.00 - 1		17

WHMIS Ingredient Disclosure List

PolyOne

# MATERIAL SAFETY DATA SHEET 4T1A-CAMEL/GF600A33

Version Number 1.0 Revision Date 03/28/2008

\_

Page 8 of 8 Print Date 1/3/2012

CAS-No. 68186-90-3 7631-86-9		
DSL	:	All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.
National Inventories:		
Australia AICS	:	Listed
China IECS	:	Listed
Europe EINECS	:	Not determined
Japan ENCS	:	Not determined
Korea KECI	:	Not determined
Philippines PICCS	:	Not determined
		16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.