PolvOne

MATERIAL SAFETY DATA SHEET **RED**

Version Number 1.0 Revision Date 04/15/2008

Page 1 of 7 Print Date 1/3/2012

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone:Emergency telephone:		Product Stewardship (770) 271-5902 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	RED
Product code	:	CC10110634
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight %
Calcium carbonate	1317-65-3	5 - 10
Benzenesulfonic acid, 5-chloro-2-[(2-	5160-02-1	10 - 30
hydroxy-1-naphthalenyl)azo]-4-methyl-,		
barium salt (2:1)		
Titanium dioxide	13463-67-7	10 - 30

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation	: Resin particles, like other inert materials, can be mechanically irritating.
Ingestion	: May be harmful if swallowed.
Eyes	: Resin particles, like other inert materials, are mechanically irritating to eyes.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.

PolyOne.

MATERIAL SAFETY DATA SHEET **RED**

ion Number 1.0 sion Date 04/15/2008	Page Print Date 1/3
Chronic exposure	: Refer to Section 11 for Toxicological Information.
Medical Conditions Aggravated by Exposure:	: None known.
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seek medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: Not applicable
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media	 Not applicable Not applicable Not applicable Carbon dioxide blanket, Water spray, Dry powder, Foam.
Special Fire Fighting Procedures	: Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne
Unusual Fire/Explosion Hazards	 contaminants. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material ir plastic, cardboard or metal containers for disposal. Refer to Sectior 13 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE



MATERIAL SAFETY DATA SHEET **RED**

Version Number 1.0 Revision Date 04/15/2008		Page 3 of 7 Print Date 1/3/2012
Handling	:	Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.
Storage	:	Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.
8. EX	POSU	RE CONTROLS/PERSONAL PROTECTION
Respiratory protection	:	No personal respiratory protective equipment normally required.
Eye/Face Protection	:	Safety glasses with side-shields
Hand protection	:	Protective gloves
Skin and body protection	:	Long sleeved clothing
Additional Protective Measures	:	Safety shoes
General Hygiene Considerations	:	Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.
Engineering measures	:	Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.

Exposure limit(s)

Components	Value	Exposure time	Exposure type	List:
Calcium carbonate	5 mg/m3	PEL:	Respirable fraction.	OSHA Z1
	15 mg/m3	PEL:	Total dust.	OSHA Z1
	10 mg/m3	Time Weighted Average		MX OEL
		(TWA):		
	20 mg/m3	Short Term Exposure Limit		MX OEL
		(STEL):		
Titanium dioxide	10 mg/m3	Time Weighted Average		ACGIH
		(TWA):		
	15 mg/m3	PEL:	Total dust.	OSHA Z1
	10 mg/m3	Time Weighted Average	as Ti	MX OEL
		(TWA):		
	20 mg/m3	Short Term Exposure Limit	as Ti	MX OEL
	_	(STEL):		

9. PHYSICAL AND CHEMICAL PROPERTIES

- Form Appearance Color Odour
- SolidpelletsREDVery faint

Evaporation rate Specific Gravity Bulk density Vapour pressure Not applicableNot determinedNot establishedNot applicable

PolyOne.

Page 4 of 7

Print Date 1/3/2012

POLYONE CORPORATION

MATERIAL SAFETY DATA SHEET **RED**

Version Number 1.0 Revision Date 04/15/2008

_

Not determinedNot applicableInsoluble	Vapour density pH	: Not applicable : Not applicable
10. STABILITY AN	D REACTIVITY	
: Stable.		
: Will not occur.		
		flame. To avoid thermal
: Incompatible with	strong acids and oxidizing	g agents.
		e e
	 Not applicable Insoluble 10. STABILITY AN Stable. Will not occur. Keep away from o decomposition, do Incompatible with Carbon dioxide (C 	 Not applicable pH Insoluble 10. STABILITY AND REACTIVITY Stable. Will not occur. Keep away from oxidizing agents and open a decomposition, do not overheat. Incompatible with strong acids and oxidizing agents and oxidizing agents and oxidizing agents and oxidizing agents and oxidizing a decomposition.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
1317-65-3	Calcium carbonate	Irritant	Eyes, Skin.
		Systemic effects	Eyes, Skin, Respiratory
			system.
5160-02-1	Benzenesulfonic acid, 5- chloro-2-[(2-hydroxy-1- naphthalenyl)azo]-4- methyl-, barium salt (2:1)	Irritant	Eyes, Skin.
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
13463-67-7	Titanium dioxide	no	2B	no

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

<u>PolyOne</u>

MATERIAL SAFETY DATA SHEET **RED**

Version Number 1.0 Revision Date 04/15/2008 Page 5 of 7 Print Date 1/3/2012

2 - The component is reasonably anticipated to be a human carcinogen.

Persistence and degradability	: Not readily biodegradable.
r crossience and degradability	. Not readily blodegradable.
Environmental Toxicity	: Chemicals are not readily available as they are bound within the polymer matrix.
Bioaccumulation Potential	: Chemicals are not readily available as they are bound within the polymer matrix.
Additional advice	: No data available
	13. DISPOSAL CONSIDERATIONS
Product	: Like most thermoplastic plastics the product can be recycled. When possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. DOT Classification	: Not regulated for transportation.
ICAO/IATA (air)	: Refer to specific regulation.
IMO / IMDG (maritime)	: Refer to specific regulation.
	15. REGULATORY INFORMATION
US Regulations:	
OSHA Status	: Classified as hazardous based on components.
TSCA Status	: All components of this product are listed on or exempt from the TSCA Inventory.
US. EPA CERCLA Hazardous	Substances (40 CFR 302)
Not applicable	

POLYONE CORPORATION

PolyOne.

MATERIAL SAFETY DATA SHEET **RED**

-0						
sion Number 1.0 ⁄ision Date 04/15/2008				I	Pa Print Date	age 6 (1/3/2)
California Proposition	· WADNINCI	This produ	at contains	a ahamiaal know	up to the St	oto of
California Proposition 65	: WARNING! California to c				wil to the St	
05	Camorina to c	cause canee	1.			
SARA Title III Section 302 E	xtremely Hazardous S	Substance				
Unless specific chemicals are	identified under this	section, thi	s product is	Not Applicable	under this:	regulat
SARA Title III Section 313 T	oxic Chemicals:					
Unless specific chemicals are	identified under this	section, thi				regulat
Chemical Name		TD C	CAS-No.	Weigh		
BARIUM COMPOUNDSE	ARIUM COMPOUN	NDS	5160-02-1	10.00	- 30.00	
[EXCEPT BASO4]						
Canadian Regulations:						
National Pollutant Rele	ease Inventory (NPRI	()				
Chemical Name		CAS-N		Weight %	NPRI ID	4
Aluminum oxide		1344-2	8-1	0.10 - 1.00		
WHMIS Classification	n : D2A					
WHMIS Ingredient Di	sclosure List					
CAS-No.						
5160-02-1						
DSL	A 11	nto of this m	modulations.	on the Consider	Domostio	
DSL	Substances Li			on the Canadian	Domestic	
	Substances Er		are exemp			
National Inventories:						
Australia AICS	: Listed					
China JECS	. I interd					
China IECS	: Listed					
Europe EINECS	: Listed					
	. 215000					
Japan ENCS	: Listed					
Korea KECI	: Listed					
Dhilingings DICCO	. Listad					
Philippines PICCS	: Listed					

PolyOne

MATERIAL SAFETY DATA SHEET **RED**

Version Number 1.0 Revision Date 04/15/2008 Page 7 of 7 Print Date 1/3/2012

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.