MATERIAL SAFETY DATA SHEET GREEN EDGE GLOW

Version Number 1.0 Revision Date 04/15/2008

Page 1 of 6 Print Date 1/3/2012

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone Emergency telephone	:	Product Stewardship (770) 271-5902 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	GREEN EDGE GLOW
Product code	:	CC10110782
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight %
Toluene	108-88-3	0.1 - 1

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation	: Resin particles, like other inert materials, can be mechanically irritating.
Ingestion	: May be harmful if swallowed.
Eyes	: Resin particles, like other inert materials, are mechanically irritating to eyes.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.
Medical Conditions Aggravated by Exposure:	: None known.

PolyOne.

MATERIAL SAFETY DATA SHEET GREEN EDGE GLOW

Version Number 1.0 Revision Date 04/15/2008 Page 2 of 6 Print Date 1/3/2012

	4. FIRST AID MEASURES				
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all case doubt seek medical advice.	g or combustion. When symptoms persist or in all cases of			
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.	5			
Eyes	: Rinse immediately with plenty of water, also under the eyelids, fo least 15 minutes. If eye irritation persists, seek medical attention.	r at			
Skin	: Wash off with soap and plenty of water. If skin irritation persists seek medical attention.				
	5. FIRE-FIGHTING MEASURES				
Flash point	: Not applicable				
Flammable Limits					
Upper explosion limit	: Not applicable				
Lower explosion limit	: Not applicable				
Autoignition temperature	: Not applicable				
Suitable extinguishing media	Carbon dioxide blanket, Water spray, Dry powder, Foam.				
Special Fire Fighting Procedures	Fullface self-contained breathing apparatus (SCBA) used in positiv pressure mode should be worn to prevent inhalation of airborne contaminants.				
Unusual Fire/Explosion Hazards	: Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.	L			
	. ACCIDENTAL RELEASE MEASURES				
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.				
Environmental precautions	: Should not be released into the environment. The product should be allowed to enter drains, water courses or the soil.	not			
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material plastic, cardboard or metal containers for disposal. Refer to Section 13 of this MSDS for proper disposal methods.				
	7. HANDLING AND STORAGE				
Handling	: Take measures to prevent the build up of electrostatic charge. Here only in areas with appropriate exhaust ventilation.	at			
Storage	: Keep containers dry and tightly closed to avoid moisture absorption	n			

2/6

PolyOne.

MATERIAL SAFETY DATA SHEET GREEN EDGE GLOW

Version Number 1.0 Revision Date 04/15/2008 Page 3 of 6 Print Date 1/3/2012

8.	EXPOSURE	CONTROLS/PERSONAL	PROTECTION			
Respiratory protection	: N	: No personal respiratory protective equipment normally require				
Eye/Face Protection	: S	afety glasses with side-shields	3			
Hand protection	: P	: Protective gloves				
Skin and body protection	: L	ong sleeved clothing				
Additional Protective Measures	: S	afety shoes				
General Hygiene Considerations		andle in accordance with goor ractice. Wash hands before by				
Engineering measures		eat only in areas with appropropropriate exhaust ventilation		Provide		
Exposure limit(s)						
Components	Value	Exposure time	Exposure type	List:		
Toluene	20 ppm	Time Weighted Average (TWA):		ACGIH		
	200 ppm	Time Weighted Average (TWA):		OSHA Z2		
	300 ppm	Ceiling Limit Value:		OSHA Z2		
	500 ppm	Maximum concentration:		OSHA Z2		
	50 ppm 188 mg/m3	Time Weighted Average (TWA):		MX OEL		
		CAL AND CHEMICAL PRO	DEDTIES	÷		
	9.11130	CAL AND CHEMICAL FRO	JF EKTIES			
Form	: Solid	1		t applicable		
Appearance	: pelle		-	determined		
Color	: GRE		5	t established		
Odour Malting gaint/manage				applicable		
Melting point/range Boiling Point:		letermined Vapou applicable pH		t applicable t applicable		
Water solubility	: Insol		. 110	applicable		
water solubility	. 111501	uoie				
	10. 5	TABILITY AND REACTIV	VITY			
		table.				
Stability						

PolyOne

MATERIAL SAFETY DATA SHEET GREEN EDGE GLOW

Version Number 1.0 Revision Date 04/15/2008		Page 4 of 6 Print Date 1/3/2012
Conditions to avoid	:	Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
Incompatible Materials	:	Incompatible with strong acids and oxidizing agents.
Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
108-88-3	Toluene	Systemic effects	central nervous system (CNS), Liver, Kidney, urinary system.
		Irritant	Skin, Eyes.

LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
108-88-3	Toluene	LC50	49 gm/m3	rat
		LC50		mouse
		LC50		rat
		Oral	636 mg/kg2,600	ratrat
		LD50Oral	- 7,500 mg/kg	rabbit
		LD50	14100 ul/kg	rabbit
		Dermal LD50	12,124 mg/kg	
		Dermal LD50		

12. ECOLOGICAL INFORMATION

Persistence and degradability	:	Not readily biodegradable.
Environmental Toxicity	:	Chemicals are not readily available as they are bound within the polymer matrix.
Bioaccumulation Potential	:	Chemicals are not readily available as they are bound within the polymer matrix.
Additional advice	:	No data available
	1	3. DISPOSAL CONSIDERATIONS
Product	:	Like most thermoplastic plastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The

PolyOne.

MATERIAL SAFETY DATA SHEET **GREEN EDGE GLOW**

sion Number 1.0 rision Date 04/15/2008	Page 5 Print Date 1/3/2
	generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. DOT Classification	: Not regulated for transportation.
ICAO/IATA (air)	: Refer to specific regulation.
IMO / IMDG (maritime)	: Refer to specific regulation.
	15. REGULATORY INFORMATION
US Regulations:	
OSHA Status	: Classified as hazardous based on components.
TSCA Status	: All components of this product are listed on or exempt from the TSCA Inventory.
US. EPA CERCLA Hazardous	Substances (40 CFR 302)
Not applicable	
California Proposition 65	: WARNING! This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.
SARA Title III Section 302 Ex	tremely Hazardous Substance
Unless specific chemicals are	dentified under this section, this product is Not Applicable under this regulat
SARA Title III Section 313 To	xic Chemicals:
Unless specific chemicals are	dentified under this section, this product is Not Applicable under this regula
Canadian Regulations:	

<u>PolyOne</u>

MATERIAL SAFETY DATA SHEET GREEN EDGE GLOW

Version Number 1.0 Revision Date 04/15/2008

_

Page 6 of 6 Print Date 1/3/2012

Chemical Name 2-Propenoic acid, 2-methyl-, methyl ester			CAS-No.	Weight %	NPRI ID#
			80-62-6	0.10 - 1.00	
Toluene			108-88-3	0.10 - 1.00	
WHMIS Classification DSL	:			nined. Quantity use	in Canada ma
ational Inventories:					
Australia AICS	:	Not determine	ed		
China IECS	:	Not determine	ed		
Europe EINECS	:	Not determine	ed		
Japan ENCS	:	Not determine	ed		
Korea KECI	:	Not determine	ed		
Philippines PICCS	:	Not determine	ed		

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.