MATERIAL SAFETY DATA SHEET YELLOW TPE G7960 LQ

Version Number 1.0 Revision Date 04/29/2008 Page 1 of 6 Print Date <u>1/3/2012</u>

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone:Emergency telephone:	Product Stewardship (770) 271-5902 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name :	YELLOW TPE G7960 LQ
Product code :	CC10110855
Chemical Name :	Mixture
CAS-No. :	Mixture
Product Use :	Industrial Applications

2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight %
Silica, amorphous	7631-86-9	0.1 - 1
Titanium dioxide	13463-67-7	10 - 30

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Skin contact, Ingestion
Acute exposure	
Inhalation	: Inhalation of airborne droplets may cause irritation of the respiratory tract.
Ingestion	: May be harmful if swallowed.
Eyes	: Irritating to eyes and respiratory system.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.
Medical Conditions Aggravated by Exposure:	: None known.

PolyOne.

MATERIAL SAFETY DATA SHEET **YELLOW TPE G7960 LQ**

Version Number 1.0 Revision Date 04/29/2008 Page 2 of 6 Print Date 1/3/2012

	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. Seek medical attention after significant exposure.
Ingestion	: Do not induce vomiting without medical advice. Seek medical attention if necessary.
Eyes	: Rinse immediately with plenty of water for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seek medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: Greater than 200 °F (93 °C)
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media	 Not applicable Not applicable Not applicable Carbon dioxide blanket, Dry powder, Foam.
Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	 Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.
	5. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: The product should not be allowed to enter drains, water courses or the soil. Should not be released into the environment.
Methods for cleaning up	: Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Package all material in appropriate container for disposal. Refer to Section 13 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Heat only in areas with appropriate exhaust ventilation.
Storage	: Keep containers dry and tightly closed to avoid moisture absorption

<u>PolyOne</u>

MATERIAL SAFETY DATA SHEET YELLOW TPE G7960 LQ

Version Number 1.0 Revision Date 04/29/2008 Page 3 of 6 Print Date 1/3/2012

8.	EXPOSURE	CONTROLS/PERSONAL I	PROTECTION	
Respiratory protection	: U	nder normal handling condition	ns a respirator may not b	be required.
Eye/Face Protection	: S	afety glasses with side-shields		
Hand protection	: P:	rotective gloves		
Skin and body protection	1 : L	ong sleeved clothing		
Additional Protective Measures	: S	afety shoes		
7	: H	andle in accordance with good	l industrial hygiene and s	safety
General Hygiene Considerations		ractice. Wash hands before br		
Considerations Engineering measures	ים : H		eaks and at the end of wo	orkday.
Considerations	ים : H	ractice. Wash hands before breat only in areas with appropriate	eaks and at the end of wo	orkday.
Considerations Engineering measures Exposure limit(s) Components	pı : H aı Value	ractice. Wash hands before brochest only in areas with appropriate exhaust ventilation a Exposure time	eaks and at the end of wo	orkday. Provide List:
Considerations Engineering measures Exposure limit(s)	pı : H aj	ractice. Wash hands before bractice. Wash hands before bracter only in areas with appropriate exhaust ventilation a	eaks and at the end of wo	orkday. Provide
Considerations Engineering measures Exposure limit(s) Components	pı : H aı Value	ractice. Wash hands before brochest only in areas with appropriate exhaust ventilation a Exposure time Time Weighted Average	eaks and at the end of wo	orkday. Provide List:
Considerations Engineering measures Exposure limit(s) Components	Pi : H aj Value 0.8 mg/m3	Exposure time Time Weighted Average (TWA): Time Weighted Average (TWA): Time Weighted Average	eaks and at the end of wo	orkday. Provide List: Z3
Considerations Engineering measures Exposure limit(s) Components	Pi : H aj 0.8 mg/m3 10 mg/m3	Exposure time Time Weighted Average (TWA): Time Weighted Average (TWA): Time Weighted Average (TWA): Time Weighted Average (TWA): Time Weighted Average	eaks and at the end of wo ate exhaust ventilation. at machinery. Exposure type Inhalable particulate.	Drkday. Provide List: Z3 MX OEL
Considerations Engineering measures Exposure limit(s) Components Silica, amorphous	Pi : H aj 0.8 mg/m3 10 mg/m3 3 mg/m3 10 mg/m3	Exposure time Time Weighted Average (TWA): Time Weighted Average (TWA): Time Weighted Average (TWA):	eaks and at the end of wo fate exhaust ventilation. at machinery. Exposure type Inhalable particulate. Respirable dust.	orkday. Provide List: Z3 MX OEL MX OEL ACGIH
Considerations Engineering measures Exposure limit(s) Components Silica, amorphous	pi : H aj <u>Value</u> 0.8 mg/m3 10 mg/m3 <u>3 mg/m3</u>	Exposure time Time Weighted Average (TWA): Time Weighted Average (TWA): Time Weighted Average (TWA): Time Weighted Average (TWA): Time Weighted Average (TWA):	eaks and at the end of wo ate exhaust ventilation. at machinery. Exposure type Inhalable particulate.	Drkday. Provide List: Z3 MX OEL MX OEL

Form Appearance Color Odour Melting point/range Boiling Point: Water solubility

10. STABILITY AND REACTIVITY

: Viscous, liquid

: Not applicable

: Not applicable

: YELLOW

: Very faint

: Immiscible

Specific Gravity

Bulk density

Vapour pressure

Vapour density

pН

: Not determined

: Not applicable

: Not determined

: Not determined

: Not applicable

MATERIAL SAFETY DATA SHEET **YELLOW TPE G7960 LQ**

Version Number 1.0 Revision Date 04/29/2008 Page 4 of 6 Print Date 1/3/2012

Stability	:	Stable.
Hazardous Polymerization	:	Will not occur.
Conditions to avoid	:	Keep away from oxidizing agents and open flame.
Incompatible Materials	:	Incompatible with strong acids and oxidizing agents.
Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
7631-86-9	Silica, amorphous	Irritant	Eyes, Respiratory system.
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.

LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
7631-86-9	Silica, amorphous	Oral LD50Oral	15,000 mg/kg22,500	mouserat
		LD50	mg/kg	

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
13463-67-7	Titanium dioxide	no	2B	no

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

12. ECOLOGICAL INFORMATION

PolyOne.

MATERIAL SAFETY DATA SHEET **YELLOW TPE G7960 LQ**

ion Number 1.0 sion Date 04/29/2008	Page Print Date 1/3,
Persistence and degradability	: Not readily biodegradable.
Environmental Toxicity	: Adverse ecological impact is not known or expected under normal use.
Bioaccumulation Potential	: Does not bioaccumulate.
Additional advice	: No data available
	13. DISPOSAL CONSIDERATIONS
Product	: Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. DOT Classification	: Not regulated for transportation.
ICAO/IATA (air)	: Not regulated for transportation.
IMO / IMDG (maritime)	: Not regulated for transportation.
	15. REGULATORY INFORMATION
US Regulations:	
OSHA Status	: Classified as hazardous based on components.
TSCA Status	: All components of this product are listed on or exempt from the TSCA Inventory.
US. EPA CERCLA Hazardous	Substances (40 CFR 302)
Not applicable	
	: Not applicable

MATERIAL SAFETY DATA SHEET **YELLOW TPE G7960 LQ**

Version Number 1.0 Revision Date 04/29/2008 Page 6 of 6 Print Date 1/3/2012

SARA Title III Section 302 Extremely Hazardous Substance

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

SARA Title III Section 313 Toxic Chemicals:

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

Canadian Regulations:

National Pollutant Release Inventory (NPRI)

Chemical Name	CAS-No.	Weight %	NPRI ID#
Phenol, nonyl-, phosphite (3:1)	26523-78-4	1.00 - 5.00	

DSL	:	All components of this product are on the Canadian Domestic
		Substances List (DSL) or are exempt.

National Inventories:

		16. OTHER INFORMATION	Т
Philippines PICCS	:	Listed	
Korea KECI	:	Listed	
Japan ENCS	:	Not determined	
Europe EINECS	:	Not determined	
China IECS	:	Not determined	
Australia AICS	:	Listed	

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.