PolvOne

MATERIAL SAFETY DATA SHEET **NP BLUE**

Version Number 1.0 Revision Date 05/01/2008 Page 1 of 7 Print Date 1/3/2012

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

| Telephone Emergency telephone | : | Product Stewardship (770) 271-5902 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident). |
|----------------------------------|---|---|
| Product name | : | NP BLUE |
| Product code | : | CC10111122 |
| Chemical Name | : | Mixture |
| CAS-No. | : | Mixture |
| Product Use | : | Industrial Applications |

2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

| Components | CAS-No. | Weight % |
|--|------------|----------|
| Cobalt titanate green spinel (C.I. Pigment | 68186-85-6 | 1 - 5 |
| Green 50) | | |
| Calcium carbonate | 1317-65-3 | 1 - 5 |
| Titanium dioxide | 13463-67-7 | 1 - 5 |

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

| Routes of Exposure: | : Inhalation, Ingestion, Skin contact |
|---------------------|---|
| Acute exposure | |
| Inhalation | : Resin particles, like other inert materials, can be mechanically irritating. |
| Ingestion | : May be harmful if swallowed. |
| Eyes | : Resin particles, like other inert materials, are mechanically irritating to eyes. |
| Skin | : Experience shows no unusual dermatitis hazard from routine handling. |

PolyOne.

MATERIAL SAFETY DATA SHEET **NP BLUE**

Version Number 1.0 Revision Date 05/01/2008 Page 2 of 7 Print Date 1/3/2012

| Medical Conditions Aggravated by Exposure: | : None known. |
|--|---|
| | 4. FIRST AID MEASURES |
| Inhalation | : Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice. |
| Ingestion | : Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice. |
| Eyes | : Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention. |
| Skin | : Wash off with soap and plenty of water. If skin irritation persists seek medical attention. |
| | 5. FIRE-FIGHTING MEASURES |
| Flash point | : Not applicable |
| Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media | Not applicable Not applicable Not applicable Carbon dioxide blanket, Water spray, Dry powder, Foam. |
| Special Fire Fighting Procedures | : Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. |
| Unusual Fire/Explosion Hazards | Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible. |
| | 6. ACCIDENTAL RELEASE MEASURES |
| Personal precautions | : Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls. |
| Environmental precautions | : Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil. |
| Methods for cleaning up | : Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 13 of this MSDS for proper disposal methods. |
| | 7. HANDLING AND STORAGE |



MATERIAL SAFETY DATA SHEET **NP BLUE**

| Version Number 1.0 Revision Date 05/01/2008 | | Page 3 of 7 Print Date 1/3/2012 |
|--|-----|---|
| Handling | : | Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation. Keep containers dry and tightly closed to avoid moisture absorption |
| U U | | and contamination. Keep in a dry, cool place. |
| 8. EXP | OSU | RE CONTROLS/PERSONAL PROTECTION |
| Respiratory protection | : | No personal respiratory protective equipment normally required. |
| Eye/Face Protection | : | Safety glasses with side-shields |
| Hand protection | : | Protective gloves |
| Skin and body protection | : | Long sleeved clothing |
| Additional Protective Measures | : | Safety shoes |
| General Hygiene Considerations | : | Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday. |
| Engineering measures | : | Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery. |

Exposure limit(s)

| Components | Value | Exposure time | Exposure type | List: |
|-----------------------|----------|---------------------------|---------------------------|---------|
| Cobalt titanate green | 0.02 | Time Weighted Average | me Weighted Average as Co | |
| spinel (C.I. Pigment | mg/m3 | (TWA): | | |
| Green 50) | | | | |
| Calcium carbonate | 5 mg/m3 | PEL: | Respirable fraction. | OSHA Z1 |
| | 15 mg/m3 | PEL: | Total dust. | OSHA Z1 |
| | 10 mg/m3 | Time Weighted Average | | MX OEL |
| | | (TWA): | | |
| | 20 mg/m3 | Short Term Exposure Limit | | MX OEL |
| | | (STEL): | | |
| Titanium dioxide | 10 mg/m3 | Time Weighted Average | | ACGIH |
| | | (TWA): | | |
| | 15 mg/m3 | PEL: | Total dust. | OSHA Z1 |
| | 10 mg/m3 | Time Weighted Average | as Ti | MX OEL |
| | | (TWA): | | |
| | 20 mg/m3 | Short Term Exposure Limit | as Ti | MX OEL |
| | | (STEL): | | |

9. PHYSICAL AND CHEMICAL PROPERTIES

Form Appearance : Solid : pellets Evaporation rate Specific Gravity Not applicableNot determined

MATERIAL SAFETY DATA SHEET **NP BLUE**

Version Number 1.0 Revision Date 05/01/2008

| Color Odour Melting point/range Boiling Point: Water solubility | : | BLUE Very faint Not determined Not applicable Insoluble | Bulk density Vapour pressure Vapour density pH | : | Not established Not applicable Not applicable Not applicable |
|---|---|---|---|-------|---|
| | | 10. STABILITY AND R | EACTIVITY | | |
| Stability | | Stable. | | | |
| Hazardous Polymerization | | : Will not occur. | | | |
| Conditions to avoid | | : Keep away from oxidiz decomposition, do not | 00 | ame. | To avoid thermal |
| Incompatible Materials | | : Incompatible with stron | ng acids and oxidizing | agent | s. |

Hazardous decomposition
products:Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen
(NOx), other hazardous materials, and smoke are all possible.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

| CAS-No. | Chemical Name | Effect | Target Organ |
|------------|--|------------------|---------------------------------|
| 68186-85-6 | Cobalt titanate green spinel (C.I. Pigment Green 50) | Irritant | Eyes, Skin. |
| 1317-65-3 | Calcium carbonate | Irritant | Eyes, Skin. |
| | | Systemic effects | Eyes, Skin, Respiratory system. |
| 13463-67-7 | Titanium dioxide | Systemic effects | Respiratory system. |

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

| CAS-No. | Chemical Name | OSHA | IARC | NTP |
|------------|------------------------------|------|------|-----|
| 68186-85-6 | Cobalt titanate green spinel | no | 2B | no |
| | (C.I. Pigment Green 50) | | | |
| 13463-67-7 | Titanium dioxide | no | 2B | no |

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.



Page 4 of 7 Print Date 1/3/2012

PolyOne.

MATERIAL SAFETY DATA SHEET **NP BLUE**

Version Number 1.0 Revision Date 05/01/2008 Page 5 of 7 Print Date 1/3/2012

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

| | 12. ECOLOGICAL INFORMATION | | | |
|---|--|--|--|--|
| Persistence and degradability : Not readily biodegradable. | | | | |
| Environmental Toxicity | : Chemicals are not readily available as they are bound within the polymer matrix. | | | |
| Bioaccumulation Potential | : Chemicals are not readily available as they are bound within the polymer matrix. | | | |
| Additional advice | : No data available | | | |
| | 13. DISPOSAL CONSIDERATIONS | | | |
| Product : Like most thermoplastic plastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations. | | | | |
| Contaminated packaging | : Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations. | | | |
| 14. TRANSPORT INFORMATION | | | | |
| U.S. DOT Classification | : Not regulated for transportation. | | | |
| ICAO/IATA (air) | : Refer to specific regulation. | | | |
| IMO / IMDG (maritime) | : Refer to specific regulation. | | | |
| | 15. REGULATORY INFORMATION | | | |
| US Regulations: | | | | |
| OSHA Status | : Classified as hazardous based on components. | | | |
| TSCA Status | : All components of this product are listed on or exempt from the TSCA Inventory. | | | |
| US. EPA CERCLA Hazardous | Substances (40 CFR 302) | | | |
| | | | | |

PolyOne.

MATERIAL SAFETY DATA SHEET **NP BLUE**

Version Number 1.0 Revision Date 05/01/2008 Page 6 of 7 Print Date 1/3/2012

Not applicable

California Proposition : Not applicable 65

SARA Title III Section 302 Extremely Hazardous Substance

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

SARA Title III Section 313 Toxic Chemicals:

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

| Chemical Name | CAS-No. | Weight % |
|------------------------------------|------------|-------------|
| COBALT COMPOUNDSCOBALT COMPOUNDS, | 68186-85-6 | 0.10 - 1.00 |
| INORGANICCOBALT COMPOUNDS, ORGANIC | | |

Canadian Regulations:

National Pollutant Release Inventory (NPRI)

| Chemical Name | CAS-No. | Weight % | NPRI ID# |
|--|------------|-------------|----------|
| Cobalt titanate green spinel (C.I. Pigment Green | 68186-85-6 | 0.10 - 1.00 | |
| 50) | | | |

WHMIS Classification : D2A

DSL

: All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.

National Inventories:

| Australia AICS | : | Listed |
|-------------------|---|----------------|
| China IECS | : | Listed |
| Europe EINECS | : | Listed |
| Japan ENCS | : | Not determined |
| Korea KECI | : | Listed |
| Philippines PICCS | : | Listed |

PolyOne

MATERIAL SAFETY DATA SHEET **NP BLUE**

Version Number 1.0 Revision Date 05/01/2008 Page 7 of 7 Print Date 1/3/2012

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.