PolvOne

MATERIAL SAFETY DATA SHEET UV BEIGE PE

Version Number 1.0 Revision Date 05/02/2008 Page 1 of 8 Print Date 1/3/2012

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone Emergency telephone	:	Product Stewardship (770) 271-5902 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	UV BEIGE PE
Product code	:	CC10111176
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight %
Formamide, N,N'-1,6-hexanediylbis[N-	124172-53-8	5 - 10
(2,2,6,6-tetramethyl-4-piperidinyl)-		
Calcium carbonate	1317-65-3	1 - 5
Iron oxide	1309-37-1	1 - 5
Silica, amorphous, fumed, crystal-free	112945-52-5	1 - 5
Titanium dioxide	13463-67-7	10 - 30

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation	: Resin particles, like other inert materials, can be mechanically irritating.
Ingestion	: May be harmful if swallowed.
Eyes	: Resin particles, like other inert materials, are mechanically irritating to eyes.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.

PolyOne.

MATERIAL SAFETY DATA SHEET UV BEIGE PE

Version Number 1.0 Revision Date 05/02/2008 Page 2 of 8 Print Date 1/3/2012

Medical Conditions : None known. Aggravated by Exposure: :			
Aggravated by Exposure:			
		4. FIRST AID MEASURES	
Inhalation	:	Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.	
Ingestion	:	Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.	
Eyes	:	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.	
Skin	:	Wash off with soap and plenty of water. If skin irritation persists seek medical attention.	
		5. FIRE-FIGHTING MEASURES	
Flash point	:	Not applicable	
Flammable Limits			
Upper explosion limit	:	Not applicable	
Lower explosion limit	:	Not applicable	
Autoignition temperature	:	Not applicable	
Suitable extinguishing media	:	Carbon dioxide blanket, Water spray, Dry powder, Foam.	
Special Fire Fighting	:	Fullface self-contained breathing apparatus (SCBA) used in positive	
Procedures		pressure mode should be worn to prevent inhalation of airborne	
		contaminants.	
Unusual Fire/Explosion Hazards	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.	
	6. A	CCIDENTAL RELEASE MEASURES	
Personal precautions	:	Wear appropriate personal protection during cleanup, such as	
L		impervious gloves, boots and coveralls.	
Environmental precautions	:	Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.	
Methods for cleaning up	:	Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 13 of this MSDS for proper disposal methods.	

PolyOne.

MATERIAL SAFETY DATA SHEET UV BEIGE PE

Version Number 1.0 Revision Date 05/02/2008 Page 3 of 8 Print Date 1/3/2012

Handling	:	Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.		
Storage	: Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.			
8. EX	POSU	RE CONTROLS/PERSONAL PROTECTION		
Respiratory protection	:	No personal respiratory protective equipment normally required.		
Eye/Face Protection	:	Safety glasses with side-shields		
Hand protection	:	Protective gloves		
Skin and body protection	:	Long sleeved clothing		
Additional Protective Measures	:	Safety shoes		
General Hygiene Considerations	:	Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.		
Engineering measures	:	Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.		

<u>PolyOne</u>

MATERIAL SAFETY DATA SHEET UV BEIGE PE

Version Number 1.0 Revision Date 05/02/2008 Page 4 of 8 Print Date 1/3/2012

Components	Value	Exposure time	Exposure type	List:
Calcium carbonate	5 mg/m3	PEL:	Respirable fraction.	OSHA Z1
	15 mg/m3	PEL:	Total dust.	OSHA Z1
	10 mg/m3	Time Weighted Average (TWA):		MX OEL
	20 mg/m3	Short Term Exposure Limit (STEL):		MX OEL
Iron oxide	5 mg/m3	Time Weighted Average (TWA):	Respirable fraction.	ACGIH
	10 mg/m3	PEL:	Fume.	OSHA Z1
	5 mg/m3	Time Weighted Average (TWA):	as Fe	MX OEL
	10 mg/m3	Short Term Exposure Limit (STEL):	as Fe	MX OEL
Silica, amorphous, fumed, crystal-free	0.8 mg/m3	Time Weighted Average (TWA):		Z3
	10 mg/m3	Time Weighted Average (TWA):	Inhalable particulate.	MX OEL
	3 mg/m3	Time Weighted Average (TWA):	Respirable dust.	MX OEL
Titanium dioxide	10 mg/m3	Time Weighted Average (TWA):		ACGIH
	15 mg/m3	PEL:	Total dust.	OSHA Z1
	10 mg/m3	Time Weighted Average (TWA):	as Ti	MX OEL
	20 mg/m3	Short Term Exposure Limit (STEL):	as Ti	MX OEL

9. PHYSICAL AND CHEMICAL PROPERTIES

Form Appearance Color Odour Melting point/range Boiling Point: Water solubility

: pellets
: BROWN
: Very faint
: Not determined
: Not applicable
: Insoluble

: Solid

Evaporation rate Specific Gravity Bulk density Vapour pressure Vapour density pH

Not applicable
Not determined
Not established
Not applicable
Not applicable
Not applicable

10. STABILITY AND REACTIVITY

Stability	:	Stable.
Hazardous Polymerization	:	Will not occur.
Conditions to avoid	:	Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
Incompatible Materials	:	Incompatible with strong acids and oxidizing agents.

olvOn<u>e</u>

MATERIAL SAFETY DATA SHEET UV BEIGE PE

Version Number 1.0 Revision Date 05/02/2008

Page 5 of 8 Print Date 1/3/2012

Hazardous decomposition products

: Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
124172-53-8	Formamide, N,N'-1,6- hexanediylbis[N-(2,2,6,6- tetramethyl-4-piperidinyl)-	Irritant	Eyes.
1317-65-3	Calcium carbonate	Irritant	Eyes, Skin.
		Systemic effects	Eyes, Skin, Respiratory system.
1309-37-1	Iron oxide	Systemic effects	Respiratory system.
112945-52-5	Silica, amorphous, fumed, crystal-free	Irritant	Eyes, Respiratory system.
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.

LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
124172-53-8	Formamide, N,N'-1,6- hexanediylbis[N-(2,2,6,6- tetramethyl-4-piperidinyl)-	LC50 Oral LD50	> 5.0 mg/l > 2,000 mg/kg	rat rat
112945-52-5	Silica, amorphous, fumed, crystal-free	Oral LD50	3,160 mg/kg	rat

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
13463-67-7Titanium dioxide		no	2B	no

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

12. ECOLOGICAL INFORMATION



MATERIAL SAFETY DATA SHEET UV BEIGE PE

sion Number 1.0 ision Date 05/02/2008	Page 6 Print Date 1/3/2
Persistence and degradability	: Not readily biodegradable.
Environmental Toxicity	: Chemicals are not readily available as they are bound within the polymer matrix.
Bioaccumulation Potential	: Chemicals are not readily available as they are bound within the polymer matrix.
Additional advice	: No data available
	13. DISPOSAL CONSIDERATIONS
Product	: Like most thermoplastic plastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. DOT Classification	: Not regulated for transportation.
ICAO/IATA (air)	: Refer to specific regulation.
IMO / IMDG (maritime)	: Refer to specific regulation.
	15. REGULATORY INFORMATION
US Regulations:	
OSHA Status	: Classified as hazardous based on components.
TSCA Status	: All components of this product are listed on or exempt from the TSCA Inventory.
US. EPA CERCLA Hazardous	Substances (40 CFR 302)
Not applicable	
California Proposition	: Not applicable

PolyOne.

MATERIAL SAFETY DATA SHEET UV BEIGE PE

rsion Number 1.0			Page 7 of Print Date 1/3/201
vision Date 05/02/2008			Pfifit Date 1/3/201
65			
05			
SARA Title III Section 302 Ex	stremely Hazardous Substance		
Unless specific chemicals are	identified under this section, this	product is Not App	licable under this regulatio
-			
SARA Title III Section 313 To	ovia Chamicala		
Unless specific chemicals are : Chemical Name	identified under this section, this		licable under this regulation
ZINC COMPOUNDS			5.00 - 10.00
Canadian Regulations:			
National Pollutant Rele	ase Inventory (NPRI)		
	, (- · , (- · ,)		
Not applicable			
WHMIS Classification	: D2A		
WHMIS Ingredient Dis	closure List		
CAS-No.			
1309-37-1 112945-52-5			
DSL	: All of the components of Inventories or are exemp		
	product is on the Canadia	n Non-Domestic Su	bstances List (NDSL).
	Quantity use in Canada is	restricted by regula	uons.
National Inventories:			
Australia AICS	: Listed		
China IECS	: Listed		
Europe EINECS	: Not determined		
Japan ENCS	: Not determined		
Korea KECI	: Listed		
Philippines PICCS	: Listed		
	16. OTHER INFORM	ATION	

PolyOne

MATERIAL SAFETY DATA SHEET UV BEIGE PE

Version Number 1.0 Revision Date 05/02/2008 Page 8 of 8 Print Date 1/3/2012

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.