MATERIAL SAFETY DATA SHEET **1655C TL. ORANGE M3014**

Version Number 1.0 Revision Date 05/06/2008 Page 1 of 7 Print Date 1/3/2012

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone:Emergency telephone:	Product Stewardship (770) 271-5902 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name :	1655C TL. ORANGE M3014
Product code :	CC10111308
Chemical Name :	Mixture
CAS-No. :	Mixture
Product Use :	Industrial Applications

2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight %
Ethyl acrylate	140-88-5	0.1 - 1
Titanium dioxide	13463-67-7	1 - 5

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact		
Acute exposure			
Inhalation	: Resin particles, like other inert materials, can be mechanically irritating.		
Ingestion	: May be harmful if swallowed.		
Eyes	: Resin particles, like other inert materials, are mechanically irritating to eyes.		
Skin	: Experience shows no unusual dermatitis hazard from routine handling.		
Chronic exposure	: Refer to Section 11 for Toxicological Information.		

PolyOne.

MATERIAL SAFETY DATA SHEET 1655C TL. ORANGE M3014

Version Number 1.0 Revision Date 05/06/2008 Page 2 of 7 Print Date 1/3/2012

Medical Conditions Aggravated by Exposure:	: None known.
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seek medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: Not applicable
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media	 Not applicable Not applicable Not applicable Carbon dioxide blanket, Water spray, Dry powder, Foam.
Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	 Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 13 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.

PolyOne

MATERIAL SAFETY DATA SHEET 1655C TL. ORANGE M3014

Version Number 1.0 Revision Date 05/06/2008 Page 3 of 7 Print Date 1/3/2012

Storage

: Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Respiratory protection	:	No personal respiratory protective equipment normally required.
Eye/Face Protection	:	Safety glasses with side-shields
Hand protection	:	Protective gloves
Skin and body protection	:	Long sleeved clothing
Additional Protective Measures	:	Safety shoes
General Hygiene Considerations	:	Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.
Engineering measures	:	Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.

Exposure limit(s)

Components	Value	Exposure time	Exposure type	List:
Titanium dioxide	10 mg/m3	Time Weighted Average		ACGIH
		(TWA):		
	15 mg/m3	PEL:	Total dust.	OSHA Z1
	10 mg/m3	Time Weighted Average (TWA):	as Ti	MX OEL
	20 mg/m3	Short Term Exposure Limit (STEL):	as Ti	MX OEL
Ethyl acrylate	5 ppm	Time Weighted Average (TWA):		ACGIH
	15 ppm	Short Term Exposure Limit (STEL):		ACGIH
	25 ppm 100 mg/m3	PEL:		OSHA Z1
	5 ppm 20 mg/m3	Time Weighted Average (TWA):		MX OEL
	25 ppm 100 mg/m3	Short Term Exposure Limit (STEL):		MX OEL

9. PHYSICAL AND CHEMICAL PROPERTIES

Form Appearance Color : Solid: pellets: ORANGE

Evaporation rate Specific Gravity Bulk density Not applicableNot determinedNot established

MATERIAL SAFETY DATA SHEET 1655C TL. ORANGE M3014

Version Number 1.0 Revision Date 05/06/2008

Melting point/range

Odour

Boiling Point: Water solubility		ot applicable soluble	рН	: Not applicable	
	1	0. STABILITY AN	ND REACTIVITY		
Stability	:	Stable.			
Hazardous Polymerization	:	Will not occur.			
Conditions to avoid	:	Keep away from decomposition, de	00	open flame. To avoid thermal	
Incompatible Materials	:	Incompatible with	h strong acids and oxi	dizing agents.	
Hazardous decomposition products	:	,	,.	de (CO), oxides of nitrogen smoke are all possible.	

: Very faint

: Not determined

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
140-88-5	Ethyl acrylate	Irritant	Eyes, Skin, Respiratory
			system.
		Systemic effects	Respiratory system, central
			nervous system (CNS),
			digestive system.
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.

LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
140-88-5	Ethyl acrylate	Oral LD50	370 mg/kg	rabbit
		Dermal LD50	2,997 mg/kg	mouse

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
140-88-5	Ethyl acrylate	no	2B	no
13463-67-7	Titanium dioxide	no	2B	no

4/7



:

:

Vapour pressure

Vapour density

Page 4 of 7 Print Date 1/3/2012

Not applicable

Not applicable

<u>PolyOne</u>

MATERIAL SAFETY DATA SHEET **1655C TL. ORANGE M3014**

Version Number 1.0 Revision Date 05/06/2008 Page 5 of 7 Print Date 1/3/2012

IARC Carcinogen Classifications:1 - The component is carcinogenic to humans.2A - The component is probably carcinogenic to humans.2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

sible recycling is preferred to disposal or incineration. The erator of waste material has the responsibility for proper waste ssification, transportation and disposal in accordance with licable federal, state/provincial and local regulations. cycling is preferred when possible. The generator of waste
ymer matrix. emicals are not readily available as they are bound within the ymer matrix. data available SPOSAL CONSIDERATIONS e most thermoplastic plastics the product can be recycled. Where sible recycling is preferred to disposal or incineration. The erator of waste material has the responsibility for proper waste ssification, transportation and disposal in accordance with dicable federal, state/provincial and local regulations. cycling is preferred when possible. The generator of waste
ymer matrix. data available SPOSAL CONSIDERATIONS e most thermoplastic plastics the product can be recycled. Where sible recycling is preferred to disposal or incineration. The erator of waste material has the responsibility for proper waste ssification, transportation and disposal in accordance with dicable federal, state/provincial and local regulations. cycling is preferred when possible. The generator of waste
SPOSAL CONSIDERATIONS e most thermoplastic plastics the product can be recycled. Where sible recycling is preferred to disposal or incineration. The erator of waste material has the responsibility for proper waste ssification, transportation and disposal in accordance with dicable federal, state/provincial and local regulations. cycling is preferred when possible. The generator of waste
e most thermoplastic plastics the product can be recycled. Where sible recycling is preferred to disposal or incineration. The erator of waste material has the responsibility for proper waste ssification, transportation and disposal in accordance with dicable federal, state/provincial and local regulations. cycling is preferred when possible. The generator of waste
sible recycling is preferred to disposal or incineration. The erator of waste material has the responsibility for proper waste ssification, transportation and disposal in accordance with licable federal, state/provincial and local regulations. cycling is preferred when possible. The generator of waste
terial has the responsibility for proper waste classification, asportation and disposal in accordance with applicable federal, e/provincial and local regulations.
RANSPORT INFORMATION
regulated for transportation.
Fer to specific regulation.
er to specific regulation.
GULATORY INFORMATION
ssified as hazardous based on components.
ſ

MATERIAL SAFETY DATA SHEET 1655C TL. ORANGE M3014

Version Number 1.0 Revision Date 05/06/2008 Page 6 of 7 Print Date 1/3/2012

TSCA Inventory.

US. EPA CERCLA Hazardous Substances (40 CFR 302)

Not applicable

California Proposition : Not applicable 65

SARA Title III Section 302 Extremely Hazardous Substance

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

SARA Title III Section 313 Toxic Chemicals:

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

Canadian Regulations:

National Pollutant Release Inventory (NPRI)Chemical NameCAS-No.Weight %NPRI ID#2-Propenoic acid, 2-methyl-, methyl ester80-62-60.10 - 1.00

WHMIS Classification : D2A, F

DSL

: DSL status has not been determined. Quantity use in Canada may be restricted by regulations.

National Inventories:

Australia AICS	:	Not determined
China IECS	:	Not determined
Europe EINECS	:	Listed
Japan ENCS	:	Not determined
Korea KECI	:	Not determined
Philippines PICCS	:	Not determined

16. OTHER INFORMATION

<u>PolyOne</u>

MATERIAL SAFETY DATA SHEET 1655C TL. ORANGE M3014

Version Number 1.0 Revision Date 05/06/2008 Page 7 of 7 Print Date 1/3/2012

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.