PolvOne

MATERIAL SAFETY DATA SHEET CLOUD GRAY PC

Version Number 1.0 Revision Date 05/28/2008 Page 1 of 8 Print Date 1/3/2012

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone Emergency telephone	:	Product Stewardship (770) 271-5902 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	CLOUD GRAY PC
Product code	:	CC10111908
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight %
Chromium (III) oxide	1308-38-9	0.1 - 1
Rutile, antimony chromium buff	68186-90-3	0.1 - 1
Silica, amorphous	7631-86-9	0.1 - 1
Titanium dioxide	13463-67-7	30 - 60

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation	: Resin particles, like other inert materials, can be mechanically irritating.
Ingestion	: May be harmful if swallowed.
Eyes	: Resin particles, like other inert materials, are mechanically irritating to eyes.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.

PolyOne.

MATERIAL SAFETY DATA SHEET CLOUD GRAY PC

Version Number 1.0 Revision Date 05/28/2008 Page 2 of 8 Print Date 1/3/2012

Medical Conditions	: None known.				
Aggravated by Exposure:					
	4. FIRST AID MEASURES				
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases doubt seek medical advice.				
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.				
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for least 15 minutes. If eye irritation persists, seek medical attention.				
Skin	: Wash off with soap and plenty of water. If skin irritation persists seek medical attention.				
	5. FIRE-FIGHTING MEASURES				
Flash point	: Not applicable				
Flammable Limits Upper explosion limit	: Not applicable				
Lower explosion limit Autoignition temperature	Not applicableNot applicable				
Suitable extinguishing media	: Carbon dioxide blanket, Water spray, Dry powder, Foam.				
Special Fire Fighting Procedures	: Fullface self-contained breathing apparatus (SCBA) used in positiv pressure mode should be worn to prevent inhalation of airborne contaminants.				
Unusual Fire/Explosion Hazards	 Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible. 				
	6. ACCIDENTAL RELEASE MEASURES				
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.				
Environmental precautions	: Should not be released into the environment. The product should n be allowed to enter drains, water courses or the soil.				
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 13 of this MSDS for proper disposal methods.				
	7. HANDLING AND STORAGE				

PolyOne.

MATERIAL SAFETY DATA SHEET **CLOUD GRAY PC**

/ersion Number 1.0 Revision Date 05/28/2008		Page 3 of 8 Print Date 1/3/2012
Handling	:	Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.
Storage	:	Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.
8. EX	POSU	RE CONTROLS/PERSONAL PROTECTION
Respiratory protection	:	No personal respiratory protective equipment normally required.
Eye/Face Protection	:	Safety glasses with side-shields
Hand protection	:	Protective gloves
Skin and body protection	:	Long sleeved clothing
Additional Protective Measures	:	Safety shoes
General Hygiene Considerations	:	Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.
Engineering measures	:	Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.
Exposure limit(s)		

<u>PolyOne</u>

MATERIAL SAFETY DATA SHEET CLOUD GRAY PC

Version Number 1.0 Revision Date 05/28/2008 Page 4 of 8 Print Date 1/3/2012

Components	Value	Exposure time	Exposure type	List:
Chromium (III) oxide	0.5 mg/m3	Time Weighted Average (TWA):	as Cr	ACGIH
	0.5 mg/m3	PEL:	as Cr	OSHA Z1
Rutile, antimony chromium buff	0.5 mg/m3	Time Weighted Average (TWA):	as Cr	ACGIH
	0.5 mg/m3	PEL:	as Cr	OSHA Z1
	0.5 mg/m3	Time Weighted Average (TWA):		MX OEL
	0.5 mg/m3	Time Weighted Average (TWA):	as Sb	ACGIH
	0.5 mg/m3	PEL:	as Sb	OSHA Z1
	0.5 mg/m3	Time Weighted Average (TWA):	as Sb	MX OEL
Silica, amorphous	0.8 mg/m3	Time Weighted Average (TWA):		Z3
	10 mg/m3	Time Weighted Average (TWA):	Inhalable particulate.	MX OEL
	3 mg/m3	Time Weighted Average (TWA):	Respirable dust.	MX OEL
Titanium dioxide	10 mg/m3	Time Weighted Average (TWA):		ACGIH
	15 mg/m3	PEL:	Total dust.	OSHA Z1
	10 mg/m3	Time Weighted Average (TWA):	as Ti	MX OEL
	20 mg/m3	Short Term Exposure Limit (STEL):	as Ti	MX OEL

9. PHYSICAL AND CHEMICAL PROPERTIES

Form Appearance Color Odour Melting point/range Boiling Point: Water solubility

: pellets
: GREY
: Very faint
: Not determined
: Not applicable
: Insoluble

: Solid

Evaporation rate Specific Gravity Bulk density Vapour pressure Vapour density pH

Not applicable
Not determined
Not established
Not applicable
Not applicable
Not applicable

10. STABILITY AND REACTIVITY

Stability	:	Stable.
Hazardous Polymerization	:	Will not occur.
Conditions to avoid	:	Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
Incompatible Materials	:	Incompatible with strong acids and oxidizing agents.

MATERIAL SAFETY DATA SHEET CLOUD GRAY PC

Version Number 1.0 Revision Date 05/28/2008

Page 5 of 8 Print Date 1/3/2012

Hazardous decomposition products

: Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
1308-38-9	Chromium (III) oxide	Irritant	Eyes, Skin.
		sensitizer	Skin.
68186-90-3	Rutile, antimony chromium buff	Irritant	Eyes, Skin, Respiratory system.
7631-86-9	Silica, amorphous	Irritant	Eyes, Respiratory system.
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.

LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
7631-86-9	Silica, amorphous	Oral LD50Oral LD50	15,000 mg/kg22,500 mg/kg	mouserat

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
13463-67-7	Titanium dioxide	no	2B	no

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

- 2A The component is probably carcinogenic to humans.
- 2B The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

- 1 The component is known to be a human carcinogen.
- 2 The component is reasonably anticipated to be a human carcinogen.

Additional Health Hazard Information:

Chromium (III) oxide 1308-38-9 The bi- and trivalent forms of chrome have a low order of acute toxicity, but may cause skin sensitization and irritation to the eyes. No effects have been reported for chromium (III) oxide. Chromium (III) compounds are not considered carcinogenic in animals or humans.

Additional Health Hazard Information:

PolyOne.

MATERIAL SAFETY DATA SHEET CLOUD GRAY PC

Version Number 1.0 Revision Date 05/28/2008 Page 6 of 8 Print Date 1/3/2012

Rutile, antimony chromium buff 68186-90-3 Can cause eye irritation. Can cause skin irritation. Symptoms may include redness and burning of skin, and other skin damage. Additional symptoms of skin contact may include: antimony measles (a red, pimply rash).

Persistence and degradability	: Not readily biodegradable.				
Environmental Toxicity	: Chemicals are not readily available as they are bound within the polymer matrix.				
Bioaccumulation Potential	: Chemicals are not readily available as they are bound within the polymer matrix.				
Additional advice	: No data available				
	13. DISPOSAL CONSIDERATIONS				
Product	: Like most thermoplastic plastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.				
Contaminated packaging	: Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.				
	14. TRANSPORT INFORMATION				
U.S. DOT Classification	: Not regulated for transportation.				
ICAO/IATA (air)	: Refer to specific regulation.				
IMO / IMDG (maritime)	: Refer to specific regulation.				
	15. REGULATORY INFORMATION				
US Regulations:					
OSHA Status	: Classified as hazardous based on components.				
TSCA Status	: All components of this product are listed on or exempt from the TSCA Inventory.				
US. EPA CERCLA Hazardous	Substances (40 CFR 302)				
Not applicable					

PolyOne

MATERIAL SAFETY DATA SHEET CLOUD GRAY PC

Version Number 1.0 Revision Date 05/28/2008 Page 7 of 8 Print Date 1/3/2012

California Proposition : Not applicable 65

SARA Title III Section 302 Extremely Hazardous Substance

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

SARA Title III Section 313 Toxic Chemicals:

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

Canadian Regulations:

National Pollutant Releas	se Ir	ventory (NPRI)			
Chemical Name			CAS-No.	Weight %	NPRI ID#
Aluminum oxide			1344-28-1	0.10 - 1.00	
Chromium (III) oxide			1308-38-9	0.10 - 1.00	
WHMIS Classification	:		s of this product a (DSL) or are exe	re on the Canadian mpt.	n Domestic
National Inventories:					
Australia AICS	:	Listed			
China IECS	:	Listed			
Europe EINECS	:	Listed			
Japan ENCS	:	Not determined			
Korea KECI	:	Listed			
Philippines PICCS	:	Listed			
		16. OTHER IN	FORMATION		

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing,

PolyOne.

MATERIAL SAFETY DATA SHEET CLOUD GRAY PC

Version Number 1.0 Revision Date 05/28/2008 Page 8 of 8 Print Date 1/3/2012

storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.