MATERIAL SAFETY DATA SHEET ABSLPPC 118106

Version Number 1.1 Revision Date 08/17/2009 Page 1 of 5 Print Date 1/8/2012

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone:Emergency telephone:		Product Stewardship (770) 271-5902 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	ABSLPPC 118106
Product code	:	CC10118106
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

There are no known hazardous components above regulatory thresholds in this product.

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	:	Inhalation, Ingestion, Skin contact
Acute exposure		
Inhalation	:	Resin particles, like other inert materials, can be mechanically irritating.
Ingestion	:	May be harmful if swallowed.
Eyes		Resin particles, like other inert materials, are mechanically irritating to eyes.
Skin	:	Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure		Refer to Section 11 for Toxicological Information.
em ome enposure	•	
Medical Conditions Aggravated by Exposure:	:	None known.

PolyOne.

MATERIAL SAFETY DATA SHEET **ABSLPPC 118106**

Version Number 1.1 Revision Date 08/17/2009 Page 2 of 5 Print Date 1/8/2012

		4. FIRST AID MEASURES
Inhalation	:	Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	:	Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	:	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	:	Wash off with soap and plenty of water. If skin irritation persists seek medical attention.
		5. FIRE-FIGHTING MEASURES
Flash point	:	not applicable
Flammable Limits		
Upper explosion limit		not applicable
Lower explosion limit	÷	not applicable
Autoignition temperature		not applicable
Suitable extinguishing media	:	Carbon dioxide blanket, Water spray, Dry powder, Foam.
Special Fire Fighting Procedures	:	Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.
Unusual Fire/Explosion Hazards	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.
	6. A	CCIDENTAL RELEASE MEASURES
Personal precautions	:	Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	:	Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	:	Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 13 of this MSDS for proper disposal methods.
		7. HANDLING AND STORAGE
Handling	:	Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.
Storage	:	Keep containers dry and tightly closed to avoid moisture absorption

2/5

PolyOne.

MATERIAL SAFETY DATA SHEET **ABSLPPC 118106**

Version Number 1.1 Revision Date 08/17/2009 Page 3 of 5 Print Date 1/8/2012

8. EXI	POSUI	RE CONTROLS/PERSONAL PROTECTION
Respiratory protection	:	No personal respiratory protective equipment normally required.
Eye/Face Protection	:	Safety glasses with side-shields
Hand protection	:	Protective gloves
Skin and body protection	:	Long sleeved clothing
Additional Protective Measures	:	Safety shoes
General Hygiene Considerations	:	Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.
Engineering measures	:	Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.
Exposure limit(s)		
9.	PHYS	SICAL AND CHEMICAL PROPERTIES
9. Form Appearance Colour Odour Melting point/range Boiling Point: Water solubility	: so : pe : N : ve : N : nc	
Form Appearance Colour Odour Melting point/range Boiling Point:	: so : pe : No : ve : No : no : in:	lidEvaporation rate:Not applicableelletsSpecific Gravity:Not determinedO PIGMENTBulk density:Not establishedery faintVapour pressure:not applicableot determinedVapour density:not applicableot applicablepH:not applicable
Form Appearance Colour Odour Melting point/range Boiling Point:	: so : pe : N(: ve : nc : in: 1(lidEvaporation rate:Not applicableelletsSpecific Gravity:Not determinedO PIGMENTBulk density:Not establishedery faintVapour pressure:not applicableot determinedVapour density:not applicableot determinedpH:not applicablesoluble:::not applicable
Form Appearance Colour Odour Melting point/range Boiling Point: Water solubility	: so : pe : N(: ve : nc : in: 1(lidEvaporation rate:Not applicableelletsSpecific Gravity:Not determinedO PIGMENTBulk density:Not establishedery faintVapour pressure:not applicableot determinedVapour density:not applicableot applicablepH:not applicablesoluble.STABILITY AND REACTIVITY.
Form Appearance Colour Odour Melting point/range Boiling Point: Water solubility Stability	: so : pe : N(: ve : nc : in: 1(lid Evaporation rate : Not applicable ellets Specific Gravity : Not determined O PIGMENT Bulk density : Not established ery faint Vapour pressure : not applicable ot determined Vapour density : not applicable ot applicable pH : not applicable soluble Stable Stable
Form Appearance Colour Odour Melting point/range Boiling Point: Water solubility Stability Hazardous Polymerization	: so : pe : N(: ve : nc : in: 1(lid Evaporation rate : Not applicable ellets Specific Gravity : Not determined O PIGMENT Bulk density : Not established ory faint Vapour pressure : not applicable ot determined Vapour density : not applicable ot applicable pH : not applicable soluble Stable . Will not occur. Keep away from oxidizing agents and open flame. To avoid thermal
Form Appearance Colour Odour Melting point/range Boiling Point: Water solubility Stability Hazardous Polymerization Conditions to avoid	: so : pe : N(: ve : nc : in: 1(lid Evaporation rate : Not applicable ellets Specific Gravity : Not determined O PIGMENT Bulk density : Not established ory faint Vapour pressure : not applicable ot determined Vapour density : not applicable ot determined Vapour density : not applicable ot applicable pH : not applicable ot applicable pH : not applicable soluble . . Stable . . Will not occur. . . Keep away from oxidizing agents and open flame. . . Accomposition, do not overheat. . .

PolyOne.

MATERIAL SAFETY DATA SHEET **ABSLPPC 118106**

Version Number 1.1 Revision Date 08/17/2009 Page 4 of 5 Print Date 1/8/2012

There are no known hazardous components above regulatory thresholds in this product.

	12. ECOLOGICAL INFORMATION
Persistence and degradability	: Not readily biodegradable.
Environmental Toxicity	: Chemicals are not readily available as they are bound within the polymer matrix.
Bioaccumulation Potential	: Chemicals are not readily available as they are bound within the polymer matrix.
Additional advice	: no data available
	13. DISPOSAL CONSIDERATIONS
Product	: Like most thermoplastic plastics the product can be recycled. Wher possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. DOT Classification	: Not regulated for transportation.
ICAO/IATA	: Refer to specific regulation.
IMO / IMDG (maritime)	: Refer to specific regulation.
	15. REGULATORY INFORMATION
US Regulations:	
OSHA Status	: There are no known hazardous components above regulatory thresholds in this product.
TSCA Status	: All components of this product are listed on or exempt from the TSCA Inventory.
US. EPA CERCLA Hazardous	Substances (40 CFR 302)
not applicable	

4/5

PolyOne

MATERIAL SAFETY DATA SHEET ABSLPPC 118106

Version Number 1.1 Revision Date 08/17/2009 Page 5 of 5 Print Date 1/8/2012

California Proposition 65	: Not applicable				
SARA Title III Section 302 Extr	remely Hazardous Substance				
Unless specific chemicals are id	entified under this section, this product is Not Applicable under this regulation				
SARA Title III Section 313 Tox	ic Chemicals:				
Unless specific chemicals are id	Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation				
Canadian Regulations:					
National Pollutant Release Inventory (NPRI)					
not applicable					
WHMIS Classification	: Not controlled.				
DSL	: All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.				
National Inventories:					
Australia AICS	: Listed				
China IECS	: Listed				
Europe EINECS	: Listed				
Japan ENCS	: Listed				
Korea KECI	: Listed				
Philippines PICCS	: Listed				

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.