## MATERIAL SAFETY DATA SHEET **PG 121603.01 FT LC UV**

Version Number 1.0 Revision Date 06/05/2009 Page 1 of 6 Print Date 1/8/2012

## 1. PRODUCT AND COMPANY IDENTIFICATION

#### POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone Emergency telephone	:	Product Stewardship (770) 271-5902 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	PG 121603.01 FT LC UV
Product code	:	CC10122193
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

## 2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight %
Silica, amorphous, fumed, crystal-free	112945-52-5	1 - 5
Bis (2-ethylhexyl) adipate	103-23-1	10 - 30

### **3. HAZARDS IDENTIFICATION**

#### **EMERGENCY OVERVIEW**

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions.

#### POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Skin contact, Ingestion
Acute exposure	
Inhalation	: Inhalation of airborne droplets may cause irritation of the respiratory tract.
Ingestion	: May be harmful if swallowed.
Eyes	: Irritating to eyes and respiratory system.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.
Medical Conditions Aggravated by Exposure:	: None known.

PolyOne.

# MATERIAL SAFETY DATA SHEET **PG 121603.01 FT LC UV**

Version Number 1.0 Revision Date 06/05/2009 Page 2 of 6 Print Date 1/8/2012

	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. Seek medical attention after significant exposure.
Ingestion	: Do not induce vomiting without medical advice. Seek medical attention if necessary.
Eyes	: Rinse immediately with plenty of water for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seek medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: Greater than 200 °F (93 °C)
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media	<ul> <li>Not applicable</li> <li>Not applicable</li> <li>Not applicable</li> <li>Carbon dioxide blanket, Dry powder, Foam.</li> </ul>
Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	<ul> <li>Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.</li> <li>Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.</li> </ul>
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: The product should not be allowed to enter drains, water courses or the soil. Should not be released into the environment.
Methods for cleaning up	: Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Package all material in appropriate container for disposal. Refer to Section 13 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Heat only in areas with appropriate exhaust ventilation.
Storage	: Keep containers dry and tightly closed to avoid moisture absorption

PolyOne.

## MATERIAL SAFETY DATA SHEET PG 121603.01 FT LC UV

Version Number 1.0 Revision Date 06/05/2009 Page 3 of 6 Print Date 1/8/2012

8. ]	EXPOSURE	CONTROLS/PERSONAL	PROTECTION			
Respiratory protection	: U	nder normal handling condition	ons a respirator may not b	e required.		
Eye/Face Protection	: S	afety glasses with side-shields				
Hand protection	: P	: Protective gloves				
Skin and body protection	: L	ong sleeved clothing				
Additional Protective Measures	: S	: Safety shoes				
General Hygiene Considerations		: Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.				
Engineering measures		eat only in areas with appropr ppropriate exhaust ventilation		Provide		
Exposure limit(s)						
Components	Value	Exposure time	Exposure type	List:		
Silica, amorphous,	0.8 mg/m3	Time Weighted Average		Z3		
Silica, amorphous, fumed, crystal-free		(TWA):	Inhalable particulate.			
	0.8 mg/m3 10 mg/m3		Inhalable particulate.	Z3 MX OEL		
		(TWA): Time Weighted Average	Inhalable particulate. Respirable dust.			
	10 mg/m3 3 mg/m3	(TWA): Time Weighted Average (TWA): Time Weighted Average	Respirable dust.	MX OEL		
fumed, crystal-free	10 mg/m3 3 mg/m3 9. PHYSIC	(TWA): Time Weighted Average (TWA): Time Weighted Average (TWA): CAL AND CHEMICAL PRO	Respirable dust.	MX OEL		
	10 mg/m3 3 mg/m3 9. PHYSIC : liquid	(TWA): Time Weighted Average (TWA): Time Weighted Average (TWA): CAL AND CHEMICAL PRO	Respirable dust. DPERTIES ration rate : Not	MX OEL		
fumed, crystal-free  Form Appearance Color	10 mg/m3 3 mg/m3 9. PHYSIC : liquid : Visco : NO H	(TWA): Time Weighted Average (TWA): Time Weighted Average (TWA): CAL AND CHEMICAL PRO d Evapo Dus, liquid Specif PIGMENT Bulk d	Respirable dust.  DPERTIES  ration rate : Not ic Gravity : Not lensity : Not	MX OEL MX OEL established determined applicable		
fumed, crystal-free Form Appearance Color Odour	10 mg/m3 3 mg/m3 9. PHYSIC : liquid : Visco : NO H : Very	(TWA):         Time Weighted Average         (TWA):         Time Weighted Average         (TWA):         Time Weighted Average         (TWA):         CAL AND CHEMICAL PRO         d       Evapo         pus, liquid       Specif         PIGMENT       Bulk d         faint       Vapou	Respirable dust. DPERTIES ration rate : Not ic Gravity : Not lensity : Not ur pressure : Not	MX OEL MX OEL established determined applicable determined		
fumed, crystal-free Form Appearance Color Odour Melting point/range	10 mg/m3 3 mg/m3 9. PHYSIC : liquid : Visco : NO H : Very : Not a	(TWA):         Time Weighted Average         (TWA):         Time Weighted Average         (TWA):         Time Weighted Average         (TWA):         CAL AND CHEMICAL PRO         d       Evapo         ous, liquid       Specif         PIGMENT       Bulk d         faint       Vapou         applicable       Vapou	Respirable dust. DPERTIES ration rate : Not ratic Gravity : Not lensity : Not r pressure : Not r density : Not	MX OEL MX OEL established determined applicable determined determined		
fumed, crystal-free form Appearance Color Odour Melting point/range Boiling Point:	10 mg/m3 3 mg/m3 9. PHYSIC : liquid : Visco : NO H : Very : Not a : Not a	(TWA):         Time Weighted Average (TWA):         Time Weighted Average (TWA):         CAL AND CHEMICAL PRODUCTION         d       Evapo Dous, liquid         Specific PIGMENT       Bulk d faint         vapou applicable       Vapou pH	Respirable dust. DPERTIES ration rate : Not ratic Gravity : Not lensity : Not r pressure : Not r density : Not	MX OEL MX OEL established determined applicable determined		
fumed, crystal-free Form Appearance Color Odour Melting point/range	10 mg/m3 3 mg/m3 9. PHYSIC : liquid : Visco : NO H : Very : Not a	(TWA):         Time Weighted Average (TWA):         Time Weighted Average (TWA):         CAL AND CHEMICAL PRODUCTION         d       Evapo Dous, liquid         Specific PIGMENT       Bulk d faint         vapou applicable       Vapou pH	Respirable dust. DPERTIES ration rate : Not ratic Gravity : Not lensity : Not r pressure : Not r density : Not	MX OEL MX OEL established determined applicable determined determined		
fumed, crystal-free form Appearance Color Odour Melting point/range Boiling Point:	10 mg/m3 3 mg/m3 9. PHYSIC : liquid : Visco : NO F : Very : Not a : Not a : Imm	(TWA):         Time Weighted Average (TWA):         Time Weighted Average (TWA):         CAL AND CHEMICAL PRODUCTION         d       Evapo Dous, liquid         Specific PIGMENT       Bulk d faint         vapou applicable       Vapou pH	Respirable dust. DPERTIES ration rate : Not ic Gravity : Not lensity : Not ur pressure : Not ur density : Not : Not	MX OEL MX OEL established determined applicable determined determined		
fumed, crystal-free form Appearance Color Odour Melting point/range Boiling Point:	10 mg/m3 3 mg/m3 9. PHYSIC : liquid : Visco : NO H : Very : Not a : Not a : Immi 10. S	(TWA):         Time Weighted Average (TWA):         Time Weighted Average (TWA):         CAL AND CHEMICAL PRO         d       Evapo pus, liquid         Specif         PIGMENT       Bulk d faint         vapou applicable       pH iscible	Respirable dust. DPERTIES ration rate : Not ic Gravity : Not lensity : Not ur pressure : Not ur density : Not : Not	MX OEL MX OEL established determined applicable determined determined		

PolyOne

## MATERIAL SAFETY DATA SHEET **PG 121603.01 FT LC UV**

Version Number 1.0 Revision Date 06/05/2009 Page 4 of 6 Print Date 1/8/2012

Incompatible Materials	:	Incompatible with strong acids and oxidizing agents.
Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.

#### 11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

**Toxicity Overview** 

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
112945-52-5	Silica, amorphous, fumed, crystal-free	Irritant	Eyes, Respiratory system.

#### LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
112945-52-5	Silica, amorphous, fumed, crystal-free	Oral LD50	3,160 mg/kg	rat
103-23-1	Bis (2-ethylhexyl) adipate	Oral LD50Oral LD50Oral LD50	9,100 mg/kg15,000 mg/kg5,600 mg/kg	ratmouserat

## **12. ECOLOGICAL INFORMATION**

Persistence and degradability	:	Not readily biodegradable.
Environmental Toxicity	:	Adverse ecological impact is not known or expected under normal use.
Bioaccumulation Potential	:	Does not bioaccumulate.
Additional advice	:	No data available

#### 13. DISPOSAL CONSIDERATIONS

Product	:	Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	:	Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.

PolyOne.

# MATERIAL SAFETY DATA SHEET **PG 121603.01 FT LC UV**

Version Number 1.0 Revision Date 06/05/2009 Page 5 of 6 Print Date 1/8/2012

U.S. DOT Classification	: Not	regulated for transportation		
ICAO/IATA (air)	: Not	regulated for transportation		
IMO / IMDG (maritime)	: Not	regulated for transportation		
	15. RE	GULATORY INFORMA	ΓΙΟΝ	
US Regulations:				
OSHA Status	: Cla	ssified as hazardous based o	n components.	
TSCA Status		components of this product CA Inventory.	are listed on or exe	mpt from the
US. EPA CERCLA Hazardo	us Substanc	es (40 CFR 302)		
Not applicable				
California Proposition	n : Not	applicable		
California Proposition	n : Not	applicable		
65				
SARA Title III Section 302 I	Extremely H	azardous Substance		
Unless specific chemicals are	e identified u	under this section, this produ	ict is Not Applicable	e under this regula
SARA Title III Section 313	Foxic Chem	icals:		
Unless specific chemicals are	e identified u	under this section, this produ	act is Not Applicable	e under this regulat
Canadian Regulations:				
National Pollutant Re	lease Invent	ory (NPRI)		
Chemical Name		CAS-No.	Weight %	NPRI ID#
Bis (2-ethylhexyl) adipate		103-23-1	10.00 - 30.00	

PolyOne

# MATERIAL SAFETY DATA SHEET **PG 121603.01 FT LC UV**

Version Number 1.0 Revision Date 06/05/2009 Page 6 of 6 Print Date *1/8/2012* 

		Substances List (DSL) or are exempt.
National Inventories:		
Australia AICS	:	Listed
China IECS	:	Listed
Europe EINECS	:	Listed
Japan ENCS	:	Not determined
Korea KECI	:	Listed
Philippines PICCS	:	Listed
		16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

#### 6/6