# MATERIAL SAFETY DATA SHEET GRAY

Version Number 1.1 Revision Date 06/24/2009 Page 1 of 8 Print Date <u>1/8/2012</u>

### 1. PRODUCT AND COMPANY IDENTIFICATION

## POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone Emergency telephone	:	Product Stewardship (770) 271-5902 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	GRAY
Product code	:	CC10122809
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

## 2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight percent
1,6-Hexanediamine, N,N'-bis(2,2,6,6- tetramethyl-4-piperidinyl)-,polymer with 2,4,6-trichloro-1,3,5-triazine, reaction products	70624-18-9	1 - 5
Phenol, 2-(2H-benzotriazol-2-yl)-4,6- bis(1,1-dimethylpropyl)-	25973-55-1	5 - 10
Silica, amorphous, precipitated and gel	112926-00-8	0.1 - 1
Carbon black	1333-86-4	1 - 5
Silica, amorphous, fumed, crystal-free	112945-52-5	1 - 5
Iron oxide	1309-37-1	5 - 10
Titanium dioxide	13463-67-7	30 - 60

## **3. HAZARDS IDENTIFICATION**

#### **EMERGENCY OVERVIEW**

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

## POTENTIAL HEALTH EFFECTS

Routes of Exposure:	:	Inhalation, Ingestion, Skin contact

## Acute exposure

Inhalation

: Resin particles, like other inert materials, can be mechanically



# MATERIAL SAFETY DATA SHEET **GRAY**

ion Number 1.1 sion Date 06/24/2009	Page 2 Print Date 1/8/2
Ingestion Eyes	<ul><li>irritating.</li><li>May be harmful if swallowed.</li><li>Resin particles, like other inert materials, are mechanically irritating to</li></ul>
Lycs	eyes.
Skin	: Experience shows no unusual dermatitis hazard from routine handling
Chronic exposure	: Refer to Section 11 for Toxicological Information.
Medical Conditions Aggravated by Exposure:	: None known.
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases o doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seek medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: not applicable
Flammable Limits	
Upper explosion limit	: not applicable
Lower explosion limit Autoignition temperature	<ul><li>not applicable</li><li>not applicable</li></ul>
Suitable extinguishing media	: Carbon dioxide blanket, Water spray, Dry powder, Foam.
Special Fire Fighting Procedures	: Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.
Unusual Fire/Explosion Hazards	<ul> <li>Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.</li> </ul>
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.

PolyOne.

# MATERIAL SAFETY DATA SHEET **GRAY**

/ersion Number 1.1 Revision Date 06/24/2009		Page 3 of 8 Print Date 1/8/2012
Methods for cleaning up	P	Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 3 of this MSDS for proper disposal methods.
	7.	. HANDLING AND STORAGE
Handling		Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.
Storage		Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.
8. EX	POSURI	E CONTROLS/PERSONAL PROTECTION
Respiratory protection	: 1	No personal respiratory protective equipment normally required.
Eye/Face Protection	: 5	Safety glasses with side-shields
Hand protection	: F	Protective gloves
Skin and body protection	: I	Long sleeved clothing
Additional Protective Measures	: 5	Safety shoes
General Hygiene Considerations		Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.
Engineering measures		Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.
Exposure limit(s)		

PolyOne.

# MATERIAL SAFETY DATA SHEET **GRAY**

Version Number 1.1

Revision Date 06/24/2009

Page 4 of 8 Print Date 1/8/2012

Components	Value	Exposure time	Exposure type	List:
Carbon black	3.5 mg/m3	Time Weighted Average (TWA):		ACGIH
	3.5 mg/m3	Recommended exposure limit (REL):		NIOSH
	0.1 mg/m3	Recommended exposure limit (REL):		NIOSH
	3.5 mg/m3	PEL:		OSHA Z1
	3.5 mg/m3	Time Weighted Average (TWA):		OSHA Z1A
	3.5 mg/m3	Time Weighted Average (TWA):		MX OEL
	7 mg/m3	Short Term Exposure Limit (STEL):		MX OEL
Iron oxide	5 mg/m3	Time Weighted Average (TWA):	Respirable fraction.	ACGIH
	10 mg/m3	PEL:	Fume.	OSHA Z1
	5 mg/m3	Time Weighted Average (TWA):	as Fe	MX OEL
	10 mg/m3	Short Term Exposure Limit (STEL):	as Fe	MX OEL
Silica, amorphous, fumed, crystal-free	0.8 mg/m3	Time Weighted Average (TWA):		Z3
	10 mg/m3	Time Weighted Average (TWA):	Inhalable particulate.	MX OEL
	3 mg/m3	Time Weighted Average (TWA):	Respirable dust.	MX OEL
Silica, amorphous, precipitated and gel	6 mg/m3	Time Weighted Average (TWA):		OSHA Z1A
	10 mg/m3	Time Weighted Average (TWA):		MX OEL
	0.8 mg/m3	Time Weighted Average (TWA):		Z3
Titanium dioxide	10 mg/m3	Time Weighted Average (TWA):		ACGIH
	15 mg/m3	PEL:	Total dust.	OSHA Z1
	10 mg/m3	Time Weighted Average (TWA):	Total dust.	OSHA Z1A
	10 mg/m3	Time Weighted Average (TWA):	as Ti	MX OEL
	20 mg/m3	Short Term Exposure Limit (STEL):	as Ti	MX OEL

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Form Appearance Colour Odour : solid: pellets: GREY: very faint

Evaporation rate Specific Gravity Bulk density Vapour pressure Not applicableNot determinedNot established

Not establishednot applicable

PolyOne.

# MATERIAL SAFETY DATA SHEET GRAY

Version Number 1.1 Revision Date 06/24/2009 Page 5 of 8 Print Date 1/8/2012

Melting point/range Boiling Point: Water solubility	<ul><li>Not determined</li><li>not applicable</li><li>insoluble</li></ul>		Vapour density pH	:	not applicable not applicable
	1(	). STABILITY AND RE	ACTIVITY		
Stability	:	Stable			
Hazardous Polymerization	:	Will not occur.			
Conditions to avoid	:	Keep away from oxidizi decomposition, do not o		me.	To avoid thermal
Incompatible Materials	:	Incompatible with strong	g acids and oxidizing a	gen	ts.
Hazardous decomposition products	:	Carbon dioxide (CO2), (NOx), other hazardous			ę

## 11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

#### **Toxicity Overview**

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
70624-18-9	1,6-Hexanediamine, N,N'-	Irritant	Eyes, Skin, Respiratory
	bis(2,2,6,6-tetramethyl-4-		system.
	piperidinyl)-,polymer with		
	2,4,6-trichloro-1,3,5-		
	triazine, reaction products		
25973-55-1	Phenol, 2-(2H-	Systemic effects	Kidney, Liver, reproductive
	benzotriazol-2-yl)-4,6-		system.
	bis(1,1-dimethylpropyl)-		
112926-00-8	Silica, amorphous,	Irritant	Respiratory system, Eyes.
	precipitated and gel		
1333-86-4	Carbon black	Systemic effects	Eyes, Respiratory system.
112945-52-5	Silica, amorphous, fumed,	Irritant	Eyes, Respiratory system.
	crystal-free		
1309-37-1	Iron oxide	Systemic effects	Respiratory system.
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.

## LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species

PolvOne

# MATERIAL SAFETY DATA SHEET **GRAY**

Version Number 1.1 Revision Date 06/24/2009 Page 6 of 8 Print Date 1/8/2012

70624-18-9	1,6-Hexanediamine, N,N'- bis(2,2,6,6-tetramethyl-4- piperidinyl)-,polymer with 2,4,6-trichloro-1,3,5- triazine, reaction products	Oral LD50 Dermal LD50	> 2,000 mg/kg > 3,000 mg/kg	rat rat
1333-86-4	Carbon black	Oral LD50 Dermal LD50	> 15,400 mg/kg > 3 gm/kg	rat rabbit
112945-52-5	Silica, amorphous, fumed, crystal-free	Oral LD50	3,160 mg/kg	rat

#### Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
1333-86-4	Carbon black	no	2B	no
13463-67-7	Titanium dioxide	no	2B	no

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

## Additional Health Hazard Information:

Carbon black 1333-86-4 Carcinogenicity: Many inhalation toxicologists believe that the tumor response observed in the referenced rat studies is species specific and does not correlate to human exposure. However, the IARC evaluation in Monograph Volume 65, issued in April 1996 concluded that, "There is sufficient evidence in experimental animals for the carcinogenicity of carbon black". Based on this evaluation, along with their evaluation of inadequate evidence of carcinogenicity in humans, IARC's overall evaluation is that "Carbon Black is possibly carcinogenic to humans (Group 2B). The IARC 2B listing only pertains to airborne, unbound carbon black particles of respirable size. Carbon Black has not been listed as a carcinogen by the National Toxicology Program (NTP) or the Occupational Safety and Health Administration (OSHA). The National Institute of Occupational Safety and Health (NIOSH) criteria document on carbon black recommends that only carbon black with PAH (polynuclear aromatic hydrocarbon) levels greater than 0.1% be considered suspect carcinogens.

## **12. ECOLOGICAL INFORMATION**

Persistence and degradability	:	Not readily biodegradable.
Environmental Toxicity	:	Chemicals are not readily available as they are bound within the polymer matrix.
Bioaccumulation Potential	:	Chemicals are not readily available as they are bound within the polymer matrix.



# MATERIAL SAFETY DATA SHEET **GRAY**

Additional advice						
	:	no data available				
	13	B. DISPOSAL CONSIDERATIONS				
Product	:	: Like most thermoplastic plastics the product can be recycled. Whe possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.				
Contaminated packaging	:	Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.				
	1	4. TRANSPORT INFORMATION				
U.S. DOT Classification	:	Not regulated for transportation.				
ICAO/IATA	:	Refer to specific regulation.				
IMO / IMDG (maritime)	:	Refer to specific regulation.				
	15	REGULATORY INFORMATION				
US Regulations:						
OSHA Status	:	Classified as hazardous based on components.				
TSCA Status	:	All components of this product are listed on or exempt from the TSCA Inventory.				
US. EPA CERCLA Hazardous	Subs	tances (40 CFR 302)				
not applicable						
California Proposition 65	:	WARNING! This product contains a chemical known to the State of California to cause cancer.				
SARA Title III Section 302 Extra	reme	ely Hazardous Substance				
Unless specific chemicals are id	enti	fied under this section, this product is Not Applicable under this regul				
SARA Title III Section 313 Tox	tic C	hemicals:				

PolyOne.

# **MATERIAL SAFETY DATA SHEET** GRAY

/ersion Number 1.1 Revision Date 06/24/2009				Dr	Pa int Date	ge 8 of	
Cevision Date 06/24/2009				FI		1/0/201	
Unless specific chemicals are identified und	ler this section, th					egulatio	
Chemical Name ZINC COMPOUNDS					ght percent - 5.00		
ZINC COMPOUNDS		00107-31	-7	1.00 - 5.	00		
Canadian Regulations:							
National Pollutant Release Inventory	(NPRI)						
Chemical Name	CAS-	CAS-No.			NPRI ID#		
Zinc ferrite brown spinel (C.I. Pigment Y	ellow 6818	68187-51-9		00		_	
119)							
Substa	omponents of this nces List (DSL) o			nadian D	Domestic		
National Inventories:							
Australia AICS : Listed							
China IECS : Listed							
Europe EINECS : Listed							
Japan ENCS : Not de	etermined						
Korea KECI : Not de	etermined						
Philippines PICCS : Not de	etermined						
16.0	THER INFORM	ATION					

## **16. OTHER INFORMATION**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.