PolvOne

MATERIAL SAFETY DATA SHEET AMBER PET 2%

Version Number 1.0 Revision Date 06/22/2009

Page 1 of 7 Print Date 1/8/2012

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012			
Telephone Emergency telephone	:	Product Stewardship (770) 271-5902 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).	
Product name	:	AMBER PET 2%	
Product code	:	CC10122948	
Chemical Name	:	Mixture	
CAS-No.	:	Mixture	
Product Use	•	Industrial Applications	

2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight %	
Carbon black	1333-86-4	1 - 5	

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation	: Resin particles, like other inert materials, can be mechanically irritating.
Ingestion	: May be harmful if swallowed.
Eyes	: Resin particles, like other inert materials, are mechanically irritating to eyes.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.
Medical Conditions Aggravated by Exposure:	: None known.

PolyOne.

MATERIAL SAFETY DATA SHEET **AMBER PET 2%**

Version Number 1.0 Revision Date 06/22/2009 Page 2 of 7 Print Date 1/8/2012

		4. FIRST AID MEASURES
Inhalation	:	Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	:	Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	:	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	:	Wash off with soap and plenty of water. If skin irritation persists seek medical attention.
		5. FIRE-FIGHTING MEASURES
Flash point	:	Not applicable
Flammable Limits		
Upper explosion limit		Not applicable
Lower explosion limit	:	Not applicable
Autoignition temperature	:	Not applicable
Suitable extinguishing media	:	Carbon dioxide blanket, Water spray, Dry powder, Foam.
Special Fire Fighting Procedures	:	Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.
Unusual Fire/Explosion Hazards	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.
	6. A	CCIDENTAL RELEASE MEASURES
Personal precautions	:	Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	:	Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	:	Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 13 of this MSDS for proper disposal methods.
		7. HANDLING AND STORAGE
Handling	:	Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.
Storage	:	Keep containers dry and tightly closed to avoid moisture absorption

POLYONE CORPORATION

PolyOne.

MATERIAL SAFETY DATA SHEET **AMBER PET 2%**

Version Number 1.0 Revision Date 06/22/2009

_

Page 3 of 7 Print Date 1/8/2012

8.]	EXPOSURE	CONTROLS/PERSONA	L PROTECTION	
Respiratory protection	: N	o personal respiratory prote	ective equipment norm	nally required.
Eye/Face Protection	: S	: Safety glasses with side-shields		
Hand protection	: P	: Protective gloves		
kin and body protection	: L	ong sleeved clothing		
Additional Protective Measures	: S	afety shoes		
General Hygiene Considerations		: Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.		
Engineering measures		leat only in areas with appro ppropriate exhaust ventilation		ation. Provide
Exposure limit(s)				
Components	Value	Exposure time	Exposure type	e List:
Carbon black	3.5 mg/m3	Time Weighted Average		ACGIH
		(IWA):		
	3.5 mg/m3	(TWA): Recommended exposure limit (REL):	;	NIOSH
	3.5 mg/m3 0.1 mg/m3	Recommended exposure limit (REL): Recommended exposure		NIOSH NIOSH
	0.1 mg/m3	Recommended exposure limit (REL):		
		Recommended exposure limit (REL): Recommended exposure limit (REL):	;	NIOSH
	0.1 mg/m3 3.5 mg/m3	Recommended exposure limit (REL): Recommended exposure limit (REL): PEL: Time Weighted Average	,,,	NIOSH OSHA Z1
	0.1 mg/m3 3.5 mg/m3 3.5 mg/m3	Recommended exposure limit (REL): Recommended exposure limit (REL): PEL: Time Weighted Average (TWA): Time Weighted Average		NIOSH OSHA Z1 OSHA Z1A
	0.1 mg/m3 3.5 mg/m3 3.5 mg/m3 3.5 mg/m3 7 mg/m3	Recommended exposure limit (REL): Recommended exposure limit (REL): PEL: Time Weighted Average (TWA): Time Weighted Average (TWA): Short Term Exposure Lim	e la	NIOSH OSHA Z1 OSHA Z1A MX OEL
Form	0.1 mg/m3 3.5 mg/m3 3.5 mg/m3 3.5 mg/m3 7 mg/m3	Recommended exposure limit (REL): Recommended exposure limit (REL): PEL: Time Weighted Average (TWA): Time Weighted Average (TWA): Short Term Exposure Lim (STEL):	e la	NIOSH OSHA Z1 OSHA Z1A MX OEL MX OEL
	0.1 mg/m3 3.5 mg/m3 3.5 mg/m3 3.5 mg/m3 7 mg/m3 9. PHYSIC	Recommended exposure limit (REL): Recommended exposure limit (REL): PEL: Time Weighted Average (TWA): Time Weighted Average (TWA): Short Term Exposure Lim (STEL):	e la	NIOSH OSHA Z1 OSHA Z1A MX OEL
Appearance	0.1 mg/m3 3.5 mg/m3 3.5 mg/m3 3.5 mg/m3 7 mg/m3 9. PHYSIC : Solic	Recommended exposure limit (REL): Recommended exposure limit (REL): PEL: Time Weighted Average (TWA): Time Weighted Average (TWA): Short Term Exposure Lime (STEL): CAL AND CHEMICAL P I Evants Spe	ROPERTIES	NIOSH OSHA Z1 OSHA Z1A OSHA Z1A MX OEL MX OEL Not applicable
Appearance Color	0.1 mg/m3 3.5 mg/m3 3.5 mg/m3 3.5 mg/m3 7 mg/m3 9. PHYSIC : Solic : pelle : BRC : Very	Recommended exposure limit (REL): Recommended exposure limit (REL): PEL: Time Weighted Average (TWA): Time Weighted Average (TWA): Short Term Exposure Limit (STEL): CAL AND CHEMICAL P I Eva ts Spe WN Bul faint Vag	ROPERTIES	NIOSH OSHA Z1 OSHA Z1A MX OEL MX OEL
Appearance Color Ddour	0.1 mg/m3 3.5 mg/m3 3.5 mg/m3 3.5 mg/m3 7 mg/m3 9. PHYSIC : Solic : pelle : BRC : Very	Recommended exposure limit (REL): Recommended exposure limit (REL): PEL: Time Weighted Average (TWA): Time Weighted Average (TWA): Short Term Exposure Limit (STEL): CAL AND CHEMICAL P I Eva ts Spe WN Bul faint Vap	ROPERTIES poration rate : cific Gravity : k density :	NIOSH OSHA Z1 OSHA Z1A MX OEL MX OEL Not applicable Not determined Not established
Form Appearance Color Ddour Melting point/range Boiling Point: Vater solubility	0.1 mg/m3 3.5 mg/m3 3.5 mg/m3 3.5 mg/m3 7 mg/m3 9. PHYSIC : Solid : pelle : BRC : Very : Not of	Recommended exposure limit (REL): Recommended exposure limit (REL): PEL: Time Weighted Average (TWA): Time Weighted Average (TWA): Short Term Exposure Lim (STEL): CAL AND CHEMICAL P I Eva ts Spe WN Bul faint Vap applicable pH	ROPERTIES aporation rate c: cific Gravity k density c: pour pressure	NIOSH OSHA ZI OSHA ZIA MX OEL MX OEL Not applicable Not determined Not established Not applicable

MATERIAL SAFETY DATA SHEET AMBER PET 2%

Version Number 1.0 Revision Date 06/22/2009		Page 4 of 7 Print Date <i>1/8/2012</i>
Stability	: Stable.	
Hazardous Polymerization	: Will not occur.	
Conditions to avoid	: Keep away from oxidizing agents and open flame. decomposition, do not overheat.	To avoid thermal
Incompatible Materials	: Incompatible with strong acids and oxidizing agen	.ts.
Hazardous decomposition products	Carbon dioxide (CO2), carbon monoxide (CO), ox (NOx), other hazardous materials, and smoke are a	<u> </u>

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
1333-86-4	Carbon black	Systemic effects	Eyes, Respiratory system.

LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
1333-86-4	Carbon black	Oral LD50	> 15,400 mg/kg	rat
		Dermal LD50	> 3 gm/kg	rabbit

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
1333-86-4	Carbon black	no	2B	no

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

Additional Health Hazard Information:

<u>PolvOne</u>

MATERIAL SAFETY DATA SHEET AMBER PET 2%

Version Number 1.0 Revision Date 06/22/2009

Page 5 of 7 Print Date 1/8/2012

Carbon black 1333-86-4 Carcinogenicity: Many inhalation toxicologists believe that the tumor response observed in the referenced rat studies is species specific and does not correlate to human exposure. However, the IARC evaluation in Monograph Volume 65, issued in April 1996 concluded that, "There is sufficient evidence in experimental animals for the carcinogenicity of carbon black". Based on this evaluation, along with their evaluation of inadequate evidence of carcinogenicity in humans, IARC's overall evaluation is that "Carbon Black is possibly carcinogenic to humans (Group 2B). The IARC 2B listing only pertains to airborne, unbound carbon black particles of respirable size. Carbon Black has not been listed as a carcinogen by the National Toxicology Program (NTP) or the Occupational Safety and Health Administration (OSHA). The National Institute of Occupational Safety and Health (NIOSH) criteria document on carbon black recommends that only carbon black with PAH (polynuclear aromatic hydrocarbon) levels greater than 0.1% be considered suspect carcinogens.

12. ECOLOGICAL INFORMATION

Persistence and degradability	: Not readily biodegradable.
Environmental Toxicity	: Chemicals are not readily available as they are bound within the polymer matrix.
Bioaccumulation Potential	: Chemicals are not readily available as they are bound within the polymer matrix.
Additional advice	: No data available
	13. DISPOSAL CONSIDERATIONS
Product	: Like most thermoplastic plastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. DOT Classification	: Not regulated for transportation.
ICAO/IATA (air)	: Refer to specific regulation.
IMO / IMDG (maritime)	: Refer to specific regulation.
	15. REGULATORY INFORMATION
US Regulations:	
OSHA Status	: Classified as hazardous based on components.

PolyOne.

MATERIAL SAFETY DATA SHEET **AMBER PET 2%**

sion Number 1.0 vision Date 06/22/2009	Page 6 of Print Date <i>1/8/201</i>
TSCA Status	: All components of this product are listed on or exempt from the TSCA Inventory.
US. EPA CERCLA Hazardou	s Substances (40 CFR 302)
Not applicable	
California Proposition 65	: WARNING! This product contains a chemical known to the State of California to cause cancer.
SARA Title III Section 302 E	xtremely Hazardous Substance
Unless specific chemicals are	identified under this section, this product is Not Applicable under this regulation
SARA Title III Section 313 To	oxic Chemicals:
Unless specific chemicals are	identified under this section, this product is Not Applicable under this regulation
Canadian Regulations:	
National Pollutant Rele	ease Inventory (NPRI)
Not applicable	
WHMIS Classification	n : D2A
WHMIS Ingredient Dis	sclosure List
CAS-No. 1333-86-4	
DSL	: All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.
National Inventories:	
Australia AICS	: Not determined
China IECS	: Listed
Europe EINECS	: Listed
Japan ENCS	: Not determined

7/7

Π

MATERIAL SAFETY DATA SHEET AMBER PET 2%

POLYONE CORPORATION

Version Number 1.0 Revision Date 06/22/2009 Page 7 of 7 Print Date 1/8/2012

Korea KECI : Listed

Philippines PICCS

: Not determined

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

