MATERIAL SAFETY DATA SHEET **ASPLA 124515**

Version Number 1.0 Revision Date 08/24/2009 Page 1 of 6 Print Date 1/8/2012

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone Emergency telephone	:	Product Stewardship (770) 271-5902 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	ASPLA 124515
Product code	:	CC10124515
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight percent
Lauric acid diethanolamide condensate	120-40-1	10 - 30
Silica, amorphous, precipitated and gel	112926-00-8	10 - 30

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	re: : Inhalation, Ingestion, Skin contact	
Acute exposure		
Inhalation	: Resin particles, like other inert materials, can be mechanically irritating.	
Ingestion	: May be harmful if swallowed.	
Eyes	: Resin particles, like other inert materials, are mechanically irritating to eyes.	
Skin	: Experience shows no unusual dermatitis hazard from routine handling.	
Chronic exposure	: Refer to Section 11 for Toxicological Information.	

PolyOne.

MATERIAL SAFETY DATA SHEET ASPLA 124515

Version Number 1.0 Revision Date 08/24/2009 Page 2 of 6 Print Date 1/8/2012

Medical Conditions Aggravated by Exposure:	: None known.
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases o doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seek medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: not applicable
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media Special Fire Fighting Procedures	 not applicable not applicable not applicable Carbon dioxide blanket, Water spray, Dry powder, Foam. Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne
Unusual Fire/Explosion Hazards	 contaminants. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 13 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.



MATERIAL SAFETY DATA SHEET ASPLA 124515

Version Number	1.0
Revision Date 0	8/24/2009

Page 3 of 6 Print Date 1/8/2012

Storage

: Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Respiratory protection	: No personal respiratory protective equipment normally req	uired.
Eye/Face Protection	: Safety glasses with side-shields	
Hand protection	: Protective gloves	
Skin and body protection	: Long sleeved clothing	
Additional Protective Measures	: Safety shoes	
General Hygiene Considerations	: Handle in accordance with good industrial hygiene and saf practice. Wash hands before breaks and at the end of work	
Engineering measures	: Heat only in areas with appropriate exhaust ventilation. Pr appropriate exhaust ventilation at machinery.	ovide

Exposure limit(s)

Components	Value	Exposure time	Exposure type	List:
Silica, amorphous,	6 mg/m3	Time Weighted Average		OSHA Z1A
precipitated and gel		(TWA):		
	10 mg/m3	Time Weighted Average		MX OEL
		(TWA):		
	0.8 mg/m3	Time Weighted Average		Z3
		(TWA):		

9. PHYSICAL AND CHEMICAL PROPERTIES

Form Appearance Colour Odour Melting point/range Boiling Point: Water solubility solid
pellets
NO PIGMENT
very faint
Not determined
not applicable
insoluble

Evaporation rate Specific Gravity Bulk density Vapour pressure Vapour density pH Not applicable
Not determined
Not established
not applicable
not applicable
not applicable
not applicable

10. STABILITY AND REACTIVITY

Stability

: Stable

Hazardous Polymerization

: Will not occur.



MATERIAL SAFETY DATA SHEET **ASPLA 124515**

ersion Number 1.0 evision Date 08/24/2009		Page 4 of 6 Print Date 1/8/2012
Conditions to avoid	:	Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
Incompatible Materials	:	Incompatible with strong acids and oxidizing agents.
Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.
	11.	TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
120-40-1	Lauric acid	Irritant	Eyes, Skin.
	diethanolamide condensate		
112926-00-8	Silica, amorphous,	Irritant	Respiratory system, Eyes.
	precipitated and gel		

LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
120-40-1	Lauric acid	Oral LD50	2,700 mg/kg	rat
	diethanolamide condensate			

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

12. ECOLOGICAL INFORMATION

Persistence and degradability	:	Not readily biodegradable.
Environmental Toxicity	:	Chemicals are not readily available as they are bound within the polymer matrix.



MATERIAL SAFETY DATA SHEET **ASPLA 124515**

sion Number 1.0 ision Date 08/24/2009	Page 5 Print Date 1/8/2
Bioaccumulation Potential	: Chemicals are not readily available as they are bound within the polymer matrix.
Additional advice	: no data available
	13. DISPOSAL CONSIDERATIONS
Product	: Like most thermoplastic plastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. DOT Classification	: Not regulated for transportation.
ICAO/IATA	: Refer to specific regulation.
IMO / IMDG (maritime)	: Refer to specific regulation.
	15. REGULATORY INFORMATION
US Regulations:	
OSHA Status	: Classified as hazardous based on components.
TSCA Status	: All components of this product are listed on or exempt from the TSCA Inventory.
US. EPA CERCLA Hazardou	is Substances (40 CFR 302)
not applicable	
California Proposition 65	a : Not applicable
SARA Title III Section 302 E	Extremely Hazardous Substance
TT 1	identified under this section, this product is Not Applicable under this regula

PolyOne

MATERIAL SAFETY DATA SHEET ASPLA 124515

Version Number 1.0 Revision Date 08/24/2009		Page 6 of 6 Print Date <i>1/8/2012</i>
11evision Date 00/24/2003		
SARA Title III Section 313 Tox	kic (Chemicals:
Unless specific chemicals are id	lenti	ified under this section, this product is Not Applicable under this regulation
Canadian Regulations:		
National Pollutant Release	se Iı	nventory (NPRI)
not applicable		
WHMIS Classification	:	D2B
DSL	:	All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.
National Inventories:		
Australia AICS	:	Listed
China IECS	:	Listed
Europe EINECS	:	Listed
Japan ENCS	:	Not determined

Korea KECI : Listed

Philippines PICCS

16. OTHER INFORMATION

Not determined

:

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.