MATERIAL SAFETY DATA SHEET MAX LOADED BLACK PP

Version Number 1.0 Revision Date 08/27/2009 Page 1 of 7 Print Date 1/8/2012

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone Emergency telephone	:	Product Stewardship (770) 271-5902 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	MAX LOADED BLACK PP
Product code	:	CC10124614
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight percent
Carbon black	1333-86-4	10 - 30

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation	: Resin particles, like other inert materials, can be mechanically irritating.
Ingestion	: May be harmful if swallowed.
Eyes	: Resin particles, like other inert materials, are mechanically irritating to eyes.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.
Medical Conditions Aggravated by Exposure:	: None known.

PolyOne.

MATERIAL SAFETY DATA SHEET MAX LOADED BLACK PP

Version Number 1.0 Revision Date 08/27/2009 Page 2 of 7 Print Date 1/8/2012

		4. FIRST AID MEASURES
Inhalation	c	Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of loubt seek medical advice.
Ingestion		Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes		Rinse immediately with plenty of water, also under the eyelids, for at east 15 minutes. If eye irritation persists, seek medical attention.
Skin		Wash off with soap and plenty of water. If skin irritation persists eek medical attention.
	5.	FIRE-FIGHTING MEASURES
Flash point	: r	ot applicable
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media Special Fire Fighting	: r : r : (not applicable not applicable not applicable Carbon dioxide blanket, Water spray, Dry powder, Foam. Fullface self-contained breathing apparatus (SCBA) used in positive
Procedures Unusual Fire/Explosion	F C : C	pressure mode should be worn to prevent inhalation of airborne contaminants. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen
Hazards		NOx), other hazardous materials, and smoke are all possible.
	6. ACC	CIDENTAL RELEASE MEASURES
Personal precautions		Wear appropriate personal protection during cleanup, such as mpervious gloves, boots and coveralls.
Environmental precautions		Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	F	Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 3 of this MSDS for proper disposal methods.
	7.	HANDLING AND STORAGE
Handling		Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.
Storage	: H	Keep containers dry and tightly closed to avoid moisture absorption

2/7

PolyOne.

MATERIAL SAFETY DATA SHEET MAX LOADED BLACK PP

Version Number 1.0 Revision Date 08/27/2009 Page 3 of 7 Print Date 1/8/2012

Q 1	FVDAGUDE	CONTROLS/PERSONAL	DDOTECTION	
0	EAI USUKE	CONTROLS/TERSONAL		
Respiratory protection	: N	o personal respiratory protect	ive equipment normal	lly required.
Eye/Face Protection	: Safety glasses with side-shields			
Hand protection	: Protective gloves			
Skin and body protection	: L	ong sleeved clothing		
Additional Protective Measures	: S	afety shoes		
General Hygiene Considerations		andle in accordance with goo ractice. Wash hands before b		
Engineering measures	: Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.			
Exposure limit(s)				
Components	Value	Exposure time	Exposure type	List:
Carbon black	3.5 mg/m3	Time Weighted Average (TWA):		ACGIH
	3.5 mg/m3	Recommended exposure limit (REL):		NIOSH
	0.1 mg/m3	Recommended exposure limit (REL):		NIOSH
	3.5 mg/m3	PEL:		OSHA Z1
		Time Weighted Average		OSHA Z1A
	3.5 mg/m3			
	3.5 mg/m3 3.5 mg/m3	(TWA): Time Weighted Average		MX OEL
	-	(TWA):		MX OEL MX OEL
	3.5 mg/m3 7 mg/m3	(TWA): Time Weighted Average (TWA): Short Term Exposure Limit (STEL):	PERTIES	
	3.5 mg/m3 7 mg/m3	(TWA): Time Weighted Average (TWA): Short Term Exposure Limit	DPERTIES	
Form	3.5 mg/m3 7 mg/m3 9. PHYSIC : solid	(TWA): Time Weighted Average (TWA): Short Term Exposure Limit (STEL): CAL AND CHEMICAL PRO Evapo	oration rate : 1	MX OEL
Appearance	3.5 mg/m3 7 mg/m3 9. PHYSIC : solid : pelle	(TWA): Time Weighted Average (TWA): Short Term Exposure Limit (STEL): CAL AND CHEMICAL PRO Evaports	oration rate : 1 fic Gravity : 1	MX OEL MX OEL Not applicable Not determined
Appearance Colour	3.5 mg/m3 7 mg/m3 9. PHYSIC : solid : pelle : BLA	(TWA): Time Weighted Average (TWA): Short Term Exposure Limit (STEL): CAL AND CHEMICAL PRO Evaports CK Bulk of CK	oration rate : 1 fic Gravity : 1 lensity : 1	MX OEL Not applicable Not determined Not established
Appearance Colour Odour	3.5 mg/m3 7 mg/m3 9. PHYSIC : solid : pelle : BLA : very	(TWA): Time Weighted Average (TWA): Short Term Exposure Limit (STEL): CAL AND CHEMICAL PRO Evaports CK Bulk of faint Vapor	oration rate :] fic Gravity :] lensity :] Ir pressure :]	MX OEL Not applicable Not determined Not established not applicable
Appearance Colour	3.5 mg/m3 7 mg/m3 9. PHYSIC : solid : pelle : BLA : very : Not o	(TWA): Time Weighted Average (TWA): Short Term Exposure Limit (STEL): CAL AND CHEMICAL PRO Evaports CK Bulk of faint Vapor	ration rate :] fic Gravity :] lensity :] Ir pressure : I Ir density :]	MX OEL Not applicable Not determined Not established

MATERIAL SAFETY DATA SHEET MAX LOADED BLACK PP

Version Number 1.0 Revision Date 08/27/2009

Page 4 of 7 Print Date 1/8/2012

Stability	:	Stable
Hazardous Polymerization	:	Will not occur.
Conditions to avoid	:	Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
Incompatible Materials	:	Incompatible with strong acids and oxidizing agents.
Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
1333-86-4	Carbon black	Systemic effects	Eyes, Respiratory system.

LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
1333-86-4	Carbon black	Oral LD50	> 15,400 mg/kg	rat
		Dermal LD50	> 3 gm/kg	rabbit

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

Γ	CAS-No.	Chemical Name	OSHA	IARC	NTP
	1333-86-4	Carbon black	no	2B	no

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

Additional Health Hazard Information:

PolvOne

MATERIAL SAFETY DATA SHEET MAX LOADED BLACK PP

Version Number 1.0 Revision Date 08/27/2009 Page 5 of 7 Print Date 1/8/2012

Carbon black 1333-86-4 Carcinogenicity: Many inhalation toxicologists believe that the tumor response observed in the referenced rat studies is species specific and does not correlate to human exposure. However, the IARC evaluation in Monograph Volume 65, issued in April 1996 concluded that, "There is sufficient evidence in experimental animals for the carcinogenicity of carbon black". Based on this evaluation, along with their evaluation of inadequate evidence of carcinogenicity in humans, IARC's overall evaluation is that "Carbon Black is possibly carcinogenic to humans (Group 2B). The IARC 2B listing only pertains to airborne, unbound carbon black particles of respirable size. Carbon Black has not been listed as a carcinogen by the National Toxicology Program (NTP) or the Occupational Safety and Health Administration (OSHA). The National Institute of Occupational Safety and Health (NIOSH) criteria document on carbon black recommends that only carbon black with PAH (polynuclear aromatic hydrocarbon) levels greater than 0.1% be considered suspect carcinogens.

12. ECOLOGICAL INFORMATION

vithin the vithin the
vithin the
ycled. Where on. The coper waste e with s.
f waste cation, ole federal,
-

PolyOne.

MATERIAL SAFETY DATA SHEET MAX LOADED BLACK PP

Version Number 1.0 Revision Date 08/27/2009 Page 6 of 7 Print Date 1/8/2012

TSCA Status US. EPA CERCLA Hazardous	 All components of this product are listed on or exempt from the TSCA Inventory. Substances (40 CFR 302)
not applicable	
California Proposition 65	: WARNING! This product contains a chemical known to the State of California to cause cancer.
SARA Title III Section 302 Ex	stremely Hazardous Substance
Unless specific chemicals are i	dentified under this section, this product is Not Applicable under this regulation
SARA Title III Section 313 To	oxic Chemicals:
Unless specific chemicals are i	dentified under this section, this product is Not Applicable under this regulation
Canadian Regulations:	
National Pollutant Rele	ase Inventory (NPRI)
not applicable	
WHMIS Classification	: D2A
WHMIS Ingredient Dis	closure List
CAS-No.	
1333-86-4 DSL	: All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.
National Inventories:	
Australia AICS	: Listed
China IECS	: Listed
Europe EINECS	: Listed
Japan ENCS	: Listed

MATERIAL SAFETY DATA SHEET MAX LOADED BLACK PP

Version Number 1.0 Revision Date 08/27/2009

> Korea KECI : Listed

Philippines PICCS

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.



Page 7 of 7 Print Date 1/8/2012

: Listed