PolvOne

MATERIAL SAFETY DATA SHEET **PVC SANDSTONE V2**

Version Number 1.0 Revision Date 08/27/2009

Page 1 of 8 Print Date 1/9/2012

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone:Emergency telephone:	Product Stewardship (770) 271-5902 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name :	PVC SANDSTONE V2
Product code :	CC10124661
Chemical Name :	Mixture
CAS-No. :	Mixture
Product Use :	Industrial Applications

2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight percent
Titanium dioxide	13463-67-7	0.1 - 1
Calcium stearate	1592-23-0	1 - 5
Manganese antimony titanium brown rutile (C.I. Pigment Yellow 164)	68412-38-4	10 - 30
Rutile, antimony chromium buff	68186-90-3	30 - 60

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation	: Particulates, like other inert materials can be mechanically irritating. Excessive inhalation of product vapors, especially during heating or processing, may be irritating to respiratory system.
Ingestion	: May be harmful if swallowed.
Eyes	: Particulates, like other inert materials can be mechanically irritating.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.

PolyOne.

MATERIAL SAFETY DATA SHEET **PVC SANDSTONE V2**

Version Number 1.0 Revision Date 08/27/2009 Page 2 of 8 Print Date 1/9/2012

Medical Conditions	: None known.
Aggravated by Exposure:	
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for a least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seek medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: not applicable
Flammable Limits	
Upper explosion limit	: not applicable
Lower explosion limit	: not applicable
Autoignition temperature	: not applicable
Suitable extinguishing media	: Carbon dioxide blanket, Water spray, Dry powder, Foam.
Special Fire Fighting Procedures	: Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.
Unusual Fire/Explosion Hazards	 Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible. May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under fire conditions.
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 13 of this MSDS for proper disposal methods.

PolyOne.

MATERIAL SAFETY DATA SHEET **PVC SANDSTONE V2**

Version Number 1.0 Revision Date 08/27/2009 Page 3 of 8 Print Date 1/9/2012

Handling	:	Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.
Storage	:	Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.
8. EXI	POSU	RE CONTROLS/PERSONAL PROTECTION
Respiratory protection	:	No personal respiratory protective equipment normally required.
Eye/Face Protection	:	Safety glasses with side-shields
Hand protection	:	Protective gloves
Skin and body protection	:	Long sleeved clothing
Additional Protective Measures	:	Safety shoes
General Hygiene Considerations	:	Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.
Engineering measures	:	Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.

<u>PolyOne</u>.

MATERIAL SAFETY DATA SHEET PVC SANDSTONE V2

Version Number 1.0 Revision Date 08/27/2009 Page 4 of 8 Print Date 1/9/2012

Components	Value	Exposure time	Exposure type	List:
Manganese antimony titanium brown rutile (C.I. Pigment Yellow 164)	1 mg/m3	Recommended exposure limit (REL):	Fume. as Mn	NIOSH
	3 mg/m3	Short Term Exposure Limit (STEL):	Fume. as Mn	NIOSH
	5 mg/m3	Ceiling Limit Value:	as Mn	OSHA Z1
	5 mg/m3	Ceiling Limit Value:	as Mn	OSHA Z1A
	0.5 mg/m3	Time Weighted Average (TWA):	as Sb	ACGIH
	0.5 mg/m3	Recommended exposure limit (REL):	as Sb	NIOSH
	0.5 mg/m3	PEL:	as Sb	OSHA Z1
	0.5 mg/m3	Time Weighted Average (TWA):	as Sb	OSHA Z1A
	0.5 mg/m3	Time Weighted Average (TWA):	as Sb	MX OEL
Calcium stearate	10 mg/m3	Time Weighted Average (TWA):		ACGIH
Rutile, antimony chromium buff	0.5 mg/m3	Recommended exposure limit (REL):	as Cr	NIOSH
	0.5 mg/m3	PEL:	as Cr	OSHA Z1
	0.5 mg/m3	Time Weighted Average (TWA):	as Sb	ACGIH
	0.5 mg/m3	Recommended exposure limit (REL):	as Sb	NIOSH
	0.5 mg/m3	PEL:	as Sb	OSHA Z1
	0.5 mg/m3	Time Weighted Average (TWA):	as Sb	OSHA Z1A
	0.5 mg/m3	Time Weighted Average (TWA):	as Sb	MX OEL
Titanium dioxide	10 mg/m3	Time Weighted Average (TWA):		ACGIH
	15 mg/m3	PEL:	Total dust.	OSHA Z1
	10 mg/m3	Time Weighted Average (TWA):	Total dust.	OSHA Z1A
	10 mg/m3	Time Weighted Average (TWA):	as Ti	MX OEL
	20 mg/m3	Short Term Exposure Limit (STEL):	as Ti	MX OEL

9. PHYSICAL AND CHEMICAL PROPERTIES

- Form Appearance Colour Odour Melting point/range
- : solid: pellets: TAN: very faint
- : Not determined

Evaporation rate Specific Gravity Bulk density Vapour pressure Vapour density Not applicableNot determinedNot established

- : not applicable
- : not applicable

Page 5 of 8 Print Date 1/9/2012

POLYONE CORPORATION

MATERIAL SAFETY DATA SHEET PVC SANDSTONE V2

Version Number 1.0 Revision Date 08/27/2009

Boiling Point: Water solubility		ot applicable soluble	рН	: not applicable
	1). STABILITY A	AND REACTIVITY	
Stability	:	Stable		
Hazardous Polymerization	:	Will not occur.		
Conditions to avoid	:		n oxidizing agents and do not overheat.	open flame. To avoid thermal
Incompatible Materials	:	or acetal copoly processing. At destructive and mechanically cl- quantities of the	mers and with amine of processing conditions, involve rapid degradate ean processing equipm	Also, avoid contact with acetal containing materials during these materials are mutually tion. Thoroughly purge and nent to avoid even trace ting in contact with each other. pocks.
Hazardous decomposition		Carbon diovida	(CO2) carbon monor	ida(CO) oxidas of nitrogan

:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen
	(NOx), hydrogen chloride (HCl), other hazardous materials, and
	smoke are all possible. Prolonged heating (approximately 30 minutes
	or more) above 392 °F (200 °C) or short term heating at 482 °F (250
	°C) may result in product decomposition and evolution of carbon
	monoxide and hydrogen chloride.
	:

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.
68412-38-4	Manganese antimony titanium brown rutile (C.I. Pigment Yellow 164)	Irritant	Eyes, Skin.
68186-90-3	Rutile, antimony chromium buff	Irritant	Eyes, Skin, Respiratory system.

LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
1592-23-0	Calcium stearate	Oral LD50	>10 gm/kg	rat

Carcinogenicity

P<u>olyOne</u>

MATERIAL SAFETY DATA SHEET **PVC SANDSTONE V2**

Version Number 1.0 Revision Date 08/27/2009 Page 6 of 8 Print Date 1/9/2012

This product contains the following components which, in their pure form, have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
13463-67-7	Titanium dioxide	no	2B	no

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

Persistence and degradability	: Not readily biodegradable.
Environmental Toxicity	: Chemicals are not readily available as they are bound within the polymer matrix.
Bioaccumulation Potential	: Chemicals are not readily available as they are bound within the polymer matrix.
Additional advice	: no data available
	13. DISPOSAL CONSIDERATIONS
Product Contaminated packaging	 Like most thermoplastic plastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations. Recycling is preferred when possible. The generator of waste
containing packaging	material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. DOT Classification	: Not regulated for transportation.
ICAO/IATA	: Refer to specific regulation.
IMO / IMDG (maritime)	: Refer to specific regulation.
	15. REGULATORY INFORMATION

PolyOne.

MATERIAL SAFETY DATA SHEET PVC SANDSTONE V2

				F	Pag Print Date 1
US Regulations:					
OSHA Status : Classified as ha	zardous b	pased on co	omponen	ts	
			-		
TSCA Status : All components of this product are listed on or exempt from the TSCA Inventory.					
JS. EPA CERCLA Hazardous Substances (40 CFR 3	302)				
not applicable					
California Proposition : Not applicable 65					
SARA Title III Section 302 Extremely Hazardous Su	ibstance				
Jnless specific chemicals are identified under this se		1		. 1 1. 1 .	1
SARA Title III Section 313 Toxic Chemicals: Jnless specific chemicals are identified under this se Chemical Name	ction, thi			plicable	under this rea
		CAS-No	о.	Weight	
MANGANESE COMPOUNDSANTIMONY		CAS-No 68412-38		Weight 10.00 -	percent
MANGANESE COMPOUNDSANTIMONY COMPOUNDS CHROMIUM III COMPOUNDSCHROMIUM III COMPOUNDSANTIMONY COMPOUNDS			8-4		- 30.00
COMPOUNDS CHROMIUM III COMPOUNDSCHROMIUM III COMPOUNDSANTIMONY COMPOUNDS		68412-38	8-4	10.00 -	- 30.00
COMPOUNDS CHROMIUM III COMPOUNDSCHROMIUM III COMPOUNDSANTIMONY COMPOUNDS		68412-38	8-4	10.00 -	- 30.00
COMPOUNDS CHROMIUM III COMPOUNDSCHROMIUM III COMPOUNDSANTIMONY COMPOUNDS Canadian Regulations:	CAS-N	68412-38 68186-90	8-4	10.00 - 30.00 -	- 30.00
COMPOUNDS CHROMIUM III COMPOUNDSCHROMIUM III COMPOUNDSANTIMONY COMPOUNDS Canadian Regulations: National Pollutant Release Inventory (NPRI) Chemical Name Manganese antimony titanium brown rutile (C.I.		68412-38 68186-90 Io.	8-4 D-3 Weigh	10.00 - 30.00 - t	percent - 30.00 - 60.00
COMPOUNDS CHROMIUM III COMPOUNDSCHROMIUM III COMPOUNDSANTIMONY COMPOUNDS Canadian Regulations: National Pollutant Release Inventory (NPRI) Chemical Name Manganese antimony titanium brown rutile (C.I. Pigment Yellow 164)	CAS-N 68412-	68412-38 68186-90 Io. 38-4	8-4 0-3 Weigh percen 10.00 - 10.00 -	10.00 - 30.00 - t t t - 30.00	percent - 30.00 - 60.00
COMPOUNDS CHROMIUM III COMPOUNDSCHROMIUM III COMPOUNDSANTIMONY COMPOUNDS Canadian Regulations: National Pollutant Release Inventory (NPRI) Chemical Name Manganese antimony titanium brown rutile (C.I.	CAS-N	68412-38 68186-90 Io. 38-4	8-4 0-3 Weigh percen 10.00 -	10.00 - 30.00 - t t t - 30.00	percent - 30.00 - 60.00
COMPOUNDS CHROMIUM III COMPOUNDSCHROMIUM III COMPOUNDSANTIMONY COMPOUNDS Canadian Regulations: National Pollutant Release Inventory (NPRI) Chemical Name Manganese antimony titanium brown rutile (C.I. Pigment Yellow 164)	CAS-N 68412-	68412-38 68186-90 Io. 38-4	8-4 0-3 Weigh percen 10.00 - 10.00 -	10.00 - 30.00 - t t t - 30.00	percent - 30.00 - 60.00
COMPOUNDS CHROMIUM III COMPOUNDSCHROMIUM III COMPOUNDSANTIMONY COMPOUNDS Canadian Regulations: National Pollutant Release Inventory (NPRI) Chemical Name Manganese antimony titanium brown rutile (C.I. Pigment Yellow 164) Rutile, antimony chromium buff	CAS-N 68412-	68412-38 68186-90 Io. 38-4	8-4 0-3 Weigh percen 10.00 - 10.00 -	10.00 - 30.00 - t t t - 30.00	percent - 30.00 - 60.00
COMPOUNDS CHROMIUM III COMPOUNDSCHROMIUM III COMPOUNDSANTIMONY COMPOUNDS Canadian Regulations: National Pollutant Release Inventory (NPRI) Chemical Name Manganese antimony titanium brown rutile (C.I. Pigment Yellow 164) Rutile, antimony chromium buff WHMIS Classification : D2A	CAS-N 68412-	68412-38 68186-90 Io. 38-4	8-4 0-3 Weigh percen 10.00 - 10.00 -	10.00 - 30.00 - t t t - 30.00	percent - 30.00 - 60.00

PolyOne

MATERIAL SAFETY DATA SHEET **PVC SANDSTONE V2**

Version Number 1.0 Revision Date 08/27/2009 Page 8 of 8 Print Date 1/9/2012

68412-38-4 68186-90-3						
DSL	:	All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.				
National Inventories:						
Australia AICS	:	Listed				
China IECS	:	Not determined				
Europe EINECS	:	Listed				
Japan ENCS	:	Not determined				
Korea KECI	:	Listed				
Philippines PICCS	:	Listed				
	16. OTHER INFORMATION					

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.