PolyOne

MATERIAL SAFETY DATA SHEET GARNET

Version Number 1.0 Revision Date 09/22/2009

Page 1 of 8 Print Date 1/9/2012

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone Emergency telephone	:	Product Stewardship (770) 271-5902 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	GARNET
Product code	:	CC10125292
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight percent
Titanium dioxide	13463-67-7	0.1 - 1
Iron oxide	1309-37-1	1 - 5
Aluminum	7429-90-5	5 - 10
Mica	12001-26-2	5 - 10

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation	: Resin particles, like other inert materials, can be mechanically irritating.
Ingestion	: May be harmful if swallowed.
Eyes	: Resin particles, like other inert materials, are mechanically irritating to eyes.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.

PolyOne.

MATERIAL SAFETY DATA SHEET **GARNET**

Version Number 1.0 Revision Date 09/22/2009 Page 2 of 8 Print Date 1/9/2012

Medical Conditions	· Non	e known.
Aggravated by Exposure:	. 1101	e known.
	4.	FIRST AID MEASURES
Inhalation	ove	ve to fresh air in case of accidental inhalation of fumes from rheating or combustion. When symptoms persist or in all cases of bt seek medical advice.
Ingestion		not induce vomiting without medical advice. When symptoms sist or in all cases of doubt seek medical advice.
Eyes		se immediately with plenty of water, also under the eyelids, for at t 15 minutes. If eye irritation persists, seek medical attention.
Skin		sh off with soap and plenty of water. If skin irritation persists a medical attention.
	5. FI	RE-FIGHTING MEASURES
Flash point	: not	applicable
Flammable Limits Upper explosion limit		applicable applicable
Lower explosion limit Autoignition temperature		applicable
Suitable extinguishing media		bon dioxide blanket, Water spray, Dry powder, Foam.
Special Fire Fighting Procedures	pres	face self-contained breathing apparatus (SCBA) used in positive ssure mode should be worn to prevent inhalation of airborne taminants.
Unusual Fire/Explosion Hazards	: Car	bon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (CO2), other hazardous materials, and smoke are all possible.
	ACCIE	DENTAL RELEASE MEASURES
Personal precautions		ar appropriate personal protection during cleanup, such as ervious gloves, boots and coveralls.
Environmental precautions		uld not be released into the environment. The product should not llowed to enter drains, water courses or the soil.
Methods for cleaning up	plas	an up promptly by sweeping or vacuum. Package all material in tic, cardboard or metal containers for disposal. Refer to Section of this MSDS for proper disposal methods.
	7. H	ANDLING AND STORAGE

PolyOne.

MATERIAL SAFETY DATA SHEET **GARNET**

Version Number 1.0 Revision Date 09/22/2009		Page 3 of 8 Print Date 1/9/2012
Handling	:	Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.
Storage	:	Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.
8. EX	POSUI	RE CONTROLS/PERSONAL PROTECTION
Respiratory protection	:	No personal respiratory protective equipment normally required.
Eye/Face Protection	:	Safety glasses with side-shields
Hand protection	:	Protective gloves
Skin and body protection	:	Long sleeved clothing
Additional Protective Measures	:	Safety shoes
General Hygiene Considerations	:	Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.
Engineering measures	:	Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.
Exposure limit(s)		

PolyOne.

MATERIAL SAFETY DATA SHEET **GARNET**

Version Number 1.0

Revision Date 09/22/2009

Page 4 of 8 Print Date 1/9/2012

Components	Value	Exposure time	Exposure type	List:
Aluminum	1 mg/m3	Time Weighted Average (TWA):	Respirable fraction.	ACGIH
	10 mg/m3	Recommended exposure limit (REL):	Total	NIOSH
	5 mg/m3	Recommended exposure limit (REL):	Respirable.	NIOSH
	5 mg/m3	Recommended exposure limit (REL):	Welding fume or pyrophoric powder. as Al	NIOSH
	15 mg/m3	PEL:	Total dust. as Al	OSHA Z1
	5 mg/m3	PEL:	Respirable dust. as Al	OSHA Z1
	15 mg/m3	Time Weighted Average (TWA):	Total dust. as Al	OSHA Z1A
	5 mg/m3	Time Weighted Average (TWA):	Respirable dust. as Al	OSHA Z1A
	5 mg/m3	Time Weighted Average (TWA):	Pyrophoric powder. as Al	OSHA Z1A
	5 mg/m3	Time Weighted Average (TWA):	Fume. as Al	OSHA Z1A
	5 mg/m3	Time Weighted Average (TWA):	Welding fume.	MX OEL
	10 mg/m3	Time Weighted Average (TWA):	Dust.	MX OEL
	5 mg/m3	Time Weighted Average (TWA):	Pyrophoric powder.	MX OEL
Iron oxide	5 mg/m3	Time Weighted Average (TWA):	Respirable fraction.	ACGIH
	10 mg/m3	PEL:	Fume.	OSHA Z1
	5 mg/m3	Time Weighted Average (TWA):	as Fe	MX OEL
	10 mg/m3	Short Term Exposure Limit (STEL):	as Fe	MX OEL
Mica	3 mg/m3	Time Weighted Average (TWA):	Respirable fraction.	ACGIH
	3 mg/m3	Recommended exposure limit (REL):	Respirable.	NIOSH
	3 mg/m3	Time Weighted Average (TWA):	Respirable dust.	OSHA Z1A
	3 mg/m3	Time Weighted Average (TWA):		MX OEL
Titanium dioxide	10 mg/m3	Time Weighted Average (TWA):		ACGIH
	15 mg/m3	PEL:	Total dust.	OSHA Z1
	10 mg/m3	Time Weighted Average (TWA):	Total dust.	OSHA Z1A
	10 mg/m3	Time Weighted Average (TWA):	as Ti	MX OEL



MATERIAL SAFETY DATA SHEET **GARNET**

Version Number 1.0 Revision Date 09/22/2009

Page 5 of 8 Print Date 1/9/2012

	20 mg/m3	Short Term Exposure (STEL):	Limit as	Ti	MX OEL
	9. PHYSIC	CAL AND CHEMICA	L PROPERTIES		
Form Appearance Colour Odour Melting point/range Boiling Point: Water solubility		ts faint determined pplicable	Evaporation rate Specific Gravity Bulk density Vapour pressure Vapour density pH	: Not : Not : not : not	applicable determined established applicable applicable applicable
Stability		STABILITY AND REA	ACTIVITY		
Hazardous Polymerization	: V	Vill not occur.			
Conditions to avoid		Leep away from oxidizin ecomposition, do not ov	001	lame. To a	woid thermal
Incompatible Materials	: Iı	ncompatible with strong	acids and oxidizing	agents.	
Hazardous decomposition products		Carbon dioxide (CO2), ca NOx), other hazardous n			
	11 TO	XICOLOGICAL INF	ORMATION		

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.
1309-37-1	Iron oxide	Systemic effects	Respiratory system.
7429-90-5	Aluminum	Irritant	Skin, Respiratory system.
		Systemic effects	Eyes, Skin, Respiratory
			system.
12001-26-2	Mica	Systemic effects	Respiratory system.

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
13463-67-7	Titanium dioxide	no	2B	no

<u>PolyOne</u>

MATERIAL SAFETY DATA SHEET GARNET

Version Number 1.0 Revision Date 09/22/2009 Page 6 of 8 Print Date 1/9/2012

IARC Carcinogen Classifications:1 - The component is carcinogenic to humans.2A - The component is probably carcinogenic to humans.2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

	12	2. ECOLOGICAL INFORMATION
Persistence and degradability	:	Not readily biodegradable.
Environmental Toxicity	:	Chemicals are not readily available as they are bound within the polymer matrix.
Bioaccumulation Potential	:	Chemicals are not readily available as they are bound within the polymer matrix.
Additional advice	:	no data available
	1.	3. DISPOSAL CONSIDERATIONS
Product	:	Like most thermoplastic plastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	:	Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	1	4. TRANSPORT INFORMATION
U.S. DOT Classification	:	Not regulated for transportation.
ICAO/IATA	:	Refer to specific regulation.
IMO / IMDG (maritime)	:	Refer to specific regulation.

15. REGULATORY INFORMATION

_

OSHA Status	:	Classified as hazardous based on components.
TSCA Status	:	All components of this product are listed on or exempt from the TSCA Inventory.

P<u>olyOne</u>

MATERIAL SAFETY DATA SHEET GARNET

Version Number 1.0 Revision Date 09/22/2009 Page 7 of 8 Print Date 1/9/2012

US. EPA CERCLA Hazardous Substances (40 CFR 302)

not applicable

California Proposition : Not applicable 65

SARA Title III Section 302 Extremely Hazardous Substance

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

SARA Title III Section 313 Toxic Chemicals:

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

ALLIMINUM (ELIME OR DUST) $7420.00.5$ 5.00 10.00	Chemical Name	CAS-No.	Weight percent
ALUMINUM (FUME OK DUST) 7429-90-5 5:00 - 10:00	ALUMINUM (FUME OR DUST)	7429-90-5	5.00 - 10.00

Canadian Regulations:

National Pollutant Release Inventory (NPRI)			
Chemical Name	CAS-No.	Weight	NPRI ID#
		percent	
Aluminum	7429-90-5	5.00 - 10.00	

WHMIS Classification : D2A

WHMIS Ingredient Disclosure List

CAS-No.
7429-90-5
1309-37-1
12001-26-2

DSL

All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.

National Inventories:

Australia AICS	:	Listed
China IECS	:	Listed

:

P<u>olyOne</u>

MATERIAL SAFETY DATA SHEET **GARNET**

Version Number 1.0 Revision Date 09/22/2009		Page 8 of 8 Print Date 1/9/2012
Europe EINECS	: Listed	
Japan ENCS	: Not determined	
Korea KECI	: Listed	
Philippines PICCS	: Listed	
	16. OTHER INFORMATION	

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.