### MATERIAL SAFETY DATA SHEET GREEN GLOW IN THE DARK

Version Number 1.0 Revision Date 10/09/2009 Page 1 of 6 Print Date 1/9/2012

#### 1. PRODUCT AND COMPANY IDENTIFICATION

#### POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone Emergency telephone	:	Product Stewardship (770) 271-5902 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	GREEN GLOW IN THE DARK
Product code	:	CC10125776
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

#### 2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight percent
Aluminate (Al(OH)63-), (OC-6-11)-,	11097-59-9	1 - 5
magnesium carbonate hydroxide (2:6:1:4)		
Calcium carbonate	1317-65-3	5 - 10

#### **3. HAZARDS IDENTIFICATION**

#### EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

#### POTENTIAL HEALTH EFFECTS

<b>Routes of Exposure:</b>	: Inhalation, Ingestion, Skin contact			
Acute exposure				
Inhalation	: Resin particles, like other inert materials, can be mechanically irritating.			
Ingestion	: May be harmful if swallowed.			
Eyes	: Resin particles, like other inert materials, are mechanically irritating to eyes.			
Skin	: Experience shows no unusual dermatitis hazard from routine handling.			
Chronic exposure	: Refer to Section 11 for Toxicological Information.			

PolyOne.

# MATERIAL SAFETY DATA SHEET **GREEN GLOW IN THE DARK**

Version Number 1.0 Revision Date 10/09/2009 Page 2 of 6 Print Date 1/9/2012

Medical Conditions Aggravated by Exposure:	: None known.
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases or doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seek medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: not applicable
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media Special Fire Fighting Procedures	<ul> <li>not applicable</li> <li>not applicable</li> <li>not applicable</li> <li>Carbon dioxide blanket, Water spray, Dry powder, Foam.</li> <li>Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.</li> </ul>
Unusual Fire/Explosion Hazards	: Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 13 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.

POLYONE CORPORATION

## MATERIAL SAFETY DATA SHEET GREEN GLOW IN THE DARK

Version Number 1.0 Revision Date 10/09/2009 Page 3 of 6 Print Date 1/9/2012

Storage

: Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.

#### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Respiratory protection	:	No personal respiratory protective equipment normally required.
Eye/Face Protection	:	Safety glasses with side-shields
Hand protection	:	Protective gloves
Skin and body protection	:	Long sleeved clothing
Additional Protective Measures	:	Safety shoes
General Hygiene Considerations	:	Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.
Engineering measures	:	Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.

Exposure limit(s)

Components	Value	Exposure time	Exposure type	List:
Calcium carbonate	5 mg/m3	PEL:	Respirable fraction.	OSHA Z1
	15 mg/m3	PEL:	Total dust.	OSHA Z1
	10 mg/m3	Time Weighted Average		MX OEL
	_	(TWA):		
	20 mg/m3	Short Term Exposure Limit		MX OEL
		(STEL):		

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

- Form Appearance Colour Odour Melting point/range Boiling Point: Water solubility
- solid
  pellets
  GREEN
  very faint
  Not determined
  not applicable
  insoluble
- Evaporation rate Specific Gravity Bulk density Vapour pressure Vapour density pH
- Not applicable
  Not determined
  Not established
  not applicable
  not applicable
  not applicable

#### **10. STABILITY AND REACTIVITY**

Stability

: Stable

Hazardous Polymerization

: Will not occur.

PolvOne

# MATERIAL SAFETY DATA SHEET GREEN GLOW IN THE DARK

 Version Number 1.0
 Page 4 of 6

 Revision Date 10/09/2009
 Print Date 1/9/2012

 Conditions to avoid
 : Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.

 Incompatible Materials
 : Incompatible with strong acids and oxidizing agents.

 Hazardous decomposition products
 : Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.

 Incompatible Materials
 : Incompatible with strong acids and oxidizing agents.

 Hazardous decomposition products
 : Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.

 Incompatible Materials
 : Description (NOx), other hazardous materials, and smoke are all possible.

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
11097-59-9	Aluminate (Al(OH)63-), (OC-6-11)-, magnesium carbonate hydroxide (2:6:1:4)	Irritant	Eyes, Skin.
1317-65-3	Calcium carbonate	Irritant	Eyes, Skin.
		Systemic effects	Eyes, Skin, Respiratory system.

12. ECOLOGICAL INFORM	IATION

Not readil	y biodegradable.
Chemicals polymer m	are not readily available as they are bound within the natrix.
Chemicals polymer m	are not readily available as they are bound within the natrix.
no data av	ailable
3. DISPOSA	AL CONSIDERATIONS
possible re generator classificati	thermoplastic plastics the product can be recycled. Where ecycling is preferred to disposal or incineration. The of waste material has the responsibility for proper waste ion, transportation and disposal in accordance with federal, state/provincial and local regulations.
material h	is preferred when possible. The generator of waste as the responsibility for proper waste classification, tion and disposal in accordance with applicable federal,
	<ul> <li>Chemicals polymer n</li> <li>Chemicals polymer n</li> <li>no data av</li> <li>13. DISPOSA</li> <li>Like most possible re generator of classification applicable</li> <li>Recycling material h</li> </ul>

PolyOne.

# MATERIAL SAFETY DATA SHEET **GREEN GLOW IN THE DARK**

Version Number 1.0 Revision Date 10/09/2009 Page 5 of 6 Print Date 1/9/2012

U.S. DOT Classification	: Not regul	ated for transportation.				
ICAO/IATA : Refer to specific regulation.						
IMO/IMDG (maritime)	: Refer to s	specific regulation.				
	15. REGUL	ATORY INFORMAT	TION			
US Regulations:						
OSHA Status	: Classified	d as hazardous based of	n components.			
TSCA Status	: All comp TSCA In	ponents of this product ventory.	are listed on or ex	empt from the		
US. EPA CERCLA Hazardo	ous Substances (40	CFR 302)				
not applicable						
California Propositio 65	n : Not appli	cable				
SARA Title III Section 302	Extremely Hazard	ous Substance				
Unless specific chemicals ar	e identified under	this section, this produ	ct is Not Applicab	le under this regula		
SARA Title III Section 313	Toxic Chemicals:					
Unless specific chemicals ar	e identified under	this section, this produ	ct is Not Applicab	le under this regula		
Canadian Regulations:						
National Pollutant Re	lease Inventory (N	NPRI)				
Chemical Name	· ``	CAS-No.	Weight percent	NPRI ID#		
Zinc stearate		557-05-1	0.10 - 1.00			

<u>PolyOne</u>

## MATERIAL SAFETY DATA SHEET GREEN GLOW IN THE DARK

Version Number 1.0 Revision Date 10/09/2009 Page 6 of 6 Print Date 1/9/2012

]	DSL	:	DSL status has not been determined. Quantity use in Carestricted by regulations.	mada may be
Nationa	l Inventories:			
1	Australia AICS	:	Not determined	
(	China IECS	:	Not determined	
]	Europe EINECS	:	Not determined	
J	Japan ENCS	:	Not determined	
]	Korea KECI	:	Not determined	
]	Philippines PICCS	:	Not determined	
			16. OTHER INFORMATION	

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.