MATERIAL SAFETY DATA SHEET BLUE GLOW IN THE DARK

Version Number 1.0 Revision Date 10/09/2009 Page 1 of 6 Print Date 1/9/2012

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone Emergency telephone	:	Product Stewardship (770) 271-5902 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	BLUE GLOW IN THE DARK
Product code	:	CC10125777
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight percent
Aluminate (Al(OH)63-), (OC-6-11)-,	11097-59-9	1 - 5
magnesium carbonate hydroxide (2:6:1:4)		
Calcium carbonate	1317-65-3	5 - 10

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation	: Particulates, like other inert materials can be mechanically irritating. Excessive inhalation of product vapors, especially during heating or processing, may be irritating to respiratory system.
Ingestion	: May be harmful if swallowed.
Eyes	: Particulates, like other inert materials can be mechanically irritating.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.

PolyOne.

MATERIAL SAFETY DATA SHEET **BLUE GLOW IN THE DARK**

Version Number 1.0 Revision Date 10/09/2009 Page 2 of 6 Print Date 1/9/2012

Medical Conditions Aggravated by Exposure:	: None known.
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases o doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seek medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: not applicable
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	 not applicable not applicable not applicable Carbon dioxide blanket, Water spray, Dry powder, Foam. Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible. May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under fire conditions.
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 13 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE

PolyOne.

_

MATERIAL SAFETY DATA SHEET **BLUE GLOW IN THE DARK**

sion Number 1.0 ision Date 10/09/2009			Prin	Page 3 t Date 1/9/2
Handling		ake measures to prevent the bunch in areas with appropriate example.		arge. Heat
Storage		: Keep containers dry and tightly closed to avoid moisture absorp and contamination. Keep in a dry, cool place.		
8.]	EXPOSURE	CONTROLS/PERSONAL I	PROTECTION	
Respiratory protection	: N	lo personal respiratory protecti	ve equipment normally 1	required.
Eye/Face Protection	: S	afety glasses with side-shields		
Hand protection	: P	rotective gloves		
Skin and body protection	: L	ong sleeved clothing		
Additional Protective Measures	: S	afety shoes		
General Hygiene Considerations		Iandle in accordance with good ractice. Wash hands before br		
Engineering measures		leat only in areas with appropri ppropriate exhaust ventilation		Provide
Exposure limit(s)				
Components	Value	Exposure time	Exposure type	List:
Calcium carbonate	5 mg/m3	PEL:	Respirable fraction.	OSHA Z1
	15 mg/m3	PEL:	Total dust.	OSHA Z1
	10 mg/m3	Time Weighted Average (TWA):		MX OEL
	20 mg/m3	Short Term Exposure Limit (STEL):		MX OEL

	9. PHYSICAL AND CHE	MICAL PROPERTIES	
Form Appearance Colour Odour Melting point/range Boiling Point: Water solubility	 solid pellets BLUE very faint Not determined not applicable insoluble 	Evaporation rate Specific Gravity Bulk density Vapour pressure Vapour density pH	 Not applicable Not determined Not established not applicable not applicable not applicable
	10. STABILITY AN	D REACTIVITY	
Stability	: Stable		

PolyOne

MATERIAL SAFETY DATA SHEET **BLUE GLOW IN THE DARK**

Version Number 1.0 Revision Date 10/09/2009 Page 4 of 6 Print Date 1/9/2012

Hazardous Polymerization Conditions to avoid	:	Will not occur. Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
Incompatible Materials	:	Avoid contact with strong oxidizers. Also, avoid contact with acetal or acetal copolymers and with amine containing materials during processing. At processing conditions, these materials are mutually destructive and involve rapid degradation. Thoroughly purge and mechanically clean processing equipment to avoid even trace quantities of these materials from coming in contact with each other. Prevent cross contamination of feedstocks.
Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), hydrogen chloride (HCl), other hazardous materials, and smoke are all possible. Prolonged heating (approximately 30 minutes or more) above 392 °F (200 °C) or short term heating at 482 °F (250 °C) may result in product decomposition and evolution of carbon monoxide and hydrogen chloride.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
11097-59-9	Aluminate (Al(OH)63-), (OC-6-11)-, magnesium carbonate hydroxide (2:6:1:4)	Irritant	Eyes, Skin.
1317-65-3	Calcium carbonate	Irritant	Eyes, Skin.
		Systemic effects	Eyes, Skin, Respiratory system.

12. ECOLOGICAL INFORMATION

	13	3. DISPOSAL CONSIDERATIONS	
Additional advice	:	no data available	
Bioaccumulation Potential	:	Chemicals are not readily available as they are bound within the polymer matrix.	
Environmental Toxicity	:	Chemicals are not readily available as they are bound within the polymer matrix.	
Persistence and degradability	:	Not readily biodegradable.	

PolyOne.

MATERIAL SAFETY DATA SHEET **BLUE GLOW IN THE DARK**

sion Number 1.0 rision Date 10/09/2009	Page 5 o Print Date 1/9/20
Product	: Like most thermoplastic plastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. DOT Classification	: Not regulated for transportation.
ICAO/IATA	: Refer to specific regulation.
IMO/IMDG (maritime)	: Refer to specific regulation.
	15. REGULATORY INFORMATION
US Regulations:	
OSHA Status	: Classified as hazardous based on components.
TSCA Status	: All components of this product are listed on or exempt from the TSCA Inventory.
US. EPA CERCLA Hazardo	us Substances (40 CFR 302)
not applicable	
California Proposition 65	n : Not applicable
SARA Title III Section 302 I	Extremely Hazardous Substance
Unless specific chemicals are	identified under this section, this product is Not Applicable under this regulati
SARA Title III Section 313	'oxic Chemicals:

PolvOne

MATERIAL SAFETY DATA SHEET **BLUE GLOW IN THE DARK**

Version Number 1.0 Revision Date 10/09/2009 Page 6 of 6 Print Date 1/9/2012

Canadian Regulations: National Pollutant Release Inventory (NPRI) NPRI ID# Chemical Name CAS-No. Weight percent Zinc stearate 557-05-1 0.10 - 1.00 WHMIS Classification : D2B DSL DSL status has not been determined. Quantity use in Canada may be : restricted by regulations. National Inventories: Australia AICS Not determined ٠ China IECS Not determined • Europe EINECS Not determined : Japan ENCS Not determined : Korea KECI : Not determined Philippines PICCS Not determined :

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.