PolvOne

MATERIAL SAFETY DATA SHEET **REDWOOD 1**

Version Number 1.0 Revision Date 01/05/2010 Page 1 of 6 Print Date 1/10/2012

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012				
Telephone	:	Product Stewardship (770) 271-5902		
Emergency telephone	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).		
Product name	:	REDWOOD 1		
Product code	:	CC10127355		
Chemical Name	:	Mixture		
CAS-No.	:	Mixture		
Product Use	:	Industrial Applications		

ComponentsCAS-No.Weight percentIron oxide1309-37-160 - 100

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Skin contact, Ingestion		
Acute exposure			
Inhalation	: Inhalation of airborne droplets may cause irritation of the respiratory tract.		
Ingestion	: May be harmful if swallowed.		
Eyes	: Irritating to eyes and respiratory system.		
Skin	: Experience shows no unusual dermatitis hazard from routine handling.		
Chronic exposure	: Refer to Section 11 for Toxicological Information.		

PolyOne.

MATERIAL SAFETY DATA SHEET **REDWOOD 1**

Version Number 1.0 Revision Date 01/05/2010 Page 2 of 6 Print Date 1/10/2012

Medical Conditions : None known. Aggravated by Exposure:		
	4. FIRST AID MEASURES	
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. Seek medical attention after significant exposure.	
Ingestion	: Do not induce vomiting without medical advice. Seek medical attention if necessary.	
Eyes	: Rinse immediately with plenty of water for at least 15 minutes. If ey irritation persists, seek medical attention.	
Skin	: Wash off with soap and plenty of water. If skin irritation persists seek medical attention.	
	5. FIRE-FIGHTING MEASURES	
Flash point	: Greater than 200 °F (93 °C)	
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media	 Not applicable Not applicable Not applicable Carbon dioxide blanket, Dry powder, Foam. 	
Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	 Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible. 	
	6. ACCIDENTAL RELEASE MEASURES	
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.	
Environmental precautions	: The product should not be allowed to enter drains, water courses or the soil. Should not be released into the environment.	
Methods for cleaning up	: Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Package all material in appropriate container for disposal. Refer to Section 13 of this MSDS for proper disposal methods.	
	7. HANDLING AND STORAGE	
Handling	: Heat only in areas with appropriate exhaust ventilation.	



MATERIAL SAFETY DATA SHEET **REDWOOD 1**

Version Number 1.0				
Revision Date	01/05/2010			

Page 3 of 6 Print Date 1/10/2012

Storage

: Keep containers dry and tightly closed to avoid moisture absorption and contamination. Store in a cool dry place.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Respiratory protection	: Under normal handling conditions a respirator may not be r	equired.
Eye/Face Protection	: Safety glasses with side-shields	
Hand protection	: Protective gloves	
Skin and body protection	: Long sleeved clothing	
Additional Protective Measures	: Safety shoes	
General Hygiene Considerations	: Handle in accordance with good industrial hygiene and safe practice. Wash hands before breaks and at the end of work	•
Engineering measures	: Heat only in areas with appropriate exhaust ventilation. Pro appropriate exhaust ventilation at machinery.	ovide

Exposure limit(s)

Components	Value	Exposure time	Exposure type	ype List:	
Iron oxide	5 mg/m3	Time Weighted Average	Respirable fraction.	ACGIH	
		(TWA):			
	10 mg/m3	PEL:	Fume.	OSHA Z1	
	5 mg/m3	Time Weighted Average	as Fe	MX OEL	
		(TWA):			
	10 mg/m3	Short Term Exposure Limit	as Fe	MX OEL	
	_	(STEL):			

9. PHYSICAL AND CHEMICAL PROPERTIES

Form
Appearance
Colour
Odour
Melting point/range
Boiling Point:
Water solubility

liquid
viscous, liquid
RED
very faint
not applicable
immiscible

Evaporation rate Specific Gravity Bulk density Vapour pressure Vapour density pH Not established
Not determined
Not applicable
Not determined
Not determined
Not applicable

10. STABILITY AND REACTIVITY

Stability

: Stable

:

Hazardous Polymerization

Will not occur.

PolyOne.

MATERIAL SAFETY DATA SHEET **REDWOOD 1**

ion Number 1.0 sion Date 01/05/2010)			Page 4 Print Date 1/10/2
Conditions to avoid	:	Keep away fro	om oxidizing agents an	id open flame.
Incompatible Materials	:	Incompatible	with strong acids and o	oxidizing agents.
1				oxide (CO), oxides of nitrogen nd smoke are all possible.
	11.	TOXICOLOG	CAL INFORMATIO	DN
health data for the indiv Toxicity Overview	idual comp	onents which co	mprise the mixture.	are effects listed are based on exi
CAS-No. 1309-37-1	Chen Iron oxide	nical Name	Effect Systemic effects	Target OrganRespiratory system.
Bioaccumulation Potential Additional advice		 use. Does not bioaccumulate. no data available 		
	1	3. DISPOSAL	CONSIDERATIONS	
Product Contaminated packaging		 Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations. Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations. 		
	-	14. TRANSPOH	RT INFORMATION	
U.S. DOT Classification	n :	Not regulated	for transportation.	
ICAO/IATA		Not regulated	for transportation.	
IMO/IMDG (maritime)	:	Not regulated	for transportation.	

MATERIAL SAFETY DATA SHEET **REDWOOD 1**

Version Number 1.0 Revision Date 01/05/2010 Page 5 of 6 Print Date 1/10/2012

US Regulations:

OSHA Status : Classified as hazardous based on components.

TSCA Status

: All components of this product are listed on or exempt from the TSCA Inventory.

US. EPA CERCLA Hazardous Substances (40 CFR 302)

not applicable

California Proposition : Not applicable 65

SARA Title III Section 302 Extremely Hazardous Substance

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

SARA Title III Section 313 Toxic Chemicals:

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

Canadian Regulations:

 National Pollutant Release Inventory (NPRI)

 Chemical Name
 CAS-No.
 Weight percent
 NPRI ID#

 Branched-nonylphenol, ethoxylate
 68412-54-4
 0.10 - 1.00
 186

 0.10 - 1.00
 100
 100
 100

 WHMIS Classification
 :
 Not controlled.

 DSL
 :
 DSL status has not been determined. Quantity use in Canada may be restricted by regulations.

 National Inventories:
 .

 Australia AICS
 :
 Not determined.

<u>PolyOne</u>

MATERIAL SAFETY DATA SHEET **REDWOOD 1**

Version Number 1.0 Revision Date 01/05/2010 Page 6 of 6 Print Date 1/10/2012

China IECS	: Not determined
Europe EINECS	: Not determined
Japan ENCS	: Not determined
Korea KECI	: Not determined
Philippines PICCS	: Not determined

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.