PolvOne

MATERIAL SAFETY DATA SHEET HUSKY ORANGE CC 2

Version Number 1.1 Revision Date 12/21/2009

Page 1 of 7 Print Date 1/10/2012

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone:Emergency telephone:	Product Stewardship (770) 271-5902 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name :	HUSKY ORANGE CC 2
Product code :	CC10127411
Chemical Name :	Mixture
CAS-No. :	Mixture
Product Use :	Industrial Applications

2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight percent
1,6-Hexanediamine, N,N'-bis(2,2,6,6- tetramethyl-4-piperidinyl)-,polymer with 2,4,6-trichloro-1,3,5-triazine, reaction products	70624-18-9	1 - 5
Silica, amorphous, precipitated and gel	112926-00-8	1 - 5

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation	: Resin particles, like other inert materials, can be mechanically irritating.
Ingestion	: May be harmful if swallowed.
Eyes	: Resin particles, like other inert materials, are mechanically irritating to eyes.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.

PolyOne.

MATERIAL SAFETY DATA SHEET HUSKY ORANGE CC 2

Version Number 1.1 Revision Date 12/21/2009 Page 2 of 7 Print Date 1/10/2012

Medical Conditions : None known. Aggravated by Exposure:				
		4. FIRST AID MEASURES		
Inhalation	:	Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.		
Ingestion	:	Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.		
Eyes	:	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.		
Skin	:	Wash off with soap and plenty of water. If skin irritation persists seek medical attention.		
		5. FIRE-FIGHTING MEASURES		
Flash point	:	not applicable		
Flammable Limits				
Upper explosion limit	:	not applicable		
Lower explosion limit	:	not applicable		
Autoignition temperature	:	not applicable		
Suitable extinguishing media	:	Carbon dioxide blanket, Water spray, Dry powder, Foam.		
Special Fire Fighting	•	Fullface self-contained breathing apparatus (SCBA) used in positive		
Procedures		pressure mode should be worn to prevent inhalation of airborne		
Unuquel Fire/Explosion		contaminants. Corbon diaxida (CO), avidas of nitrogen		
Unusual Fire/Explosion Hazards	·	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.		
	6. A	CCIDENTAL RELEASE MEASURES		
Personal precautions	•	Wear appropriate personal protection during cleanup, such as		
		impervious gloves, boots and coveralls.		
Environmental precautions	:	Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.		
Methods for cleaning up	:	Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 13 of this MSDS for proper disposal methods.		

PolyOne.

MATERIAL SAFETY DATA SHEET HUSKY ORANGE CC 2

Version Number 1.1 Revision Date 12/21/2009 Page 3 of 7 Print Date 1/10/2012

	7.	HANDLING AND ST	JRAG	÷E		
Handling		ake measures to prevent nly in areas with approp				narge. Heat
Storage		eep containers dry and t nd contamination. Keep			l moistur	e absorption
8.]	EXPOSURE	CONTROLS/PERSO	NAL I	PROTECTION	N	
Respiratory protection	: N	lo personal respiratory p	rotecti	ve equipment n	ormally	required.
Eye/Face Protection	: S	afety glasses with side-s	hields			
Hand protection	: P	rotective gloves				
Skin and body protection	: L	ong sleeved clothing				
Additional Protective Measures	: S	afety shoes				
General Hygiene Considerations		landle in accordance wit ractice. Wash hands bef				
Engineering measures	: Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.					
Exposure limit(s)						
Components	Value	Exposure time		Exposure	type	List:
Silica, amorphous, precipitated and gel	6 mg/m3	Time Weighted Aver (TWA):	age	Laposure	type	OSHA Z1A
	10 mg/m3	Time Weighted Aver (TWA):	age			MX OEL
	0.8 mg/m3	Time Weighted Aver (TWA):	age			Z3
	9. PHYSIC	CAL AND CHEMICAI	. PRC	PERTIES		
Form	: solid	.]	Evapoi	ration rate		applicable
Appearance Colour	: pelle : RED				determined established	
Odour	: KED			r pressure		applicable
Melting point/range				r density		applicable
Boiling Point:			оH	2		applicable
Water solubility	: insol					

PolvO<u>ne</u>

MATERIAL SAFETY DATA SHEET HUSKY ORANGE CC 2

Version Number 1.1 Revision Date 12/21/2009 Page 4 of 7 Print Date 1/10/2012

Stability	:	Stable
Hazardous Polymerization	:	Will not occur.
Conditions to avoid	:	Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
Incompatible Materials	:	Incompatible with strong acids and oxidizing agents.
Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
70624-18-9	1,6-Hexanediamine, N,N'- bis(2,2,6,6-tetramethyl-4- piperidinyl)-,polymer with 2,4,6-trichloro-1,3,5- triazine, reaction products	Irritant	Eyes, Skin, Respiratory system.
112926-00-8	Silica, amorphous, precipitated and gel	Irritant	Respiratory system, Eyes.

LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
70624-18-9	1,6-Hexanediamine, N,N'-	Oral LD50	> 2,000 mg/kg	rat
	bis(2,2,6,6-tetramethyl-4-	Dermal LD50	> 3,000 mg/kg	rat
	piperidinyl)-,polymer with			
	2,4,6-trichloro-1,3,5-			
	triazine, reaction products			

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

<u>PolyOne</u>

MATERIAL SAFETY DATA SHEET HUSKY ORANGE CC 2

Version Number 1.1 Revision Date 12/21/2009 Page 5 of 7 Print Date 1/10/2012

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

	12. ECOLOGICAL INFORMATION
Persistence and degradability	: Not readily biodegradable.
Environmental Toxicity	: Chemicals are not readily available as they are bound within the polymer matrix.
Bioaccumulation Potential	: Chemicals are not readily available as they are bound within the polymer matrix.
Additional advice	: no data available
	13. DISPOSAL CONSIDERATIONS
Product	: Like most thermoplastic plastics the product can be recycled. When possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. DOT Classification	: Not regulated for transportation.
ICAO/IATA	: Refer to specific regulation.
IMO/IMDG (maritime)	: Refer to specific regulation.
	15. REGULATORY INFORMATION
US Regulations:	
OSHA Status	: Classified as hazardous based on components.
TSCA Status	: All components of this product are listed on or exempt from the TSCA Inventory.
US. EPA CERCLA Hazardous	Substances (40 CFR 302)
not applicable	

PolvOne

MATERIAL SAFETY DATA SHEET HUSKY ORANGE CC 2

Version Number 1.1 Revision Date 12/21/2009 Page 6 of 7 Print Date 1/10/2012

California Proposition : Not applicable 65

SARA Title III Section 302 Extremely Hazardous Substance

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

SARA Title III Section 313 Toxic Chemicals:

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

Chemical Name	CAS-No.	Weight percent
VANADIUM COMPOUNDSVANADIUM	14059-33-7	5.00 - 10.00
COMPOUNDS		
ZINC COMPOUNDS	1314-98-3	10.00 - 30.00

Canadian Regulations:

National Pollutant Release Inventory (N	IPRI)		
Chemical Name	CAS-No.	Weight	NPRI ID#
		percent	
Bismuth vanadium oxide (BiVO4)	14059-33-7	5.00 - 10.00	
		5.00 - 10.00	
		5.00 - 10.00	
Zinc sulfide	1314-98-3	10.00 - 30.00	

WHMIS Classification : D2B

DSL

: DSL status has not been determined. Quantity use in Canada may be restricted by regulations.

National Inventories:

Australia AICS	:	Not determined
China IECS	:	Not determined
Europe EINECS	:	Listed
Japan ENCS	:	Not determined
Korea KECI	:	Not determined

PolyOne

MATERIAL SAFETY DATA SHEET HUSKY ORANGE CC 2

Version Number 1.1 Revision Date 12/21/2009 Page 7 of 7 Print Date 1/10/2012

Philippines PICCS

: Not determined

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.