PolvOne

MATERIAL SAFETY DATA SHEET LIME GREEN 376C W/SLIP

Version Number 1.1 Revision Date 12/11/2009 Page 1 of 7 Print Date 1/10/2012

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone Emergency telephone	:	Product Stewardship (770) 271-5902 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	LIME GREEN 376C W/SLIP
Product code	:	CC10127524
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight percent
Chromium (III) oxide	1308-38-9	1 - 5
Titanium dioxide	13463-67-7	1 - 5
Glyceryl monostearate	31566-31-1	5 - 10
Silica, amorphous	7631-86-9	10 - 30

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation	: Resin particles, like other inert materials, can be mechanically irritating.
Ingestion	: May be harmful if swallowed.
Eyes	: Resin particles, like other inert materials, are mechanically irritating to eyes.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.

PolyOne.

MATERIAL SAFETY DATA SHEET LIME GREEN 376C W/SLIP

Version Number 1.1 Revision Date 12/11/2009 Page 2 of 7 Print Date 1/10/2012

Medical Conditions : None known.						
Medical Conditions : None known. Aggravated by Exposure:						
		4. FIRST AID MEASURES				
Inhalation	:	Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.				
Ingestion	:	Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.				
Eyes	:	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.				
Skin	:	Wash off with soap and plenty of water. If skin irritation persists seek medical attention.				
		5. FIRE-FIGHTING MEASURES				
Flash point	:	not applicable				
Flammable Limits						
Upper explosion limit	:	not applicable				
Lower explosion limit	:	not applicable				
Autoignition temperature	:	not applicable				
Suitable extinguishing media	:	Carbon dioxide blanket, Water spray, Dry powder, Foam.				
Special Fire Fighting	:	Fullface self-contained breathing apparatus (SCBA) used in positive				
Procedures		pressure mode should be worn to prevent inhalation of airborne				
Unuquel Fire/Explosion		contaminants.				
Unusual Fire/Explosion Hazards	·	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.				
	6. A	CCIDENTAL RELEASE MEASURES				
Personal precautions	:	Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.				
Environmental precautions	:	Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.				
Methods for cleaning up	:	Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 13 of this MSDS for proper disposal methods.				

PolyOne.

MATERIAL SAFETY DATA SHEET LIME GREEN 376C W/SLIP

Version Number 1.1 Revision Date 12/11/2009 Page 3 of 7 Print Date 1/10/2012

Handling	:	Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.			
Storage	:	: Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.			
8. EXI	POSU	RE CONTROLS/PERSONAL PROTECTION			
Respiratory protection	:	No personal respiratory protective equipment normally required.			
Eye/Face Protection	:	Safety glasses with side-shields			
Hand protection	:	Protective gloves			
Skin and body protection	:	Long sleeved clothing			
Additional Protective Measures	:	Safety shoes			
General Hygiene Considerations	:	Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.			
Engineering measures	:	Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.			

PolvOne.

MATERIAL SAFETY DATA SHEET LIME GREEN 376C W/SLIP

Version Number 1.1 Revision Date 12/11/2009

Page 4 of 7 Print Date 1/10/2012

Components	Value	Exposure time	Exposure type	List:
Chromium (III) oxide 0.5 mg/s		Recommended exposure limit (REL):	as Cr	NIOSH
	0.5 mg/m3	PEL:	as Cr	OSHA Z1
Glyceryl monostearate	10 mg/m3	Time Weighted Average (TWA):		ACGIH
Silica, amorphous	6 mg/m3	Recommended exposure limit (REL):		NIOSH
	0.8 mg/m3	Time Weighted Average (TWA):		Z3
	10 mg/m3	Time Weighted Average (TWA):	Inhalable particulate.	MX OEL
	3 mg/m3	Time Weighted Average (TWA):	Respirable dust.	MX OEL
Titanium dioxide	10 mg/m3	Time Weighted Average (TWA):		ACGIH
	15 mg/m3	PEL:	Total dust.	OSHA Z1
	10 mg/m3	Time Weighted Average (TWA):	Total dust.	OSHA Z1A
	10 mg/m3	Time Weighted Average (TWA):	as Ti	MX OEL
	20 mg/m3	Short Term Exposure Limit (STEL):	as Ti	MX OEL

9. PHYSICAL AND CHEMICAL PROPERTIES

10. STABILITY AND REACTIVITY

decomposition, do not overheat.

Form Appearance Colour Odour Melting point/range Boiling Point: Water solubility

Hazardous Polymerization

Conditions to avoid

Incompatible Materials

Hazardous decomposition

- : pellets : GREEN : very faint Not determined : : not applicable : insoluble
- Evaporation rate Specific Gravity Bulk density Vapour pressure Vapour density pН

Keep away from oxidizing agents and open flame. To avoid thermal

Not applicable Not determined Not established not applicable not applicable

: : not applicable :

:

:

:

Stability

products

: Stable

:

:

:

: solid

Will not occur.

Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen : (NOx), other hazardous materials, and smoke are all possible.

Incompatible with strong acids and oxidizing agents.

11. TOXICOLOGICAL INFORMATION

MATERIAL SAFETY DATA SHEET LIME GREEN 376C W/SLIP

Version Number 1.1 Revision Date 12/11/2009 Page 5 of 7 Print Date 1/10/2012

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
1308-38-9	Chromium (III) oxide	Irritant	Eyes, Skin.
		sensitizer	Skin.
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.
7631-86-9	Silica, amorphous	Irritant	Eyes, Respiratory system.

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
13463-67-7	Titanium dioxide	no	2B	no

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

- 2A The component is probably carcinogenic to humans.
- 2B The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

- 1 The component is known to be a human carcinogen.
- 2 The component is reasonably anticipated to be a human carcinogen.

Additional Health Hazard Information:

Chromium (III) oxide 1308-38-9 The bi- and trivalent forms of chrome have a low order of acute toxicity, but may cause skin sensitization and irritation to the eyes. No effects have been reported for chromium (III) oxide. Chromium (III) compounds are not considered carcinogenic in animals or humans.

Persistence and degradability	: Not readily biodegradable.
Environmental Toxicity	: Chemicals are not readily available as they are bound within the polymer matrix.
Bioaccumulation Potential	: Chemicals are not readily available as they are bound within the polymer matrix.
Additional advice	: no data available
	13. DISPOSAL CONSIDERATIONS
Product	: Like most thermoplastic plastics the product can be recycled. When

<u>PolyOne</u>

MATERIAL SAFETY DATA SHEET LIME GREEN 376C W/SLIP

Contaminated packaging	generato classific applicab : Recyclin material transpor	or of waste material has ation, transportation an ole federal, state/provin ng is preferred when po has the responsibility t tation and disposal in a	to disposal or incineration. The s the responsibility for proper waste ad disposal in accordance with cial and local regulations. ossible. The generator of waste for proper waste classification, accordance with applicable federal,
	-	ovincial and local regul	
	14. I KAN	SFORT INFORMAT	
U.S. DOT Classification	: Not regu	ulated for transportation	1.
ICAO/IATA	: Refer to	specific regulation.	
IMO/IMDG (maritime)	: Refer to	specific regulation.	
	15. REGUI	LATORY INFORMA	TION
US Regulations:			
OSHA Status	: Classifie	ed as hazardous based o	on components.
TSCA Status		ponents of this produc	t are listed on or exempt from the
US. EPA CERCLA Hazardou:	s Substances (4	0 CFR 302)	
Chemical Name C	CAS-No.	RQ for component	RQ for Mixture/Product
Chromium (III) 1 oxide	308-38-9	010 lbs	227 LB
California Proposition 65 SARA Title III Section 302 E			

SARA Title III Section 313 Toxic Chemicals:

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

PolvOne

MATERIAL SAFETY DATA SHEET LIME GREEN 376C W/SLIP

Version Number 1.1 Revision Date 12/11/2009 Page 7 of 7 Print Date 1/10/2012

Chemical Name	CAS-No.	Weight percent
CHROMIUM III COMPOUNDSCHROMIUM	1308-38-9	1.00 - 5.00
COMPOUNDS		

Canadian Regulations:

National Pollutant Release Inventory (NPRI)			
Chemical Name	CAS-No.	Weight	NPRI ID#
		percent	
Chromium (III) oxide	1308-38-9	1.00 - 5.00	
Phthalocyanine green	1328-53-6	0.10 - 1.00	

WHMIS Classification : D2A

WHMIS Ingredient Disclosure List

1308-38-9	No.
1500-50-7	8-9
7631-86-9	6-9

DSL

All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.

National Inventories:

Australia AICS	: Not determined
China IECS	: Not determined
Europe EINECS	: Listed
Japan ENCS	: Not determined
Korea KECI	: Not determined
Philippines PICCS	: Not determined

:

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.