## MATERIAL SAFETY DATA SHEET WEATHERED WOOD

Version Number 1.1 Revision Date 03/13/2014

CAS-No.

Product Use

Page 1 of 8 Print Date 3/20/2014

### 1. PRODUCT AND COMPANY IDENTIFICATION

#### POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone Emergency telephone number	:	1 (440) 930-1000 or 1 (866) POLYONE CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	WEATHERED WOOD
Product code	:	CC10129737
Chemical Name	:	Mixture

- : Mixture
  - : Industrial Applications

#### 2. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS-No.	Weight percent
1,6-Hexanediamine, N,N'-bis(2,2,6,6- tetramethyl-4-piperidinyl)-,polymer with 2,4,6-trichloro-1,3,5-triazine, reaction	70624-18-9	1 - 5
products		
Phenol, 2-(2H-benzotriazol-2-yl)-4,6-	25973-55-1	5 - 10
bis(1,1-dimethylpropyl)-		
Carbon black	1333-86-4	1 - 5
Iron oxide	1309-37-1	1 - 5
Titanium dioxide	13463-67-7	10 - 30

#### **3. HAZARDS IDENTIFICATION**

#### EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

#### POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation	: Resin particles, like other inert materials, can be mechanically

PolyOne.

# MATERIAL SAFETY DATA SHEET **WEATHERED WOOD**

ion Number 1.1 sion Date 03/13/2014	Page 2 Print Date 3/20/2
<b>T</b>	irritating.
Ingestion	: May be harmful if swallowed.
Eyes	: Resin particles, like other inert materials, are mechanically irritating to eyes.
Skin	: Experience shows no unusual dermatitis hazard from routine handling
Chronic exposure	: Refer to Section 11 for Toxicological Information.
Medical Conditions Aggravated by Exposure:	: None known.
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases o doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for a least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seek medical attention.
	5. FIREFIGHTING MEASURES
Flash point	: not applicable
Flammable Limits	
Upper explosion limit	: not applicable
Lower explosion limit	: not applicable
Auto-ignition temperature	: not applicable
Suitable extinguishing media	: Carbon dioxide blanket, Water spray, Dry powder, Foam.
Special Fire Fighting	: Fullface self-contained breathing apparatus (SCBA) used in positive
Procedures	pressure mode should be worn to prevent inhalation of airborne
	contaminants.
Unusual Fire/Explosion	: Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen
Hazards	(NOx), other hazardous materials, and smoke are all possible.
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should no be allowed to enter drains, water courses or the soil.

PolyOne.

# MATERIAL SAFETY DATA SHEET **WEATHERED WOOD**

WEATHERED WOOD	,	
Version Number 1.1 Revision Date 03/13/2014		Page 3 of 8 Print Date <i>3/20/2014</i>
Methods for cleaning up	:	Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal.
		7. HANDLING AND STORAGE
Handling	:	Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.
Storage	:	Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.
8. EXI	POSUI	RE CONTROLS/PERSONAL PROTECTION
Respiratory protection	:	No personal respiratory protective equipment normally required.
Eye/Face Protection	:	Safety glasses with side-shields
Hand protection	:	Protective gloves
Skin and body protection	:	Long sleeved clothing
Additional Protective Measures	:	Safety shoes
General Hygiene Considerations	:	Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.
Engineering measures	:	Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.

Exposure limit(s)

\_

PolyOne

## MATERIAL SAFETY DATA SHEET WEATHERED WOOD

Version Number 1.1 Revision Date 03/13/2014 Page 4 of 8 Print Date 3/20/2014

Components	Value	Exposure time	Exposure type	List:
Carbon black	3.5 mg/m3	Recommended exposure limit (REL):		NIOSH
	0.1 mg/m3	Recommended exposure limit (REL):		NIOSH
	3.5 mg/m3	PEL:		OSHA Z1
	3.5 mg/m3	Time Weighted Average (TWA):		OSHA Z1A
	3.5 mg/m3	Time Weighted Average (TWA):		MX OEL
	7 mg/m3	Short Term Exposure Limit (STEL):		MX OEL
	3 mg/m3	Time Weighted Average (TWA):	Inhalable fraction.	ACGIH
Iron oxide	10 mg/m3	PEL:	Fume.	OSHA Z1
	5 mg/m3	Time Weighted Average (TWA):	as Fe	MX OEL
	10 mg/m3	Short Term Exposure Limit (STEL):	as Fe	MX OEL
	5 mg/m3	Time Weighted Average (TWA):	Respirable fraction.	ACGIH
Titanium dioxide	10 mg/m3	Time Weighted Average (TWA):		ACGIH
	15 mg/m3	PEL:	Total dust.	OSHA Z1
	10 mg/m3	Time Weighted Average (TWA):	Total dust.	OSHA Z1A
	10 mg/m3	Time Weighted Average (TWA):	as Ti	MX OEL
	20 mg/m3	Short Term Exposure Limit (STEL):	as Ti	MX OEL

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

- Form Appearance Colour Odour Melting point/range Boiling Point: Water solubility
- solid
  pellets
  BROWN
  very faint
  Not determined
  not applicable
  insoluble

Evapouration rate Specific Gravity Bulk density Vapour pressure Vapour density pH

- Not applicableNot determinedNot establishednot applicablenot applicable
- : not applicable

#### **10. STABILITY AND REACTIVITY**

Stability	:	The product is stable if stored and handled as prescribed.
Hazardous Polymerization	:	Will not occur.
Conditions to avoid	:	Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.

PolvUne

## MATERIAL SAFETY DATA SHEET WEATHERED WOOD

Version Number 1.1 Revision Date 03/13/2014 Page 5 of 8 Print Date 3/20/2014

Incompatible Materials	:	Incompatible with strong acids and oxidizing agents.
Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.

#### **11. TOXICOLOGICAL INFORMATION**

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

**Toxicity Overview** 

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
70624-18-9	1,6-Hexanediamine, N,N'-	Irritant	Eyes, Skin, Respiratory
	bis(2,2,6,6-tetramethyl-4-		system.
	piperidinyl)-,polymer with		
	2,4,6-trichloro-1,3,5-		
	triazine, reaction products		
25973-55-1	Phenol, 2-(2H-	Systemic effects	Kidney, Liver, reproductive
	benzotriazol-2-yl)-4,6-		system.
	bis(1,1-dimethylpropyl)-		
1333-86-4	Carbon black	Systemic effects	Eyes, Respiratory system.
1309-37-1	Iron oxide	Systemic effects	Respiratory system.
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.

#### LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
70624-18-9	1,6-Hexanediamine, N,N'-	Oral LD50	> 2,000 mg/kg	rat
	bis(2,2,6,6-tetramethyl-4-	Dermal LD50	> 3,000 mg/kg	rat
	piperidinyl)-,polymer with			
	2,4,6-trichloro-1,3,5-			
	triazine, reaction products			
1333-86-4	Carbon black	Oral LD50	> 15,400 mg/kg	rat
		Dermal LD50	> 3 gm/kg	rabbit

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
13463-67-7	Titanium dioxide	no	2B	no

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

PolvOne

## MATERIAL SAFETY DATA SHEET **WEATHERED WOOD**

Version Number 1.1 Revision Date 03/13/2014

Page 6 of 8 Print Date 3/20/2014

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

#### Additional Health Hazard Information:

Carbon black 1333-86-4 Carcinogenicity: Many inhalation toxicologists believe that the tumor response observed in the referenced rat studies is species specific and does not correlate to human exposure. However, the IARC evaluation in Monograph Volume 65, issued in April 1996 concluded that, "There is sufficient evidence in experimental animals for the carcinogenicity of carbon black". Based on this evaluation, along with their evaluation of inadequate evidence of carcinogenicity in humans, IARC's overall evaluation is that "Carbon Black is possibly carcinogenic to humans (Group 2B). The IARC 2B listing only pertains to airborne, unbound carbon black particles of respirable size. Carbon Black has not been listed as a carcinogen by the National Toxicology Program (NTP) or the Occupational Safety and Health Administration (OSHA). The National Institute of Occupational Safety and Health (NIOSH) criteria document on carbon black recommends that only carbon black with PAH (polynuclear aromatic hydrocarbon) levels greater than 0.1% be considered suspect carcinogens.

	12. ECOLOGICAL INFORMATION
Persistence and degradability	: Not readily biodegradable.
Environmental Toxicity	: Chemicals are not readily available as they are bound within the polymer matrix.
Bioaccumulation Potential	: Chemicals are not readily available as they are bound within the polymer matrix.
Additional advice	: no data available
	13. DISPOSAL CONSIDERATIONS
Product Contaminated packaging	<ul> <li>Like most thermoplastic plastics the product can be recycled. Wher possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.</li> <li>Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.</li> </ul>
	14. TRANSPORT INFORMATION
U.S. DOT Classification	: Not regulated for transportation.
ICAO/IATA	: Refer to specific regulation.
IMO/IMDG (maritime)	: Refer to specific regulation.

PolyOne.

Page 7 of 8 Print Date 3/20/2014

## POLYONE CORPORATION

# MATERIAL SAFETY DATA SHEET **WEATHERED WOOD**

Version Number 1.1 Revision Date 03/13/2014

	15. REGULATO	RY INFORMA	TION			
US Regulations:						
OSHA Status	: Classified as ha	azardous based o	on componen	ts.		
TSCA Status	: All components of this product are listed on or exempt from the TSCA Inventory.					
US. EPA CERCLA Hazardous	s Substances (40 CFR	302)				
not applicable						
California Proposition 65	: Not applicable					
SARA Title III Section 302 Ex	stremely Hazardous S	ubstance				
	demery mazardous s	ubstance				
			uct is Not Ap	plicable	under this r	
Unless specific chemicals are i SARA Title III Section 313 To	identified under this s	ection, this prod ection, this prod CAS	-	plicable	under this r	
Unless specific chemicals are in SARA Title III Section 313 To Unless specific chemicals are in Chemical Name ZINC COMPOUNDS	identified under this s	ection, this prod ection, this prod CAS	<u>uct is Not Ap</u> 5-No.	plicable Weight	under this r	
Unless specific chemicals are in SARA Title III Section 313 To Unless specific chemicals are in Chemical Name ZINC COMPOUNDS Canadian Regulations:	identified under this s oxic Chemicals: identified under this s	ection, this prod ection, this prod CAS 6818	<u>uct is Not Ap</u> 5-No.	plicable Weight	under this r	
Unless specific chemicals are i SARA Title III Section 313 To Unless specific chemicals are i Chemical Name ZINC COMPOUNDS	identified under this s oxic Chemicals: identified under this s	ection, this prod ection, this prod CAS 6818	uct is Not Ap S-No. 7-51-9 Weigh	plicable Weight 10.00 -	under this r	
Unless specific chemicals are i SARA Title III Section 313 To Unless specific chemicals are i Chemical Name ZINC COMPOUNDS Canadian Regulations: National Pollutant Rele	identified under this s oxic Chemicals: identified under this s ase Inventory (NPRI)	ection, this prod ection, this prod CAS 6818	uct is Not Ap S-No. 7-51-9	plicable Weight 10.00 - t t	under this r percent - 30.00	
Unless specific chemicals are i SARA Title III Section 313 To Unless specific chemicals are i Chemical Name ZINC COMPOUNDS Canadian Regulations: National Pollutant Rele Chemical Name Zinc ferrite brown spinel (C	identified under this s oxic Chemicals: identified under this s ase Inventory (NPRI)	ection, this prod ection, this prod CAS 6818	uct is Not Ap S-No. 7-51-9 Weigh percen	plicable Weight 10.00 - t t	under this r percent - 30.00	
Unless specific chemicals are i SARA Title III Section 313 To Unless specific chemicals are i Chemical Name ZINC COMPOUNDS Canadian Regulations: National Pollutant Rele Chemical Name Zinc ferrite brown spinel (C	identified under this s oxic Chemicals: identified under this s ase Inventory (NPRI) I. Pigment Yellow	ection, this prod ection, this prod CAS 6818	uct is Not Ap S-No. 7-51-9 Weigh percen	plicable Weight 10.00 - t t	under this r percent - 30.00	
Unless specific chemicals are in SARA Title III Section 313 To Unless specific chemicals are in Chemical Name ZINC COMPOUNDS Canadian Regulations: National Pollutant Rele Chemical Name Zinc ferrite brown spinel (C 119)	identified under this s oxic Chemicals: identified under this s ase Inventory (NPRI) I. Pigment Yellow : D2A	ection, this prod ection, this prod CAS 6818	uct is Not Ap S-No. 7-51-9 Weigh percen	plicable Weight 10.00 - t t	under this r percent - 30.00	

PolyOne

## MATERIAL SAFETY DATA SHEET WEATHERED WOOD

Version Number 1.1 Revision Date 03/13/2014 Page 8 of 8 Print Date 3/20/2014

DSL	:	All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.	
National Inventories:			
Australia AICS	:	Listed	
China IECS	:	Listed	
Europe EINECS	:	Listed	
Japan ENCS	:	Not determined	
Korea KECI	:	Not determined	
Philippines PICCS	:	Not determined	
			╞

#### **16. OTHER INFORMATION**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.