PolvOne

## MATERIAL SAFETY DATA SHEET **TAN WOOD**

Version Number 1.1 Revision Date 03/25/2014 Page 1 of 6 Print Date 4/1/2014

POLYONE CORPORATI 33587 Walker Road, Avoi	ON	UCT AND COMPANY IDENTIFICATION OH 44012
Telephone Emergency telephone number	:	1 (440) 930-1000 or 1 (866) POLYONE CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	TAN WOOD
Product code	:	CC10130971
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

### 2. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS-No.	Weight percent
Rutile, antimony chromium buff	68186-90-3	10 - 30

#### **3. HAZARDS IDENTIFICATION**

#### **EMERGENCY OVERVIEW**

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

#### POTENTIAL HEALTH EFFECTS

<b>Routes of Exposure:</b>	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation	: Resin particles, like other inert materials, can be mechanically irritating.
Ingestion	: May be harmful if swallowed.
Eyes	: Resin particles, like other inert materials, are mechanically irritating to eyes.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.

PolyOne.

# MATERIAL SAFETY DATA SHEET **TAN WOOD**

Version Number 1.1 Revision Date 03/25/2014 Page 2 of 6 Print Date 4/1/2014

Medical Conditions Aggravated by Exposure:	: None known.		
	4. FIRST AID MEASURES		
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases o doubt seek medical advice.		
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.		
Eyes: Rinse immediately with plenty of water, also under the eyel least 15 minutes. If eye irritation persists, seek medical atter			
Skin	: Wash off with soap and plenty of water. If skin irritation persists seek medical attention.		
	5. FIREFIGHTING MEASURES		
Flash point	: not applicable		
Flammable Limits Upper explosion limit Lower explosion limit Auto-ignition temperature Suitable extinguishing media Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	<ul> <li>not applicable</li> <li>not applicable</li> <li>not applicable</li> <li>Carbon dioxide blanket, Water spray, Dry powder, Foam.</li> <li>Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.</li> <li>Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.</li> </ul>		
	6. ACCIDENTAL RELEASE MEASURES		
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.		
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.		
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal.		
	7. HANDLING AND STORAGE		
Handling	: Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.		



# MATERIAL SAFETY DATA SHEET **TAN WOOD**

#### Version Number 1.1 Revision Date 03/25/2014

Page 3 of 6 Print Date 4/1/2014

Storage	Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.			
8. EXPOSURE CONTROLS/PERSONAL PROTECTION				
Respiratory protection	: No personal respiratory protective equipment normally required.			
Eye/Face Protection	: Safety glasses with side-shields			
Hand protection	: Protective gloves			
Skin and body protection	: Long sleeved clothing			
Additional Protective Measures	: Safety shoes			
General Hygiene Considerations	: Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.			
Engineering measures	: Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.			

Exposure limit(s)

Components	Value	Exposure time	Exposure type	List:
Rutile, antimony chromium buff	0.5 mg/m3	Recommended exposure limit (REL):	as Cr	NIOSH
	0.5 mg/m3	PEL:	as Cr	OSHA Z1
	0.5 mg/m3	Time Weighted Average (TWA):	as Sb	ACGIH
	0.5 mg/m3	Recommended exposure limit (REL):	as Sb	NIOSH
	0.5 mg/m3	PEL:	as Sb	OSHA Z1
	0.5 mg/m3	Time Weighted Average (TWA):	as Sb	OSHA Z1A
	0.5 mg/m3	Time Weighted Average (TWA):	as Sb	MX OEL

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

- Form Appearance Colour Odour Melting point/range Boiling Point: Water solubility
- solid
  pellets
  TAN
  very faint
  Not determined
  not applicable
  insoluble

Evapouration rate Specific Gravity Bulk density Vapour pressure Vapour density pH Not applicable
Not determined
Not established
not applicable
not applicable
not applicable

#### **10. STABILITY AND REACTIVITY**



# MATERIAL SAFETY DATA SHEET **TAN WOOD**

Stability	: The product is	stable if stored and ha	ndled as prescribed.			
•	: Will not occur.					
Hazardous Polymerization	: will not occur.					
Conditions to avoid		Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.				
Incompatible Materials	: Incompatible w	with strong acids and o	xidizing agents.			
Hazardous decomposition products			xide (CO), oxides of nitrogen d smoke are all possible.			
	11. TOXICOLOGI	CAL INFORMATIO	N			
This mixture has not been ev health data for the individual Toxicity Overview		1	re effects listed are based on exi			

	antimony um buff	Irritant	Eyes, Skin, Respiratory system.			
chromi	um buff		system.			
		•				
	12. ECOLOGICA	AL INFORMATION	1			
ability	: Not readily bio	odegradable.				
Environmental Toxicity		: Chemicals are not readily available as they are bound within the polymer matrix.				
Bioaccumulation Potential		: Chemicals are not readily available as they are bound within the polymer matrix.				
	: no data available					
	13. DISPOSAL (	CONSIDERATIONS	5			
	possible recycl generator of wa classification, t	Like most thermoplastic plastics the product can be recycled. W possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper wast classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.				
ng	material has th transportation	e responsibility for pr and disposal in accord	oper waste classification, lance with applicable federal,			
	у	y : Chemicals are polymer matrix ntial : Chemicals are polymer matrix : no data availab 13. DISPOSAL ( : Like most ther possible recycl generator of w classification, t applicable fede ng : Recycling is pr material has th transportation a	<ul> <li>y : Chemicals are not readily available a polymer matrix.</li> <li>antial : Chemicals are not readily available a polymer matrix.</li> <li>and at available</li> <li>13. DISPOSAL CONSIDERATIONS</li> <li>Clike most thermoplastic plastics the possible recycling is preferred to dis generator of waste material has the r classification, transportation and dispapplicable federal, state/provincial a</li> </ul>			

PolyOne.

# MATERIAL SAFETY DATA SHEET **TAN WOOD**

Version Number 1.1 Revision Date 03/25/2014 Page 5 of 6 Print Date 4/1/2014

		4. TRANSPORT	INFORM	AATIO	N			
J.S. DOT Classification	:	Not regulated for	r transport	ation.				
CAO/IATA	:	Refer to specific	regulation	1.				
MO/IMDG (maritime)	:	Refer to specific	regulation	1.				
	15	. REGULATOR	Y INFOR	MATIC	DN			
US Regulations:								
OSHA Status	:	Classified as haz	ardous ba	sed on co	omponent	zs.		
TSCA Status	:	: All components of this product are listed on or exempt from the TSCA Inventory.						
US. EPA CERCLA Hazardo	us Sub	stances (40 CFR 3	302)					
not applicable								
California Propositio 65	n :	Not applicable						
SARA Title III Section 302 l	Extrem	ely Hazardous Sul	bstance					
Unless specific chemicals are	e identi	fied under this sec	ction, this	product i	is Not Ap	plicable	under this	regula
I. I			,		· · · · · ·	<b>r</b>		0
SARA Title III Section 313	Foxic (	Chemicals:						
Unless specific chemicals are	e identi	fied under this sec	ction, this					regula
Chemical Name CHROMIUM III COMPO	UNDS	CHROMIUM III		CAS-No 58186-90		10.00 ·	percent - 30.00	
COMPOUNDSANTIMON				50100 7	0.5	10.00	20.00	
COMPOUNDSCHROMI	JM CC	MPOUNDS						
Canadian Regulations:								
2		NDDI						
Notional Dallatart D	100C- T	iveniory (NPRI)					1	
National Pollutant Re	lease I		CAS-No		Weight	-	NPRI ID	#
National Pollutant Re Chemical Name	lease In		CAS-No		Weight percent		NPRI ID	#

*PolyOne* 

# MATERIAL SAFETY DATA SHEET **TAN WOOD**

Version Number 1.1 Revision Date 03/25/2014 Page 6 of 6 Print Date *4/1/2014* 

WHMIS Classification : D2B WHMIS Ingredient Disclosure List CAS-No. 68186-90-3 DSL All components of this product are on the Canadian Domestic : Substances List (DSL) or are exempt. National Inventories: Australia AICS Listed : China IECS : Listed **Europe EINECS** : Listed Japan ENCS Not determined : Korea KECI : Listed Philippines PICCS : Listed **16. OTHER INFORMATION** 

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.