MATERIAL SAFETY DATA SHEET MAHOGANY 6

Version Number 1.1 Revision Date 03/25/2014 Page 1 of 8 Print Date 4/1/2014

1. PRODUCT AND COMPANY IDENTIFICATION POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012 Telephone : 1 (440) 930-1000 or 1 (866) POLYONE Emergency telephone : CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).

Product name	: MAHOGANY 6
Product code	: CC10131277
Chemical Name	: Mixture
CAS-No.	: Mixture
Product Use	: Industrial Applications

2. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS-No.	Weight percent
1,6-Hexanediamine, N,N'-bis(2,2,6,6- tetramethyl-4-piperidinyl)-,polymer with 2,4,6-trichloro-1,3,5-triazine, reaction products	70624-18-9	1 - 5
Phenol, 2-(2H-benzotriazol-2-yl)-4,6- bis(1,1-dimethylpropyl)-	25973-55-1	1 - 5
Silica, amorphous, precipitated and gel	112926-00-8	1 - 5
Iron oxide	1309-37-1	10 - 30
Titanium dioxide	13463-67-7	10 - 30

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation	: Resin particles, like other inert materials, can be mechanically

PolyOne.

MATERIAL SAFETY DATA SHEET MAHOGANY 6

ls, are mechanically irritating to
s hazard from routine handling
nformation.
inhalation of fumes from
nptoms persist or in all cases o
cal advice. When symptoms edical advice.
er, also under the eyelids, for at ists, seek medical attention.
er. If skin irritation persists
Dry powder, Foam.
ratus (SCBA) used in positive
ent inhalation of airborne
ide (CO), oxides of nitrogen
smoke are all possible.
S
during cleanup, such as
S.
mont. The product should be
nment. The product should not ses or the soil.
1



MATERIAL SAFETY DATA SHEET MAHOGANY 6

Version Number 1.1PageRevision Date 03/25/2014Print Date 4/1				
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal.			
	7. HANDLING AND STORAGE			
Handling	: Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.			
Storage	: Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.			
8. EXP	OSURE CONTROLS/PERSONAL PROTECTION			
Respiratory protection	: No personal respiratory protective equipment normally required.			
Eye/Face Protection	: Safety glasses with side-shields			
Hand protection	: Protective gloves			
Skin and body protection	: Long sleeved clothing			
Additional Protective Measures	: Safety shoes			
General Hygiene Considerations	: Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.			
Engineering measures	: Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.			
Exposure limit(s)				

PolyOne

MATERIAL SAFETY DATA SHEET MAHOGANY 6

Version Number 1.1 Revision Date 03/25/2014

Page 4 of 8 Print Date 4/1/2014

Iron oxide	10 mg/m3 5 mg/m3	PEL: Time Weighted Average	Fume. as Fe	OSHA Z1
	5 mg/m3	Time Weighted Average	as Ea	MU OFI
		inter it orginee it orage	as re	MX OEL
		(TWA):		
	10 mg/m3	Short Term Exposure Limit (STEL):	as Fe	MX OEL
	5 mg/m3	Time Weighted Average (TWA):	Respirable fraction.	ACGIH
Silica, amorphous, precipitated and gel	6 mg/m3	Time Weighted Average (TWA):		OSHA Z1A
	10 mg/m3	Time Weighted Average (TWA):		MX OEL
	0.8 mg/m3	Time Weighted Average (TWA):		Z3
Titanium dioxide	10 mg/m3	Time Weighted Average (TWA):		ACGIH
	15 mg/m3	PEL:	Total dust.	OSHA Z1
	10 mg/m3	Time Weighted Average (TWA):	Total dust.	OSHA Z1A
	10 mg/m3	Time Weighted Average (TWA):	as Ti	MX OEL
	20 mg/m3	Short Term Exposure Limit (STEL):	as Ti	MX OEL

Form Appearance Colour Odour Melting point/range Boiling Point: Water solubility

Stability

products

: pellets : BROWN : very faint : Not determined : not applicable

: solid

Specific Gravity Bulk density Vapour pressure Vapour density pН

Evapouration rate

Not applicable : Not determined : Not established not applicable not applicable not applicable

:

:

:

:

: insoluble **10. STABILITY AND REACTIVITY** The product is stable if stored and handled as prescribed. : Hazardous Polymerization Will not occur. : Conditions to avoid Keep away from oxidizing agents and open flame. To avoid thermal : decomposition, do not overheat. Incompatible Materials Incompatible with strong acids and oxidizing agents. : Hazardous decomposition : Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen

- (NOx), other hazardous materials, and smoke are all possible.
 - **11. TOXICOLOGICAL INFORMATION**

MATERIAL SAFETY DATA SHEET MAHOGANY 6

Version Number 1.1 Revision Date 03/25/2014 Page 5 of 8 Print Date 4/1/2014

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
70624-18-9	1,6-Hexanediamine, N,N'-	Irritant	Eyes, Skin, Respiratory
	bis(2,2,6,6-tetramethyl-4-		system.
	piperidinyl)-,polymer with		
	2,4,6-trichloro-1,3,5-		
	triazine, reaction products		
25973-55-1	Phenol, 2-(2H-	Systemic effects	Kidney, Liver, reproductive
benzotriazol-2-yl)-4,6-			system.
bis(1,1-dimethylpropyl)-			
112926-00-8	Silica, amorphous,	Irritant	Respiratory system, Eyes.
precipitated and gel			
1309-37-1	Iron oxide	Systemic effects	Respiratory system.
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.

LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
70624-18-9	1,6-Hexanediamine, N,N'- bis(2,2,6,6-tetramethyl-4- piperidinyl)-,polymer with 2,4,6-trichloro-1,3,5- triazine, reaction products	Oral LD50 Dermal LD50	> 2,000 mg/kg > 3,000 mg/kg	rat rat

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
13463-67-7	Titanium dioxide	no	2B	no

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

12. ECOLOGICAL INFORMATION

Persistence and degradability

: Not readily biodegradable.



MATERIAL SAFETY DATA SHEET MAHOGANY 6

sion Number 1.1 ision Date 03/25/2014	Page 6 Print Date 4/1/2				
Environmental Toxicity	: Chemicals are not readily available as they are bound within the polymer matrix.				
Bioaccumulation Potential	: Chemicals are not readily available as they are bound within the polymer matrix.				
Additional advice	: no data available				
	13. DISPOSAL CONSIDERATIONS				
Product : Like most thermoplastic plastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.					
Contaminated packaging	: Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.				
	14. TRANSPORT INFORMATION				
U.S. DOT Classification	: Not regulated for transportation.				
ICAO/IATA : Refer to specific regulation.					
IMO/IMDG (maritime)	: Refer to specific regulation.				
	15. REGULATORY INFORMATION				
US Regulations:					
OSHA Status	: Classified as hazardous based on components.				
TSCA Status	: All components of this product are listed on or exempt from the TSCA Inventory.				
US. EPA CERCLA Hazardou	s Substances (40 CFR 302)				
not applicable					
California Proposition 65	: Not applicable				

PolvOne

MATERIAL SAFETY DATA SHEET MAHOGANY 6

Version Number 1.1 Revision Date 03/25/2014 Page 7 of 8 Print Date 4/1/2014

SARA Title III Section 302 Extremely Hazardous Substance

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

SARA Title III Section 313 Toxic Chemicals:

U	Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation				
	Chemical Name	CAS-No.	Weight percent		
	ZINC COMPOUNDS	68187-51-9	10.00 - 30.00		

Canadian Regulations:

National Pollutant Release Inventory (NPRI)			
Chemical Name	CAS-No.	Weight	NPRI ID#
		percent	
Zinc ferrite brown spinel (C.I. Pigment Yellow	68187-51-9	10.00 - 30.00	
119)			

WHMIS Classification : D2A

WHMIS Ingredient Disclosure List

Γ	CAS-No.
	1309-37-1

DSL

All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.

National Inventories:

:	Listed
:	Listed
:	Listed
:	Not determined
:	Not determined
:	Not determined
	:

:

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing,

PolyOne.

MATERIAL SAFETY DATA SHEET MAHOGANY 6

Version Number 1.1 Revision Date 03/25/2014 Page 8 of 8 Print Date 4/1/2014

storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.