PolvOne

MATERIAL SAFETY DATA SHEET WHITE

Version Number 1.0 Revision Date 06/03/2010

Page 1 of 7 Print Date 1/13/2012

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone Emergency telephone	:	Product Stewardship (770) 271-5902 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	WHITE
Product code	:	CC10132412
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight percent
Silica, amorphous, precipitated and gel	112926-00-8	0.1 - 1
Silica, amorphous	7631-86-9	1 - 5
Calcium carbonate	1317-65-3	5 - 10
Titanium dioxide	13463-67-7	30 - 60

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact	
Acute exposure		
Inhalation	: Resin particles, like other inert materials, can be mechanically irritating.	
Ingestion	: May be harmful if swallowed.	
Eyes	: Resin particles, like other inert materials, are mechanically irritating to eyes.	
Skin	: Experience shows no unusual dermatitis hazard from routine handling.	

POLYONE CORPORATION

PolyOne.

MATERIAL SAFETY DATA SHEET WHITE

Version Number 1.0 Revision Date 06/03/2010 Page 2 of 7 Print Date 1/13/2012

Medical Conditions : None known.		
Aggravated by Exposure:		
		4. FIRST AID MEASURES
Inhalation	:	Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	:	Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	:	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	:	Wash off with soap and plenty of water. If skin irritation persists seek medical attention.
		5. FIRE-FIGHTING MEASURES
Flash point	:	not applicable
Flammable Limits		
Upper explosion limit	:	not applicable
Lower explosion limit	:	not applicable
Autoignition temperature	:	not applicable
Suitable extinguishing media	:	Carbon dioxide blanket, Water spray, Dry powder, Foam.
Special Fire Fighting	:	Fullface self-contained breathing apparatus (SCBA) used in positive
Procedures		pressure mode should be worn to prevent inhalation of airborne
		contaminants.
Unusual Fire/Explosion Hazards	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.
	6. A	CCIDENTAL RELEASE MEASURES
Personal precautions	:	Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	:	Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	:	Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 13 of this MSDS for proper disposal methods.

PolyOne.

MATERIAL SAFETY DATA SHEET WHITE

Version Number 1.0 Revision Date 06/03/2010

Page 3 of 7 Print Date 1/13/2012

Handling	:	Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.
Storage	:	Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.
8. EX	POSU	RE CONTROLS/PERSONAL PROTECTION
Respiratory protection	:	No personal respiratory protective equipment normally required.
Eye/Face Protection	:	Safety glasses with side-shields
Hand protection	:	Protective gloves
Skin and body protection	:	Long sleeved clothing
Additional Protective Measures	:	Safety shoes
General Hygiene Considerations	:	Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.
Engineering measures	:	Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.

PolyOne

MATERIAL SAFETY DATA SHEET WHITE

Version Number 1.0

Revision Date 06/03/2010

Page 4 of 7 Print Date 1/13/2012

Components	Value	Exposure time	Exposure type	List:
Calcium carbonate	5 mg/m3	PEL:	Respirable fraction.	OSHA Z1
	15 mg/m3	PEL:	Total dust.	OSHA Z1
	10 mg/m3	Time Weighted Average (TWA):		MX OEL
	20 mg/m3	Short Term Exposure Limit (STEL):		MX OEL
Silica, amorphous	6 mg/m3	Recommended exposure limit (REL):		NIOSH
	0.8 mg/m3	Time Weighted Average (TWA):		Z3
	10 mg/m3	Time Weighted Average (TWA):	Inhalable particulate.	MX OEL
	3 mg/m3	Time Weighted Average (TWA):	Respirable dust.	MX OEL
Silica, amorphous, precipitated and gel	6 mg/m3	Time Weighted Average (TWA):		OSHA Z1A
	10 mg/m3	Time Weighted Average (TWA):		MX OEL
	0.8 mg/m3	Time Weighted Average (TWA):		Z3
Titanium dioxide	10 mg/m3	Time Weighted Average (TWA):		ACGIH
	15 mg/m3	PEL:	Total dust.	OSHA Z1
	10 mg/m3	Time Weighted Average (TWA):	Total dust.	OSHA Z1A
	10 mg/m3	Time Weighted Average (TWA):	as Ti	MX OEL
	20 mg/m3	Short Term Exposure Limit (STEL):	as Ti	MX OEL

9. PHYSICAL AND CHEMICAL PROPERTIES

- Form Appearance Colour Odour Melting point/range Boiling Point: Water solubility
- solid
 pellets
 WHITE
 very faint
 Not determined
 not applicable
 insoluble

Evaporation rate Specific Gravity Bulk density Vapour pressure Vapour density pH Not applicableNot determinedNot establishednot applicable

not applicable

:

: not applicable

10. STABILITY AND REACTIVITY

Stability

Hazardous Polymerization

: Stable

: Will not occur.

Conditions to avoid

: Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.

MATERIAL SAFETY DATA SHEET WHITE

Version Number 1.0 Page 5 of 7 Revision Date 06/03/2010 Print Date 1/13/2012 Incompatible Materials : Incompatible with strong acids and oxidizing agents. Hazardous decomposition products : Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
112926-00-8	Silica, amorphous,	Irritant	Respiratory system, Eyes.
	precipitated and gel		
7631-86-9	Silica, amorphous	Irritant	Eyes, Respiratory system.
1317-65-3	Calcium carbonate	Irritant	Eyes, Skin.
		Systemic effects	Eyes, Skin, Respiratory
			system.
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
13463-67-7	Titanium dioxide	no	2B	no

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

12. ECOLOGICAL INFORMATION

Persistence and degradability	:	Not readily biodegradable.
Environmental Toxicity	:	Chemicals are not readily available as they are bound within the polymer matrix.
Bioaccumulation Potential	:	Chemicals are not readily available as they are bound within the polymer matrix.
Additional advice	:	no data available

Version Number 1.0



Page 6 of 7

MATERIAL SAFETY DATA SHEET **WHITE**

13. DISPOSAL CONSIDERATIONS
 Like most thermoplastic plastics the product can be recycled. Whe possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations. Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
state/provincial and local regulations.
14. TRANSPORT INFORMATION
: Not regulated for transportation.
: Refer to specific regulation.
: Refer to specific regulation.
15. REGULATORY INFORMATION
: Classified as hazardous based on components.
: All components of this product are listed on or exempt from the TSCA Inventory.
us Substances (40 CFR 302)
n : Not applicable
Extremely Hazardous Substance
identified under this section, this product is Not Applicable under this reg
Coxic Chemicals:

<u>PolyOne</u>

MATERIAL SAFETY DATA SHEET **WHITE**

Version Number 1.0				
Revision Date	06/03/2010			

_

Page 7 of 7 Print Date 1/13/2012

Canadian Regulations:	
National Pollutant Rel	ease Inventory (NPRI)
not applicable	
WHMIS Classification	n : D2A
WHMIS Ingredient Di	sclosure List
CAS-No. 7631-86-9	
DSL	: All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.
National Inventories:	
Australia AICS	: Listed
China IECS	: Listed
Europe EINECS	: Listed
Japan ENCS	: Listed
Korea KECI	: Listed
Philippines PICCS	: Listed
	16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.