PolyOne

# MATERIAL SAFETY DATA SHEET **NY YELLOW 2 SY-01**

Version Number 1.1 Revision Date 03/13/2014

Page 1 of 7 Print Date 3/23/2014

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012					
Telephone	:	1 (440) 930-1000 or 1 (866) POLYONE			
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).			
Product name	:	NY YELLOW 2 SY-01			
Product code	:	CC10133469			
Chemical Name	:	Mixture			
CAS-No.	:	Mixture			
Product Use	:	Industrial Applications			

Components	CAS-No.	Weight percent
Nickel antimony yellow rutile (C.I. Pigment	8007-18-9	10 - 30
Yellow 53)		

#### **3. HAZARDS IDENTIFICATION**

#### **EMERGENCY OVERVIEW**

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

#### POTENTIAL HEALTH EFFECTS

<b>Routes of Exposure:</b>	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation	: Resin particles, like other inert materials, can be mechanically irritating.
Ingestion	: May be harmful if swallowed.
Eyes	: Resin particles, like other inert materials, are mechanically irritating to eyes.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.

PolyOne.

# MATERIAL SAFETY DATA SHEET NY YELLOW 2 SY-01

Version Number 1.1 Revision Date 03/13/2014 Page 2 of 7 Print Date 3/23/2014

Medical Conditions Aggravated by Exposure:	: None known.
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for a least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seek medical attention.
	5. FIREFIGHTING MEASURES
Flash point	: not applicable
Flammable Limits Upper explosion limit Lower explosion limit Auto-ignition temperature Suitable extinguishing media Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	<ul> <li>not applicable</li> <li>not applicable</li> <li>not applicable</li> <li>Carbon dioxide blanket, Water spray, Dry powder, Foam.</li> <li>Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.</li> <li>Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.</li> </ul>
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal.
	7. HANDLING AND STORAGE
Handling	: Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.

PolyOne

# MATERIAL SAFETY DATA SHEET NY YELLOW 2 SY-01

Version Number 1.1 Revision Date 03/13/2014 Page 3 of 7 Print Date 3/23/2014

Storage

: Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.

#### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Respiratory protection	:	No personal respiratory protective equipment normally required.
Eye/Face Protection	:	Safety glasses with side-shields
Hand protection	:	Protective gloves
Skin and body protection	:	Long sleeved clothing
Additional Protective Measures	:	Safety shoes
General Hygiene Considerations	:	Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.
Engineering measures	:	Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.

Exposure limit(s)

Components	Value	Exposure time	Exposure type	List:
Nickel antimony	0.015	Recommended exposure	as Ni	NIOSH
yellow rutile (C.I.	mg/m3	limit (REL):		
Pigment Yellow 53)				
	1 mg/m3	PEL:	as Ni	OSHA Z1
	1 mg/m3	Time Weighted Average	as Ni	OSHA Z1A
		(TWA):		
	0.2 mg/m3	Time Weighted Average	Inhalable fraction. as	ACGIH
	_	(TWA):	Ni	
	0.5 mg/m3	Time Weighted Average	as Sb	ACGIH
	_	(TWA):		
	0.5 mg/m3	Recommended exposure	as Sb	NIOSH
		limit (REL):		
	0.5 mg/m3	PEL:	as Sb	OSHA Z1
	0.5 mg/m3	Time Weighted Average	as Sb	OSHA Z1A
	_	(TWA):		
	0.5 mg/m3	Time Weighted Average	as Sb	MX OEL
	_	(TWA):		

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

Form Appearance Colour : solid: pellets: YELLOW

Evapouration rate Specific Gravity Bulk density

Not applicableNot determinedNot established

#### **MATERIAL SAFETY DATA SHEET** NY YELLOW 2 SY-01

Version Number 1.1 Revision Date 03/13/2014

Melting point/range

Odour

Boiling Point: Water solubility		ot applicable soluble	рН	: not applicable	
	1	0. STABILITY A	ND REACTIVITY		
Stability	:	The product is st	able if stored and hand	lled as prescribed.	
Hazardous Polymerization	:	Will not occur.			
Conditions to avoid	:	Keep away from decomposition, d	00	open flame. To avoid thermal	
Incompatible Materials	:	Incompatible wit	h strong acids and oxi	dizing agents.	
Hazardous decomposition products	:			de (CO), oxides of nitrogen smoke are all possible.	

: very faint

: Not determined

#### **11. TOXICOLOGICAL INFORMATION**

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

#### Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

	CAS-No.	Chemical Name	Effect	Target Organ
	8007-18-9	Nickel antimony yellow rutile (C.I. Pigment Yellow 53)	Irritant	Eyes, Skin.
ľ			sensitizer	Skin.

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
8007-18-9	Nickel antimony yellow rutile	no	1	no
	(C.I. Pigment Yellow 53)			

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

Page 4 of 7 Print Date 3/23/2014

: not applicable : not applicable

Vapour pressure Vapour density

PolyOne.

### MATERIAL SAFETY DATA SHEET NY YELLOW 2 SY-01

Version Number 1.1 Revision Date 03/13/2014 Page 5 of 7 Print Date 3/23/2014

<u>Additional Health Hazard Information:</u> Nickel antimony yellow rutile (C.I. Pigment Yellow 53) 8007-18-9 Skin sensitizer "nickel itch", with pulmonary, brain, liver, kidney and muscle effects.

Persistence and degradability	: Not readily biodegradable.				
Environmental Toxicity	: Chemicals are not readily available as they are bound within the polymer matrix.				
Bioaccumulation Potential : Chemicals are not readily available as they are bound within the polymer matrix.					
Additional advice	: no data available				
	13. DISPOSAL CONSIDERATIONS				
Product	: Like most thermoplastic plastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.				
Contaminated packaging : Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.					
	14. TRANSPORT INFORMATION				
U.S. DOT Classification	: Not regulated for transportation.				
ICAO/IATA	: Refer to specific regulation.				
IMO/IMDG (maritime)	: Refer to specific regulation.				
	15. REGULATORY INFORMATION				
US Regulations:					
OSHA Status	: Classified as hazardous based on components.				
TSCA Status	: All components of this product are listed on or exempt from the TSCA Inventory.				
US. EPA CERCLA Hazardous	Substances (40 CFR 302)				
not applicable	not applicable				

### MATERIAL SAFETY DATA SHEET NY YELLOW 2 SY-01

Version Number 1.1 Revision Date 03/13/2014 Page 6 of 7 Print Date 3/23/2014

California Proposition : WARNING! This product contains a chemical known to the State of California to cause cancer.

SARA Title III Section 302 Extremely Hazardous Substance

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

SARA Title III Section 313 Toxic Chemicals:

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

Chemical Name	CAS-No.	Weight percent
NICKEL COMPOUNDSNICKEL	8007-18-9	10.00 - 30.00
COMPOUNDSANTIMONY COMPOUNDS		
ZINC COMPOUNDS	1314-98-3	10.00 - 30.00

Canadian Regulations:

National Pollutant Release Inventory (NPR)	()		
Chemical Name	CAS-No.	Weight	NPRI ID#
		percent	
Nickel antimony yellow rutile (C.I. Pigment	8007-18-9	10.00 - 30.00	
Yellow 53)			
		10.00 - 30.00	
Zinc sulfide	1314-98-3	10.00 - 30.00	

WHMIS Classification : D2A

WHMIS Ingredient Disclosure List

CAS-No.	
8007-18-9	

DSL

All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.

National Inventories:

Australia AICS	:	Listed
China IECS	:	Listed
Europe EINECS	:	Listed

:

PolyOne

#### MATERIAL SAFETY DATA SHEET NY YELLOW 2 SY-01

Version Number 1.1 Revision Date 03/13/2014 Page 7 of 7 Print Date 3/23/2014

Japan ENCS

: Not determined

Korea KECI : Not determined

Philippines PICCS : Not determined

#### **16. OTHER INFORMATION**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.