PolvOne

MATERIAL SAFETY DATA SHEET UV CALIFORNIA REDWOOD

Version Number 1.1 Revision Date 03/26/2014 Page 1 of 7 Print Date 4/2/2014

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone Emergency telephone number	:	1 (440) 930-1000 or 1 (866) POLYONE CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	UV CALIFORNIA REDWOOD
Product code	:	CC10133640
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS-No.	Weight percent
1,6-Hexanediamine, N,N'-bis(2,2,6,6- tetramethyl-4-piperidinyl)-,polymer with 2,4,6-trichloro-1,3,5-triazine, reaction products	70624-18-9	1 - 5
Iron oxide	1309-37-1	5 - 10
Rutile, antimony chromium buff	68186-90-3	10 - 30

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	Inhalation, Ingestion, Skin contact		
Acute exposure			
Inhalation	: Resin particles, like other inert materials, can be mechanically irritating.		
Ingestion Eyes	May be harmful if swallowed.Resin particles, like other inert materials, are mechanically irritating to		

PolyOne.

MATERIAL SAFETY DATA SHEET UV CALIFORNIA REDWOOD

Version Number 1.1 Revision Date 03/26/2014 Page 2 of 7 Print Date 4/2/2014

Skin	eyes. : Experience shows no unusual dermatitis hazard from routine handling
Chronic exposure	: Refer to Section 11 for Toxicological Information.
Medical Conditions Aggravated by Exposure:	: None known.
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases o doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for a least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seek medical attention.
	5. FIREFIGHTING MEASURES
Flash point	: not applicable
Flammable Limits Upper explosion limit Lower explosion limit Auto-ignition temperature Suitable extinguishing media	 not applicable not applicable not applicable Carbon dioxide blanket, Water spray, Dry powder, Foam.
Special Fire Fighting Procedures	: Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.
riocedures	
Procedures Unusual Fire/Explosion Hazards	: Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.
Unusual Fire/Explosion	
Unusual Fire/Explosion	(NOx), other hazardous materials, and smoke are all possible.
Unusual Fire/Explosion Hazards	 (NOx), other hazardous materials, and smoke are all possible. 6. ACCIDENTAL RELEASE MEASURES Wear appropriate personal protection during cleanup, such as

PolyOne.

MATERIAL SAFETY DATA SHEET UV CALIFORNIA REDWOOD

Version Number 1.1 Revision Date 03/26/2014 Page 3 of 7 Print Date 4/2/2014

Handling	:	Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.
Storage	:	Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.
8. EXI	POSU	RE CONTROLS/PERSONAL PROTECTION
Respiratory protection	:	No personal respiratory protective equipment normally required.
Eye/Face Protection	:	Safety glasses with side-shields
Hand protection	:	Protective gloves
Skin and body protection	:	Long sleeved clothing
Additional Protective Measures	:	Safety shoes
General Hygiene Considerations	:	Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.
Engineering measures	:	Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.

PolyOne

MATERIAL SAFETY DATA SHEET UV CALIFORNIA REDWOOD

Version Number 1.1 Revision Date 03/26/2014 Page 4 of 7 Print Date 4/2/2014

Components	Value	Exposure time	Exposure type	List:
Iron oxide	10 mg/m3	PEL:	Fume.	OSHA Z1
	5 mg/m3	Time Weighted Average (TWA):	as Fe	MX OEL
	10 mg/m3	Short Term Exposure Limit (STEL):	as Fe	MX OEL
	5 mg/m3	Time Weighted Average (TWA):	Respirable fraction.	ACGIH
Rutile, antimony chromium buff	0.5 mg/m3	Recommended exposure limit (REL):	as Cr	NIOSH
	0.5 mg/m3	PEL:	as Cr	OSHA Z1
	0.5 mg/m3	Time Weighted Average (TWA):	as Sb	ACGIH
	0.5 mg/m3	Recommended exposure limit (REL):	as Sb	NIOSH
	0.5 mg/m3	PEL:	as Sb	OSHA Z1
	0.5 mg/m3	Time Weighted Average (TWA):	as Sb	OSHA Z1A
	0.5 mg/m3	Time Weighted Average (TWA):	as Sb	MX OEL

9. PHYSICAL AND CHEMICAL PROPERTIES

- Form Appearance Colour Odour Melting point/range Boiling Point: Water solubility
- solid
 pellets
 BROWN
 very faint
 Not determined
 not applicable
 insoluble
- Evapouration rate Specific Gravity Bulk density Vapour pressure Vapour density pH
- Not applicable
 Not determined
 Not established
 not applicable
 not applicable
 not applicable

10. STABILITY AND REACTIVITY

Stability	:	The product is stable if stored and handled as prescribed.
Hazardous Polymerization	:	Will not occur.
Conditions to avoid	:	Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
Incompatible Materials	:	Incompatible with strong acids and oxidizing agents.
Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

PolyOne.

MATERIAL SAFETY DATA SHEET **UV CALIFORNIA REDWOOD**

Version Number 1.1 Revision Date 03/26/2014 Page 5 of 7 Print Date 4/2/2014

<u>Toxicity Overview</u> This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
70624-18-9	1,6-Hexanediamine, N,N'-	Irritant	Eyes, Skin, Respiratory
	bis(2,2,6,6-tetramethyl-4-		system.
	piperidinyl)-,polymer with		
	2,4,6-trichloro-1,3,5-		
	triazine, reaction products		
1309-37-1	Iron oxide	Systemic effects	Respiratory system.
68186-90-3	Rutile, antimony	Irritant	Eyes, Skin, Respiratory
	chromium buff		system.

LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
70624-18-9	1,6-Hexanediamine, N,N'-	Oral LD50	> 2,000 mg/kg	rat
	bis(2,2,6,6-tetramethyl-4-	Dermal LD50	> 3,000 mg/kg	rat
	piperidinyl)-,polymer with			
	2,4,6-trichloro-1,3,5-			
	triazine, reaction products			

	12. ECOLOGICAL INFORMATION
Persistence and degradability	: Not readily biodegradable.
Environmental Toxicity	: Chemicals are not readily available as they are bound within the polymer matrix.
Bioaccumulation Potential	: Chemicals are not readily available as they are bound within the polymer matrix.
Additional advice	: no data available
	13. DISPOSAL CONSIDERATIONS
Product	: Like most thermoplastic plastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION

PolyOne.

MATERIAL SAFETY DATA SHEET UV CALIFORNIA REDWOOD

Version Number 1.1 Revision Date 03/26/2014 Page 6 of 7 Print Date 4/2/2014

U.S. DOT Classification	: N	Not regulated for transportation.
ICAO/IATA	: F	Refer to specific regulation.
IMO/IMDG (maritime)	: F	Refer to specific regulation.
	15. I	REGULATORY INFORMATION
US Regulations:		
OSHA Status	: (Classified as hazardous based on components.
TSCA Status	: .	All components of this product are listed on or exempt from the ISCA Inventory.
US. EPA CERCLA Hazardous	s Substa	ances (40 CFR 302)
not applicable		
California Proposition 65 SARA Title III Section 302 E		Not applicable y Hazardous Substance
	-	ed under this section, this product is Not Applicable under this regula
Liniess specific chemicals are	lucinin	ed under uns section, uns product is Not Applicable under uns regula
Unless specific chemicals are		
-	ovic Ch	emicals
SARA Title III Section 313 To		
SARA Title III Section 313 To Unless specific chemicals are		ed under this section, this product is Not Applicable under this regula
SARA Title III Section 313 To	identifie	ed under this section, this product is Not Applicable under this regula CAS-No. Weight percent
SARA Title III Section 313 To Unless specific chemicals are Chemical Name CHROMIUM III COMPOU COMPOUNDSANTIMON	identifie JNDSCI Y	ed under this section, this product is Not Applicable under this regulaCAS-No.Weight percentHROMIUM III68186-90-310.00 - 30.00
SARA Title III Section 313 To Unless specific chemicals are Chemical Name CHROMIUM III COMPOU	identifie JNDSCI Y	ed under this section, this product is Not Applicable under this regulaCAS-No.Weight percentHROMIUM III68186-90-310.00 - 30.00
SARA Title III Section 313 To Unless specific chemicals are Chemical Name CHROMIUM III COMPOU COMPOUNDSANTIMON	identifie JNDSCI Y	ed under this section, this product is Not Applicable under this regulaCAS-No.Weight percentHROMIUM III68186-90-310.00 - 30.00
SARA Title III Section 313 To Unless specific chemicals are Chemical Name CHROMIUM III COMPOU COMPOUNDSANTIMON COMPOUNDSCHROMIUM Canadian Regulations: National Pollutant Rele	identifie JNDSCI Y M COM	ed under this section, this product is Not Applicable under this regula CAS-No. Weight percent HROMIUM III 68186-90-3 10.00 - 30.00 IPOUNDS entory (NPRI)
SARA Title III Section 313 To Unless specific chemicals are Chemical Name CHROMIUM III COMPOU COMPOUNDSANTIMON COMPOUNDSCHROMIUM	identifie JNDSCI Y M COM	ed under this section, this product is Not Applicable under this regula CAS-No. Weight percent HROMIUM III 68186-90-3 10.00 - 30.00 IPOUNDS Interval of the section

PolyOne.

MATERIAL SAFETY DATA SHEET UV CALIFORNIA REDWOOD

Version Number 1.1 Revision Date 03/26/2014 Page 7 of 7 Print Date 4/2/2014

WHMIS Classification	:	D2B	
WHMIS Ingredient Discl	losu	re List	
CAS-No. 1309-37-1 68186-90-3 DSL		All components of this product are on the Canadian Domestic	
DSL	•	Substances List (DSL) or are exempt.	
National Inventories:			
Australia AICS	:	Listed	
China IECS	:	Listed	
Europe EINECS	:	Listed	
Japan ENCS	:	Not determined	
Korea KECI	:	Not determined	
Philippines PICCS	:	Not determined	
		16. OTHER INFORMATION	t

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.