PolvOne

## MATERIAL SAFETY DATA SHEET **TALC 20:1 PP**

Version Number 1.1 Revision Date 03/13/2014 Page 1 of 6 Print Date 3/26/2014

POLYONE CORPORATI 33587 Walker Road, Avoi		OH 44012
Telephone Emergency telephone number	:	1 (440) 930-1000 or 1 (866) POLYONE CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	TALC 20:1 PP
Product code	:	CC10134817
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

Components	CAS-No.	Weight percent
Talc	14807-96-6	30 - 60

#### **3. HAZARDS IDENTIFICATION**

#### **EMERGENCY OVERVIEW**

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

#### POTENTIAL HEALTH EFFECTS

<b>Routes of Exposure:</b>	: Inhalation, Ingestion, Skin contact		
Acute exposure			
Inhalation	: Resin particles, like other inert materials, can be mechanically irritating.		
Ingestion	: May be harmful if swallowed.		
Eyes	: Resin particles, like other inert materials, are mechanically irritating to eyes.		
Skin	: Experience shows no unusual dermatitis hazard from routine handling.		
Chronic exposure	: Refer to Section 11 for Toxicological Information.		

PolyOne.

## MATERIAL SAFETY DATA SHEET **TALC 20:1 PP**

Version Number 1.1 Revision Date 03/13/2014 Page 2 of 6 Print Date 3/26/2014

Medical Conditions Aggravated by Exposure:	: None known.
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases o doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seek medical attention.
	5. FIREFIGHTING MEASURES
Flash point	: not applicable
Flammable Limits Upper explosion limit Lower explosion limit Auto-ignition temperature Suitable extinguishing media Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	<ul> <li>not applicable</li> <li>not applicable</li> <li>not applicable</li> <li>Carbon dioxide blanket, Water spray, Dry powder, Foam.</li> <li>Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.</li> <li>Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.</li> </ul>
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal.
	7. HANDLING AND STORAGE
Handling	: Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.



### **MATERIAL SAFETY DATA SHEET TALC 20:1 PP**

#### Version Number 1.1 Revision Date 03/13/2014

Page 3 of 6 Print Date 3/26/2014

:	Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.
POSU	RE CONTROLS/PERSONAL PROTECTION
:	No personal respiratory protective equipment normally required.
:	Safety glasses with side-shields
:	Protective gloves
:	Long sleeved clothing
:	Safety shoes
:	Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.
:	Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.
	: <u>POSU</u> : : : : :

Exposure limit(s)

Components	Value	Exposure time	Exposure type	List:
Talc	2 mg/m3	Time Weighted Average (TWA):	Respirable fraction.	ACGIH
	2 mg/m3	Recommended exposure limit (REL):	Respirable.	NIOSH
	2 mg/m3	Time Weighted Average (TWA):	Respirable dust.	OSHA Z1A
	0.1 mg/m3	Time Weighted Average (TWA):	Respirable.	Z3
	0.3 mg/m3	Time Weighted Average (TWA):	Total dust.	Z3

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

Form Appearance Colour Odour Melting point/range **Boiling Point:** Water solubility

: solid pellets NO PIGMENT very faint Not determined not applicable : insoluble

:

:

:

:

:

Evapouration rate Specific Gravity Bulk density Vapour pressure Vapour density pН

Not applicable : Not determined Not established : not applicable : not applicable : not applicable

:

:

#### **10. STABILITY AND REACTIVITY**

Stability

: The product is stable if stored and handled as prescribed.

## MATERIAL SAFETY DATA SHEET **TALC 20:1 PP**

Version Number 1.1 Revision Date 03/13/2014 Page 4 of 6 Print Date 3/26/2014

Hazardous Polymerization	:	Will not occur.
Conditions to avoid	:	Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
Incompatible Materials	:	Incompatible with strong acids and oxidizing agents.
Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.

#### **11. TOXICOLOGICAL INFORMATION**

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
14807-96-6	Talc	Systemic effects	Eyes, Respiratory system, Skin.

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
14807-96-6	Talc	no	2B	no

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

#### **12. ECOLOGICAL INFORMATION**

Persistence and degradability	:	Not readily biodegradable.
Environmental Toxicity	:	Chemicals are not readily available as they are bound within the polymer matrix.
Bioaccumulation Potential	:	Chemicals are not readily available as they are bound within the polymer matrix.
Additional advice	:	no data available



# MATERIAL SAFETY DATA SHEET **TALC 20:1 PP**

Version Number 1.1 Revision Date 03/13/2014 Page 5 of 6 Print Date 3/26/2014

Product	: Like most thermoplastic plastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. DOT Classification	: Not regulated for transportation.
ICAO/IATA	: Refer to specific regulation.
IMO/IMDG (maritime)	: Refer to specific regulation.
	15. REGULATORY INFORMATION
US Regulations:	
OSHA Status	: Classified as hazardous based on components.
TSCA Status	: All components of this product are listed on or exempt from the TSCA Inventory.
US. EPA CERCLA Hazardou	as Substances (40 CFR 302)
not applicable	
California Proposition 65	n : Not applicable
SARA Title III Section 302 E	Extremely Hazardous Substance
Unless specific chemicals are	identified under this section, this product is Not Applicable under this regula
SARA Title III Section 313 7	'oxic Chemicals:

POLYONE CORPORATION



### **MATERIAL SAFETY DATA SHEET TALC 20:1 PP**

Version Number 1.1 Revision Date 03/13/2014

Page 6 of 6 Print Date 3/26/2014

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation						
Canadian Regulations:						
National Pollutant Release Inventory (NPRI)						
not applicable						
WHMIS Classification	:	D2A				
DSL	:	All of the components of this product are listed on the Canadian Inventories or are exempt. However, at least one component of this product is on the Canadian Non-Domestic Substances List (NDSL). Quantity use in Canada is restricted by regulations.				
National Inventories:						
Australia AICS	:	Not determined				
China IECS	:	Listed				
Europe EINECS	:	Listed				
Japan ENCS	:	Not determined				
Korea KECI	:	Listed				
Philippines PICCS	:	Listed				
		16 OTHER INFORMATION	+			

#### κ μηγυκινία μοη

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.