MATERIAL SAFETY DATA SHEET LIGHT GREY CRASTIN 427C

Version Number 1.2 Revision Date 10/18/2012 Page 1 of 7 Print Date 10/18/2012

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone Emergency telephone number	:	1 (440) 930-1000 or 1 (866) POLYONE CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	LIGHT GREY CRASTIN 427C
Product code	:	CC10135547
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS-No.	Weight percent
Nickel antimony yellow rutile (C.I. Pigment	8007-18-9	0.1 - 1
Yellow 53)		

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation	: Resin particles, like other inert materials, can be mechanically irritating.
Ingestion	: May be harmful if swallowed.
Eyes	: Resin particles, like other inert materials, are mechanically irritating to eyes.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.

PolyOne.

MATERIAL SAFETY DATA SHEET LIGHT GREY CRASTIN 427C

Version Number 1.2 Revision Date 10/18/2012 Page 2 of 7 Print Date 10/18/2012

Medical Conditions Aggravated by Exposure:	: None known.					
	4. FIRST AID MEASURES					
Inhalation : Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.						
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.					
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for a least 15 minutes. If eye irritation persists, seek medical attention.					
Skin	: Wash off with soap and plenty of water. If skin irritation persists seek medical attention.					
	5. FIREFIGHTING MEASURES					
Flash point	: not applicable					
Flammable Limits Upper explosion limit Lower explosion limit Auto-ignition temperature Suitable extinguishing media Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	 not applicable not applicable not applicable Carbon dioxide blanket, Water spray, Dry powder, Foam. Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible. 					
	6. ACCIDENTAL RELEASE MEASURES					
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.					
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.					
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal.					
	7. HANDLING AND STORAGE					
Handling	: Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.					

POLYONE CORPORATION

PolyOne

MATERIAL SAFETY DATA SHEET LIGHT GREY CRASTIN 427C

Version Number 1.2 Revision Date 10/18/2012 Page 3 of 7 Print Date 10/18/2012

Storage

: Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Respiratory protection	:	No personal respiratory protective equipment normally required.
Eye/Face Protection	:	Safety glasses with side-shields
Hand protection	:	Protective gloves
Skin and body protection	:	Long sleeved clothing
Additional Protective Measures	:	Safety shoes
General Hygiene Considerations	:	Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.
Engineering measures	:	Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.

Exposure limit(s)

Components	Value	Exposure time	Exposure type	List:
Nickel antimony	0.015	Recommended exposure	as Ni	NIOSH
yellow rutile (C.I.	mg/m3	limit (REL):		
Pigment Yellow 53)				
	1 mg/m3	PEL:	as Ni	OSHA Z1
	1 mg/m3	Time Weighted Average	as Ni	OSHA Z1A
		(TWA):		
	0.2 mg/m3	Time Weighted Average	Inhalable fraction. as	ACGIH
		(TWA):	Ni	
	0.5 mg/m3	Time Weighted Average	as Sb	ACGIH
		(TWA):		
	0.5 mg/m3	Recommended exposure	as Sb	NIOSH
		limit (REL):		
	0.5 mg/m3	PEL:	as Sb	OSHA Z1
	0.5 mg/m3	Time Weighted Average	as Sb	OSHA Z1A
		(TWA):		
	0.5 mg/m3	Time Weighted Average	as Sb	MX OEL
		(TWA):		

9. PHYSICAL AND CHEMICAL PROPERTIES

Form Appearance Colour : solid : pellets : GREY Evaporation rate Specific Gravity Bulk density Not applicableNot determinedNot established

4/7

POLYONE CORPORATION

MATERIAL SAFETY DATA SHEET LIGHT GREY CRASTIN 427C

: very faint

: insoluble

: Not determined

: not applicable

Version Number 1.2 Revision Date 10/18/2012

Melting point/range

Boiling Point:

Water solubility

Odour

10. STABILITY AND REACTIVITY		
Stability	:	The product is stable if stored and handled as prescribed.
Hazardous Polymerization	:	Will not occur.
Conditions to avoid	:	Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
Incompatible Materials	:	Incompatible with strong acids and oxidizing agents.
Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
8007-18-9	Nickel antimony yellow rutile (C.I. Pigment Yellow 53)	Irritant	Eyes, Skin.
		sensitizer	Skin.

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
8007-18-9	Nickel antimony yellow rutile	no	1	no
	(C.I. Pigment Yellow 53)			

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

:

Vapour pressure

Vapour density

pН

Page 4 of 7

Print Date 10/18/2012

: not applicable

: not applicable

not applicable

<u>PolyOne</u>.

MATERIAL SAFETY DATA SHEET **LIGHT GREY CRASTIN 427C**

Version Number 1.2 Revision Date 10/18/2012 Page 5 of 7 Print Date 10/18/2012

<u>Additional Health Hazard Information:</u> Nickel antimony yellow rutile (C.I. Pigment Yellow 53) 8007-18-9 Skin sensitizer "nickel itch", with pulmonary, brain, liver, kidney and muscle effects.

	12. ECOLOGICAL INFORMATION			
Persistence and degradability	: Not readily biodegradable.			
Environmental Toxicity	: Chemicals are not readily available as they are bound within the polymer matrix.			
Bioaccumulation Potential	: Chemicals are not readily available as they are bound within the polymer matrix.			
Additional advice	: no data available			
	13. DISPOSAL CONSIDERATIONS			
Product : Like most thermoplastic plastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.				
Contaminated packaging	: Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.			
	14. TRANSPORT INFORMATION			
U.S. DOT Classification	: Not regulated for transportation.			
ICAO/IATA	: Refer to specific regulation.			
IMO/IMDG (maritime)	: Refer to specific regulation.			
	15. REGULATORY INFORMATION			
US Regulations:				
OSHA Status	: Classified as hazardous based on components.			
TSCA Status	: All components of this product are listed on or exempt from the TSCA Inventory.			
US. EPA CERCLA Hazardous	Substances (40 CFR 302)			
not applicable				

olvUn<u>e</u>

MATERIAL SAFETY DATA SHEET LIGHT GREY CRASTIN 427C

Version Number 1.2 Revision Date 10/18/2012 Page 6 of 7 Print Date 10/18/2012

California Proposition : WARNING! This product contains a chemical known to the State of California to cause cancer.

SARA Title III Section 302 Extremely Hazardous Substance

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

SARA Title III Section 313 Toxic Chemicals:

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

Chemical Name	CAS-No.	Weight percent
NICKEL COMPOUNDSNICKEL	8007-18-9	0.10 - 1.00
COMPOUNDSANTIMONY COMPOUNDS		

Canadian Regulations:

National Pollutant Release Inventory (NPRI)

Chemical Name	CAS-No.	Weight	NPRI ID#
		percent	
Nickel antimony yellow rutile (C.I. Pigment	8007-18-9	0.10 - 1.00	
Yellow 53)			
		0.10 - 1.00	

WHMIS Classification : D2A

DSL

: DSL status has not been determined. Quantity use in Canada may be restricted by regulations.

National Inventories:

Australia AICS	:	Not determined
China IECS	:	Not determined
Europe EINECS	:	Not determined
Japan ENCS	:	Not determined
Korea KECI	:	Not determined
Philippines PICCS	:	Not determined

PolyOne

MATERIAL SAFETY DATA SHEET LIGHT GREY CRASTIN 427C

Version Number 1.2 Revision Date 10/18/2012 Page 7 of 7 Print Date 10/18/2012

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.