PolyOne

## MATERIAL SAFETY DATA SHEET STAN-TONE VC-33299 COASTAL GRN 633

Version Number 1.2 Revision Date 11/07/2013

Page 1 of 7 Print Date 11/7/2013

#### 1. PRODUCT AND COMPANY IDENTIFICATION

#### POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone:Emergency telephone:number		1 (440) 930-1000 or 1 (866) POLYONE CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	STAN-TONE VC-33299 COASTAL GRN 633
Product code	:	CC10135702
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

#### 2. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS-No.	Weight percent
Silica, amorphous	7631-86-9	1 - 5
Iron oxide	1309-37-1	10 - 30
Titanium dioxide	13463-67-7	30 - 60

#### 3. HAZARDS IDENTIFICATION

#### **EMERGENCY OVERVIEW**

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions.

#### **POTENTIAL HEALTH EFFECTS**

Routes of Exposure:	: Inhalation, Skin contact, Ingestion
Acute exposure	
Inhalation	: Resin particles, like other inert materials, can be mechanically irritating.
Ingestion	: May be harmful if swallowed.
Eyes	: Particulates, like other inert materials can be mechanically irritating.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.

# MATERIAL SAFETY DATA SHEET STAN-TONE VC-33299 COASTAL GRN 633

Version Number 1.2 Revision Date 11/07/2013 Page 2 of 7 Print Date 11/7/2013

PolyOne.

doubt seek medical advice.         Ingestion       : Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.         Eyes       : Rinse immediately with plenty of water, also under the eyelids, fo least 15 minutes. If eye irritation persists, seek medical attention.         Skin       : Wash off with soap and plenty of water. If skin irritation persists seek medical attention.         Skin       : Wash off with soap and plenty of water. If skin irritation persists seek medical attention.         Skin       : InstepFIGHTING MEASURES         Flash point       : not applicable         Flammable Limits       : not applicable         Upper explosion limit       : not applicable         Auto-ignition temperature       : Not relevant         Suitable extinguishing media       : Carbon dioxide blanket, Water spray, Dry powder, Foam.         Special Fire Fighting       : Fullface self-contained breathing apparatus (SCBA) used in positi pressure mode should be worn to prevent inhalation of airborne contaminants.         Unusual Fire/Explosion       : May emit Hydrogen Chloride (HCI) or Carbon Monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke a all possible.         6. ACCIDENTAL RELEASE MEASURES       all possible.         Personal precautions       : Wear appropriate personal protection during cleanup, such as	Medical Conditions Aggravated by Exposure:	: None known.
overheating or combustion. When symptoms persist or in all case doubt seek medical advice.         Ingestion       :       Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.         Eyes       :       Rinse immediately with plenty of water, also under the eyelids, fo least 15 minutes. If eye irritation persists, seek medical attention.         Skin       :       Wash off with soap and plenty of water. If skin irritation persists seek medical attention.         Skin       :       Not applicable         Flash point       :       not applicable         Flammable Limits       :       not applicable         Auto-ignition temperature       :       Not relevant         Suitable extinguishing media       :       Carbon dioxide blanket, Water spray, Dry powder, Foam.         Special Fire Fighting       :       Fullface self-contained breathing apparatus (SCBA) used in positi pressure mode should be worn to prevent inhalation of airborne contaminants.         Unusual Fire/Explosion       :       May emit Hydrogen Chloride (HCI) or Carbon Monoxide (CO) ur fire conditions. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOX), other hazardous materials, and smoke a all possible.         Personal precautions       :       Wear appropriate personal protection during cleanup, such as		4. FIRST AID MEASURES
Eyes       : Rinse immediately with plenty of water, also under the eyelids, fo least 15 minutes. If eye irritation persists, seek medical attention.         Skin       : Wash off with soap and plenty of water. If skin irritation persists seek medical attention.         Skin       : Wash off with soap and plenty of water. If skin irritation persists seek medical attention.         Skin       : Inot applicable         Flash point       : not applicable         Flammable Limits       : not applicable         Lower explosion limit       : not applicable         Suitable extinguishing media       : Carbon dioxide blanket, Water spray, Dry powder, Foam.         Special Fire Fighting       : Fullface self-contained breathing apparatus (SCBA) used in positi pressure mode should be worn to prevent inhalation of airborne contaminants.         Unusual Fire/Explosion       : May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) ur fire conditions. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke a all possible.         Personal precautions       : Wear appropriate personal protection during cleanup, such as	Inhalation	overheating or combustion. When symptoms persist or in all cases of
Ieast 15 minutes. If eye irritation persists, seek medical attention.         Skin       : Wash off with soap and plenty of water. If skin irritation persists seek medical attention.         Skin       : Nash off with soap and plenty of water. If skin irritation persists seek medical attention.         Flash point       : not applicable         Flammable Limits       : not applicable         Lower explosion limit       : not applicable         Auto-ignition temperature       : Not relevant         Suitable extinguishing media       : Carbon dioxide blanket, Water spray, Dry powder, Foam.         Special Fire Fighting       : Fullface self-contained breathing apparatus (SCBA) used in positi pressure mode should be worn to prevent inhalation of airborne contaminants.         Unusual Fire/Explosion       : May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) ur fire conditions. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke a all possible.         Personal precautions       : Wear appropriate personal protection during cleanup, such as	Ingestion	
seek medical attention.         Flash point         I not applicable         Lower explosion limit         Lower explosion limit         Lower explosion limit         Auto-ignition temperature         Suitable extinguishing media         Suitable extinguishing media         Secial Fire Fighting         Fullface self-contained breathing apparatus (SCBA) used in positi pressure mode should be worn to prevent inhalation of airborne contaminants.         Unusual Fire/Explosion       :       May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) ur fire conditions. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke a all possible.         Expresonal precautions         Fersonal precautions         : Wear appropriate personal protection during cleanup, such as <td>Eyes</td> <td>: Rinse immediately with plenty of water, also under the eyelids, for a least 15 minutes. If eye irritation persists, seek medical attention.</td>	Eyes	: Rinse immediately with plenty of water, also under the eyelids, for a least 15 minutes. If eye irritation persists, seek medical attention.
Flash point       : not applicable         Flammable Limits	Skin	
Flammable Limits       Interpret and a poince of the poince		5. FIREFIGHTING MEASURES
Upper explosion limit Lower explosion limit:not applicable not applicableAuto-ignition temperature Suitable extinguishing media:Not relevantSpecial Fire Fighting 	Flash point	: not applicable
Upper explosion limit Lower explosion limit:not applicable not applicableAuto-ignition temperature Suitable extinguishing media:Not relevantSpecial Fire Fighting Procedures:Fullface self-contained breathing apparatus (SCBA) used in positi pressure mode should be worn to prevent inhalation of airborne contaminants.Unusual Fire/Explosion Hazards:May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) un fire conditions. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke a all possible.Personal precautions:Wear appropriate personal protection during cleanup, such as	Flammable Limits	
Auto-ignition temperature Suitable extinguishing media: Not relevant Carbon dioxide blanket, Water spray, Dry powder, Foam.Special Fire Fighting Procedures: Fullface self-contained breathing apparatus (SCBA) used in positi pressure mode should be worn to prevent inhalation of airborne contaminants.Unusual Fire/Explosion Hazards: May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) un fire conditions. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke a all possible.Personal precautions: Wear appropriate personal protection during cleanup, such as	Upper explosion limit	: not applicable
Suitable extinguishing media       : Carbon dioxide blanket, Water spray, Dry powder, Foam.         Special Fire Fighting       : Fullface self-contained breathing apparatus (SCBA) used in positi pressure mode should be worn to prevent inhalation of airborne contaminants.         Unusual Fire/Explosion       : May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) un fire conditions. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke a all possible.         Personal precautions       : Wear appropriate personal protection during cleanup, such as		
Special Fire Fighting       : Fullface self-contained breathing apparatus (SCBA) used in positi pressure mode should be worn to prevent inhalation of airborne contaminants.         Unusual Fire/Explosion       : May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) un fire conditions. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke a all possible. <b>6. ACCIDENTAL RELEASE MEASURES</b> : Wear appropriate personal protection during cleanup, such as		
Procedures       pressure mode should be worn to prevent inhalation of airborne contaminants.         Unusual Fire/Explosion       : May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) un fire conditions. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke a all possible.         6. ACCIDENTAL RELEASE MEASURES         Personal precautions       : Wear appropriate personal protection during cleanup, such as	Suitable extinguishing media	: Carbon dioxide blanket, Water spray, Dry powder, Foam.
Hazards       fire conditions. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke a all possible.         6. ACCIDENTAL RELEASE MEASURES         Personal precautions       : Wear appropriate personal protection during cleanup, such as		pressure mode should be worn to prevent inhalation of airborne
Personal precautions : Wear appropriate personal protection during cleanup, such as		oxides of nitrogen (NOx), other hazardous materials, and smoke are
		6. ACCIDENTAL RELEASE MEASURES
impervious gloves, boots and coveralls.	Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions : Should not be released into the environment. The product should be allowed to enter drains, water courses or the soil.	Environmental precautions	: Should not be released into the environment. The product should no be allowed to enter drains, water courses or the soil.
Methods for cleaning up : Clean up promptly by sweeping or vacuum. Package all material plastic, cardboard or metal containers for disposal.	Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal.



# MATERIAL SAFETY DATA SHEET STAN-TONE VC-33299 COASTAL GRN 633

Version Number 1.2 Revision Date 11/07/2013		Page 3 of 7 Print Date 11/7/2013
Handling	:	Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation. Processing fume condensates may contain combustible or toxic residue. Periodically clean hoods, ducts, and other surfaces to minimize accumulation of these materials.
Storage	:	Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.
8. EX	POSUI	RE CONTROLS/PERSONAL PROTECTION
Respiratory protection	:	No personal respiratory protective equipment normally required. If dusty conditions occur wear appropriate respiratory protection.
Eye/Face Protection	:	Safety glasses with side-shields
Hand protection	:	Protective gloves
Skin and body protection	:	Long sleeved clothing
Additional Protective Measures	:	Safety shoes
General Hygiene Considerations	:	Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.
Engineering measures	:	Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.
Exposure limit(s)		

PolyOne

## MATERIAL SAFETY DATA SHEET STAN-TONE VC-33299 COASTAL GRN 633

Version Number 1.2 Revision Date 11/07/2013 Page 4 of 7 Print Date 11/7/2013

Components	Value	Exposure time	Exposure type	List:
Iron oxide	10 mg/m3	PEL:	Fume.	OSHA Z1
	5 mg/m3	Time Weighted Average (TWA):	as Fe	MX OEL
	10 mg/m3	Short Term Exposure Limit (STEL):	as Fe	MX OEL
	5 mg/m3	Time Weighted Average (TWA):	Respirable fraction.	ACGIH
Silica, amorphous	6 mg/m3	Recommended exposure limit (REL):		NIOSH
	0.8 mg/m3	Time Weighted Average (TWA):		Z3
	10 mg/m3	Time Weighted Average (TWA):	Inhalable particulate.	MX OEL
	3 mg/m3	Time Weighted Average (TWA):	Respirable dust.	MX OEL
Titanium dioxide	10 mg/m3	Time Weighted Average (TWA):		ACGIH
	15 mg/m3	PEL:	Total dust.	OSHA Z1
	10 mg/m3	Time Weighted Average (TWA):	Total dust.	OSHA Z1A
	10 mg/m3	Time Weighted Average (TWA):	as Ti	MX OEL
	20 mg/m3	Short Term Exposure Limit (STEL):	as Ti	MX OEL

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

Form Appearance Colour Odour Melting point/range Boiling Point: Water solubility

#### powder, granular GREEN very faint Not determined not applicable : insoluble

: solid

:

:

:

:

:

Evapouration rate Specific Gravity Bulk density Vapour pressure Vapour density pН

Not applicable : Not determined : Not determined : : not applicable : not applicable

not applicable :

#### **10. STABILITY AND REACTIVITY**

Stability	:	The product is stable if stored and handled as prescribed.
Hazardous Polymerization	:	Will not occur.
Conditions to avoid	:	To avoid thermal decomposition, do not overheat. Keep away from oxidizing agents and open flame.
Incompatible Materials	:	Incompatible with strong acids and oxidizing agents., Avoid contact with acetal homopolymers and acetal copolymers during processing.
Hazardous decomposition	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen

# MATERIAL SAFETY DATA SHEET STAN-TONE VC-33299 COASTAL GRN 633

Version Number 1.2 Revision Date 11/07/2013 Page 5 of 7 Print Date 11/7/2013

products

(NOx), hydrogen chloride (HCl), other hazardous materials, and smoke are all possible. Prolonged heating (approximately 30 minutes or more) above 392 °F (200 °C) or short term heating at 482 °F (250 °C) may result in product decomposition and evolution of carbon monoxide and hydrogen chloride.

#### **11. TOXICOLOGICAL INFORMATION**

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

**Toxicity Overview** 

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
7631-86-9	Silica, amorphous	Irritant	Eyes, Respiratory system.
1309-37-1	Iron oxide	Systemic effects	Respiratory system.
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
13463-67-7	Titanium dioxide	no	2B	no

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

#### **12. ECOLOGICAL INFORMATION**

Persistence and degradability	Not readily biodegradable.	
Environmental Toxicity	Adverse ecological impact is not known or expected under normal use.	
<b>Bioaccumulation Potential</b>	no data available	
Additional advice	no data available	
	13. DISPOSAL CONSIDERATIONS	
Product	Where possible recycling is preferred to disposal or incineration. The	e

generator of waste material has the responsibility for proper waste



# MATERIAL SAFETY DATA SHEET STAN-TONE VC-33299 COASTAL GRN 633

sion Number 1.2 rision Date 11/07/2013	Page 6 of Print Date <i>11/7/201</i>
	classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. DOT Classification	: Not classified as dangerous good under transport regulations.
ICAO/IATA	: Not classified as dangerous good under transport regulations.
IMO/IMDG (maritime)	: Not classified as dangerous good under transport regulations.
	15. REGULATORY INFORMATION
US Regulations:	
OSHA Status	: Classified as hazardous based on components.
TSCA Status	: All components of this product are listed on or exempt from the TSCA Inventory.
US. EPA CERCLA Hazardous	s Substances (40 CFR 302)
not applicable	
California Proposition 65	: WARNING! This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.
SARA Title III Section 302 Ex	stremely Hazardous Substance
Unless specific chemicals are	identified under this section, this product is Not Applicable under this regulation
SARA Title III Section 313 To	oxic Chemicals:
Unless specific chemicals are	identified under this section, this product is Not Applicable under this regulation
Canadian Regulations:	
National Pollutant Rele	ase Inventory (NPRI)

PolyOne

### MATERIAL SAFETY DATA SHEET STAN-TONE VC-33299 COASTAL GRN 633

Version Number 1.2 Revision Date 11/07/2013

\_

Page 7 of 7 Print Date 11/7/2013

Chemical Name			CAS-No.	Weight	NPRI ID#
				percent	
Phthalocyanine green			1328-53-6	1.00 - 5.00	
WHMIS Classification WHMIS Ingredient Disc CAS-No.					
1309-37-1 1328-53-6 7631-86-9 513-77-9					
DSL	:		s of this product a (DSL) or are exe	are on the Canadia empt.	n Domestic
lational Inventories:					
Australia AICS	:	Not determined			
China IECS	:	Not determined			
Europe EINECS	:	Listed			
Europe EINECS Japan ENCS	:	Listed Not determined			
-					

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.