PolvOne

MATERIAL SAFETY DATA SHEET SKY BLUE P-553 3

Version Number 1.1 Revision Date 03/21/2014

Page 1 of 7 Print Date 3/25/2014

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone Emergency telephone number	:	1 (440) 930-1000 or 1 (866) POLYONE CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	SKY BLUE P-553 3
Product code	:	CC10135878
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS-No.	Weight percent
Decanedioic acid, bis(2,2,6,6-tetramethyl-4-	52829-07-9	5 - 10
piperidinyl) ester		
Titanium dioxide	13463-67-7	5 - 10
Cobalt aluminate blue spinel (C.I. Pigment	1345-16-0	10 - 30
Blue 28)		

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation	: Resin particles, like other inert materials, can be mechanically irritating.
Ingestion	: May be harmful if swallowed.
Eyes	: Resin particles, like other inert materials, are mechanically irritating to eyes.

POLYONE CORPORATION



MATERIAL SAFETY DATA SHEET **SKY BLUE P-553 3**

Version Number 1.1 Revision Date 03/21/2014 Page 2 of 7 Print Date 3/25/2014

	: Experience shows no unusual dermatitis hazard from routine handling
Chronic exposure	: Refer to Section 11 for Toxicological Information.
Medical Conditions Aggravated by Exposure:	: None known.
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases o doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for a least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seek medical attention.
	5. FIREFIGHTING MEASURES
Flash point	: not applicable
Flash point Flammable Limits Upper explosion limit Lower explosion limit Auto-ignition temperature Suitable extinguishing media	 not applicable not applicable not applicable not applicable Carbon dioxide blanket, Water spray, Dry powder, Foam.
Flammable Limits Upper explosion limit Lower explosion limit Auto-ignition temperature	 not applicable not applicable not applicable carbon dioxide blanket, Water spray, Dry powder, Foam. Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne
Flammable Limits Upper explosion limit Lower explosion limit Auto-ignition temperature Suitable extinguishing media Special Fire Fighting	 not applicable not applicable not applicable Carbon dioxide blanket, Water spray, Dry powder, Foam. Fullface self-contained breathing apparatus (SCBA) used in positive
Flammable Limits Upper explosion limit Lower explosion limit Auto-ignition temperature Suitable extinguishing media Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	 not applicable not applicable not applicable Carbon dioxide blanket, Water spray, Dry powder, Foam. Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen
Flammable Limits Upper explosion limit Lower explosion limit Auto-ignition temperature Suitable extinguishing media Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	 not applicable not applicable not applicable Carbon dioxide blanket, Water spray, Dry powder, Foam. Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.
Flammable Limits Upper explosion limit Lower explosion limit Auto-ignition temperature Suitable extinguishing media Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	 not applicable not applicable not applicable Carbon dioxide blanket, Water spray, Dry powder, Foam. Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible. 6. ACCIDENTAL RELEASE MEASURES Wear appropriate personal protection during cleanup, such as

POLYONE CORPORATION

<u>PolyOne</u>

MATERIAL SAFETY DATA SHEET **SKY BLUE P-553 3**

Version Number 1.1 Revision Date 03/21/2014 Page 3 of 7 Print Date 3/25/2014

		7. HANDLING AND STORAGE
Handling	:	Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.
Storage	:	Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.
8. EX	POSU	RE CONTROLS/PERSONAL PROTECTION
Respiratory protection	:	No personal respiratory protective equipment normally required.
Eye/Face Protection	:	Safety glasses with side-shields
Hand protection	:	Protective gloves
Skin and body protection	:	Long sleeved clothing
Additional Protective Measures	:	Safety shoes
General Hygiene Considerations	:	Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.
Engineering measures	:	Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.

Exposure limit(s)

Components	Value	Exposure time	Exposure type	List:
Cobalt aluminate blue	0.02	Time Weighted Average	as Co	ACGIH
spinel (C.I. Pigment	mg/m3	(TWA):		
Blue 28)				
Titanium dioxide	10 mg/m3	Time Weighted Average		ACGIH
		(TWA):		
	15 mg/m3	PEL:	Total dust.	OSHA Z1
	10 mg/m3	Time Weighted Average	Total dust.	OSHA Z1A
		(TWA):		
	10 mg/m3	Time Weighted Average	as Ti	MX OEL
	_	(TWA):		
	20 mg/m3	Short Term Exposure Limit	as Ti	MX OEL
		(STEL):		

9. PHYSICAL AND CHEMICAL PROPERTIES

Form Appearance Colour : solid: pellets: BLUE

Evapouration rate Specific Gravity Bulk density Not applicableNot determinedNot established

MATERIAL SAFETY DATA SHEET SKY BLUE P-553 3

Version Number 1.1 Revision Date 03/21/2014

Page 4 of 7 Print Date 3/25/2014

Odour Melting point/range Boiling Point: Water solubility	 very faint Not determined not applicable not applicable insoluble
	10. STABILITY AND REACTIVITY
Stability	: The product is stable if stored and handled as prescribed.
Hazardous Polymerization	: Will not occur.
Conditions to avoid	: Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
Incompatible Materials	: Incompatible with strong acids and oxidizing agents.
Hazardous decomposition products	: Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

<u>Toxicity Overview</u> This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
52829-07-9	Decanedioic acid,	Irritant	Eyes.
	bis(2,2,6,6-tetramethyl-4-		
	piperidinyl) ester		
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.
1345-16-0	Cobalt aluminate blue	Irritant	Eyes, Skin, Respiratory
	spinel (C.I. Pigment Blue		system.
	28)		
		sensitizer	Skin.

LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
52829-07-9	Decanedioic acid, bis(2,2,6,6-tetramethyl-4- piperidinyl) ester	Oral LD50 Dermal LD50	3,700 mg/kg > 3,100 mg/kg	rat rabbit

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP

PolyOne.

MATERIAL SAFETY DATA SHEET **SKY BLUE P-553 3**

Version Number 1.1

Revision Date 03/21/2014

Page 5 of 7 Print Date 3/25/2014

<u>13463-67-7</u> 1345-16-0		minate blue spinel ent Blue 28)	no no	2B 2B	no
2B - The component	carcinogenic is probably ca is possibly car	to humans. rcinogenic to humans. rcinogenic to humans.			
NTP Carcinogen Cla 1 - The component is 2 - The component is	known to be a	a human carcinogen. ticipated to be a huma	n carcinogen.		
	12	2. ECOLOGICAL IN	FORMATION		
Persistence and degra	adability :	Not readily biodegrad	lable.		
Environmental Toxic	ity :	Chemicals are not reapolymer matrix.	adily available as	s they are bound w	within the
Bioaccumulation Pot	ential :	Chemicals are not reapolymer matrix.	adily available as	s they are bound w	within the
Additional advice	:	no data available			
	1	3. DISPOSAL CONS	IDERATIONS		
Product	:	Like most thermopla possible recycling is generator of waste m classification, transpo applicable federal, st	preferred to disp aterial has the re ortation and disp	osal or incinerations of the second sponsibility for provident of the second se	on. The oper waste e with
Contaminated packag	ging :	Recycling is preferre material has the resp transportation and dis state/provincial and l	onsibility for pro sposal in accorda	per waste classific ince with applicat	cation,
	1	4. TRANSPORT IN	ORMATION		
U.S. DOT Classificat	ion :	Not regulated for trai	nsportation.		
ICAO/IATA	:	Refer to specific regu	llation.		
IMO/IMDG (maritim	ne) :	Refer to specific regu	llation.		
	15	5. REGULATORY IN	FORMATION		
US Regulations:					

PolyOne.

MATERIAL SAFETY DATA SHEET **SKY BLUE P-553 3**

ersion Number 1.1 evision Date 03/21/2014				Pr	Pao int Date 3/2	ge 6 of 7 25/2014
						20,201
OSHA Status : Classified as ha	azardous b	based on con	mponent	s.		
TSCA Status : All componen TSCA Inventor		roduct are	listed on	or exen	npt from the	
US. EPA CERCLA Hazardous Substances (40 CFR	302)					
not applicable						
California Proposition : Not applicable 65						
SARA Title III Section 302 Extremely Hazardous S	ubstance					
Unless specific chemicals are identified under this set	ection, this	s product is	Not Ap	plicable	under this re	gulation
SARA Title III Section 313 Toxic Chemicals:						
Unless specific chemicals are identified under this sector Chemical Name	ection, this	s product is CAS-No.			under this re	gulation
COBALT COMPOUNDSCOBALT COMPOUN		1345-16-0		10.00 -		
INORGANICCOBALT COMPOUNDS, ORGAN	NIC					
Canadian Regulations:						
National Pollutant Release Inventory (NPRI)						
Chemical Name	CAS-N	0.	Weight		NPRI ID#]
Cobalt aluminate blue spinel (C.I. Pigment Blue	1345-1	6-0	percent 10.00 -			-
28)						
WHMIS Classification : D2A						
DSL : All componen Substances Lis				anadian	Domestic	
National Inventories:						
Australia AICS : Listed						
China IECS : Listed						
Europe EINECS : Listed						

PolyOne.

MATERIAL SAFETY DATA SHEET **SKY BLUE P-553 3**

Version Number 1.1 Revision Date 03/21/2014 Page 7 of 7 Print Date 3/25/2014

Japan ENCS

: Not determined

Korea KECI : Listed

Philippines PICCS : Listed

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.