MATERIAL SAFETY DATA SHEET YELLOW 2 NY

Version Number 1.2 Revision Date 03/21/2014 Page 1 of 7 Print Date 3/25/2014

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone:Emergency telephone:number		1 (440) 930-1000 or 1 (866) POLYONE CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	YELLOW 2 NY
Product code	:	CC10135892
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS-No.	Weight percent
Silica, amorphous	7631-86-9	1 - 5
Titanium dioxide	13463-67-7	10 - 30

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

: Inhalation, Ingestion, Skin contact	
: Resin particles, like other inert materials, can be mechanically irritating.	
: May be harmful if swallowed.	
: Resin particles, like other inert materials, are mechanically irritating to eyes.	
: Experience shows no unusual dermatitis hazard from routine handling.	
: Refer to Section 11 for Toxicological Information.	

PolyOne.

MATERIAL SAFETY DATA SHEET **YELLOW 2 NY**

Version Number 1.2 Revision Date 03/21/2014 Page 2 of 7 Print Date 3/25/2014

Medical Conditions Aggravated by Exposure:	: None known.
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for a least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seek medical attention.
	5. FIREFIGHTING MEASURES
Flash point	: not applicable
Flammable Limits Upper explosion limit Lower explosion limit Auto-ignition temperature Suitable extinguishing media	 not applicable not applicable not applicable Carbon dioxide blanket, Water spray, Dry powder, Foam.
Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	 Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should no be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal.
	7. HANDLING AND STORAGE
Handling	: Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.

PolyOne

MATERIAL SAFETY DATA SHEET YELLOW 2 NY

Version Number 1.2 Revision Date 03/21/2014 Page 3 of 7 Print Date 3/25/2014

Storage

: Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Respiratory protection	: No personal respiratory protective equipment normally require	red.
Eye/Face Protection	: Safety glasses with side-shields	
Hand protection	: Protective gloves	
Skin and body protection	: Long sleeved clothing	
Additional Protective Measures	: Safety shoes	
General Hygiene Considerations	: Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workda	
Engineering measures	: Heat only in areas with appropriate exhaust ventilation. Prov appropriate exhaust ventilation at machinery.	ride

Exposure limit(s)

Components	Value	Exposure time	Exposure type	List:
Silica, amorphous 6 mg/m3		Recommended exposure limit (REL):		NIOSH
	0.8 mg/m3	Time Weighted Average (TWA):		Z3
	10 mg/m3	Time Weighted Average (TWA):	Inhalable particulate.	MX OEL
	3 mg/m3	Time Weighted Average (TWA):	Respirable dust.	MX OEL
Titanium dioxide	10 mg/m3	Time Weighted Average (TWA):		ACGIH
	15 mg/m3	PEL:	Total dust.	OSHA Z1
	10 mg/m3	Time Weighted Average (TWA):	Total dust.	OSHA Z1A
	10 mg/m3	Time Weighted Average (TWA):	as Ti	MX OEL
	20 mg/m3	Short Term Exposure Limit (STEL):	as Ti	MX OEL

9. PHYSICAL AND CHEMICAL PROPERTIES

Form Appearance Colour : solid: pellets: YELLOW

Evapouration rate Specific Gravity Bulk density

Not applicableNot determinedNot established

MATERIAL SAFETY DATA SHEET YELLOW 2 NY

Version Number 1.2 Revision Date 03/21/2014 Page 4 of 7 Print Date 3/25/2014

Odour Melting point/range Boiling Point: Water solubility	very faintNot determinednot applicableinsoluble	Vapour pressure Vapour density pH	not applicablenot applicablenot applicable
	10. STABILITY ANI	D REACTIVITY	
Stability	: The product is stab	le if stored and handled as	prescribed.
Hazardous Polymerization	: Will not occur.		
Conditions to avoid	: Keep away from or decomposition, do	xidizing agents and open fl not overheat.	lame. To avoid thermal
Incompatible Materials	: Incompatible with	strong acids and oxidizing	agents.
Hazardous decomposition products		O2), carbon monoxide (CC dous materials, and smoke	

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
7631-86-9	Silica, amorphous	Irritant	Eyes, Respiratory system.
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
13463-67-7	Titanium dioxide	no	2B	no

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

12. ECOLOGICAL INFORMATION

Persistence and degradability

: Not readily biodegradable.



MATERIAL SAFETY DATA SHEET **YELLOW 2 NY**

ion Number 1.2 sion Date 03/21/2014			Page 5 Print Date 3/25/2		
Environmental Toxicity		Chemicals are not readily available as they are bound within the polymer matrix.			
Bioaccumulation Potential		cals are not readily availer matrix.	able as they are bound within the		
Additional advice	: no data	available			
	13. DISP	OSAL CONSIDERAT	IONS		
Product	possibl generat classifi	e recycling is preferred tor of waste material has cation, transportation ar	es the product can be recycled. Where to disposal or incineration. The s the responsibility for proper waste ad disposal in accordance with cial and local regulations.		
Contaminated packaging	materia transpo	 Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations. 			
	14. TRA	NSPORT INFORMAT	TION		
U.S. DOT Classification	: Not reg	gulated for transportation	n.		
ICAO/IATA	: Refer t	o specific regulation.			
IMO/IMDG (maritime)	: Refer t	o specific regulation.			
	15. REGU	LATORY INFORMA	TION		
US Regulations:					
OSHA Status					
		ied as hazardous based	-		
TSCA Status		mponents of this produc Inventory.	t are listed on or exempt from the		
US. EPA CERCLA Hazard	lous Substances (40 CFR 302)			
Chemical Name	CAS-No.	RQ for component	RQ for Mixture/Product		
Chromium (III) oxide	1308-38-9	010 lbs	2,594 LB		

MATERIAL SAFETY DATA SHEET YELLOW 2 NY

Version Number 1.2 Revision Date 03/21/2014 Page 6 of 7 Print Date 3/25/2014

65

SARA Title III Section 302 Extremely Hazardous Substance

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

SARA Title III Section 313 Toxic Chemicals:

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

Canadian Regulations:

National Pollutant Release Inventory (NPRI)			
Chemical Name	CAS-No.	Weight	NPRI ID#
		percent	
Chromium (III) oxide	1308-38-9	0.10 - 1.00	

WHMIS Classification : D2A

WHMIS Ingredient Disclosure List

CAS-No.
7631-86-9

DSL

All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.

National Inventories:

Australia AICS	:	Listed
China IECS	:	Listed
Europe EINECS	:	Listed
Japan ENCS	:	Not determined
Korea KECI	:	Listed
Philippines PICCS	:	Listed

:

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing,

PolyOne.

MATERIAL SAFETY DATA SHEET YELLOW 2 NY

Version Number 1.2 Revision Date 03/21/2014 Page 7 of 7 Print Date 3/25/2014

storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.