PolvOne

MATERIAL SAFETY DATA SHEET **DC YELLOW LDPE**

Version Number 1.1 Revision Date 03/21/2014

Page 1 of 6 Print Date 3/25/2014

POLYONE CORPORATI 33587 Walker Road, Avoi		OH 44012
Telephone Emergency telephone number	:	1 (440) 930-1000 or 1 (866) POLYONE CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	DC YELLOW LDPE
Product code	:	CC10136413
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

Components	CAS-No.	Weight percent
Titanium dioxide	13463-67-7	30 - 60

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Skin contact, Ingestion
Acute exposure	
Inhalation	: Resin particles, like other inert materials, can be mechanically irritating.
Ingestion	: May be harmful if swallowed.
Eyes	: Particulates, like other inert materials can be mechanically irritating.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.

PolyOne.

MATERIAL SAFETY DATA SHEET **DC YELLOW LDPE**

Version Number 1.1 Revision Date 03/21/2014 Page 2 of 6 Print Date 3/25/2014

Medical Conditions Aggravated by Exposure:	: None known.
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases o doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for a least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seek medical attention.
	5. FIREFIGHTING MEASURES
Flash point	: not applicable
Flammable Limits Upper explosion limit Lower explosion limit Auto-ignition temperature Suitable extinguishing media Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	 not applicable not applicable Not relevant Carbon dioxide blanket, Water spray, Dry powder, Foam. Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should no be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal.
	7. HANDLING AND STORAGE
Handling	: Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.

POLYONE CORPORATION



MATERIAL SAFETY DATA SHEET **DC YELLOW LDPE**

Version Number 1.1 Revision Date 03/21/2014 Page 3 of 6 Print Date 3/25/2014

0.1	EXPOSURE	CONTROLS/PER	SONAL PI	ROTECTION			
Respiratory protection				ective equipment normally required. If appropriate respiratory protection.			
Eye/Face Protection	: S	: Safety glasses with side-shields					
Hand protection	: P	: Protective gloves. Refer to equipment supplier to ensure protection.					
Skin and body protection	: L	ong sleeved clothing	5				
Additional Protective Measures	: S	afety shoes					
General Hygiene Considerations		Iandle in accordance ractice. Wash hands					
Engineering measures		leat only in areas wit ppropriate exhaust v			tion. Provide		
Exposure limit(s) Components	Value	Exposure tir	ne	Exposure type	e List:		
Titanium dioxide	10 mg/m3	Time Weighted A (TWA):			ACGIH		
	15 mg/m3	PEL:		Total dust.	OSHA Z1		
	10 mg/m3	Time Weighted A (TWA):	Average	Total dust.	OSHA Z1A		
	10 mg/m3	Time Weighted A (TWA):	Average	as Ti	MX OEL		
	20 mg/m3	Short Term Expose (STEL):	ure Limit	as Ti	MX OEL		
	9. PHYSI	CAL AND CHEMI	CAL PROI	PERTIES			
					NT . 11 11		
Earm	1' 1		E		Not applicable		
Form	: solid		Evapour				
Appearance	: powe	der, granular	Specific	Gravity :	Not applicable		
	: powe : YEL	der, granular LOW	Specific Bulk der	Gravity : nsity :	Not applicable Not determined		
Appearance Colour	: power : YEL : very	der, granular LOW	Specific Bulk der	Gravity : nsity : pressure :	Not applicable		
Appearance Colour Odour Melting point/range Boiling Point:	: power : YEL : very : Not e : not a	der, granular LOW faint determined pplicable	Specific Bulk der Vapour	Gravity : nsity : pressure :	Not applicable Not determined not applicable		
Appearance Colour Odour Melting point/range	: powe : YEL : very : Not	der, granular LOW faint determined pplicable	Specific Bulk der Vapour Vapour	Gravity : nsity : pressure :	Not applicable Not determined not applicable not applicable		

3/6

MATERIAL SAFETY DATA SHEET **DC YELLOW LDPE**

Version Number 1.1 Revision Date 03/21/2014 Page 4 of 6 Print Date 3/25/2014

Hazardous Polymerization	:	Will not occur.
Conditions to avoid	:	To avoid thermal decomposition, do not overheat. Keep away from oxidizing agents and open flame.
Incompatible Materials	:	Incompatible with strong acids and oxidizing agents.
Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
13463-67-7	Titanium dioxide	no	2B	no

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

	12. ECOLOGICAL INFORMATION		
Persistence and degradability	: Not readily biodegradable.		
Environmental Toxicity	: Chemicals are not readily available as they are bound within the polymer matrix.		
Bioaccumulation Potential	: Chemicals are not readily available as they are bound within the polymer matrix.		
Additional advice	: no data available		

PolyOne.

MATERIAL SAFETY DATA SHEET **DC YELLOW LDPE**

Version Number 1.1 Revision Date 03/21/2014 Page 5 of 6 Print Date 3/25/2014

	13. DISPOSAL CONSIDERATIONS
Product	: Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. DOT Classification	: Not regulated for transportation.
ICAO/IATA	: Refer to specific regulation.
IMO/IMDG (maritime)	: Refer to specific regulation.
	15. REGULATORY INFORMATION
US Regulations:	
OSHA Status	: Classified as hazardous based on components.
TSCA Status	: All components of this product are listed on or exempt from the TSCA Inventory.
US. EPA CERCLA Hazardo	us Substances (40 CFR 302)
not applicable	
California Proposition 65	n : Not applicable
SARA Title III Section 302 H	Extremely Hazardous Substance
	e identified under this section, this product is Not Applicable under this regula

PolyOne

MATERIAL SAFETY DATA SHEET **DC YELLOW LDPE**

Version Number 1.1 Revision Date 03/21/2014 Page 6 of 6 Print Date 3/25/2014

Chemical Name	CAS-No.	Weight percent
ZINC COMPOUNDS	68187-51-9	5.00 - 10.00

Canadian Regulations:

National Pollutant Release Inventory (NPRI) Chemical Name Aluminum oxide Zinc ferrite brown spinel (C.I. Pigment Yellow 119)			CAS-No.	Weight percent 0.10 - 1.00 5.00 - 10.00	NPRI ID#
			1344-28-1 68187-51-9		
WHMIS Classification	:	D2A			
DSL	: All components of this product are on the Canadian Domest Substances List (DSL) or are exempt.				n Domestic
lational Inventories:					
Australia AICS	:	Listed			
China IECS	:	Listed			
Europe EINECS	:	Listed			
Japan ENCS	:	Not determined	l		
Korea KECI	:	Not determined	l		
Philippines PICCS	:	Not determined	l		
		16. OTHER I	NFORMATION		

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.