MATERIAL SAFETY DATA SHEET JAVA (GRAY TINT)

Version Number 1.1 Revision Date 03/21/2014

Page 1 of 6 Print Date 3/25/2014

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone Emergency telephone number	:	1 (440) 930-1000 or 1 (866) POLYONE CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	JAVA (GRAY TINT)
Product code	:	CC10136682
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON INGREDIENTS

There are no known hazardous components above regulatory thresholds in this product.

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation	: Resin particles, like other inert materials, can be mechanically irritating.
Ingestion	: May be harmful if swallowed.
Eyes	: Resin particles, like other inert materials, are mechanically irritating to eyes.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.

PolyOne.

MATERIAL SAFETY DATA SHEET JAVA (GRAY TINT)

Version Number 1.1 Revision Date 03/21/2014 Page 2 of 6 Print Date 3/25/2014

Medical Conditions Aggravated by Exposure:	: None known.
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases o doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for a least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seek medical attention.
	5. FIREFIGHTING MEASURES
Flash point	: not applicable
Flammable Limits Upper explosion limit Lower explosion limit Auto-ignition temperature Suitable extinguishing media Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	 not applicable not applicable not applicable Carbon dioxide blanket, Water spray, Dry powder, Foam. Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal.
	7. HANDLING AND STORAGE
Handling	: Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.

PolyOne.

MATERIAL SAFETY DATA SHEET JAVA (GRAY TINT)

Version Number 1.1 Revision Date 03/21/2014 Page 3 of 6 Print Date 3/25/2014

	: Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.				
8. EX	POSURE	CONTROLS/PE	CRSONAL PROTECTIO	DN	
Respiratory protection	: No personal respiratory protective equipment normally required.				
Eye/Face Protection	: Sat	Safety glasses with side-shields			
Hand protection	: Pro	Protective gloves			
Skin and body protection	: Lo	Long sleeved clothing			
Additional Protective Measures	: Sat	Safety shoes			
General Hygiene Considerations		Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.			
Engineering measures		Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.			
•	us compone	ents above regula	tory thresholds in this pro	oduct.	
Exposure limit(s) There are no known hazardou 9	-		tory thresholds in this pro	oduct.	
There are no known hazardo	: solid : pellets : GREY : very fa	AL AND CHEM s Y aint etermined oplicable		 Not applicable Not determined Not established not applicable not applicable not applicable 	
There are no known hazardon 9 Form Appearance Colour Odour Melting point/range Boiling Point:	 PHYSIC solid pellets GREY very fr very fa Not de not ap insolu 	AL AND CHEM s Y aint etermined oplicable	IICAL PROPERTIES Evapouration rate Specific Gravity Bulk density Vapour pressure Vapour density pH	 Not applicable Not determined Not established not applicable not applicable 	
There are no known hazardon 9 Form Appearance Colour Odour Melting point/range Boiling Point:	 PHYSIC. solid pellets GREY very fa very fa not de not ap insolu 10. ST	AL AND CHEM s Y faint etermined oplicable ible TABILITY AND	IICAL PROPERTIES Evapouration rate Specific Gravity Bulk density Vapour pressure Vapour density pH	 Not applicable Not determined Not established not applicable not applicable not applicable 	
There are no known hazardon 9 Form Appearance Colour Odour Melting point/range Boiling Point: Water solubility	• PHYSIC · solid · pellets · GREY · very fa · Not de · not ap · insolu 10. ST · Th	AL AND CHEM s Y faint etermined oplicable ible TABILITY AND	IICAL PROPERTIES Evapouration rate Specific Gravity Bulk density Vapour pressure Vapour density pH	 Not applicable Not determined Not established not applicable not applicable not applicable 	
There are no known hazardou 9 Form Appearance Colour Odour Melting point/range Boiling Point: Water solubility Stability	• PHYSIC : solid : pellets : GREY : very fa : Not de : not ap : insolu 10. ST : Th : Wi : Wi	AL AND CHEM s Y faint etermined oplicable able TABILITY AND the product is stable ill not occur.	IICAL PROPERTIES Evapouration rate Specific Gravity Bulk density Vapour pressure Vapour density pH PREACTIVITY e if stored and handled as idizing agents and open fi	: Not applicable : Not determined : Not established : not applicable : not applicable : not applicable prescribed.	
There are no known hazardou 9 Form Appearance Colour Odour Melting point/range Boiling Point: Water solubility Stability Hazardous Polymerization	• PHYSIC : solid : pellets : GREY : very fr : Not de : not ap : insolu 10. ST : Th : Wi : Ke dec	AL AND CHEM s Y aint etermined oplicable ible TABILITY AND the product is stable ill not occur. eep away from oxic composition, do n	IICAL PROPERTIES Evapouration rate Specific Gravity Bulk density Vapour pressure Vapour density pH PREACTIVITY e if stored and handled as idizing agents and open fi	 Not applicable Not determined Not established not applicable not applicable not applicable prescribed. lame. To avoid thermal	

PolyOne.

MATERIAL SAFETY DATA SHEET JAVA (GRAY TINT)

Version Number 1.1 Revision Date 03/21/2014 Page 4 of 6 Print Date 3/25/2014

	12	. ECOLOGICAL INFORMATION
Persistence and degradability	:	Not readily biodegradable.
Environmental Toxicity	:	Chemicals are not readily available as they are bound within the polymer matrix.
Bioaccumulation Potential	:	Chemicals are not readily available as they are bound within the polymer matrix.
Additional advice	:	no data available
	13	3. DISPOSAL CONSIDERATIONS
Product	:	Like most thermoplastic plastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	:	Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	1	4. TRANSPORT INFORMATION
U.S. DOT Classification	:	Not regulated for transportation.
ICAO/IATA	:	Refer to specific regulation.
IMO/IMDG (maritime)	:	Refer to specific regulation.
	15	REGULATORY INFORMATION
US Regulations:		
OSHA Status	:	There are no known hazardous components above regulatory thresholds in this product.
TSCA Status	:	All components of this product are listed on or exempt from the TSCA Inventory.

PolvOne

MATERIAL SAFETY DATA SHEET JAVA (GRAY TINT)

Version Number 1.1 Revision Date 03/21/2014 Page 5 of 6 Print Date 3/25/2014

not applicable

California Proposition : Not applicable 65

SARA Title III Section 302 Extremely Hazardous Substance

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

SARA Title III Section 313 Toxic Chemicals:

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

Canadian Regulations:

National Pollutant Release Inventory (NPRI)

not applicable

WHMIS Classification	:	Not controlled.
DSL	:	All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.

National Inventories:

:	Not determined
:	Listed
:	Listed
:	Not determined
:	Listed
:	Not determined
	:

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

PolyOne.

MATERIAL SAFETY DATA SHEET JAVA (GRAY TINT)

Version Number 1.1 Revision Date 03/21/2014 Page 6 of 6 Print Date 3/25/2014